



API Reference

AWS Device Farm Documentation



API Version 2015-06-23

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

AWS Device Farm Documentation: API Reference

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
CreateDevicePool	5
Request Syntax	5
Request Parameters	5
Response Syntax	6
Response Elements	7
Errors	7
See Also	8
CreateInstanceProfile	9
Request Syntax	9
Request Parameters	9
Response Syntax	10
Response Elements	10
Errors	11
See Also	12
CreateNetworkProfile	13
Request Syntax	13
Request Parameters	13
Response Syntax	16
Response Elements	16
Errors	16
See Also	17
CreateProject	19
Request Syntax	19
Request Parameters	19
Response Syntax	20
Response Elements	21
Errors	21
See Also	22
CreateRemoteAccessSession	24
Request Syntax	24
Request Parameters	24
Response Syntax	26

Response Elements	28
Errors	29
See Also	29
CreateTestGridProject	31
Request Syntax	31
Request Parameters	31
Response Syntax	32
Response Elements	32
Errors	32
See Also	33
CreateTestGridUrl	35
Request Syntax	35
Request Parameters	35
Response Syntax	35
Response Elements	36
Errors	36
See Also	37
CreateUpload	38
Request Syntax	38
Request Parameters	38
Response Syntax	41
Response Elements	41
Errors	41
See Also	42
CreateVPCEConfiguration	44
Request Syntax	44
Request Parameters	44
Response Syntax	45
Response Elements	45
Errors	46
See Also	46
DeleteDevicePool	48
Request Syntax	48
Request Parameters	48
Response Elements	48
Errors	48

See Also	49
DeleteInstanceProfile	51
Request Syntax	51
Request Parameters	51
Response Elements	51
Errors	51
See Also	52
DeleteNetworkProfile	54
Request Syntax	54
Request Parameters	54
Response Elements	54
Errors	54
See Also	55
DeleteProject	57
Request Syntax	57
Request Parameters	57
Response Elements	57
Errors	57
See Also	58
DeleteRemoteAccessSession	60
Request Syntax	60
Request Parameters	60
Response Elements	60
Errors	60
See Also	61
DeleteRun	63
Request Syntax	63
Request Parameters	63
Response Elements	63
Errors	63
See Also	64
DeleteTestGridProject	66
Request Syntax	66
Request Parameters	66
Response Elements	66
Errors	66

See Also	67
DeleteUpload	69
Request Syntax	69
Request Parameters	69
Response Elements	69
Errors	69
See Also	70
DeleteVPCEConfiguration	72
Request Syntax	72
Request Parameters	72
Response Elements	72
Errors	72
See Also	73
GetAccountSettings	75
Response Syntax	75
Response Elements	75
Errors	76
See Also	76
GetDevice	78
Request Syntax	78
Request Parameters	78
Response Syntax	78
Response Elements	79
Errors	80
See Also	81
GetDeviceInstance	82
Request Syntax	82
Request Parameters	82
Response Syntax	82
Response Elements	83
Errors	83
See Also	84
GetDevicePool	85
Request Syntax	85
Request Parameters	85
Response Syntax	85

Response Elements	86
Errors	86
See Also	87
GetDevicePoolCompatibility	88
Request Syntax	88
Request Parameters	89
Response Syntax	91
Response Elements	94
Errors	94
See Also	95
GetInstanceProfile	96
Request Syntax	96
Request Parameters	96
Response Syntax	96
Response Elements	97
Errors	97
See Also	98
GetJob	99
Request Syntax	99
Request Parameters	99
Response Syntax	99
Response Elements	101
Errors	102
See Also	103
GetNetworkProfile	104
Request Syntax	104
Request Parameters	104
Response Syntax	104
Response Elements	105
Errors	105
See Also	106
GetOfferingStatus	107
Request Syntax	107
Request Parameters	107
Response Syntax	107
Response Elements	108

Errors	109
Examples	110
See Also	111
GetProject	113
Request Syntax	113
Request Parameters	113
Response Syntax	113
Response Elements	114
Errors	114
See Also	115
GetRemoteAccessSession	116
Request Syntax	116
Request Parameters	116
Response Syntax	116
Response Elements	118
Errors	119
See Also	119
GetRun	121
Request Syntax	121
Request Parameters	121
Response Syntax	121
Response Elements	124
Errors	124
See Also	125
GetSuite	127
Request Syntax	127
Request Parameters	127
Response Syntax	127
Response Elements	128
Errors	128
See Also	129
GetTest	131
Request Syntax	131
Request Parameters	131
Response Syntax	131
Response Elements	132

Errors	132
See Also	133
GetTestGridProject	135
Request Syntax	135
Request Parameters	135
Response Syntax	135
Response Elements	136
Errors	136
See Also	137
GetTestGridSession	138
Request Syntax	138
Request Parameters	138
Response Syntax	139
Response Elements	139
Errors	140
See Also	140
GetUpload	142
Request Syntax	142
Request Parameters	142
Response Syntax	142
Response Elements	143
Errors	143
See Also	144
GetVPCEConfiguration	145
Request Syntax	145
Request Parameters	145
Response Syntax	145
Response Elements	146
Errors	146
See Also	147
InstallToRemoteAccessSession	148
Request Syntax	148
Request Parameters	148
Response Syntax	149
Response Elements	149
Errors	149

See Also	150
ListArtifacts	152
Request Syntax	152
Request Parameters	152
Response Syntax	153
Response Elements	153
Errors	154
See Also	155
ListDeviceInstances	156
Request Syntax	156
Request Parameters	156
Response Syntax	156
Response Elements	157
Errors	157
See Also	158
ListDevicePools	160
Request Syntax	160
Request Parameters	160
Response Syntax	161
Response Elements	161
Errors	162
See Also	163
ListDevices	164
Request Syntax	164
Request Parameters	164
Response Syntax	166
Response Elements	167
Errors	168
See Also	169
ListInstanceProfiles	170
Request Syntax	170
Request Parameters	170
Response Syntax	170
Response Elements	171
Errors	171
See Also	172

ListJobs	174
Request Syntax	174
Request Parameters	174
Response Syntax	174
Response Elements	177
Errors	177
See Also	178
ListNetworkProfiles	180
Request Syntax	180
Request Parameters	180
Response Syntax	181
Response Elements	181
Errors	182
See Also	183
ListOfferingPromotions	184
Request Syntax	184
Request Parameters	184
Response Syntax	184
Response Elements	185
Errors	185
See Also	186
ListOfferings	188
Request Syntax	188
Request Parameters	188
Response Syntax	188
Response Elements	189
Errors	189
Examples	190
See Also	191
ListOfferingTransactions	193
Request Syntax	193
Request Parameters	193
Response Syntax	193
Response Elements	194
Errors	195
Examples	196

See Also	204
ListProjects	205
Request Syntax	205
Request Parameters	205
Response Syntax	206
Response Elements	206
Errors	207
See Also	208
ListRemoteAccessSessions	209
Request Syntax	209
Request Parameters	209
Response Syntax	209
Response Elements	212
Errors	212
See Also	213
ListRuns	214
Request Syntax	214
Request Parameters	214
Response Syntax	214
Response Elements	217
Errors	218
See Also	219
ListSamples	220
Request Syntax	220
Request Parameters	220
Response Syntax	220
Response Elements	221
Errors	221
See Also	222
ListSuites	224
Request Syntax	224
Request Parameters	224
Response Syntax	224
Response Elements	225
Errors	226
See Also	227

ListTagsForResource	228
Request Syntax	228
Request Parameters	228
Response Syntax	228
Response Elements	229
Errors	229
See Also	230
ListTestGridProjects	231
Request Syntax	231
Request Parameters	231
Response Syntax	231
Response Elements	232
Errors	232
See Also	233
ListTestGridSessionActions	234
Request Syntax	234
Request Parameters	234
Response Syntax	235
Response Elements	235
Errors	235
See Also	236
ListTestGridSessionArtifacts	238
Request Syntax	238
Request Parameters	238
Response Syntax	239
Response Elements	239
Errors	240
See Also	240
ListTestGridSessions	242
Request Syntax	242
Request Parameters	242
Response Syntax	244
Response Elements	244
Errors	244
See Also	245
ListTests	247

Request Syntax	247
Request Parameters	247
Response Syntax	247
Response Elements	248
Errors	249
See Also	250
ListUniqueProblems	251
Request Syntax	251
Request Parameters	251
Response Syntax	252
Response Elements	253
Errors	254
See Also	255
ListUploads	257
Request Syntax	257
Request Parameters	257
Response Syntax	259
Response Elements	260
Errors	260
See Also	261
ListVPCEConfigurations	262
Request Syntax	262
Request Parameters	262
Response Syntax	262
Response Elements	263
Errors	263
See Also	264
PurchaseOffering	265
Request Syntax	265
Request Parameters	265
Response Syntax	266
Response Elements	266
Errors	267
Examples	268
See Also	269
RenewOffering	270

Request Syntax	270
Request Parameters	270
Response Syntax	270
Response Elements	271
Errors	272
Examples	273
See Also	274
ScheduleRun	275
Request Syntax	275
Request Parameters	276
Response Syntax	278
Response Elements	281
Errors	281
See Also	282
StopJob	284
Request Syntax	284
Request Parameters	284
Response Syntax	284
Response Elements	287
Errors	287
See Also	288
StopRemoteAccessSession	289
Request Syntax	289
Request Parameters	289
Response Syntax	289
Response Elements	291
Errors	292
See Also	292
StopRun	294
Request Syntax	294
Request Parameters	294
Response Syntax	294
Response Elements	297
Errors	297
See Also	298
TagResource	300

Request Syntax	300
Request Parameters	300
Response Elements	301
Errors	301
See Also	302
UntagResource	303
Request Syntax	303
Request Parameters	303
Response Elements	304
Errors	304
See Also	304
UpdateDeviceInstance	306
Request Syntax	306
Request Parameters	306
Response Syntax	307
Response Elements	307
Errors	307
See Also	308
UpdateDevicePool	310
Request Syntax	310
Request Parameters	310
Response Syntax	312
Response Elements	312
Errors	313
See Also	313
UpdateInstanceProfile	315
Request Syntax	315
Request Parameters	315
Response Syntax	316
Response Elements	317
Errors	317
See Also	318
UpdateNetworkProfile	319
Request Syntax	319
Request Parameters	319
Response Syntax	322

Response Elements	322
Errors	322
See Also	323
UpdateProject	325
Request Syntax	325
Request Parameters	325
Response Syntax	327
Response Elements	327
Errors	328
See Also	328
UpdateTestGridProject	330
Request Syntax	330
Request Parameters	330
Response Syntax	331
Response Elements	331
Errors	332
See Also	333
UpdateUpload	334
Request Syntax	334
Request Parameters	334
Response Syntax	335
Response Elements	335
Errors	336
See Also	337
UpdateVPCEConfiguration	338
Request Syntax	338
Request Parameters	338
Response Syntax	339
Response Elements	340
Errors	340
See Also	341
Data Types	342
AccountSettings	345
Contents	345
See Also	346
Artifact	348

Contents	348
See Also	350
Counters	351
Contents	351
See Also	352
CPU	353
Contents	353
See Also	353
CreateRemoteAccessSessionConfiguration	354
Contents	354
See Also	355
CustomerArtifactPaths	356
Contents	356
See Also	356
Device	358
Contents	358
See Also	362
DeviceFilter	363
Contents	363
See Also	366
DeviceInstance	367
Contents	367
See Also	368
DeviceMinutes	369
Contents	369
See Also	369
DevicePool	370
Contents	370
See Also	371
DevicePoolCompatibilityResult	372
Contents	372
See Also	372
DeviceProxy	373
Contents	373
See Also	373
DeviceSelectionConfiguration	374

Contents	374
See Also	376
DeviceSelectionResult	377
Contents	377
See Also	377
EnvironmentVariable	378
Contents	378
See Also	378
ExecutionConfiguration	379
Contents	379
See Also	380
IncompatibilityMessage	381
Contents	381
See Also	382
InstanceProfile	383
Contents	383
See Also	384
Job	385
Contents	385
See Also	389
JobInsights	390
Contents	390
See Also	390
JobReport	391
Contents	391
See Also	391
JobReportMetrics	393
Contents	393
See Also	394
ListTestGridProjectsRequest	396
Contents	396
See Also	396
ListTestGridSessionsRequest	397
Contents	397
See Also	398
Location	399

Contents	399
See Also	399
MonetaryAmount	400
Contents	400
See Also	400
NetworkProfile	401
Contents	401
See Also	403
Offering	404
Contents	404
See Also	405
OfferingPromotion	406
Contents	406
See Also	406
OfferingStatus	407
Contents	407
See Also	407
OfferingTransaction	409
Contents	409
See Also	410
Problem	411
Contents	411
See Also	412
ProblemDetail	414
Contents	414
See Also	414
Project	415
Contents	415
See Also	416
Radios	417
Contents	417
See Also	417
RecurringCharge	419
Contents	419
See Also	419
RemoteAccessEndpoints	420

Contents	420
See Also	420
RemoteAccessSession	421
Contents	421
See Also	426
Resolution	427
Contents	427
See Also	427
Rule	428
Contents	428
See Also	430
Run	431
Contents	431
See Also	440
RunInsights	441
Contents	441
See Also	441
Sample	442
Contents	442
See Also	443
ScheduleRunConfiguration	444
Contents	444
See Also	447
ScheduleRunTest	448
Contents	448
See Also	450
Suite	452
Contents	452
See Also	455
Tag	456
Contents	456
See Also	456
Test	457
Contents	457
See Also	460
TestGridProject	461

Contents	461
See Also	462
TestGridSession	463
Contents	463
See Also	464
TestGridSessionAction	465
Contents	465
See Also	466
TestGridSessionArtifact	467
Contents	467
See Also	467
TestGridVpcConfig	469
Contents	469
See Also	470
TestReport	471
Contents	471
See Also	471
TestReportMetrics	473
Contents	473
See Also	474
TrialMinutes	475
Contents	475
See Also	475
UniqueProblem	476
Contents	476
See Also	476
Upload	477
Contents	477
See Also	481
VpcConfig	482
Contents	482
See Also	483
VPCEConfiguration	484
Contents	484
See Also	485
Common Parameters	486

Common Error Types 489

Welcome

Welcome to the AWS Device Farm API documentation, which contains APIs for:

- Testing on desktop browsers

Device Farm makes it possible for you to test your web applications on desktop browsers using Selenium. The APIs for desktop browser testing contain TestGrid in their names. For more information, see [Testing Web Applications on Selenium with Device Farm](#).

- Testing on real mobile devices

Device Farm makes it possible for you to test apps on physical phones, tablets, and other devices in the cloud. For more information, see the [Device Farm Developer Guide](#).

This document was last published on September 18, 2026.

Actions

The following actions are supported:

- [CreateDevicePool](#)
- [CreateInstanceProfile](#)
- [CreateNetworkProfile](#)
- [CreateProject](#)
- [CreateRemoteAccessSession](#)
- [CreateTestGridProject](#)
- [CreateTestGridUrl](#)
- [CreateUpload](#)
- [CreateVPCEConfiguration](#)
- [DeleteDevicePool](#)
- [DeleteInstanceProfile](#)
- [DeleteNetworkProfile](#)
- [DeleteProject](#)
- [DeleteRemoteAccessSession](#)
- [DeleteRun](#)
- [DeleteTestGridProject](#)
- [DeleteUpload](#)
- [DeleteVPCEConfiguration](#)
- [GetAccountSettings](#)
- [GetDevice](#)
- [GetDeviceInstance](#)
- [GetDevicePool](#)
- [GetDevicePoolCompatibility](#)
- [GetInstanceProfile](#)
- [GetJob](#)
- [GetNetworkProfile](#)
- [GetOfferingStatus](#)

- [GetProject](#)
- [GetRemoteAccessSession](#)
- [GetRun](#)
- [GetSuite](#)
- [GetTest](#)
- [GetTestGridProject](#)
- [GetTestGridSession](#)
- [GetUpload](#)
- [GetVPCEConfiguration](#)
- [InstallToRemoteAccessSession](#)
- [ListArtifacts](#)
- [ListDeviceInstances](#)
- [ListDevicePools](#)
- [ListDevices](#)
- [ListInstanceProfiles](#)
- [ListJobs](#)
- [ListNetworkProfiles](#)
- [ListOfferingPromotions](#)
- [ListOfferings](#)
- [ListOfferingTransactions](#)
- [ListProjects](#)
- [ListRemoteAccessSessions](#)
- [ListRuns](#)
- [ListSamples](#)
- [ListSuites](#)
- [ListTagsForResource](#)
- [ListTestGridProjects](#)
- [ListTestGridSessionActions](#)
- [ListTestGridSessionArtifacts](#)
- [ListTestGridSessions](#)

- [ListTests](#)
- [ListUniqueProblems](#)
- [ListUploads](#)
- [ListVPCEConfigurations](#)
- [PurchaseOffering](#)
- [RenewOffering](#)
- [ScheduleRun](#)
- [StopJob](#)
- [StopRemoteAccessSession](#)
- [StopRun](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdateDeviceInstance](#)
- [UpdateDevicePool](#)
- [UpdateInstanceProfile](#)
- [UpdateNetworkProfile](#)
- [UpdateProject](#)
- [UpdateTestGridProject](#)
- [UpdateUpload](#)
- [UpdateVPCEConfiguration](#)

CreateDevicePool

Creates a device pool.

Request Syntax

```
{
  "description": "string",
  "maxDevices": number,
  "name": "string",
  "projectArn": "string",
  "rules": [
    {
      "attribute": "string",
      "operator": "string",
      "value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

description

The device pool's description.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

Required: No

maxDevices

The number of devices that Device Farm can add to your device pool. Device Farm adds devices that are available and meet the criteria that you assign for the `rules` parameter. Depending on how many devices meet these constraints, your device pool might contain fewer devices than the value for this parameter.

By specifying the maximum number of devices, you can control the costs that you incur by running tests.

Type: Integer

Required: No

name

The device pool's name.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: Yes

projectArn

The ARN of the project for the device pool.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: Yes

rules

The device pool's rules.

Type: Array of [Rule](#) objects

Required: Yes

Response Syntax

```
{
  "devicePool": {
    "arn": "string",
    "description": "string",
    "maxDevices": number,
    "name": "string",
```

```
  "rules": [  
    {  
      "attribute": "string",  
      "operator": "string",  
      "value": "string"  
    },  
  ],  
  "type": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[devicePool](#)

The newly created device pool.

Type: [DevicePool](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

CreateInstanceProfile

Creates a profile that can be applied to one or more private fleet device instances.

Request Syntax

```
{  
  "description": "string",  
  "excludeAppPackagesFromCleanup": [ "string" ],  
  "name": "string",  
  "packageCleanup": boolean,  
  "rebootAfterUse": boolean  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

description

The description of your instance profile.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

Required: No

excludeAppPackagesFromCleanup

An array of strings that specifies the list of app packages that should not be cleaned up from the device after a test run.

The list of packages is considered only if you set packageCleanup to true.

Type: Array of strings

Required: No

name

The name of your instance profile.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: Yes

packageCleanup

When set to `true`, Device Farm removes app packages after a test run. The default value is `false` for private devices.

Type: Boolean

Required: No

rebootAfterUse

When set to `true`, Device Farm reboots the instance after a test run. The default value is `true`.

Type: Boolean

Required: No

Response Syntax

```
{
  "instanceProfile": {
    "arn": "string",
    "description": "string",
    "excludeAppPackagesFromCleanup": [ "string" ],
    "name": "string",
    "packageCleanup": boolean,
    "rebootAfterUse": boolean
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

instanceProfile

An object that contains information about your instance profile.

Type: [InstanceProfile](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

CreateNetworkProfile

Creates a network profile.

Request Syntax

```
{  
  "description": "string",  
  "downlinkBandwidthBits": number,  
  "downlinkDelayMs": number,  
  "downlinkJitterMs": number,  
  "downlinkLossPercent": number,  
  "name": "string",  
  "projectArn": "string",  
  "type": "string",  
  "uplinkBandwidthBits": number,  
  "uplinkDelayMs": number,  
  "uplinkJitterMs": number,  
  "uplinkLossPercent": number  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

description

The description of the network profile.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

Required: No

downlinkBandwidthBits

The data throughput rate in bits per second, as an integer from 0 to 104857600.

Type: Long

Required: No

[downlinkDelayMs](#)

Delay time for all packets to destination in milliseconds as an integer from 0 to 2000.

Type: Long

Required: No

[downlinkJitterMs](#)

Time variation in the delay of received packets in milliseconds as an integer from 0 to 2000.

Type: Long

Required: No

[downlinkLossPercent](#)

Proportion of received packets that fail to arrive from 0 to 100 percent.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 100.

Required: No

[name](#)

The name for the new network profile.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: Yes

[projectArn](#)

The Amazon Resource Name (ARN) of the project for which you want to create a network profile.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: Yes

type

The type of network profile to create. Valid values are listed here.

Type: String

Valid Values: CURATED | PRIVATE

Required: No

uplinkBandwidthBits

The data throughput rate in bits per second, as an integer from 0 to 104857600.

Type: Long

Required: No

uplinkDelayMs

Delay time for all packets to destination in milliseconds as an integer from 0 to 2000.

Type: Long

Required: No

uplinkJitterMs

Time variation in the delay of received packets in milliseconds as an integer from 0 to 2000.

Type: Long

Required: No

uplinkLossPercent

Proportion of transmitted packets that fail to arrive from 0 to 100 percent.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 100.

Required: No

Response Syntax

```
{
  "networkProfile": {
    "arn": "string",
    "description": "string",
    "downlinkBandwidthBits": number,
    "downlinkDelayMs": number,
    "downlinkJitterMs": number,
    "downlinkLossPercent": number,
    "name": "string",
    "type": "string",
    "uplinkBandwidthBits": number,
    "uplinkDelayMs": number,
    "uplinkJitterMs": number,
    "uplinkLossPercent": number
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

networkProfile

The network profile that is returned by the create network profile request.

Type: [NetworkProfile](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

CreateProject

Creates a project.

Request Syntax

```
{
  "defaultJobTimeoutMinutes": number,
  "environmentVariables": [
    {
      "name": "string",
      "value": "string"
    }
  ],
  "executionRoleArn": "string",
  "name": "string",
  "vpcConfig": {
    "securityGroupIds": [ "string" ],
    "subnetIds": [ "string" ],
    "vpcId": "string"
  }
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

defaultJobTimeoutMinutes

Sets the execution timeout value (in minutes) for a project. All test runs in this project use the specified execution timeout value unless overridden when scheduling a run.

Type: Integer

Required: No

environmentVariables

A set of environment variables which are used by default for all runs in the project. These environment variables are applied to the test run during the execution of a test spec file.

For more information about using test spec files, please see [Custom test environments](#) in *AWS Device Farm*.

Type: Array of [EnvironmentVariable](#) objects

Array Members: Minimum number of 1 item. Maximum number of 32 items.

Required: No

[executionRoleArn](#)

An IAM role to be assumed by the test host for all runs in the project.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `^arn:aws:iam:[0-9]{12}:role/.+`

Required: No

[name](#)

The project's name.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: Yes

[vpcConfig](#)

The VPC security groups and subnets that are attached to a project.

Type: [VpcConfig](#) object

Required: No

Response Syntax

```
{
  "project": {
    "arn": "string",
```

```
"created": number,
"defaultJobTimeoutMinutes": number,
"environmentVariables": [
  {
    "name": "string",
    "value": "string"
  }
],
"executionRoleArn": "string",
"name": "string",
"vpcConfig": {
  "securityGroupIds": [ "string " ],
  "subnetIds": [ "string " ],
  "vpcId": "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

project

The newly created project.

Type: [Project](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

TagOperationException

The operation was not successful. Try again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

CreateRemoteAccessSession

Specifies and starts a remote access session.

Request Syntax

```
{
  "appArn": "string",
  "configuration": {
    "auxiliaryApps": [ "string" ],
    "billingMethod": "string",
    "deviceProxy": {
      "host": "string",
      "port": number
    },
    "vpceConfigurationArns": [ "string" ]
  },
  "deviceArn": "string",
  "instanceArn": "string",
  "interactionMode": "string",
  "name": "string",
  "projectArn": "string",
  "skipAppResign": boolean
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

appArn

The Amazon Resource Name (ARN) of the app to create the remote access session.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

configuration

The configuration information for the remote access session request.

Type: [CreateRemoteAccessSessionConfiguration](#) object

Required: No

deviceArn

The ARN of the device for which you want to create a remote access session.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: Yes

instanceArn

The Amazon Resource Name (ARN) of the device instance for which you want to create a remote access session.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

interactionMode

This parameter has been deprecated.

The interaction mode of the remote access session. Changing the interactive mode of remote access sessions is no longer available.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 64.

Valid Values: INTERACTIVE | NO_VIDEO | VIDEO_ONLY

Required: No

name

The name of the remote access session to create.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

projectArn

The Amazon Resource Name (ARN) of the project for which you want to create a remote access session.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: Yes

skipAppResign

When set to `true`, for private devices, Device Farm does not sign your app again. For public devices, Device Farm always signs your apps again.

For more information on how Device Farm modifies your uploads during tests, see [Do you modify my app?](#)

Type: Boolean

Required: No

Response Syntax

```
{
  "remoteAccessSession": {
    "appUpload": "string",
    "arn": "string",
    "billingMethod": "string",
    "created": number,
    "device": {
      "arn": "string",
```

```

    "availability": "string",
    "carrier": "string",
    "cpu": {
        "architecture": "string",
        "clock": number,
        "frequency": "string"
    },
    "fleetName": "string",
    "fleetType": "string",
    "formFactor": "string",
    "heapSize": number,
    "image": "string",
    "instances": [
        {
            "arn": "string",
            "deviceArn": "string",
            "instanceProfile": {
                "arn": "string",
                "description": "string",
                "excludeAppPackagesFromCleanup": [ "string" ],
                "name": "string",
                "packageCleanup": boolean,
                "rebootAfterUse": boolean
            },
            "labels": [ "string" ],
            "status": "string",
            "udid": "string"
        }
    ],
    "manufacturer": "string",
    "memory": number,
    "model": "string",
    "modelId": "string",
    "name": "string",
    "os": "string",
    "platform": "string",
    "radio": "string",
    "remoteAccessEnabled": boolean,
    "remoteDebugEnabled": boolean,
    "resolution": {
        "height": number,
        "width": number
    }
},

```

```
"deviceMinutes": {
  "metered": number,
  "total": number,
  "unmetered": number
},
"deviceProxy": {
  "host": "string",
  "port": number
},
"deviceUdid": "string",
"endpoint": "string",
"endpoints": {
  "interactiveEndpoint": "string",
  "remoteDriverEndpoint": "string"
},
"instanceArn": "string",
"interactionMode": "string",
"message": "string",
"name": "string",
"result": "string",
"skipAppResign": boolean,
"started": number,
"status": "string",
"stopped": number,
"vpcConfig": {
  "securityGroupIds": [ "string" ],
  "subnetIds": [ "string" ],
  "vpcId": "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

remoteAccessSession

A container that describes the remote access session when the request to create a remote access session is sent.

Type: [RemoteAccessSession](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

CreateTestGridProject

Creates a Selenium testing project. Projects are used to track [TestGridSession](#) instances.

Request Syntax

```
{
  "description": "string",
  "name": "string",
  "vpcConfig": {
    "securityGroupIds": [ "string" ],
    "subnetIds": [ "string" ],
    "vpcId": "string"
  }
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[description](#)

Human-readable description of the project.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `.*\S.*`

Required: No

[name](#)

Human-readable name of the Selenium testing project.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `.*\S.*`

Required: Yes

vpcConfig

The VPC security groups and subnets that are attached to a project.

Type: [TestGridVpcConfig](#) object

Required: No

Response Syntax

```
{
  "testGridProject": {
    "arn": "string",
    "created": number,
    "description": "string",
    "name": "string",
    "vpcConfig": {
      "securityGroupIds": [ "string" ],
      "subnetIds": [ "string" ],
      "vpcId": "string"
    }
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

testGridProject

ARN of the Selenium testing project that was created.

Type: [TestGridProject](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

InternalServiceException

An internal exception was raised in the service. Contact aws-devicefarm-support@amazon.com if you see this error.

HTTP Status Code: 500

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)

- [AWS SDK for Ruby V3](#)

CreateTestGridUrl

Creates a signed, short-term URL that can be passed to a Selenium RemoteWebDriver constructor.

Request Syntax

```
{  
  "expiresInSeconds": number,  
  "projectArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

expiresInSeconds

Lifetime, in seconds, of the URL.

Type: Integer

Valid Range: Minimum value of 60. Maximum value of 86400.

Required: Yes

projectArn

ARN (from [CreateTestGridProject](#) or [ListTestGridProjects](#)) to associate with the short-term URL.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Syntax

```
{
```

```
"expires": number,  
"url": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[expires](#)

The number of seconds the URL from [CreateTestGridUrl:url](#) stays active.

Type: Timestamp

[url](#)

A signed URL, expiring in [CreateTestGridUrl:expiresInSeconds](#) seconds, to be passed to a RemoteWebDriver.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

InternalServiceException

An internal exception was raised in the service. Contact aws-devicefarm-support@amazon.com if you see this error.

HTTP Status Code: 500

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

CreateUpload

Uploads an app or test scripts.

Request Syntax

```
{  
  "contentType": "string",  
  "name": "string",  
  "projectArn": "string",  
  "type": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

contentType

The upload's content type (for example, `application/octet-stream`).

Type: String

Length Constraints: Minimum length of 0. Maximum length of 64.

Required: No

name

The upload's file name. The name should not contain any forward slashes (/). If you are uploading an iOS app, the file name must end with the `.ipa` extension. If you are uploading an Android app, the file name must end with the `.apk` extension. For all others, the file name must end with the `.zip` file extension.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: Yes

projectArn

The ARN of the project for the upload.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: Yes

type

The upload's upload type.

Must be one of the following values:

- ANDROID_APP
- IOS_APP
- WEB_APP
- EXTERNAL_DATA
- APPIUM_JAVA_JUNIT_TEST_PACKAGE
- APPIUM_JAVA_TESTNG_TEST_PACKAGE
- APPIUM_PYTHON_TEST_PACKAGE
- APPIUM_NODE_TEST_PACKAGE
- APPIUM_RUBY_TEST_PACKAGE
- APPIUM_WEB_JAVA_JUNIT_TEST_PACKAGE
- APPIUM_WEB_JAVA_TESTNG_TEST_PACKAGE
- APPIUM_WEB_PYTHON_TEST_PACKAGE
- APPIUM_WEB_NODE_TEST_PACKAGE
- APPIUM_WEB_RUBY_TEST_PACKAGE
- INSTRUMENTATION_TEST_PACKAGE
- XCTEST_TEST_PACKAGE
- XCTEST_UI_TEST_PACKAGE

- `APPIUM_JAVA_JUNIT_TEST_SPEC`
- `APPIUM_JAVA_TESTNG_TEST_SPEC`
- `APPIUM_PYTHON_TEST_SPEC`
- `APPIUM_NODE_TEST_SPEC`
- `APPIUM_RUBY_TEST_SPEC`
- `APPIUM_WEB_JAVA_JUNIT_TEST_SPEC`
- `APPIUM_WEB_JAVA_TESTNG_TEST_SPEC`
- `APPIUM_WEB_PYTHON_TEST_SPEC`
- `APPIUM_WEB_NODE_TEST_SPEC`
- `APPIUM_WEB_RUBY_TEST_SPEC`
- `INSTRUMENTATION_TEST_SPEC`
- `XCTEST_UI_TEST_SPEC`

If you call `CreateUpload` with `WEB_APP` specified, AWS Device Farm throws an `ArgumentException` error.

Type: String

Valid Values: `ANDROID_APP` | `IOS_APP` | `WEB_APP` | `EXTERNAL_DATA` | `APPIUM_JAVA_JUNIT_TEST_PACKAGE` | `APPIUM_JAVA_TESTNG_TEST_PACKAGE` | `APPIUM_PYTHON_TEST_PACKAGE` | `APPIUM_NODE_TEST_PACKAGE` | `APPIUM_RUBY_TEST_PACKAGE` | `APPIUM_WEB_JAVA_JUNIT_TEST_PACKAGE` | `APPIUM_WEB_JAVA_TESTNG_TEST_PACKAGE` | `APPIUM_WEB_PYTHON_TEST_PACKAGE` | `APPIUM_WEB_NODE_TEST_PACKAGE` | `APPIUM_WEB_RUBY_TEST_PACKAGE` | `CALABASH_TEST_PACKAGE` | `INSTRUMENTATION_TEST_PACKAGE` | `UIAUTOMATION_TEST_PACKAGE` | `UIAUTOMATOR_TEST_PACKAGE` | `XCTEST_TEST_PACKAGE` | `XCTEST_UI_TEST_PACKAGE` | `APPIUM_JAVA_JUNIT_TEST_SPEC` | `APPIUM_JAVA_TESTNG_TEST_SPEC` | `APPIUM_PYTHON_TEST_SPEC` | `APPIUM_NODE_TEST_SPEC` | `APPIUM_RUBY_TEST_SPEC` | `APPIUM_WEB_JAVA_JUNIT_TEST_SPEC` | `APPIUM_WEB_JAVA_TESTNG_TEST_SPEC` | `APPIUM_WEB_PYTHON_TEST_SPEC` | `APPIUM_WEB_NODE_TEST_SPEC` | `APPIUM_WEB_RUBY_TEST_SPEC` | `INSTRUMENTATION_TEST_SPEC` | `XCTEST_UI_TEST_SPEC`

Required: Yes

Response Syntax

```
{
  "upload": {
    "arn": "string",
    "category": "string",
    "contentType": "string",
    "created": number,
    "message": "string",
    "metadata": "string",
    "name": "string",
    "status": "string",
    "type": "string",
    "url": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

upload

The newly created upload.

Type: [Upload](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

CreateVPCEConfiguration

Creates a configuration record in Device Farm for your Amazon Virtual Private Cloud (VPC) endpoint.

Request Syntax

```
{  
  "serviceDnsName": "string",  
  "vpceConfigurationDescription": "string",  
  "vpceConfigurationName": "string",  
  "vpceServiceName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[serviceDnsName](#)

The DNS name of the service running in your VPC that you want Device Farm to test.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Required: Yes

[vpceConfigurationDescription](#)

An optional description that provides details about your VPC endpoint configuration.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Required: No

[vpceConfigurationName](#)

The friendly name you give to your VPC endpoint configuration, to manage your configurations more easily.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: Yes

vpceServiceName

The name of the VPC endpoint service running in your AWS account that you want Device Farm to test.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Required: Yes

Response Syntax

```
{
  "vpceConfiguration": {
    "arn": "string",
    "serviceDnsName": "string",
    "vpceConfigurationDescription": "string",
    "vpceConfigurationName": "string",
    "vpceServiceName": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

vpceConfiguration

An object that contains information about your VPC endpoint configuration.

Type: VPCEConfiguration object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DeleteDevicePool

Deletes a device pool given the pool ARN. Does not allow deletion of curated pools owned by the system.

Request Syntax

```
{  
  "arn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

Represents the Amazon Resource Name (ARN) of the Device Farm device pool to delete.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DeleteInstanceProfile

Deletes a profile that can be applied to one or more private device instances.

Request Syntax

```
{  
  "arn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The Amazon Resource Name (ARN) of the instance profile you are requesting to delete.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DeleteNetworkProfile

Deletes a network profile.

Request Syntax

```
{  
  "arn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The ARN of the network profile to delete.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DeleteProject

Deletes an AWS Device Farm project, given the project ARN. You cannot delete a project if it has an active run or session.

Important

You cannot undo this operation.

Request Syntax

```
{  
  "arn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

Represents the Amazon Resource Name (ARN) of the Device Farm project to delete.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DeleteRemoteAccessSession

Deletes a completed remote access session and its results. You cannot delete a remote access session if it is still active.

Important

You cannot undo this operation.

Request Syntax

```
{  
  "arn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The Amazon Resource Name (ARN) of the session for which you want to delete remote access.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DeleteRun

Deletes the run, given the run ARN. You cannot delete a run if it is still active.

Important

You cannot undo this operation.

Request Syntax

```
{  
  "arn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The Amazon Resource Name (ARN) for the run to delete.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DeleteTestGridProject

Deletes a Selenium testing project and all content generated under it. You cannot delete a project if it has active sessions.

Important

You cannot undo this operation.

Request Syntax

```
{
  "projectArn": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

projectArn

The ARN of the project to delete, from [CreateTestGridProject](#) or [ListTestGridProjects](#).

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

CannotDeleteException

The requested object could not be deleted.

HTTP Status Code: 400

InternalServiceException

An internal exception was raised in the service. Contact aws-devicefarm-support@amazon.com if you see this error.

HTTP Status Code: 500

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DeleteUpload

Deletes an upload given the upload ARN.

Request Syntax

```
{  
  "arn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

Represents the Amazon Resource Name (ARN) of the Device Farm upload to delete.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DeleteVPCEConfiguration

Deletes a configuration for your Amazon Virtual Private Cloud (VPC) endpoint.

Request Syntax

```
{
  "arn": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The Amazon Resource Name (ARN) of the VPC endpoint configuration you want to delete.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

InvalidOperationException

There was an error with the update request, or you do not have sufficient permissions to update this VPC endpoint configuration.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetAccountSettings

Returns the number of unmetered iOS or unmetered Android devices that have been purchased by the account.

Response Syntax

```
{
  "accountSettings": {
    "awsAccountNumber": "string",
    "defaultJobTimeoutMinutes": number,
    "maxJobTimeoutMinutes": number,
    "maxSlots": {
      "string" : number
    },
    "skipAppResign": boolean,
    "trialMinutes": {
      "remaining": number,
      "total": number
    },
    "unmeteredDevices": {
      "string" : number
    },
    "unmeteredRemoteAccessDevices": {
      "string" : number
    }
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

accountSettings

The account settings.

Type: [AccountSettings](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetDevice

Gets information about a unique device type.

Request Syntax

```
{
  "arn": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The device type's ARN.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Syntax

```
{
  "device": {
    "arn": "string",
    "availability": "string",
    "carrier": "string",
    "cpu": {
      "architecture": "string",
      "clock": number,
      "frequency": "string"
    },
    "fleetName": "string",
  },
}
```

```

    "fleetType": "string",
    "formFactor": "string",
    "heapSize": number,
    "image": "string",
    "instances": [
      {
        "arn": "string",
        "deviceArn": "string",
        "instanceProfile": {
          "arn": "string",
          "description": "string",
          "excludeAppPackagesFromCleanup": [ "string" ],
          "name": "string",
          "packageCleanup": boolean,
          "rebootAfterUse": boolean
        },
        "labels": [ "string" ],
        "status": "string",
        "udid": "string"
      }
    ],
    "manufacturer": "string",
    "memory": number,
    "model": "string",
    "modelId": "string",
    "name": "string",
    "os": "string",
    "platform": "string",
    "radio": "string",
    "remoteAccessEnabled": boolean,
    "remoteDebugEnabled": boolean,
    "resolution": {
      "height": number,
      "width": number
    }
  }
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

device

An object that contains information about the requested device.

Type: [Device](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetDeviceInstance

Returns information about a device instance that belongs to a private device fleet.

Request Syntax

```
{  
  "arn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The Amazon Resource Name (ARN) of the instance you're requesting information about.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Syntax

```
{  
  "deviceInstance": {  
    "arn": "string",  
    "deviceArn": "string",  
    "instanceProfile": {  
      "arn": "string",  
      "description": "string",  
      "excludeAppPackagesFromCleanup": [ "string" ],  
      "name": "string",  
      "packageCleanup": boolean,  
    },  
  },  
}
```

```
    "rebootAfterUse": boolean
  },
  "labels": [ "string" ],
  "status": "string",
  "udid": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[deviceInstance](#)

An object that contains information about your device instance.

Type: [DeviceInstance](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetDevicePool

Gets information about a device pool.

Request Syntax

```
{  
  "arn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The device pool's ARN.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Syntax

```
{  
  "devicePool": {  
    "arn": "string",  
    "description": "string",  
    "maxDevices": number,  
    "name": "string",  
    "rules": [  
      {  
        "attribute": "string",  
        "operator": "string",  
        "value": "string"  
      }  
    ]  
  }  
}
```

```
    }  
  ],  
  "type": "string"  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

devicePool

An object that contains information about the requested device pool.

Type: [DevicePool](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetDevicePoolCompatibility

Gets information about compatibility with a device pool.

Request Syntax

```
{
  "appArn": "string",
  "configuration": {
    "auxiliaryApps": [ "string" ],
    "billingMethod": "string",
    "customerArtifactPaths": {
      "androidPaths": [ "string" ],
      "deviceHostPaths": [ "string" ],
      "iosPaths": [ "string" ]
    },
    "deviceProxy": {
      "host": "string",
      "port": number
    },
    "environmentVariables": [
      {
        "name": "string",
        "value": "string"
      }
    ],
    "executionRoleArn": "string",
    "extraDataPackageArn": "string",
    "insightsTypes": [ "string" ],
    "locale": "string",
    "location": {
      "latitude": number,
      "longitude": number
    },
    "networkProfileArn": "string",
    "radios": {
      "bluetooth": boolean,
      "gps": boolean,
      "nfc": boolean,
      "wifi": boolean
    },
    "vpceConfigurationArns": [ "string" ]
  },
}
```

```
{
  "devicePoolArn": "string",
  "projectArn": "string",
  "test": {
    "filter": "string",
    "parameters": {
      "string": "string"
    },
    "testPackageArn": "string",
    "testSpecArn": "string",
    "type": "string"
  },
  "testType": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[appArn](#)

The ARN of the app that is associated with the specified device pool.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: No

[configuration](#)

An object that contains information about the settings for a run.

Type: [ScheduleRunConfiguration](#) object

Required: No

[devicePoolArn](#)

The device pool's ARN.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: Yes

projectArn

The ARN of the project for which you want to check device pool compatibility.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

test

Information about the uploaded test to be run against the device pool.

Type: [ScheduleRunTest](#) object

Required: No

testType

The test type for the specified device pool.

Allowed values include the following:

- BUILTIN_FUZZ.
- APPIUM_JAVA_JUNIT.
- APPIUM_JAVA_TESTNG.
- APPIUM_PYTHON.
- APPIUM_NODE.
- APPIUM_RUBY.
- APPIUM_WEB_JAVA_JUNIT.
- APPIUM_WEB_JAVA_TESTNG.
- APPIUM_WEB_PYTHON.
- APPIUM_WEB_NODE.
- APPIUM_WEB_RUBY.

- INSTRUMENTATION.
- XCTEST.
- XCTEST_UI.

Type: String

Valid Values: BUILTIN_FUZZ | APPIUM_JAVA_JUNIT | APPIUM_JAVA_TESTNG | APPIUM_PYTHON | APPIUM_NODE | APPIUM_RUBY | APPIUM_WEB_JAVA_JUNIT | APPIUM_WEB_JAVA_TESTNG | APPIUM_WEB_PYTHON | APPIUM_WEB_NODE | APPIUM_WEB_RUBY | INSTRUMENTATION | XCTEST | XCTEST_UI

Required: No

Response Syntax

```
{
  "compatibleDevices": [
    {
      "compatible": boolean,
      "device": {
        "arn": "string",
        "availability": "string",
        "carrier": "string",
        "cpu": {
          "architecture": "string",
          "clock": number,
          "frequency": "string"
        },
        "fleetName": "string",
        "fleetType": "string",
        "formFactor": "string",
        "heapSize": number,
        "image": "string",
        "instances": [
          {
            "arn": "string",
            "deviceArn": "string",
            "instanceProfile": {
              "arn": "string",
              "description": "string",
              "excludeAppPackagesFromCleanup": [ "string" ],

```

```
        "name": "string",
        "packageCleanup": boolean,
        "rebootAfterUse": boolean
    },
    "labels": [ "string" ],
    "status": "string",
    "udid": "string"
}
],
"manufacturer": "string",
"memory": number,
"model": "string",
"modelId": "string",
"name": "string",
"os": "string",
"platform": "string",
"radio": "string",
"remoteAccessEnabled": boolean,
"remoteDebugEnabled": boolean,
"resolution": {
    "height": number,
    "width": number
}
},
"incompatibilityMessages": [
    {
        "message": "string",
        "type": "string"
    }
]
}
],
"incompatibleDevices": [
    {
        "compatible": boolean,
        "device": {
            "arn": "string",
            "availability": "string",
            "carrier": "string",
            "cpu": {
                "architecture": "string",
                "clock": number,
                "frequency": "string"
            }
        },
    },
]
```

```

    "fleetName": "string",
    "fleetType": "string",
    "formFactor": "string",
    "heapSize": number,
    "image": "string",
    "instances": [
      {
        "arn": "string",
        "deviceArn": "string",
        "instanceProfile": {
          "arn": "string",
          "description": "string",
          "excludeAppPackagesFromCleanup": [ "string" ],
          "name": "string",
          "packageCleanup": boolean,
          "rebootAfterUse": boolean
        },
        "labels": [ "string" ],
        "status": "string",
        "udid": "string"
      }
    ],
    "manufacturer": "string",
    "memory": number,
    "model": "string",
    "modelId": "string",
    "name": "string",
    "os": "string",
    "platform": "string",
    "radio": "string",
    "remoteAccessEnabled": boolean,
    "remoteDebugEnabled": boolean,
    "resolution": {
      "height": number,
      "width": number
    }
  },
  "incompatibilityMessages": [
    {
      "message": "string",
      "type": "string"
    }
  ]
}

```

```
]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

compatibleDevices

Information about compatible devices.

Type: Array of [DevicePoolCompatibilityResult](#) objects

incompatibleDevices

Information about incompatible devices.

Type: Array of [DevicePoolCompatibilityResult](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetInstanceProfile

Returns information about the specified instance profile.

Request Syntax

```
{  
  "arn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The Amazon Resource Name (ARN) of an instance profile.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Syntax

```
{  
  "instanceProfile": {  
    "arn": "string",  
    "description": "string",  
    "excludeAppPackagesFromCleanup": [ "string" ],  
    "name": "string",  
    "packageCleanup": boolean,  
    "rebootAfterUse": boolean  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

instanceProfile

An object that contains information about an instance profile.

Type: [InstanceProfile](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetJob

Gets information about a job.

Request Syntax

```
{
  "arn": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The job's ARN.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Syntax

```
{
  "job": {
    "arn": "string",
    "counters": {
      "errored": number,
      "failed": number,
      "passed": number,
      "skipped": number,
      "stopped": number,
      "total": number,
      "warned": number
    },
  },
}
```

```
"created": number,
"device": {
  "arn": "string",
  "availability": "string",
  "carrier": "string",
  "cpu": {
    "architecture": "string",
    "clock": number,
    "frequency": "string"
  },
  "fleetName": "string",
  "fleetType": "string",
  "formFactor": "string",
  "heapSize": number,
  "image": "string",
  "instances": [
    {
      "arn": "string",
      "deviceArn": "string",
      "instanceProfile": {
        "arn": "string",
        "description": "string",
        "excludeAppPackagesFromCleanup": [ "string" ],
        "name": "string",
        "packageCleanup": boolean,
        "rebootAfterUse": boolean
      },
      "labels": [ "string" ],
      "status": "string",
      "udid": "string"
    }
  ],
  "manufacturer": "string",
  "memory": number,
  "model": "string",
  "modelId": "string",
  "name": "string",
  "os": "string",
  "platform": "string",
  "radio": "string",
  "remoteAccessEnabled": boolean,
  "remoteDebugEnabled": boolean,
  "resolution": {
    "height": number,
```

```

        "width": number
    }
},
"deviceMinutes": {
    "metered": number,
    "total": number,
    "unmetered": number
},
"insights": {
    "status": "string",
    "testReport": {
        "message": "string",
        "metrics": {
            "medianTestExecutionDurationSeconds": number,
            "testsErrored": number,
            "testsFailed": number,
            "testsOther": number,
            "testsPassed": number,
            "testsPassedPercentage": number,
            "testsSkipped": number,
            "testsTotal": number,
            "totalTestExecutionDurationSeconds": number
        }
    },
    "testDetailsUrl": "string"
}
},
"instanceArn": "string",
"message": "string",
"name": "string",
"result": "string",
"started": number,
"status": "string",
"stopped": number,
"type": "string",
"videoCapture": boolean,
"videoEndpoint": "string"
}
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

job

An object that contains information about the requested job.

Type: [Job](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetNetworkProfile

Returns information about a network profile.

Request Syntax

```
{  
  "arn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The ARN of the network profile to return information about.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Syntax

```
{  
  "networkProfile": {  
    "arn": "string",  
    "description": "string",  
    "downlinkBandwidthBits": number,  
    "downlinkDelayMs": number,  
    "downlinkJitterMs": number,  
    "downlinkLossPercent": number,  
    "name": "string",  
    "type": "string",  
    "uplinkBandwidthBits": number,  
  }
```

```
"uplinkDelayMs": number,  
"uplinkJitterMs": number,  
"uplinkLossPercent": number  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[networkProfile](#)

The network profile.

Type: [NetworkProfile](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetOfferingStatus

Gets the current status and future status of all offerings purchased by an AWS account. The response indicates how many offerings are currently available and the offerings that will be available in the next period. The API returns a `NotEligible` error if the user is not permitted to invoke the operation. If you must be able to invoke this operation, contact aws-devicefarm-support@amazon.com.

Request Syntax

```
{  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

nextToken

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

Response Syntax

```
{  
  "current": {  
    "string" : {  
      "effectiveOn": number,  
      "offering": {  
        "description": "string",  
        "id": "string",  
        "platform": "string",
```

```
    "recurringCharges": [
      {
        "cost": {
          "amount": number,
          "currencyCode": "string"
        },
        "frequency": "string"
      }
    ],
    "type": "string"
  },
  "quantity": number,
  "type": "string"
}
},
"nextPeriod": {
  "string" : {
    "effectiveOn": number,
    "offering": {
      "description": "string",
      "id": "string",
      "platform": "string",
      "recurringCharges": [
        {
          "cost": {
            "amount": number,
            "currencyCode": "string"
          },
          "frequency": "string"
        }
      ],
      "type": "string"
    },
    "quantity": number,
    "type": "string"
  }
},
"nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

current

When specified, gets the offering status for the current period.

Type: String to [OfferingStatus](#) object map

Key Length Constraints: Minimum length of 32.

nextPeriod

When specified, gets the offering status for the next period.

Type: String to [OfferingStatus](#) object map

Key Length Constraints: Minimum length of 32.

nextToken

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotEligibleException

Exception gets thrown when a user is not eligible to perform the specified transaction.

message

The HTTP response code of a Not Eligible exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

Examples

Example

The following example checks the current and renewal status.

Sample Response

```
{  
  "current": {
```

```
    "offering-id-ios": {
      "offering": {
        "platform": "IOS",
        "type": "RECURRING",
        "id": "offering-id-ios",
        "description": "iOS Unmetered Device Slot"
      },
      "quantity": 1
    },
    "nextPeriod": {
      "offering-id-ios": {
        "effectiveOn": 1459468800.0,
        "offering": {
          "platform": "IOS",
          "type": "RECURRING",
          "id": "offering-id-ios",
          "description": "iOS Unmetered Device Slot"
        },
        "quantity": 1
      }
    }
  }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetProject

Gets information about a project.

Request Syntax

```
{  
  "arn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The project's ARN.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Syntax

```
{  
  "project": {  
    "arn": "string",  
    "created": number,  
    "defaultJobTimeoutMinutes": number,  
    "environmentVariables": [  
      {  
        "name": "string",  
        "value": "string"  
      }  
    ]  
  }  
}
```

```
    ],  
    "executionRoleArn": "string",  
    "name": "string",  
    "vpcConfig": {  
        "securityGroupIds": [ "string" ],  
        "subnetIds": [ "string" ],  
        "vpcId": "string"  
    }  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

project

The project to get information about.

Type: [Project](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetRemoteAccessSession

Returns a link to a currently running remote access session.

Request Syntax

```
{  
  "arn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The Amazon Resource Name (ARN) of the remote access session about which you want to get session information.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Syntax

```
{  
  "remoteAccessSession": {  
    "appUpload": "string",  
    "arn": "string",  
    "billingMethod": "string",  
    "created": number,  
    "device": {  
      "arn": "string",  
      "availability": "string",  
      "carrier": "string",  
      "cpu": {
```

```

    "architecture": "string",
    "clock": number,
    "frequency": "string"
  },
  "fleetName": "string",
  "fleetType": "string",
  "formFactor": "string",
  "heapSize": number,
  "image": "string",
  "instances": [
    {
      "arn": "string",
      "deviceArn": "string",
      "instanceProfile": {
        "arn": "string",
        "description": "string",
        "excludeAppPackagesFromCleanup": [ "string" ],
        "name": "string",
        "packageCleanup": boolean,
        "rebootAfterUse": boolean
      },
      "labels": [ "string" ],
      "status": "string",
      "udid": "string"
    }
  ],
  "manufacturer": "string",
  "memory": number,
  "model": "string",
  "modelId": "string",
  "name": "string",
  "os": "string",
  "platform": "string",
  "radio": "string",
  "remoteAccessEnabled": boolean,
  "remoteDebugEnabled": boolean,
  "resolution": {
    "height": number,
    "width": number
  }
},
"deviceMinutes": {
  "metered": number,
  "total": number,

```

```
    "unmetered": number
  },
  "deviceProxy": {
    "host": "string",
    "port": number
  },
  "deviceUdid": "string",
  "endpoint": "string",
  "endpoints": {
    "interactiveEndpoint": "string",
    "remoteDriverEndpoint": "string"
  },
  "instanceArn": "string",
  "interactionMode": "string",
  "message": "string",
  "name": "string",
  "result": "string",
  "skipAppResign": boolean,
  "started": number,
  "status": "string",
  "stopped": number,
  "vpcConfig": {
    "securityGroupIds": [ "string " ],
    "subnetIds": [ "string " ],
    "vpcId": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[remoteAccessSession](#)

A container that lists detailed information about the remote access session.

Type: [RemoteAccessSession](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetRun

Gets information about a run.

Request Syntax

```
{  
  "arn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The run's ARN.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Syntax

```
{  
  "run": {  
    "appUpload": "string",  
    "arn": "string",  
    "billingMethod": "string",  
    "completedJobs": number,  
    "counters": {  
      "errored": number,  
      "failed": number,  
      "passed": number,  
      "skipped": number,  
      "stopped": number,  
    }  
  }  
}
```

```
    "total": number,
    "warned": number
  },
  "created": number,
  "customerArtifactPaths": {
    "androidPaths": [ "string" ],
    "deviceHostPaths": [ "string" ],
    "iosPaths": [ "string" ]
  },
  "deviceMinutes": {
    "metered": number,
    "total": number,
    "unmetered": number
  },
  "devicePoolArn": "string",
  "deviceProxy": {
    "host": "string",
    "port": number
  },
  "deviceSelectionResult": {
    "filters": [
      {
        "attribute": "string",
        "operator": "string",
        "values": [ "string" ]
      }
    ],
    "matchedDevicesCount": number,
    "maxDevices": number
  },
  "environmentVariables": [
    {
      "name": "string",
      "value": "string"
    }
  ],
  "eventCount": number,
  "executionRoleArn": "string",
  "insights": {
    "jobReport": {
      "jobDetailsUrl": "string",
      "message": "string",
      "metrics": {
        "averageJobExecutionDurationSeconds": number,
```

```
        "jobsErrored": number,
        "jobsFailed": number,
        "jobsPassed": number,
        "jobsPassedPercentage": number,
        "jobsSkipped": number,
        "jobsStopped": number,
        "jobsTotal": number,
        "medianJobExecutionDurationSeconds": number,
        "totalJobExecutionDurationSeconds": number
    }
},
    "status": "string"
},
    "insightsTypes": [ "string" ],
    "jobTimeoutMinutes": number,
    "locale": "string",
    "location": {
        "latitude": number,
        "longitude": number
    },
    "message": "string",
    "name": "string",
    "networkProfile": {
        "arn": "string",
        "description": "string",
        "downlinkBandwidthBits": number,
        "downlinkDelayMs": number,
        "downlinkJitterMs": number,
        "downlinkLossPercent": number,
        "name": "string",
        "type": "string",
        "uplinkBandwidthBits": number,
        "uplinkDelayMs": number,
        "uplinkJitterMs": number,
        "uplinkLossPercent": number
    },
    "parsingResultUrl": "string",
    "platform": "string",
    "radios": {
        "bluetooth": boolean,
        "gps": boolean,
        "nfc": boolean,
        "wifi": boolean
    },
},
```

```
"result": "string",
"resultCode": "string",
"seed": number,
"skipAppResign": boolean,
"started": number,
"status": "string",
"stopped": number,
"testSpecArn": "string",
"totalJobs": number,
"type": "string",
"vpcConfig": {
  "securityGroupIds": [ "string" ],
  "subnetIds": [ "string" ],
  "vpcId": "string"
},
"webUrl": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

run

The run to get results from.

Type: [Run](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetSuite

Gets information about a suite.

Request Syntax

```
{  
  "arn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The suite's ARN.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Syntax

```
{  
  "suite": {  
    "arn": "string",  
    "counters": {  
      "errored": number,  
      "failed": number,  
      "passed": number,  
      "skipped": number,  
      "stopped": number,  
      "total": number,  
    }  
  }  
}
```

```
    "warned": number
  },
  "created": number,
  "deviceMinutes": {
    "metered": number,
    "total": number,
    "unmetered": number
  },
  "message": "string",
  "name": "string",
  "result": "string",
  "started": number,
  "status": "string",
  "stopped": number,
  "type": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

suite

A collection of one or more tests.

Type: [Suite](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetTest

Gets information about a test.

Request Syntax

```
{  
  "arn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The test's ARN.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Syntax

```
{  
  "test": {  
    "arn": "string",  
    "counters": {  
      "errored": number,  
      "failed": number,  
      "passed": number,  
      "skipped": number,  
      "stopped": number,  
      "total": number,  
    }  
  }  
}
```

```
    "warned": number
  },
  "created": number,
  "deviceMinutes": {
    "metered": number,
    "total": number,
    "unmetered": number
  },
  "message": "string",
  "name": "string",
  "result": "string",
  "started": number,
  "status": "string",
  "stopped": number,
  "type": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

test

A test condition that is evaluated.

Type: [Test](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetTestGridProject

Retrieves information about a Selenium testing project.

Request Syntax

```
{  
  "projectArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[projectArn](#)

The ARN of the Selenium testing project, from either [CreateTestGridProject](#) or [ListTestGridProjects](#).

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Syntax

```
{  
  "testGridProject": {  
    "arn": "string",  
    "created": number,  
    "description": "string",  
    "name": "string",  
    "vpcConfig": {  
      "securityGroupIds": [ "string" ],  
      "subnetIds": [ "string" ],  
      "vpcId": "string"  
    }  
  }  
}
```

```
}  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

testGridProject

A [TestGridProject](#).

Type: [TestGridProject](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

InternalServiceException

An internal exception was raised in the service. Contact aws-devicefarm-support@amazon.com if you see this error.

HTTP Status Code: 500

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetTestGridSession

A session is an instance of a browser created through a `RemoteWebDriver` with the URL from [CreateTestGridUrl:url](#). You can use the following to look up sessions:

- The session ARN ([GetTestGridSession:sessionArn](#)).
- The project ARN and a session ID ([GetTestGridSession:projectArn](#) and [GetTestGridSession:sessionId](#)).

Request Syntax

```
{
  "projectArn": "string",
  "sessionArn": "string",
  "sessionId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[projectArn](#)

The ARN for the project that this session belongs to. See [CreateTestGridProject](#) and [ListTestGridProjects](#).

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

[sessionArn](#)

An ARN that uniquely identifies a [TestGridSession](#).

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: No

sessionId

An ID associated with this session.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: .*\\S.*

Required: No

Response Syntax

```
{
  "testGridSession": {
    "arn": "string",
    "billingMinutes": number,
    "created": number,
    "ended": number,
    "seleniumProperties": "string",
    "status": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

testGridSession

The TestGridSession that was requested.

Type: [TestGridSession](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

InternalServiceException

An internal exception was raised in the service. Contact aws-devicefarm-support@amazon.com if you see this error.

HTTP Status Code: 500

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetUpload

Gets information about an upload.

Request Syntax

```
{  
  "arn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The upload's ARN.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Syntax

```
{  
  "upload": {  
    "arn": "string",  
    "category": "string",  
    "contentType": "string",  
    "created": number,  
    "message": "string",  
    "metadata": "string",  
    "name": "string",  
    "status": "string",  
  }  
}
```

```
    "type": "string",  
    "url": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

upload

An app or a set of one or more tests to upload or that have been uploaded.

Type: [Upload](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetVPCEConfiguration

Returns information about the configuration settings for your Amazon Virtual Private Cloud (VPC) endpoint.

Request Syntax

```
{  
  "arn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The Amazon Resource Name (ARN) of the VPC endpoint configuration you want to describe.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*

Required: Yes

Response Syntax

```
{  
  "vpceConfiguration": {  
    "arn": "string",  
    "serviceDnsName": "string",  
    "vpceConfigurationDescription": "string",  
    "vpceConfigurationName": "string",  
    "vpceServiceName": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

vpceConfiguration

An object that contains information about your VPC endpoint configuration.

Type: [VPCEConfiguration](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

InstallToRemoteAccessSession

Installs an application to the device in a remote access session. For Android applications, the file must be in .apk format. For iOS applications, the file must be in .ipa format.

Request Syntax

```
{  
  "appArn": "string",  
  "remoteAccessSessionArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

appArn

The ARN of the app about which you are requesting information.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

remoteAccessSessionArn

The Amazon Resource Name (ARN) of the remote access session about which you are requesting information.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Syntax

```
{
  "appUpload": {
    "arn": "string",
    "category": "string",
    "contentType": "string",
    "created": number,
    "message": "string",
    "metadata": "string",
    "name": "string",
    "status": "string",
    "type": "string",
    "url": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[appUpload](#)

An app to upload or that has been uploaded.

Type: [Upload](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListArtifacts

Gets information about artifacts.

Request Syntax

```
{
  "arn": "string",
  "nextToken": "string",
  "type": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The run, job, suite, or test ARN.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

nextToken

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

type

The artifacts' type.

Allowed values include:

- FILE
- LOG
- SCREENSHOT

Type: String

Valid Values: SCREENSHOT | FILE | LOG

Required: Yes

Response Syntax

```
{
  "artifacts": [
    {
      "arn": "string",
      "extension": "string",
      "name": "string",
      "type": "string",
      "url": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

artifacts

Information about the artifacts.

Type: Array of [Artifact](#) objects

nextToken

If the number of items that are returned is significantly large, this is an identifier that is also returned. It can be used in a subsequent call to this operation to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListDeviceInstances

Returns information about the private device instances associated with one or more AWS accounts.

Request Syntax

```
{  
  "maxResults": number,  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[maxResults](#)

An integer that specifies the maximum number of items you want to return in the API response.

Type: Integer

Required: No

[nextToken](#)

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

Response Syntax

```
{  
  "deviceInstances": [  
    {  
      ...  
    }  
  ]  
}
```

```
{
  "arn": "string",
  "deviceArn": "string",
  "instanceProfile": {
    "arn": "string",
    "description": "string",
    "excludeAppPackagesFromCleanup": [ "string" ],
    "name": "string",
    "packageCleanup": boolean,
    "rebootAfterUse": boolean
  },
  "labels": [ "string" ],
  "status": "string",
  "udid": "string"
},
],
"nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

deviceInstances

An object that contains information about your device instances.

Type: Array of [DeviceInstance](#) objects

nextToken

An identifier that can be used in the next call to this operation to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListDevicePools

Gets information about device pools.

Request Syntax

```
{  
  "arn": "string",  
  "nextToken": "string",  
  "type": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The project ARN.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*

Required: Yes

nextToken

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

type

The device pools' type.

Allowed values include:

- **CURATED**: A device pool that is created and managed by AWS Device Farm.
- **PRIVATE**: A device pool that is created and managed by the device pool developer.

Type: String

Valid Values: CURATED | PRIVATE

Required: No

Response Syntax

```
{
  "devicePools": [
    {
      "arn": "string",
      "description": "string",
      "maxDevices": number,
      "name": "string",
      "rules": [
        {
          "attribute": "string",
          "operator": "string",
          "value": "string"
        }
      ],
      "type": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

devicePools

Information about the device pools.

Type: Array of [DevicePool](#) objects

nextToken

If the number of items that are returned is significantly large, this is an identifier that is also returned. It can be used in a subsequent call to this operation to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListDevices

Gets information about unique device types.

Request Syntax

```
{
  "arn": "string",
  "filters": [
    {
      "attribute": "string",
      "operator": "string",
      "values": [ "string" ]
    }
  ],
  "nextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The Amazon Resource Name (ARN) of the project.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*

Required: No

filters

Used to select a set of devices. A filter is made up of an attribute, an operator, and one or more values.

- **Attribute:** The aspect of a device such as platform or model used as the selection criteria in a device filter.

Allowed values include:

- **ARN:** The Amazon Resource Name (ARN) of the device (for example, `arn:aws:devicefarm:us-west-2::device:12345Example`).
- **PLATFORM:** The device platform. Valid values are `ANDROID` or `IOS`.
- **OS_VERSION:** The operating system version (for example, `10.3.2`).
- **MODEL:** The device model (for example, `iPad 5th Gen`).
- **AVAILABILITY:** The current availability of the device. Valid values are `AVAILABLE`, `HIGHLY_AVAILABLE`, `BUSY`, or `TEMPORARY_NOT_AVAILABLE`.
- **FORM_FACTOR:** The device form factor. Valid values are `PHONE` or `TABLET`.
- **MANUFACTURER:** The device manufacturer (for example, `Apple`).
- **REMOTE_ACCESS_ENABLED:** Whether the device is enabled for remote access. Valid values are `TRUE` or `FALSE`.
- **REMOTE_DEBUG_ENABLED:** Whether the device is enabled for remote debugging. Valid values are `TRUE` or `FALSE`. Because remote debugging is [no longer supported](#), this attribute is ignored.
- **INSTANCE_ARN:** The Amazon Resource Name (ARN) of the device instance.
- **INSTANCE_LABELS:** The label of the device instance.
- **FLEET_TYPE:** The fleet type. Valid values are `PUBLIC` or `PRIVATE`.
- **Operator:** The filter operator.
 - The `EQUALS` operator is available for every attribute except `INSTANCE_LABELS`.
 - The `CONTAINS` operator is available for the `INSTANCE_LABELS` and `MODEL` attributes.
 - The `IN` and `NOT_IN` operators are available for the `ARN`, `OS_VERSION`, `MODEL`, `MANUFACTURER`, and `INSTANCE_ARN` attributes.
 - The `LESS_THAN`, `GREATER_THAN`, `LESS_THAN_OR_EQUALS`, and `GREATER_THAN_OR_EQUALS` operators are also available for the `OS_VERSION` attribute.
- **Values:** An array of one or more filter values.
 - The `IN` and `NOT_IN` operators take a values array that has one or more elements.
 - The other operators require an array with a single element.
 - In a request, the `AVAILABILITY` attribute takes the following values: `AVAILABLE`, `HIGHLY_AVAILABLE`, `BUSY`, or `TEMPORARY_NOT_AVAILABLE`.

Required: No

nextToken

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

Response Syntax

```
{
  "devices": [
    {
      "arn": "string",
      "availability": "string",
      "carrier": "string",
      "cpu": {
        "architecture": "string",
        "clock": number,
        "frequency": "string"
      },
      "fleetName": "string",
      "fleetType": "string",
      "formFactor": "string",
      "heapSize": number,
      "image": "string",
      "instances": [
        {
          "arn": "string",
          "deviceArn": "string",
          "instanceProfile": {
            "arn": "string",
            "description": "string",
            "excludeAppPackagesFromCleanup": [ "string" ],
            "name": "string",
            "packageCleanup": boolean,
            "rebootAfterUse": boolean
          },

```

```
        "labels": [ "string" ],
        "status": "string",
        "udid": "string"
    }
],
"manufacturer": "string",
"memory": number,
"model": "string",
"modelId": "string",
"name": "string",
"os": "string",
"platform": "string",
"radio": "string",
"remoteAccessEnabled": boolean,
"remoteDebugEnabled": boolean,
"resolution": {
    "height": number,
    "width": number
}
}
],
"nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

devices

Information about the devices.

Type: Array of [Device](#) objects

nextToken

If the number of items that are returned is significantly large, this is an identifier that is also returned. It can be used in a subsequent call to this operation to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListInstanceProfiles

Returns information about all the instance profiles in an AWS account.

Request Syntax

```
{  
  "maxResults": number,  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[maxResults](#)

An integer that specifies the maximum number of items you want to return in the API response.

Type: Integer

Required: No

[nextToken](#)

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

Response Syntax

```
{  
  "instanceProfiles": [  
    {  
      ...  
    }  
  ]  
}
```

```
    "arn": "string",
    "description": "string",
    "excludeAppPackagesFromCleanup": [ "string" ],
    "name": "string",
    "packageCleanup": boolean,
    "rebootAfterUse": boolean
  }
],
"nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[instanceProfiles](#)

An object that contains information about your instance profiles.

Type: Array of [InstanceProfile](#) objects

[nextToken](#)

An identifier that can be used in the next call to this operation to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListJobs

Gets information about jobs for a given test run.

Request Syntax

```
{  
  "arn": "string",  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The run's Amazon Resource Name (ARN).

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

nextToken

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

Response Syntax

```
{
```

```
"jobs": [  
  {  
    "arn": "string",  
    "counters": {  
      "errored": number,  
      "failed": number,  
      "passed": number,  
      "skipped": number,  
      "stopped": number,  
      "total": number,  
      "warned": number  
    },  
    "created": number,  
    "device": {  
      "arn": "string",  
      "availability": "string",  
      "carrier": "string",  
      "cpu": {  
        "architecture": "string",  
        "clock": number,  
        "frequency": "string"  
      },  
      "fleetName": "string",  
      "fleetType": "string",  
      "formFactor": "string",  
      "heapSize": number,  
      "image": "string",  
      "instances": [  
        {  
          "arn": "string",  
          "deviceArn": "string",  
          "instanceProfile": {  
            "arn": "string",  
            "description": "string",  
            "excludeAppPackagesFromCleanup": [ "string" ],  
            "name": "string",  
            "packageCleanup": boolean,  
            "rebootAfterUse": boolean  
          },  
          "labels": [ "string" ],  
          "status": "string",  
          "udid": "string"  
        }  
      ],  
    },  
  ],  
]
```

```
    "manufacturer": "string",
    "memory": number,
    "model": "string",
    "modelId": "string",
    "name": "string",
    "os": "string",
    "platform": "string",
    "radio": "string",
    "remoteAccessEnabled": boolean,
    "remoteDebugEnabled": boolean,
    "resolution": {
      "height": number,
      "width": number
    }
  },
  "deviceMinutes": {
    "metered": number,
    "total": number,
    "unmetered": number
  },
  "insights": {
    "status": "string",
    "testReport": {
      "message": "string",
      "metrics": {
        "medianTestExecutionDurationSeconds": number,
        "testsErrored": number,
        "testsFailed": number,
        "testsOther": number,
        "testsPassed": number,
        "testsPassedPercentage": number,
        "testsSkipped": number,
        "testsTotal": number,
        "totalTestExecutionDurationSeconds": number
      },
      "testDetailsUrl": "string"
    }
  },
  "instanceArn": "string",
  "message": "string",
  "name": "string",
  "result": "string",
  "started": number,
  "status": "string",
```

```
    "stopped": number,
    "type": "string",
    "videoCapture": boolean,
    "videoEndpoint": "string"
  }
],
"nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[jobs](#)

Information about the jobs.

Type: Array of [Job](#) objects

[nextToken](#)

If the number of items that are returned is significantly large, this is an identifier that is also returned. It can be used in a subsequent call to this operation to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListNetworkProfiles

Returns the list of available network profiles.

Request Syntax

```
{  
  "arn": "string",  
  "nextToken": "string",  
  "type": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The Amazon Resource Name (ARN) of the project for which you want to list network profiles.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

nextToken

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

type

The type of network profile to return information about. Valid values are listed here.

Type: String

Valid Values: CURATED | PRIVATE

Required: No

Response Syntax

```
{
  "networkProfiles": [
    {
      "arn": "string",
      "description": "string",
      "downlinkBandwidthBits": number,
      "downlinkDelayMs": number,
      "downlinkJitterMs": number,
      "downlinkLossPercent": number,
      "name": "string",
      "type": "string",
      "uplinkBandwidthBits": number,
      "uplinkDelayMs": number,
      "uplinkJitterMs": number,
      "uplinkLossPercent": number
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

networkProfiles

A list of the available network profiles.

Type: Array of [NetworkProfile](#) objects

[nextToken](#)

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListOfferingPromotions

Returns a list of offering promotions. Each offering promotion record contains the ID and description of the promotion. The API returns a `NotEligible` error if the caller is not permitted to invoke the operation. Contact aws-devicefarm-support@amazon.com if you must be able to invoke this operation.

Request Syntax

```
{
  "nextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

nextToken

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

Response Syntax

```
{
  "nextToken": "string",
  "offeringPromotions": [
    {
      "description": "string",
      "id": "string"
    }
  ]
}
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

An identifier to be used in the next call to this operation, to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

offeringPromotions

Information about the offering promotions.

Type: Array of [OfferingPromotion](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotEligibleException

Exception gets thrown when a user is not eligible to perform the specified transaction.

message

The HTTP response code of a Not Eligible exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListOfferings

Returns a list of products or offerings that the user can manage through the API. Each offering record indicates the recurring price per unit and the frequency for that offering. The API returns a `NotEligible` error if the user is not permitted to invoke the operation. If you must be able to invoke this operation, contact aws-devicefarm-support@amazon.com.

Request Syntax

```
{
  "nextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

nextToken

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

Response Syntax

```
{
  "nextToken": "string",
  "offerings": [
    {
      "description": "string",
      "id": "string",
      "platform": "string",
      "recurringCharges": [
        {
```

```
        "cost": {
            "amount": number,
            "currencyCode": "string"
        },
        "frequency": "string"
    }
],
"type": "string"
}
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

offerings

A value that represents the list offering results.

Type: Array of [Offering](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotEligibleException

Exception gets thrown when a user is not eligible to perform the specified transaction.

message

The HTTP response code of a Not Eligible exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

Examples

Example

The following example response shows a list of device offerings for the user's account.

Sample Response

```
{
  "offerings": [
    {
      "recurringCharges": [
        {
          "cost": {
            "amount": 250.0,
            "currencyCode": "USD"
          },
          "frequency": "MONTHLY"
        }
      ],
      "platform": "IOS",
      "type": "RECURRING",
      "id": "offering-id-ios",
      "description": "iOS Unmetered Device Slot"
    },
    {
      "recurringCharges": [
        {
          "cost": {
            "amount": 250.0,
            "currencyCode": "USD"
          },
          "frequency": "MONTHLY"
        }
      ],
      "platform": "ANDROID",
      "type": "RECURRING",
      "id": "offering-id-android",
      "description": "Android Unmetered Device Slot"
    }
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListOfferingTransactions

Returns a list of all historical purchases, renewals, and system renewal transactions for an AWS account. The list is paginated and ordered by a descending timestamp (most recent transactions are first). The API returns a `NotEligible` error if the user is not permitted to invoke the operation. If you must be able to invoke this operation, contact aws-devicefarm-support@amazon.com.

Request Syntax

```
{  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

nextToken

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

Response Syntax

```
{  
  "nextToken": "string",  
  "offeringTransactions": [  
    {  
      "cost": {  
        "amount": number,  
        "currencyCode": "string"  
      },  
      "createdOn": number,
```

```
"offeringPromotionId": "string",
"offeringStatus": {
  "effectiveOn": number,
  "offering": {
    "description": "string",
    "id": "string",
    "platform": "string",
    "recurringCharges": [
      {
        "cost": {
          "amount": number,
          "currencyCode": "string"
        },
        "frequency": "string"
      }
    ],
    "type": "string"
  },
  "quantity": number,
  "type": "string"
},
"transactionId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

offeringTransactions

The audit log of subscriptions you have purchased and modified through AWS Device Farm.

Type: Array of [OfferingTransaction](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotEligibleException

Exception gets thrown when a user is not eligible to perform the specified transaction.

message

The HTTP response code of a Not Eligible exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

Examples

Example

The following example response contains all the transactions that the customer has made.

Sample Response

```
{
  "offeringTransactions": [
    {
      "createdOn": 1458596241.001,
      "offeringStatus": {
        "effectiveOn": 1458596240.974,
        "type": "PURCHASE",
        "offering": {
          "platform": "IOS",
          "type": "RECURRING",
          "id": "offering-id-ios",
          "description": "iOS Unmetered Device Slot"
        },
        "quantity": 1
      },
      "cost": {
        "amount": 80.65,
        "currencyCode": "USD"
      },
      "transactionId": "transaction-id"
    },
    {
      "createdOn": 1458587590.308,
      "offeringStatus": {
        "effectiveOn": 1458587590.24,
        "type": "PURCHASE",
        "offering": {
          "platform": "IOS",
          "type": "RECURRING",
```

```
        "id": "offering-id-ios",
        "description": "iOS Unmetered Device Slot"
    },
    "quantity": 1
},
"cost": {
    "amount": 80.65,
    "currencyCode": "USD"
},
"transactionId": "transaction-id"
},
{
    "createdOn": 1458541943.395,
    "offeringStatus": {
        "effectiveOn": 1458541943.34,
        "type": "PURCHASE",
        "offering": {
            "platform": "ANDROID",
            "type": "RECURRING",
            "id": "offering-id-android",
            "description": "Android Unmetered Device Slot"
        },
        "quantity": 10
    },
    "cost": {
        "amount": 806.45,
        "currencyCode": "USD"
    },
    "transactionId": "transaction-id"
},
{
    "createdOn": 1458584276.849,
    "offeringStatus": {
        "effectiveOn": 1458584276.811,
        "type": "PURCHASE",
        "offering": {
            "platform": "ANDROID",
            "type": "RECURRING",
            "id": "offering-id-android",
            "description": "Android Unmetered Device Slot"
        },
        "quantity": 2
    },
    "cost": {
```

```
        "amount": 161.29,
        "currencyCode": "USD"
    },
    "transactionId": "transaction-id"
},
{
    "createdOn": 1458592981.171,
    "offeringStatus": {
        "effectiveOn": 1458592981.137,
        "type": "PURCHASE",
        "offering": {
            "platform": "IOS",
            "type": "RECURRING",
            "id": "offering-id-ios",
            "description": "iOS Unmetered Device Slot"
        },
        "quantity": 1
    },
    "cost": {
        "amount": 80.65,
        "currencyCode": "USD"
    },
    "transactionId": "transaction-id"
},
{
    "createdOn": 1458591927.511,
    "offeringStatus": {
        "effectiveOn": 1458591927.468,
        "type": "PURCHASE",
        "offering": {
            "platform": "IOS",
            "type": "RECURRING",
            "id": "offering-id-ios",
            "description": "iOS Unmetered Device Slot"
        },
        "quantity": 1
    },
    "cost": {
        "amount": 80.65,
        "currencyCode": "USD"
    },
    "transactionId": "transaction-id"
},
{
```

```
    "createdOn": 1458581880.117,
    "offeringStatus": {
      "effectiveOn": 1459468800.0,
      "type": "RENEW",
      "offering": {
        "platform": "IOS",
        "type": "RECURRING",
        "id": "offering-id-ios",
        "description": "iOS Unmetered Device Slot"
      },
      "quantity": 0
    },
    "cost": {
      "amount": 0.0,
      "currencyCode": "USD"
    },
    "transactionId": "transaction-id"
  },
  {
    "createdOn": 1458587390.031,
    "offeringStatus": {
      "effectiveOn": 1458587390.008,
      "type": "PURCHASE",
      "offering": {
        "platform": "ANDROID",
        "type": "RECURRING",
        "id": "offering-id-android",
        "description": "Android Unmetered Device Slot"
      },
      "quantity": 1
    },
    "cost": {
      "amount": 80.65,
      "currencyCode": "USD"
    },
    "transactionId": "transaction-id"
  },
  {
    "createdOn": 1458591927.99,
    "offeringStatus": {
      "effectiveOn": 1459468800.0,
      "type": "RENEW",
      "offering": {
        "platform": "ANDROID",
```

```
        "type": "RECURRING",
        "id": "offering-id-android",
        "description": "Android Unmetered Device Slot"
    },
    "quantity": 3
},
"cost": {
    "amount": 750.0,
    "currencyCode": "USD"
},
"transactionId": "transaction-id"
},
{
    "createdOn": 1458581580.426,
    "offeringStatus": {
        "effectiveOn": 1458581580.377,
        "type": "PURCHASE",
        "offering": {
            "platform": "ANDROID",
            "type": "RECURRING",
            "id": "offering-id-android",
            "description": "Android Unmetered Device Slot"
        },
        "quantity": 1
    },
    "cost": {
        "amount": 80.65,
        "currencyCode": "USD"
    },
    "transactionId": "transaction-id"
},
{
    "createdOn": 1458582235.794,
    "offeringStatus": {
        "effectiveOn": 1459468800.0,
        "type": "RENEW",
        "offering": {
            "platform": "ANDROID",
            "type": "RECURRING",
            "id": "offering-id-android",
            "description": "Android Unmetered Device Slot"
        },
        "quantity": 1
    },
    "transactionId": "transaction-id"
}
```

```
    "cost": {
      "amount": 250.0,
      "currencyCode": "USD"
    },
    "transactionId": "transaction-id"
  },
  {
    "createdOn": 1458581580.429,
    "offeringStatus": {
      "effectiveOn": 1458581580.372,
      "type": "PURCHASE",
      "offering": {
        "platform": "IOS",
        "type": "RECURRING",
        "id": "offering-id-ios",
        "description": "iOS Unmetered Device Slot"
      },
      "quantity": 1
    },
    "cost": {
      "amount": 80.65,
      "currencyCode": "USD"
    },
    "transactionId": "transaction-id"
  },
  {
    "createdOn": 1458593014.881,
    "offeringStatus": {
      "effectiveOn": 1458593014.856,
      "type": "PURCHASE",
      "offering": {
        "platform": "IOS",
        "type": "RECURRING",
        "id": "offering-id-ios",
        "description": "iOS Unmetered Device Slot"
      },
      "quantity": 2
    },
    "cost": {
      "amount": 161.29,
      "currencyCode": "USD"
    },
    "transactionId": "transaction-id"
  },
}
```

```
{
  "createdOn": 1458581880.415,
  "offeringStatus": {
    "effectiveOn": 1459468800.0,
    "type": "RENEW",
    "offering": {
      "platform": "ANDROID",
      "type": "RECURRING",
      "id": "offering-id-android",
      "description": "Android Unmetered Device Slot"
    },
    "quantity": 0
  },
  "cost": {
    "amount": 0.0,
    "currencyCode": "USD"
  },
  "transactionId": "transaction-id"
},
{
  "createdOn": 1458591927.662,
  "offeringStatus": {
    "effectiveOn": 1458591927.491,
    "type": "PURCHASE",
    "offering": {
      "platform": "ANDROID",
      "type": "RECURRING",
      "id": "offering-id-android",
      "description": "Android Unmetered Device Slot"
    },
    "quantity": 1
  },
  "cost": {
    "amount": 80.65,
    "currencyCode": "USD"
  },
  "transactionId": "transaction-id"
},
{
  "createdOn": 1458582235.834,
  "offeringStatus": {
    "effectiveOn": 1459468800.0,
    "type": "RENEW",
    "offering": {
```

```
        "platform": "IOS",
        "type": "RECURRING",
        "id": "offering-id-ios",
        "description": "iOS Unmetered Device Slot"
    },
    "quantity": 1
},
"cost": {
    "amount": 250.0,
    "currencyCode": "USD"
},
"transactionId": "transaction-id"
},
{
    "createdOn": 1458583642.184,
    "offeringStatus": {
        "effectiveOn": 1459468800.0,
        "type": "RENEW",
        "offering": {
            "platform": "IOS",
            "type": "RECURRING",
            "id": "offering-id-ios",
            "description": "iOS Unmetered Device Slot"
        },
        "quantity": 0
    },
    "cost": {
        "amount": 0.0,
        "currencyCode": "USD"
    },
    "transactionId": "transaction-id"
},
{
    "createdOn": 1458581880.007,
    "offeringStatus": {
        "effectiveOn": 1458581879.937,
        "type": "PURCHASE",
        "offering": {
            "platform": "ANDROID",
            "type": "RECURRING",
            "id": "offering-id-android",
            "description": "Android Unmetered Device Slot"
        },
        "quantity": 1
    },
    "cost": {
        "amount": 0.0,
        "currencyCode": "USD"
    },
    "transactionId": "transaction-id"
}
```

```
    },
    "cost": {
      "amount": 80.65,
      "currencyCode": "USD"
    },
    "transactionId": "transaction-id"
  }
]
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListProjects

Gets information about projects.

Request Syntax

```
{
  "arn": "string",
  "nextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

Optional. If no Amazon Resource Name (ARN) is specified, then AWS Device Farm returns a list of all projects for the AWS account. You can also specify a project ARN.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: No

nextToken

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

Response Syntax

```
{
  "nextToken": "string",
  "projects": [
    {
      "arn": "string",
      "created": number,
      "defaultJobTimeoutMinutes": number,
      "environmentVariables": [
        {
          "name": "string",
          "value": "string"
        }
      ],
      "executionRoleArn": "string",
      "name": "string",
      "vpcConfig": {
        "securityGroupIds": [ "string" ],
        "subnetIds": [ "string" ],
        "vpcId": "string"
      }
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

If the number of items that are returned is significantly large, this is an identifier that is also returned. It can be used in a subsequent call to this operation to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

[projects](#)

Information about the projects.

Type: Array of [Project](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListRemoteAccessSessions

Returns a list of all currently running remote access sessions.

Request Syntax

```
{  
  "arn": "string",  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The Amazon Resource Name (ARN) of the project about which you are requesting information.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

nextToken

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

Response Syntax

```
{
```

```
"nextToken": "string",
"remoteAccessSessions": [
  {
    "appUpload": "string",
    "arn": "string",
    "billingMethod": "string",
    "created": number,
    "device": {
      "arn": "string",
      "availability": "string",
      "carrier": "string",
      "cpu": {
        "architecture": "string",
        "clock": number,
        "frequency": "string"
      },
      "fleetName": "string",
      "fleetType": "string",
      "formFactor": "string",
      "heapSize": number,
      "image": "string",
      "instances": [
        {
          "arn": "string",
          "deviceArn": "string",
          "instanceProfile": {
            "arn": "string",
            "description": "string",
            "excludeAppPackagesFromCleanup": [ "string" ],
            "name": "string",
            "packageCleanup": boolean,
            "rebootAfterUse": boolean
          },
          "labels": [ "string" ],
          "status": "string",
          "udid": "string"
        }
      ],
      "manufacturer": "string",
      "memory": number,
      "model": "string",
      "modelId": "string",
      "name": "string",
      "os": "string",
```

```

    "platform": "string",
    "radio": "string",
    "remoteAccessEnabled": boolean,
    "remoteDebugEnabled": boolean,
    "resolution": {
      "height": number,
      "width": number
    }
  },
  "deviceMinutes": {
    "metered": number,
    "total": number,
    "unmetered": number
  },
  "deviceProxy": {
    "host": "string",
    "port": number
  },
  "deviceUdid": "string",
  "endpoint": "string",
  "endpoints": {
    "interactiveEndpoint": "string",
    "remoteDriverEndpoint": "string"
  },
  "instanceArn": "string",
  "interactionMode": "string",
  "message": "string",
  "name": "string",
  "result": "string",
  "skipAppResign": boolean,
  "started": number,
  "status": "string",
  "stopped": number,
  "vpcConfig": {
    "securityGroupIds": [ "string" ],
    "subnetIds": [ "string" ],
    "vpcId": "string"
  }
}
]
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

remoteAccessSessions

A container that represents the metadata from the service about each remote access session you are requesting.

Type: Array of [RemoteAccessSession](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListRuns

Gets information about runs, given an AWS Device Farm project ARN.

Request Syntax

```
{  
  "arn": "string",  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The Amazon Resource Name (ARN) of the project for which you want to list runs.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*

Required: Yes

nextToken

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

Response Syntax

```
{
```

```
"nextToken": "string",
"runs": [
  {
    "appUpload": "string",
    "arn": "string",
    "billingMethod": "string",
    "completedJobs": number,
    "counters": {
      "errored": number,
      "failed": number,
      "passed": number,
      "skipped": number,
      "stopped": number,
      "total": number,
      "warned": number
    },
    "created": number,
    "customerArtifactPaths": {
      "androidPaths": [ "string" ],
      "deviceHostPaths": [ "string" ],
      "iosPaths": [ "string" ]
    },
    "deviceMinutes": {
      "metered": number,
      "total": number,
      "unmetered": number
    },
    "devicePoolArn": "string",
    "deviceProxy": {
      "host": "string",
      "port": number
    },
    "deviceSelectionResult": {
      "filters": [
        {
          "attribute": "string",
          "operator": "string",
          "values": [ "string" ]
        }
      ],
      "matchedDevicesCount": number,
      "maxDevices": number
    },
    "environmentVariables": [
```

```
{
  "name": "string",
  "value": "string"
},
"eventCount": number,
"executionRoleArn": "string",
"insights": {
  "jobReport": {
    "jobDetailsUrl": "string",
    "message": "string",
    "metrics": {
      "averageJobExecutionDurationSeconds": number,
      "jobsErrored": number,
      "jobsFailed": number,
      "jobsPassed": number,
      "jobsPassedPercentage": number,
      "jobsSkipped": number,
      "jobsStopped": number,
      "jobsTotal": number,
      "medianJobExecutionDurationSeconds": number,
      "totalJobExecutionDurationSeconds": number
    }
  },
  "status": "string"
},
"insightsTypes": [ "string" ],
"jobTimeoutMinutes": number,
"locale": "string",
"location": {
  "latitude": number,
  "longitude": number
},
"message": "string",
"name": "string",
"networkProfile": {
  "arn": "string",
  "description": "string",
  "downlinkBandwidthBits": number,
  "downlinkDelayMs": number,
  "downlinkJitterMs": number,
  "downlinkLossPercent": number,
  "name": "string",
  "type": "string",
```

```

        "uplinkBandwidthBits": number,
        "uplinkDelayMs": number,
        "uplinkJitterMs": number,
        "uplinkLossPercent": number
    },
    "parsingResultUrl": "string",
    "platform": "string",
    "radios": {
        "bluetooth": boolean,
        "gps": boolean,
        "nfc": boolean,
        "wifi": boolean
    },
    "result": "string",
    "resultCode": "string",
    "seed": number,
    "skipAppResign": boolean,
    "started": number,
    "status": "string",
    "stopped": number,
    "testSpecArn": "string",
    "totalJobs": number,
    "type": "string",
    "vpcConfig": {
        "securityGroupIds": [ "string" ],
        "subnetIds": [ "string" ],
        "vpcId": "string"
    },
    "webUrl": "string"
}
]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[nextToken](#)

If the number of items that are returned is significantly large, this is an identifier that is also returned. It can be used in a subsequent call to this operation to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

[runs](#)

Information about the runs.

Type: Array of [Run](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListSamples

Gets information about samples, given an AWS Device Farm job ARN.

Request Syntax

```
{  
  "arn": "string",  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The Amazon Resource Name (ARN) of the job used to list samples.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

nextToken

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

Response Syntax

```
{
```

```
"nextToken": "string",
"samples": [
  {
    "arn": "string",
    "type": "string",
    "url": "string"
  }
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

If the number of items that are returned is significantly large, this is an identifier that is also returned. It can be used in a subsequent call to this operation to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

samples

Information about the samples.

Type: Array of [Sample](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListSuites

Gets information about test suites for a given job.

Request Syntax

```
{  
  "arn": "string",  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The job's Amazon Resource Name (ARN).

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

nextToken

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

Response Syntax

```
{
```

```
"nextToken": "string",
"suites": [
  {
    "arn": "string",
    "counters": {
      "errored": number,
      "failed": number,
      "passed": number,
      "skipped": number,
      "stopped": number,
      "total": number,
      "warned": number
    },
    "created": number,
    "deviceMinutes": {
      "metered": number,
      "total": number,
      "unmetered": number
    },
    "message": "string",
    "name": "string",
    "result": "string",
    "started": number,
    "status": "string",
    "stopped": number,
    "type": "string"
  }
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

If the number of items that are returned is significantly large, this is an identifier that is also returned. It can be used in a subsequent call to this operation to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

suites

Information about the suites.

Type: Array of [Suite](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

List the tags for an AWS Device Farm resource.

Request Syntax

```
{  
  "ResourceARN": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ResourceARN

The Amazon Resource Name (ARN) of the resource or resources for which to list tags. You can associate tags with the following Device Farm resources: PROJECT, TESTGRID_PROJECT, RUN, NETWORK_PROFILE, INSTANCE_PROFILE, DEVICE_INSTANCE, SESSION, DEVICE_POOL, DEVICE, and VPCE_CONFIGURATION.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Syntax

```
{  
  "Tags": [  
    {  
      "Key": "string",  
      "Value": "string"  
    }  
  ]  
}
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Tags

The tags to add to the resource. A tag is an array of key-value pairs. Tag keys can have a maximum character length of 128 characters. Tag values can have a maximum length of 256 characters.

Type: Array of [Tag](#) objects

Array Members: Maximum number of 150 items.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

TagOperationException

The operation was not successful. Try again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListTestGridProjects

Gets a list of all Selenium testing projects in your account.

Request Syntax

```
{  
  "maxResult": number,  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

maxResult

Return no more than this number of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

nextToken

From a response, used to continue a paginated listing.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

Response Syntax

```
{  
  "nextToken": "string",  
}
```

```
"testGridProjects": [
  {
    "arn": "string",
    "created": number,
    "description": "string",
    "name": "string",
    "vpcConfig": {
      "securityGroupIds": [ "string" ],
      "subnetIds": [ "string" ],
      "vpcId": "string"
    }
  }
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

Used for pagination. Pass into [ListTestGridProjects](#) to get more results in a paginated request.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

testGridProjects

The list of TestGridProjects, based on a [ListTestGridProjectsRequest](#).

Type: Array of [TestGridProject](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

InternalServiceException

An internal exception was raised in the service. Contact aws-devicefarm-support@amazon.com if you see this error.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListTestGridSessionActions

Returns a list of the actions taken in a [TestGridSession](#).

Request Syntax

```
{  
  "maxResult": number,  
  "nextToken": "string",  
  "sessionArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[maxResult](#)

The maximum number of sessions to return per response.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

[nextToken](#)

Pagination token.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

[sessionArn](#)

The ARN of the session to retrieve.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: Yes

Response Syntax

```
{
  "actions": [
    {
      "action": "string",
      "duration": number,
      "requestMethod": "string",
      "started": number,
      "statusCode": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

actions

The action taken by the session.

Type: Array of [TestGridSessionAction](#) objects

nextToken

Pagination token.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

InternalServiceException

An internal exception was raised in the service. Contact aws-devicefarm-support@amazon.com if you see this error.

HTTP Status Code: 500

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)

- [AWS SDK for Ruby V3](#)

ListTestGridSessionArtifacts

Retrieves a list of artifacts created during the session.

Request Syntax

```
{
  "maxResult": number,
  "nextToken": "string",
  "sessionArn": "string",
  "type": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[maxResult](#)

The maximum number of results to be returned by a request.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

[nextToken](#)

Pagination token.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

[sessionArn](#)

The ARN of a [TestGridSession](#).

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: Yes

type

Limit results to a specified type of artifact.

Type: String

Valid Values: VIDEO | LOG

Required: No

Response Syntax

```
{
  "artifacts": [
    {
      "filename": "string",
      "type": "string",
      "url": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

artifacts

A list of test grid session artifacts for a [TestGridSession](#).

Type: Array of [TestGridSessionArtifact](#) objects

nextToken

Pagination token.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

InternalServiceException

An internal exception was raised in the service. Contact aws-devicefarm-support@amazon.com if you see this error.

HTTP Status Code: 500

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListTestGridSessions

Retrieves a list of sessions for a [TestGridProject](#).

Request Syntax

```
{  
  "creationTimeAfter": number,  
  "creationTimeBefore": number,  
  "endTimeAfter": number,  
  "endTimeBefore": number,  
  "maxResult": number,  
  "nextToken": "string",  
  "projectArn": "string",  
  "status": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[creationTimeAfter](#)

Return only sessions created after this time.

Type: Timestamp

Required: No

[creationTimeBefore](#)

Return only sessions created before this time.

Type: Timestamp

Required: No

[endTimeAfter](#)

Return only sessions that ended after this time.

Type: Timestamp

Required: No

endTimeBefore

Return only sessions that ended before this time.

Type: Timestamp

Required: No

maxResult

Return only this many results at a time.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

nextToken

Pagination token.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

projectArn

ARN of a [TestGridProject](#).

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

status

Return only sessions in this state.

Type: String

Valid Values: ACTIVE | CLOSED | ERRORRED

Required: No

Response Syntax

```
{
  "nextToken": "string",
  "testGridSessions": [
    {
      "arn": "string",
      "billingMinutes": number,
      "created": number,
      "ended": number,
      "seleniumProperties": "string",
      "status": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

Pagination token.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

testGridSessions

The sessions that match the criteria in a [ListTestGridSessionsRequest](#).

Type: Array of [TestGridSession](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

InternalServiceException

An internal exception was raised in the service. Contact aws-devicefarm-support@amazon.com if you see this error.

HTTP Status Code: 500

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)

- [AWS SDK for Ruby V3](#)

ListTests

Gets information about tests in a given test suite.

Request Syntax

```
{  
  "arn": "string",  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The test suite's Amazon Resource Name (ARN).

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

nextToken

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

Response Syntax

```
{
```

```
"nextToken": "string",
"tests": [
  {
    "arn": "string",
    "counters": {
      "errored": number,
      "failed": number,
      "passed": number,
      "skipped": number,
      "stopped": number,
      "total": number,
      "warned": number
    },
    "created": number,
    "deviceMinutes": {
      "metered": number,
      "total": number,
      "unmetered": number
    },
    "message": "string",
    "name": "string",
    "result": "string",
    "started": number,
    "status": "string",
    "stopped": number,
    "type": "string"
  }
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

If the number of items that are returned is significantly large, this is an identifier that is also returned. It can be used in a subsequent call to this operation to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

[tests](#)

Information about the tests.

Type: Array of [Test](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListUniqueProblems

Gets information about unique problems, such as exceptions or crashes.

Unique problems are defined as a single instance of an error across a run, job, or suite. For example, if a call in your application consistently raises an exception (`OutOfBoundsException` in `MyActivity.java:386`), `ListUniqueProblems` returns a single entry instead of many individual entries for that exception.

Request Syntax

```
{
  "arn": "string",
  "nextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The unique problems' ARNs.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: Yes

nextToken

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

Response Syntax

```
{
  "nextToken": "string",
  "uniqueProblems": {
    "string" : [
      {
        "message": "string",
        "problems": [
          {
            "device": {
              "arn": "string",
              "availability": "string",
              "carrier": "string",
              "cpu": {
                "architecture": "string",
                "clock": number,
                "frequency": "string"
              },
              "fleetName": "string",
              "fleetType": "string",
              "formFactor": "string",
              "heapSize": number,
              "image": "string",
              "instances": [
                {
                  "arn": "string",
                  "deviceArn": "string",
                  "instanceProfile": {
                    "arn": "string",
                    "description": "string",
                    "excludeAppPackagesFromCleanup": [ "string" ],
                    "name": "string",
                    "packageCleanup": boolean,
                    "rebootAfterUse": boolean
                  },
                  "labels": [ "string" ],
                  "status": "string",
                  "udid": "string"
                }
              ],
              "manufacturer": "string",
              "memory": number,
```

```

    "model": "string",
    "modelId": "string",
    "name": "string",
    "os": "string",
    "platform": "string",
    "radio": "string",
    "remoteAccessEnabled": boolean,
    "remoteDebugEnabled": boolean,
    "resolution": {
        "height": number,
        "width": number
    }
},
"job": {
    "arn": "string",
    "name": "string"
},
"message": "string",
"result": "string",
"run": {
    "arn": "string",
    "name": "string"
},
"suite": {
    "arn": "string",
    "name": "string"
},
"test": {
    "arn": "string",
    "name": "string"
}
}
]
}
]
}
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[nextToken](#)

If the number of items that are returned is significantly large, this is an identifier that is also returned. It can be used in a subsequent call to this operation to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

[uniqueProblems](#)

Information about the unique problems.

Allowed values include:

- PENDING
- PASSED
- WARNED
- FAILED
- SKIPPED
- ERRORED
- STOPPED

Type: String to array of [UniqueProblem](#) objects map

Valid Keys: PENDING | PASSED | WARNED | FAILED | SKIPPED | ERRORED | STOPPED

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListUploads

Gets information about uploads, given an AWS Device Farm project ARN.

Request Syntax

```
{  
  "arn": "string",  
  "nextToken": "string",  
  "type": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The Amazon Resource Name (ARN) of the project for which you want to list uploads.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*

Required: Yes

nextToken

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

type

The type of upload.

Must be one of the following values:

- `ANDROID_APP`
- `IOS_APP`
- `WEB_APP`
- `EXTERNAL_DATA`
- `APPIUM_JAVA_JUNIT_TEST_PACKAGE`
- `APPIUM_JAVA_TESTNG_TEST_PACKAGE`
- `APPIUM_PYTHON_TEST_PACKAGE`
- `APPIUM_NODE_TEST_PACKAGE`
- `APPIUM_RUBY_TEST_PACKAGE`
- `APPIUM_WEB_JAVA_JUNIT_TEST_PACKAGE`
- `APPIUM_WEB_JAVA_TESTNG_TEST_PACKAGE`
- `APPIUM_WEB_PYTHON_TEST_PACKAGE`
- `APPIUM_WEB_NODE_TEST_PACKAGE`
- `APPIUM_WEB_RUBY_TEST_PACKAGE`
- `INSTRUMENTATION_TEST_PACKAGE`
- `XCTEST_TEST_PACKAGE`
- `XCTEST_UI_TEST_PACKAGE`
- `APPIUM_JAVA_JUNIT_TEST_SPEC`
- `APPIUM_JAVA_TESTNG_TEST_SPEC`
- `APPIUM_PYTHON_TEST_SPEC`
- `APPIUM_NODE_TEST_SPEC`
- `APPIUM_RUBY_TEST_SPEC`
- `APPIUM_WEB_JAVA_JUNIT_TEST_SPEC`
- `APPIUM_WEB_JAVA_TESTNG_TEST_SPEC`
- `APPIUM_WEB_PYTHON_TEST_SPEC`
- `APPIUM_WEB_NODE_TEST_SPEC`
- `APPIUM_WEB_RUBY_TEST_SPEC`
- `INSTRUMENTATION_TEST_SPEC`
- `XCTEST_UI_TEST_SPEC`

Type: String

Valid Values: ANDROID_APP | IOS_APP | WEB_APP | EXTERNAL_DATA |
APPIUM_JAVA_JUNIT_TEST_PACKAGE | APPIUM_JAVA_TESTNG_TEST_PACKAGE
| APPIUM_PYTHON_TEST_PACKAGE | APPIUM_NODE_TEST_PACKAGE |
APPIUM_RUBY_TEST_PACKAGE | APPIUM_WEB_JAVA_JUNIT_TEST_PACKAGE |
APPIUM_WEB_JAVA_TESTNG_TEST_PACKAGE | APPIUM_WEB_PYTHON_TEST_PACKAGE
| APPIUM_WEB_NODE_TEST_PACKAGE | APPIUM_WEB_RUBY_TEST_PACKAGE
| CALABASH_TEST_PACKAGE | INSTRUMENTATION_TEST_PACKAGE
| UIAUTOMATION_TEST_PACKAGE | UIAUTOMATOR_TEST_PACKAGE
| XCTEST_TEST_PACKAGE | XCTEST_UI_TEST_PACKAGE |
APPIUM_JAVA_JUNIT_TEST_SPEC | APPIUM_JAVA_TESTNG_TEST_SPEC |
APPIUM_PYTHON_TEST_SPEC | APPIUM_NODE_TEST_SPEC | APPIUM_RUBY_TEST_SPEC
| APPIUM_WEB_JAVA_JUNIT_TEST_SPEC | APPIUM_WEB_JAVA_TESTNG_TEST_SPEC
| APPIUM_WEB_PYTHON_TEST_SPEC | APPIUM_WEB_NODE_TEST_SPEC
| APPIUM_WEB_RUBY_TEST_SPEC | INSTRUMENTATION_TEST_SPEC |
XCTEST_UI_TEST_SPEC

Required: No

Response Syntax

```
{
  "nextToken": "string",
  "uploads": [
    {
      "arn": "string",
      "category": "string",
      "contentType": "string",
      "created": number,
      "message": "string",
      "metadata": "string",
      "name": "string",
      "status": "string",
      "type": "string",
      "url": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

If the number of items that are returned is significantly large, this is an identifier that is also returned. It can be used in a subsequent call to this operation to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

uploads

Information about the uploads.

Type: Array of [Upload](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListVPCEConfigurations

Returns information about all Amazon Virtual Private Cloud (VPC) endpoint configurations in the AWS account.

Request Syntax

```
{
  "maxResults": number,
  "nextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[maxResults](#)

An integer that specifies the maximum number of items you want to return in the API response.

Type: Integer

Required: No

[nextToken](#)

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

Response Syntax

```
{
  "nextToken": "string",
  "vpceConfigurations": [
```

```
{
  "arn": "string",
  "serviceDnsName": "string",
  "vpceConfigurationDescription": "string",
  "vpceConfigurationName": "string",
  "vpceServiceName": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

An identifier that was returned from the previous call to this operation, which can be used to return the next set of items in the list.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

vpceConfigurations

An array of VPCEConfiguration objects that contain information about your VPC endpoint configuration.

Type: Array of [VPCEConfiguration](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

PurchaseOffering

Immediately purchases offerings for an AWS account. Offerings renew with the latest total purchased quantity for an offering, unless the renewal was overridden. The API returns a `NotEligible` error if the user is not permitted to invoke the operation. If you must be able to invoke this operation, contact aws-devicefarm-support@amazon.com.

Request Syntax

```
{
  "offeringId": "string",
  "offeringPromotionId": "string",
  "quantity": number
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[offeringId](#)

The ID of the offering.

Type: String

Length Constraints: Minimum length of 32.

Required: Yes

[offeringPromotionId](#)

The ID of the offering promotion to be applied to the purchase.

Type: String

Length Constraints: Minimum length of 4.

Required: No

[quantity](#)

The number of device slots to purchase in an offering request.

Type: Integer

Required: Yes

Response Syntax

```
{
  "offeringTransaction": {
    "cost": {
      "amount": number,
      "currencyCode": "string"
    },
    "createdOn": number,
    "offeringPromotionId": "string",
    "offeringStatus": {
      "effectiveOn": number,
      "offering": {
        "description": "string",
        "id": "string",
        "platform": "string",
        "recurringCharges": [
          {
            "cost": {
              "amount": number,
              "currencyCode": "string"
            },
            "frequency": "string"
          }
        ],
        "type": "string"
      },
      "quantity": number,
      "type": "string"
    },
    "transactionId": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

offeringTransaction

Represents the offering transaction for the purchase result.

Type: [OfferingTransaction](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotEligibleException

Exception gets thrown when a user is not eligible to perform the specified transaction.

message

The HTTP response code of a Not Eligible exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

Examples

Example

The following example purchases one unmetered iOS device.

Sample Request

```
{
  "transactions": [
    "purchase": {
      "offeringId": "offering-id-ios",
      "quantity": 1
    }
  ]
}
```

Sample Response

```
{
  "offeringTransaction": {
    "createdOn": 1458587590.308,
    "offeringStatus": {
      "effectiveOn": 1458587590.24,
      "type": "RECURRING",
      "offering": {
        "platform": "IOS",
```

```
        "type": "RECURRING",
        "id": "offering-id-ios",
        "description": "iOS Unmetered Device Slot"
    },
    "quantity": 1
},
"cost": {
    "amount": 80.65,
    "currencyCode": "USD"
},
"transactionId": "transaction-id"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

RenewOffering

Explicitly sets the quantity of devices to renew for an offering, starting from the `effectiveDate` of the next period. The API returns a `NotEligible` error if the user is not permitted to invoke the operation. If you must be able to invoke this operation, contact aws-devicefarm-support@amazon.com.

Request Syntax

```
{  
  "offeringId": "string",  
  "quantity": number  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[offeringId](#)

The ID of a request to renew an offering.

Type: String

Length Constraints: Minimum length of 32.

Required: Yes

[quantity](#)

The quantity requested in an offering renewal.

Type: Integer

Required: Yes

Response Syntax

```
{
```

```
"offeringTransaction": {
  "cost": {
    "amount": number,
    "currencyCode": "string"
  },
  "createdOn": number,
  "offeringPromotionId": "string",
  "offeringStatus": {
    "effectiveOn": number,
    "offering": {
      "description": "string",
      "id": "string",
      "platform": "string",
      "recurringCharges": [
        {
          "cost": {
            "amount": number,
            "currencyCode": "string"
          },
          "frequency": "string"
        }
      ],
      "type": "string"
    },
    "quantity": number,
    "type": "string"
  },
  "transactionId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

offeringTransaction

Represents the status of the offering transaction for the renewal.

Type: [OfferingTransaction](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotEligibleException

Exception gets thrown when a user is not eligible to perform the specified transaction.

message

The HTTP response code of a Not Eligible exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

Examples

Example

The following example renews the offering for one unmetered iOS device.

Sample Request

```
{
  "transactions": [
    "renew": {
      "offeringId": "offering-id-ios",
      "quantity": 1,
    }
  ]
}
```

Sample Response

```
{
  "offeringTransaction": {
    "createdOn": 1458596930.431,
    "offeringStatus": {
      "effectiveOn": 1459468800.0,
      "type": "RECURRING",
      "offering": {
        "platform": "IOS",
        "type": "RECURRING",
        "id": "offering-id-ios",
        "description": "iOS Unmetered Device Slot"
      },
      "quantity": 1
    },
    "cost": {
      "amount": 250.0,
      "currencyCode": "USD"
    }
  }
}
```

```
    },  
    "transactionId": "transaction-id"  
  }  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ScheduleRun

Schedules a run.

Request Syntax

```
{
  "appArn": "string",
  "configuration": {
    "auxiliaryApps": [ "string" ],
    "billingMethod": "string",
    "customerArtifactPaths": {
      "androidPaths": [ "string" ],
      "deviceHostPaths": [ "string" ],
      "iosPaths": [ "string" ]
    },
    "deviceProxy": {
      "host": "string",
      "port": number
    },
    "environmentVariables": [
      {
        "name": "string",
        "value": "string"
      }
    ],
    "executionRoleArn": "string",
    "extraDataPackageArn": "string",
    "insightsTypes": [ "string" ],
    "locale": "string",
    "location": {
      "latitude": number,
      "longitude": number
    },
    "networkProfileArn": "string",
    "radios": {
      "bluetooth": boolean,
      "gps": boolean,
      "nfc": boolean,
      "wifi": boolean
    },
    "vpceConfigurationArns": [ "string" ]
  },
}
```

```
{
  "devicePoolArn": "string",
  "deviceSelectionConfiguration": {
    "filters": [
      {
        "attribute": "string",
        "operator": "string",
        "values": [ "string" ]
      }
    ],
    "maxDevices": number
  },
  "executionConfiguration": {
    "accountsCleanup": boolean,
    "appPackagesCleanup": boolean,
    "jobTimeoutMinutes": number,
    "skipAppResign": boolean,
    "videoCapture": boolean
  },
  "name": "string",
  "projectArn": "string",
  "test": {
    "filter": "string",
    "parameters": {
      "string": "string"
    },
    "testPackageArn": "string",
    "testSpecArn": "string",
    "type": "string"
  }
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

appArn

The ARN of an application package to run tests against, created with [CreateUpload](#). See [ListUploads](#).

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

configuration

Information about the settings for the run to be scheduled.

Type: [ScheduleRunConfiguration](#) object

Required: No

devicePoolArn

The ARN of the device pool for the run to be scheduled.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

deviceSelectionConfiguration

The filter criteria used to dynamically select a set of devices for a test run and the maximum number of devices to be included in the run.

Either **devicePoolArn** or **deviceSelectionConfiguration** is required in a request.

Type: [DeviceSelectionConfiguration](#) object

Required: No

executionConfiguration

Specifies configuration information about a test run, such as the execution timeout (in minutes).

Type: [ExecutionConfiguration](#) object

Required: No

name

The name for the run to be scheduled.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

projectArn

The ARN of the project for the run to be scheduled.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: Yes

test

Information about the test for the run to be scheduled.

Type: [ScheduleRunTest](#) object

Required: Yes

Response Syntax

```
{
  "run": {
    "appUpload": "string",
    "arn": "string",
    "billingMethod": "string",
    "completedJobs": number,
    "counters": {
      "errored": number,
      "failed": number,
      "passed": number,
      "skipped": number,
      "stopped": number,
      "total": number,
      "warned": number
    },
    "created": number,
    "customerArtifactPaths": {
```

```
    "androidPaths": [ "string" ],
    "deviceHostPaths": [ "string" ],
    "iosPaths": [ "string" ]
  },
  "deviceMinutes": {
    "metered": number,
    "total": number,
    "unmetered": number
  },
  "devicePoolArn": "string",
  "deviceProxy": {
    "host": "string",
    "port": number
  },
  "deviceSelectionResult": {
    "filters": [
      {
        "attribute": "string",
        "operator": "string",
        "values": [ "string" ]
      }
    ],
    "matchedDevicesCount": number,
    "maxDevices": number
  },
  "environmentVariables": [
    {
      "name": "string",
      "value": "string"
    }
  ],
  "eventCount": number,
  "executionRoleArn": "string",
  "insights": {
    "jobReport": {
      "jobDetailsUrl": "string",
      "message": "string",
      "metrics": {
        "averageJobExecutionDurationSeconds": number,
        "jobsErrored": number,
        "jobsFailed": number,
        "jobsPassed": number,
        "jobsPassedPercentage": number,
        "jobsSkipped": number,
```

```
        "jobsStopped": number,
        "jobsTotal": number,
        "medianJobExecutionDurationSeconds": number,
        "totalJobExecutionDurationSeconds": number
    }
},
"status": "string"
},
"insightsTypes": [ "string" ],
"jobTimeoutMinutes": number,
"locale": "string",
"location": {
    "latitude": number,
    "longitude": number
},
"message": "string",
"name": "string",
"networkProfile": {
    "arn": "string",
    "description": "string",
    "downlinkBandwidthBits": number,
    "downlinkDelayMs": number,
    "downlinkJitterMs": number,
    "downlinkLossPercent": number,
    "name": "string",
    "type": "string",
    "uplinkBandwidthBits": number,
    "uplinkDelayMs": number,
    "uplinkJitterMs": number,
    "uplinkLossPercent": number
},
"parsingResultUrl": "string",
"platform": "string",
"radios": {
    "bluetooth": boolean,
    "gps": boolean,
    "nfc": boolean,
    "wifi": boolean
},
"result": "string",
"resultCode": "string",
"seed": number,
"skipAppResign": boolean,
"started": number,
```

```
  "status": "string",
  "stopped": number,
  "testSpecArn": "string",
  "totalJobs": number,
  "type": "string",
  "vpcConfig": {
    "securityGroupIds": [ "string" ],
    "subnetIds": [ "string" ],
    "vpcId": "string"
  },
  "webUrl": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

run

Information about the scheduled run.

Type: [Run](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

IdempotencyException

An entity with the same name already exists.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

StopJob

Initiates a stop request for the current job. AWS Device Farm immediately stops the job on the device where tests have not started. You are not billed for this device. On the device where tests have started, setup suite and teardown suite tests run to completion on the device. You are billed for setup, teardown, and any tests that were in progress or already completed.

Request Syntax

```
{
  "arn": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

Represents the Amazon Resource Name (ARN) of the Device Farm job to stop.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*

Required: Yes

Response Syntax

```
{
  "job": {
    "arn": "string",
    "counters": {
      "errored": number,
      "failed": number,
      "passed": number,
      "skipped": number,

```

```
"stopped": number,
"total": number,
"warned": number
},
"created": number,
"device": {
  "arn": "string",
  "availability": "string",
  "carrier": "string",
  "cpu": {
    "architecture": "string",
    "clock": number,
    "frequency": "string"
  },
  "fleetName": "string",
  "fleetType": "string",
  "formFactor": "string",
  "heapSize": number,
  "image": "string",
  "instances": [
    {
      "arn": "string",
      "deviceArn": "string",
      "instanceProfile": {
        "arn": "string",
        "description": "string",
        "excludeAppPackagesFromCleanup": [ "string" ],
        "name": "string",
        "packageCleanup": boolean,
        "rebootAfterUse": boolean
      },
      "labels": [ "string" ],
      "status": "string",
      "udid": "string"
    }
  ],
  "manufacturer": "string",
  "memory": number,
  "model": "string",
  "modelId": "string",
  "name": "string",
  "os": "string",
  "platform": "string",
  "radio": "string",
```

```

    "remoteAccessEnabled": boolean,
    "remoteDebugEnabled": boolean,
    "resolution": {
      "height": number,
      "width": number
    }
  },
  "deviceMinutes": {
    "metered": number,
    "total": number,
    "unmetered": number
  },
  "insights": {
    "status": "string",
    "testReport": {
      "message": "string",
      "metrics": {
        "medianTestExecutionDurationSeconds": number,
        "testsErrored": number,
        "testsFailed": number,
        "testsOther": number,
        "testsPassed": number,
        "testsPassedPercentage": number,
        "testsSkipped": number,
        "testsTotal": number,
        "totalTestExecutionDurationSeconds": number
      }
    },
    "testDetailsUrl": "string"
  }
},
"instanceArn": "string",
"message": "string",
"name": "string",
"result": "string",
"started": number,
"status": "string",
"stopped": number,
"type": "string",
"videoCapture": boolean,
"videoEndpoint": "string"
}
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

job

The job that was stopped.

Type: Job object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

StopRemoteAccessSession

Ends a specified remote access session.

Request Syntax

```
{  
  "arn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The Amazon Resource Name (ARN) of the remote access session to stop.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Syntax

```
{  
  "remoteAccessSession": {  
    "appUpload": "string",  
    "arn": "string",  
    "billingMethod": "string",  
    "created": number,  
    "device": {  
      "arn": "string",  
      "availability": "string",  
      "carrier": "string",  
      "cpu": {  
        "architecture": "string",
```

```
    "clock": number,
    "frequency": "string"
  },
  "fleetName": "string",
  "fleetType": "string",
  "formFactor": "string",
  "heapSize": number,
  "image": "string",
  "instances": [
    {
      "arn": "string",
      "deviceArn": "string",
      "instanceProfile": {
        "arn": "string",
        "description": "string",
        "excludeAppPackagesFromCleanup": [ "string" ],
        "name": "string",
        "packageCleanup": boolean,
        "rebootAfterUse": boolean
      },
      "labels": [ "string" ],
      "status": "string",
      "udid": "string"
    }
  ],
  "manufacturer": "string",
  "memory": number,
  "model": "string",
  "modelId": "string",
  "name": "string",
  "os": "string",
  "platform": "string",
  "radio": "string",
  "remoteAccessEnabled": boolean,
  "remoteDebugEnabled": boolean,
  "resolution": {
    "height": number,
    "width": number
  }
},
"deviceMinutes": {
  "metered": number,
  "total": number,
  "unmetered": number
}
```

```
    },
    "deviceProxy": {
      "host": "string",
      "port": number
    },
    "deviceUdid": "string",
    "endpoint": "string",
    "endpoints": {
      "interactiveEndpoint": "string",
      "remoteDriverEndpoint": "string"
    },
    "instanceArn": "string",
    "interactionMode": "string",
    "message": "string",
    "name": "string",
    "result": "string",
    "skipAppResign": boolean,
    "started": number,
    "status": "string",
    "stopped": number,
    "vpcConfig": {
      "securityGroupIds": [ "string" ],
      "subnetIds": [ "string" ],
      "vpcId": "string"
    }
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

remoteAccessSession

A container that represents the metadata from the service about the remote access session you are stopping.

Type: [RemoteAccessSession](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

StopRun

Initiates a stop request for the current test run. AWS Device Farm immediately stops the run on devices where tests have not started. You are not billed for these devices. On devices where tests have started executing, setup suite and teardown suite tests run to completion on those devices. You are billed for setup, teardown, and any tests that were in progress or already completed.

Request Syntax

```
{
  "arn": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

Represents the Amazon Resource Name (ARN) of the Device Farm run to stop.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

Response Syntax

```
{
  "run": {
    "appUpload": "string",
    "arn": "string",
    "billingMethod": "string",
    "completedJobs": number,
    "counters": {
      "errored": number,
```

```
    "failed": number,
    "passed": number,
    "skipped": number,
    "stopped": number,
    "total": number,
    "warned": number
  },
  "created": number,
  "customerArtifactPaths": {
    "androidPaths": [ "string" ],
    "deviceHostPaths": [ "string" ],
    "iosPaths": [ "string" ]
  },
  "deviceMinutes": {
    "metered": number,
    "total": number,
    "unmetered": number
  },
  "devicePoolArn": "string",
  "deviceProxy": {
    "host": "string",
    "port": number
  },
  "deviceSelectionResult": {
    "filters": [
      {
        "attribute": "string",
        "operator": "string",
        "values": [ "string" ]
      }
    ],
    "matchedDevicesCount": number,
    "maxDevices": number
  },
  "environmentVariables": [
    {
      "name": "string",
      "value": "string"
    }
  ],
  "eventCount": number,
  "executionRoleArn": "string",
  "insights": {
    "jobReport": {
```

```
    "jobDetailsUrl": "string",
    "message": "string",
    "metrics": {
      "averageJobExecutionDurationSeconds": number,
      "jobsErrored": number,
      "jobsFailed": number,
      "jobsPassed": number,
      "jobsPassedPercentage": number,
      "jobsSkipped": number,
      "jobsStopped": number,
      "jobsTotal": number,
      "medianJobExecutionDurationSeconds": number,
      "totalJobExecutionDurationSeconds": number
    },
    "status": "string"
  },
  "insightsTypes": [ "string" ],
  "jobTimeoutMinutes": number,
  "locale": "string",
  "location": {
    "latitude": number,
    "longitude": number
  },
  "message": "string",
  "name": "string",
  "networkProfile": {
    "arn": "string",
    "description": "string",
    "downlinkBandwidthBits": number,
    "downlinkDelayMs": number,
    "downlinkJitterMs": number,
    "downlinkLossPercent": number,
    "name": "string",
    "type": "string",
    "uplinkBandwidthBits": number,
    "uplinkDelayMs": number,
    "uplinkJitterMs": number,
    "uplinkLossPercent": number
  },
  "parsingResultUrl": "string",
  "platform": "string",
  "radios": {
    "bluetooth": boolean,
```

```
    "gps": boolean,
    "nfc": boolean,
    "wifi": boolean
  },
  "result": "string",
  "resultCode": "string",
  "seed": number,
  "skipAppResign": boolean,
  "started": number,
  "status": "string",
  "stopped": number,
  "testSpecArn": "string",
  "totalJobs": number,
  "type": "string",
  "vpcConfig": {
    "securityGroupIds": [ "string " ],
    "subnetIds": [ "string " ],
    "vpcId": "string"
  },
  "webUrl": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

run

The run that was stopped.

Type: [Run](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

TagResource

Associates the specified tags to a resource with the specified `resourceArn`. If existing tags on a resource are not specified in the request parameters, they are not changed. When a resource is deleted, the tags associated with that resource are also deleted.

Request Syntax

```
{
  "ResourceARN": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ResourceARN

The Amazon Resource Name (ARN) of the resource or resources to which to add tags. You can associate tags with the following Device Farm resources: PROJECT, TESTGRID_PROJECT, RUN, NETWORK_PROFILE, INSTANCE_PROFILE, DEVICE_INSTANCE, SESSION, DEVICE_POOL, DEVICE, and VPCE_CONFIGURATION.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: Yes

Tags

The tags to add to the resource. A tag is an array of key-value pairs. Tag keys can have a maximum character length of 128 characters. Tag values can have a maximum length of 256 characters.

Type: Array of [Tag](#) objects

Array Members: Maximum number of 150 items.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

TagOperationException

The operation was not successful. Try again.

HTTP Status Code: 400

TagPolicyException

The request doesn't comply with the AWS Identity and Access Management (IAM) tag policy. Correct your request and then retry it.

HTTP Status Code: 400

TooManyTagsException

The list of tags on the repository is over the limit. The maximum number of tags that can be applied to a repository is 50.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

UntagResource

Deletes the specified tags from a resource.

Request Syntax

```
{  
  "ResourceARN": "string",  
  "TagKeys": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ResourceARN](#)

The Amazon Resource Name (ARN) of the resource or resources from which to delete tags. You can associate tags with the following Device Farm resources: PROJECT, TESTGRID_PROJECT, RUN, NETWORK_PROFILE, INSTANCE_PROFILE, DEVICE_INSTANCE, SESSION, DEVICE_POOL, DEVICE, and VPCE_CONFIGURATION.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

[TagKeys](#)

The keys of the tags to be removed.

Type: Array of strings

Array Members: Maximum number of 150 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

TagOperationException

The operation was not successful. Try again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

UpdateDeviceInstance

Updates information about a private device instance.

Request Syntax

```
{  
  "arn": "string",  
  "labels": [ "string" ],  
  "profileArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The Amazon Resource Name (ARN) of the device instance.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

labels

An array of strings that you want to associate with the device instance.

Type: Array of strings

Required: No

profileArn

The ARN of the profile that you want to associate with the device instance.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

Response Syntax

```
{
  "deviceInstance": {
    "arn": "string",
    "deviceArn": "string",
    "instanceProfile": {
      "arn": "string",
      "description": "string",
      "excludeAppPackagesFromCleanup": [ "string" ],
      "name": "string",
      "packageCleanup": boolean,
      "rebootAfterUse": boolean
    },
    "labels": [ "string" ],
    "status": "string",
    "udid": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

deviceInstance

An object that contains information about your device instance.

Type: [DeviceInstance](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

UpdateDevicePool

Modifies the name, description, and rules in a device pool given the attributes and the pool ARN. Rule updates are all-or-nothing, meaning they can only be updated as a whole (or not at all).

Request Syntax

```
{
  "arn": "string",
  "clearMaxDevices": boolean,
  "description": "string",
  "maxDevices": number,
  "name": "string",
  "rules": [
    {
      "attribute": "string",
      "operator": "string",
      "value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The Amazon Resource Name (ARN) of the Device Farm device pool to update.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*

Required: Yes

clearMaxDevices

Sets whether the maxDevices parameter applies to your device pool. If you set this parameter to true, the maxDevices parameter does not apply, and Device Farm does not limit the

number of devices that it adds to your device pool. In this case, Device Farm adds all available devices that meet the criteria specified in the `rules` parameter.

If you use this parameter in your request, you cannot use the `maxDevices` parameter in the same request.

Type: Boolean

Required: No

description

A description of the device pool to update.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

Required: No

maxDevices

The number of devices that Device Farm can add to your device pool. Device Farm adds devices that are available and that meet the criteria that you assign for the `rules` parameter. Depending on how many devices meet these constraints, your device pool might contain fewer devices than the value for this parameter.

By specifying the maximum number of devices, you can control the costs that you incur by running tests.

If you use this parameter in your request, you cannot use the `clearMaxDevices` parameter in the same request.

Type: Integer

Required: No

name

A string that represents the name of the device pool to update.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

rules

Represents the rules to modify for the device pool. Updating rules is optional. If you update rules for your request, the update replaces the existing rules.

Type: Array of [Rule](#) objects

Required: No

Response Syntax

```
{
  "devicePool": {
    "arn": "string",
    "description": "string",
    "maxDevices": number,
    "name": "string",
    "rules": [
      {
        "attribute": "string",
        "operator": "string",
        "value": "string"
      }
    ],
    "type": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

devicePool

The device pool you just updated.

Type: [DevicePool](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

UpdateInstanceProfile

Updates information about an existing private device instance profile.

Request Syntax

```
{  
  "arn": "string",  
  "description": "string",  
  "excludeAppPackagesFromCleanup": [ "string" ],  
  "name": "string",  
  "packageCleanup": boolean,  
  "rebootAfterUse": boolean  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The Amazon Resource Name (ARN) of the instance profile.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

description

The updated description for your instance profile.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

Required: No

[excludeAppPackagesFromCleanup](#)

An array of strings that specifies the list of app packages that should not be cleaned up from the device after a test run is over.

The list of packages is only considered if you set `packageCleanup` to `true`.

Type: Array of strings

Required: No

[name](#)

The updated name for your instance profile.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

[packageCleanup](#)

The updated choice for whether you want to specify package cleanup. The default value is `false` for private devices.

Type: Boolean

Required: No

[rebootAfterUse](#)

The updated choice for whether you want to reboot the device after use. The default value is `true`.

Type: Boolean

Required: No

Response Syntax

```
{  
  "instanceProfile": {
```

```
  "arn": "string",
  "description": "string",
  "excludeAppPackagesFromCleanup": [ "string" ],
  "name": "string",
  "packageCleanup": boolean,
  "rebootAfterUse": boolean
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

instanceProfile

An object that contains information about your instance profile.

Type: [InstanceProfile](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

UpdateNetworkProfile

Updates the network profile.

Request Syntax

```
{  
  "arn": "string",  
  "description": "string",  
  "downlinkBandwidthBits": number,  
  "downlinkDelayMs": number,  
  "downlinkJitterMs": number,  
  "downlinkLossPercent": number,  
  "name": "string",  
  "type": "string",  
  "uplinkBandwidthBits": number,  
  "uplinkDelayMs": number,  
  "uplinkJitterMs": number,  
  "uplinkLossPercent": number  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The Amazon Resource Name (ARN) of the project for which you want to update network profile settings.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

description

The description of the network profile about which you are returning information.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

Required: No

[downlinkBandwidthBits](#)

The data throughput rate in bits per second, as an integer from 0 to 104857600.

Type: Long

Required: No

[downlinkDelayMs](#)

Delay time for all packets to destination in milliseconds as an integer from 0 to 2000.

Type: Long

Required: No

[downlinkJitterMs](#)

Time variation in the delay of received packets in milliseconds as an integer from 0 to 2000.

Type: Long

Required: No

[downlinkLossPercent](#)

Proportion of received packets that fail to arrive from 0 to 100 percent.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 100.

Required: No

[name](#)

The name of the network profile about which you are returning information.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

type

The type of network profile to return information about. Valid values are listed here.

Type: String

Valid Values: CURATED | PRIVATE

Required: No

uplinkBandwidthBits

The data throughput rate in bits per second, as an integer from 0 to 104857600.

Type: Long

Required: No

uplinkDelayMs

Delay time for all packets to destination in milliseconds as an integer from 0 to 2000.

Type: Long

Required: No

uplinkJitterMs

Time variation in the delay of received packets in milliseconds as an integer from 0 to 2000.

Type: Long

Required: No

uplinkLossPercent

Proportion of transmitted packets that fail to arrive from 0 to 100 percent.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 100.

Required: No

Response Syntax

```
{
  "networkProfile": {
    "arn": "string",
    "description": "string",
    "downlinkBandwidthBits": number,
    "downlinkDelayMs": number,
    "downlinkJitterMs": number,
    "downlinkLossPercent": number,
    "name": "string",
    "type": "string",
    "uplinkBandwidthBits": number,
    "uplinkDelayMs": number,
    "uplinkJitterMs": number,
    "uplinkLossPercent": number
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

networkProfile

A list of the available network profiles.

Type: [NetworkProfile](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

UpdateProject

Modifies the specified project name, given the project ARN and a new name.

Request Syntax

```
{
  "arn": "string",
  "defaultJobTimeoutMinutes": number,
  "environmentVariables": [
    {
      "name": "string",
      "value": "string"
    }
  ],
  "executionRoleArn": "string",
  "name": "string",
  "vpcConfig": {
    "securityGroupIds": [ "string" ],
    "subnetIds": [ "string" ],
    "vpcId": "string"
  }
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The Amazon Resource Name (ARN) of the project whose name to update.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

defaultJobTimeoutMinutes

The number of minutes a test run in the project executes before it times out.

Type: Integer

Required: No

environmentVariables

A set of environment variables which are used by default for all runs in the project. These environment variables are applied to the test run during the execution of a test spec file.

For more information about using test spec files, please see [Custom test environments](#) in *AWS Device Farm*.

Type: Array of [EnvironmentVariable](#) objects

Array Members: Minimum number of 1 item. Maximum number of 32 items.

Required: No

executionRoleArn

An IAM role to be assumed by the test host for all runs in the project.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `^arn:aws:iam:[0-9]{12}:role/.+`

Required: No

name

A string that represents the new name of the project that you are updating.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

vpcConfig

The VPC security groups and subnets that are attached to a project.

Type: [VpcConfig](#) object

Required: No

Response Syntax

```
{
  "project": {
    "arn": "string",
    "created": number,
    "defaultJobTimeoutMinutes": number,
    "environmentVariables": [
      {
        "name": "string",
        "value": "string"
      }
    ],
    "executionRoleArn": "string",
    "name": "string",
    "vpcConfig": {
      "securityGroupIds": [ "string" ],
      "subnetIds": [ "string" ],
      "vpcId": "string"
    }
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

project

The project to update.

Type: [Project](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

UpdateTestGridProject

Change details of a project.

Request Syntax

```
{
  "description": "string",
  "name": "string",
  "projectArn": "string",
  "vpcConfig": {
    "securityGroupIds": [ "string" ],
    "subnetIds": [ "string" ],
    "vpcId": "string"
  }
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

description

Human-readable description for the project.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `.*\S.*`

Required: No

name

Human-readable name for the project.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `.*\S.*`

Required: No

projectArn

ARN of the project to update.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*+`

Required: Yes

vpcConfig

The VPC security groups and subnets that are attached to a project.

Type: [TestGridVpcConfig](#) object

Required: No

Response Syntax

```
{
  "testGridProject": {
    "arn": "string",
    "created": number,
    "description": "string",
    "name": "string",
    "vpcConfig": {
      "securityGroupIds": [ "string" ],
      "subnetIds": [ "string" ],
      "vpcId": "string"
    }
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

testGridProject

The project, including updated information.

Type: [TestGridProject](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

InternalServiceException

An internal exception was raised in the service. Contact aws-devicefarm-support@amazon.com if you see this error.

HTTP Status Code: 500

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

UpdateUpload

Updates an uploaded test spec.

Request Syntax

```
{  
  "arn": "string",  
  "contentType": "string",  
  "editContent": boolean,  
  "name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The Amazon Resource Name (ARN) of the uploaded test spec.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

contentType

The upload's content type (for example, application/x-yaml).

Type: String

Length Constraints: Minimum length of 0. Maximum length of 64.

Required: No

editContent

Set to true if the YAML file has changed and must be updated. Otherwise, set to false.

Type: Boolean

Required: No

name

The upload's test spec file name. The name must not contain any forward slashes (/). The test spec file name must end with the .yaml or .yml file extension.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
{
  "upload": {
    "arn": "string",
    "category": "string",
    "contentType": "string",
    "created": number,
    "message": "string",
    "metadata": "string",
    "name": "string",
    "status": "string",
    "type": "string",
    "url": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

upload

A test spec uploaded to Device Farm.

Type: [Upload](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

LimitExceededException

A limit was exceeded.

message

Any additional information about the exception.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

UpdateVPCEConfiguration

Updates information about an Amazon Virtual Private Cloud (VPC) endpoint configuration.

Request Syntax

```
{  
  "arn": "string",  
  "serviceDnsName": "string",  
  "vpceConfigurationDescription": "string",  
  "vpceConfigurationName": "string",  
  "vpceServiceName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

arn

The Amazon Resource Name (ARN) of the VPC endpoint configuration you want to update.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*

Required: Yes

serviceDnsName

The DNS (domain) name used to connect to your private service in your VPC. The DNS name must not already be in use on the internet.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Required: No

vpceConfigurationDescription

An optional description that provides details about your VPC endpoint configuration.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Required: No

vpceConfigurationName

The friendly name you give to your VPC endpoint configuration to manage your configurations more easily.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

vpceServiceName

The name of the VPC endpoint service running in your AWS account that you want Device Farm to test.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Required: No

Response Syntax

```
{
  "vpceConfiguration": {
    "arn": "string",
    "serviceDnsName": "string",
    "vpceConfigurationDescription": "string",
    "vpceConfigurationName": "string",
    "vpceServiceName": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

vpceConfiguration

An object that contains information about your VPC endpoint configuration.

Type: [VPCEConfiguration](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ArgumentException

An invalid argument was specified.

message

Any additional information about the exception.

HTTP Status Code: 400

InvalidOperationException

There was an error with the update request, or you do not have sufficient permissions to update this VPC endpoint configuration.

HTTP Status Code: 400

NotFoundException

The specified entity was not found.

message

Any additional information about the exception.

HTTP Status Code: 400

ServiceAccountException

There was a problem with the service account.

message

Any additional information about the exception.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

Data Types

The AWS Device Farm API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AccountSettings](#)
- [Artifact](#)
- [Counters](#)
- [CPU](#)
- [CreateRemoteAccessSessionConfiguration](#)
- [CustomerArtifactPaths](#)
- [Device](#)
- [DeviceFilter](#)
- [DeviceInstance](#)
- [DeviceMinutes](#)
- [DevicePool](#)
- [DevicePoolCompatibilityResult](#)
- [DeviceProxy](#)
- [DeviceSelectionConfiguration](#)
- [DeviceSelectionResult](#)
- [EnvironmentVariable](#)
- [ExecutionConfiguration](#)
- [IncompatibilityMessage](#)
- [InstanceProfile](#)
- [Job](#)

- [JobInsights](#)
- [JobReport](#)
- [JobReportMetrics](#)
- [ListTestGridProjectsRequest](#)
- [ListTestGridSessionsRequest](#)
- [Location](#)
- [MonetaryAmount](#)
- [NetworkProfile](#)
- [Offering](#)
- [OfferingPromotion](#)
- [OfferingStatus](#)
- [OfferingTransaction](#)
- [Problem](#)
- [ProblemDetail](#)
- [Project](#)
- [Radios](#)
- [RecurringCharge](#)
- [RemoteAccessEndpoints](#)
- [RemoteAccessSession](#)
- [Resolution](#)
- [Rule](#)
- [Run](#)
- [RunInsights](#)
- [Sample](#)
- [ScheduleRunConfiguration](#)
- [ScheduleRunTest](#)
- [Suite](#)
- [Tag](#)
- [Test](#)
- [TestGridProject](#)

- [TestGridSession](#)
- [TestGridSessionAction](#)
- [TestGridSessionArtifact](#)
- [TestGridVpcConfig](#)
- [TestReport](#)
- [TestReportMetrics](#)
- [TrialMinutes](#)
- [UniqueProblem](#)
- [Upload](#)
- [VpcConfig](#)
- [VPCEConfiguration](#)

AccountSettings

A container for account-level settings in AWS Device Farm.

Contents

awsAccountNumber

The AWS account number specified in the AccountSettings container.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 16.

Required: No

defaultJobTimeoutMinutes

The default number of minutes (at the account level) a test run executes before it times out.
The default value is 150 minutes.

Type: Integer

Required: No

maxJobTimeoutMinutes

The maximum number of minutes a test run executes before it times out.

Type: Integer

Required: No

maxSlots

The maximum number of device slots that the AWS account can purchase. Each maximum is expressed as an `offering-id:number` pair, where the `offering-id` represents one of the IDs returned by the `ListOfferings` command.

Type: String to integer map

Required: No

skipAppResign

When set to `true`, for private devices, Device Farm does not sign your app again. For public devices, Device Farm always signs your apps again.

For more information about how Device Farm re-signs your apps, see [Do you modify my app?](#) in the *AWS Device Farm FAQs*.

Type: Boolean

Required: No

trialMinutes

Information about an AWS account's usage of free trial device minutes.

Type: [TrialMinutes](#) object

Required: No

unmeteredDevices

Returns the unmetered devices you have purchased or want to purchase.

Type: String to integer map

Valid Keys: ANDROID | IOS

Required: No

unmeteredRemoteAccessDevices

Returns the unmetered remote access devices you have purchased or want to purchase.

Type: String to integer map

Valid Keys: ANDROID | IOS

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Artifact

Represents the output of a test. Examples of artifacts include logs and screenshots.

Contents

arn

The artifact's ARN.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

extension

The artifact's file extension.

Type: String

Required: No

name

The artifact's name.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

type

The artifact's type.

Allowed values include the following:

- UNKNOWN
- SCREENSHOT

- `DEVICE_LOG`
- `MESSAGE_LOG`
- `VIDEO_LOG`
- `RESULT_LOG`
- `SERVICE_LOG`
- `WEBKIT_LOG`
- `INSTRUMENTATION_OUTPUT`
- `EXERCISER_MONKEY_OUTPUT`: the artifact (log) generated by an Android fuzz test.
- `APPIUM_SERVER_OUTPUT`
- `APPIUM_JAVA_OUTPUT`
- `APPIUM_JAVA_XML_OUTPUT`
- `APPIUM_PYTHON_OUTPUT`
- `APPIUM_PYTHON_XML_OUTPUT`
- `APPLICATION_CRASH_REPORT`
- `XCTEST_LOG`
- `VIDEO`
- `CUSTOMER_ARTIFACT`
- `CUSTOMER_ARTIFACT_LOG`
- `TESTSPEC_OUTPUT`

Type: String

Valid Values: `UNKNOWN` | `SCREENSHOT` | `DEVICE_LOG` | `MESSAGE_LOG` | `VIDEO_LOG` | `RESULT_LOG` | `SERVICE_LOG` | `WEBKIT_LOG` | `INSTRUMENTATION_OUTPUT` | `EXERCISER_MONKEY_OUTPUT` | `CALABASH_JSON_OUTPUT` | `CALABASH_PRETTY_OUTPUT` | `CALABASH_STANDARD_OUTPUT` | `CALABASH_JAVA_XML_OUTPUT` | `AUTOMATION_OUTPUT` | `APPIUM_SERVER_OUTPUT` | `APPIUM_JAVA_OUTPUT` | `APPIUM_JAVA_XML_OUTPUT` | `APPIUM_PYTHON_OUTPUT` | `APPIUM_PYTHON_XML_OUTPUT` | `EXPLORER_EVENT_LOG` | `EXPLORER_SUMMARY_LOG` | `APPLICATION_CRASH_REPORT` | `XCTEST_LOG` | `VIDEO` | `CUSTOMER_ARTIFACT` | `CUSTOMER_ARTIFACT_LOG` | `TESTSPEC_OUTPUT`

Required: No

url

The presigned Amazon S3 URL that can be used with a GET request to download the artifact's file.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Counters

Represents entity counters.

Contents

errored

The number of errored entities.

Type: Integer

Required: No

failed

The number of failed entities.

Type: Integer

Required: No

passed

The number of passed entities.

Type: Integer

Required: No

skipped

The number of skipped entities.

Type: Integer

Required: No

stopped

The number of stopped entities.

Type: Integer

Required: No

total

The total number of entities.

Type: Integer

Required: No

warned

The number of warned entities.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CPU

Represents the amount of CPU that an app is using on a physical device. Does not represent system-wide CPU usage.

Contents

architecture

The CPU's architecture (for example, x86 or ARM).

Type: String

Required: No

clock

The clock speed of the device's CPU, expressed in hertz (Hz). For example, a 1.2 GHz CPU is expressed as 1200000000.

Type: Double

Required: No

frequency

The CPU's frequency.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CreateRemoteAccessSessionConfiguration

Configuration settings for a remote access session, including billing method.

Contents

auxiliaryApps

A list of upload ARNs for app packages to be installed onto your device. (Maximum 3)

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 3 items.

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

billingMethod

The billing method for the remote access session.

Type: String

Valid Values: `METERED` | `UNMETERED`

Required: No

deviceProxy

The device proxy to be configured on the device for the remote access session.

Type: [DeviceProxy](#) object

Required: No

vpceConfigurationArns

An array of ARNs included in the VPC endpoint configuration.

Type: Array of strings

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CustomerArtifactPaths

A JSON object that specifies the paths where the artifacts generated by the customer's tests, on the device or in the test environment, are pulled from.

Specify `deviceHostPaths` and optionally specify either `iosPaths` or `androidPaths`.

For web app tests, you can specify both `iosPaths` and `androidPaths`.

Contents

androidPaths

Comma-separated list of paths on the Android device where the artifacts generated by the customer's tests are pulled from.

Type: Array of strings

Required: No

deviceHostPaths

Comma-separated list of paths in the test execution environment where the artifacts generated by the customer's tests are pulled from.

Type: Array of strings

Required: No

iosPaths

Comma-separated list of paths on the iOS device where the artifacts generated by the customer's tests are pulled from.

Type: Array of strings

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Device

Represents a device type that an app is tested against.

Contents

arn

The device's ARN.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

availability

Indicates how likely a device is available for a test run. Currently available in the [ListDevices](#) and [GetDevice](#) API methods.

Type: String

Valid Values: `TEMPORARY_NOT_AVAILABLE` | `BUSY` | `AVAILABLE` | `HIGHLY_AVAILABLE`

Required: No

carrier

The device's carrier.

Type: String

Required: No

cpu

Information about the device's CPU.

Type: [CPU](#) object

Required: No

fleetName

The name of the fleet to which this device belongs.

Type: String

Required: No

fleetType

The type of fleet to which this device belongs. Possible values are PRIVATE and PUBLIC.

Type: String

Required: No

formFactor

The device's form factor.

Allowed values include:

- PHONE
- TABLET

Type: String

Valid Values: PHONE | TABLET

Required: No

heapSize

The device's heap size, expressed in bytes.

Type: Long

Required: No

image

The device's image name.

Type: String

Required: No

instances

The instances that belong to this device.

Type: Array of [DeviceInstance](#) objects

Required: No

manufacturer

The device's manufacturer name.

Type: String

Required: No

memory

The device's total memory size, expressed in bytes.

Type: Long

Required: No

model

The device's model name.

Type: String

Required: No

modelId

The device's model ID.

Type: String

Required: No

name

The device's display name.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

os

The device's operating system type.

Type: String

Required: No

platform

The device's platform.

Allowed values include:

- ANDROID
- IOS

Type: String

Valid Values: ANDROID | IOS

Required: No

radio

The device's radio.

Type: String

Required: No

remoteAccessEnabled

Specifies whether remote access has been enabled for the specified device.

Type: Boolean

Required: No

remoteDebugEnabled

This member has been deprecated.

This flag is set to `true` if remote debugging is enabled for the device.

Remote debugging is [no longer supported](#).

Type: Boolean

Required: No

resolution

The resolution of the device.

Type: [Resolution](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DeviceFilter

Represents a device filter used to select a set of devices to be included in a test run. This data structure is passed in as the `deviceSelectionConfiguration` parameter to `ScheduleRun`. For an example of the JSON request syntax, see [ScheduleRun](#).

It is also passed in as the `filters` parameter to `ListDevices`. For an example of the JSON request syntax, see [ListDevices](#).

Contents

attribute

The aspect of a device such as platform or model used as the selection criteria in a device filter.

The supported operators for each attribute are provided in the following list.

ARN

The Amazon Resource Name (ARN) of the device (for example, `arn:aws:devicefarm:us-west-2::device:12345Example`).

Supported operators: EQUALS, IN, NOT_IN

PLATFORM

The device platform. Valid values are ANDROID or IOS.

Supported operators: EQUALS

OS_VERSION

The operating system version (for example, 10.3.2).

Supported operators: EQUALS, GREATER_THAN, GREATER_THAN_OR_EQUALS, IN, LESS_THAN, LESS_THAN_OR_EQUALS, NOT_IN

MODEL

The device model (for example, iPad 5th Gen).

Supported operators: CONTAINS, EQUALS, IN, NOT_IN

AVAILABILITY

The current availability of the device. Valid values are AVAILABLE, HIGHLY_AVAILABLE, BUSY, or TEMPORARY_NOT_AVAILABLE.

Supported operators: EQUALS

FORM_FACTOR

The device form factor. Valid values are PHONE or TABLET.

Supported operators: EQUALS

MANUFACTURER

The device manufacturer (for example, Apple).

Supported operators: EQUALS, IN, NOT_IN

REMOTE_ACCESS_ENABLED

Whether the device is enabled for remote access. Valid values are TRUE or FALSE.

Supported operators: EQUALS

REMOTE_DEBUG_ENABLED

Whether the device is enabled for remote debugging. Valid values are TRUE or FALSE.

Supported operators: EQUALS

Because remote debugging is [no longer supported](#), this filter is ignored.

INSTANCE_ARN

The Amazon Resource Name (ARN) of the device instance.

Supported operators: EQUALS, IN, NOT_IN

INSTANCE_LABELS

The label of the device instance.

Supported operators: CONTAINS

FLEET_TYPE

The fleet type. Valid values are PUBLIC or PRIVATE.

Supported operators: EQUALS

Type: String

Valid Values: ARN | PLATFORM | OS_VERSION | MODEL | AVAILABILITY
| FORM_FACTOR | MANUFACTURER | REMOTE_ACCESS_ENABLED |
REMOTE_DEBUG_ENABLED | INSTANCE_ARN | INSTANCE_LABELS | FLEET_TYPE

Required: Yes

operator

Specifies how Device Farm compares the filter's attribute to the value. See the attribute descriptions.

Type: String

Valid Values: EQUALS | LESS_THAN | LESS_THAN_OR_EQUALS | GREATER_THAN |
GREATER_THAN_OR_EQUALS | IN | NOT_IN | CONTAINS

Required: Yes

values

An array of one or more filter values used in a device filter.

Operator Values

- The IN and NOT_IN operators can take a values array that has more than one element.
- The other operators require an array with a single element.

Attribute Values

- The PLATFORM attribute can be set to ANDROID or IOS.
- The AVAILABILITY attribute can be set to AVAILABLE, HIGHLY_AVAILABLE, BUSY, or TEMPORARY_NOT_AVAILABLE.
- The FORM_FACTOR attribute can be set to PHONE or TABLET.
- The FLEET_TYPE attribute can be set to PUBLIC or PRIVATE.

Type: Array of strings

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DeviceInstance

Represents the device instance.

Contents

arn

The Amazon Resource Name (ARN) of the device instance.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

deviceArn

The ARN of the device.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

instanceProfile

A object that contains information about the instance profile.

Type: [InstanceProfile](#) object

Required: No

labels

An array of strings that describe the device instance.

Type: Array of strings

Required: No

status

The status of the device instance. Valid values are listed here.

Type: String

Valid Values: IN_USE | PREPARING | AVAILABLE | NOT_AVAILABLE

Required: No

udid

Unique device identifier for the device instance.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DeviceMinutes

Represents the total (metered or unmetered) minutes used by the resource to run tests. Contains the sum of minutes consumed by all children.

Contents

metered

When specified, represents only the sum of metered minutes used by the resource to run tests.

Type: Double

Required: No

total

When specified, represents the total minutes used by the resource to run tests.

Type: Double

Required: No

unmetered

When specified, represents only the sum of unmetered minutes used by the resource to run tests.

Type: Double

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DevicePool

Represents a collection of device types.

Contents

arn

The device pool's ARN.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

description

The device pool's description.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

Required: No

maxDevices

The number of devices that Device Farm can add to your device pool. Device Farm adds devices that are available and meet the criteria that you assign for the `rules` parameter. Depending on how many devices meet these constraints, your device pool might contain fewer devices than the value for this parameter.

By specifying the maximum number of devices, you can control the costs that you incur by running tests.

Type: Integer

Required: No

name

The device pool's name.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

rules

Information about the device pool's rules.

Type: Array of [Rule](#) objects

Required: No

type

The device pool's type.

Allowed values include:

- CURATED: A device pool that is created and managed by AWS Device Farm.
- PRIVATE: A device pool that is created and managed by the device pool developer.

Type: String

Valid Values: CURATED | PRIVATE

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DevicePoolCompatibilityResult

Represents a device pool compatibility result.

Contents

compatible

Whether the result was compatible with the device pool.

Type: Boolean

Required: No

device

The device (phone or tablet) to return information about.

Type: [Device](#) object

Required: No

incompatibilityMessages

Information about the compatibility.

Type: Array of [IncompatibilityMessage](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DeviceProxy

Represents the http/s proxy configuration that will be applied to a device during a run.

Contents

host

Hostname or IPv4 address of the proxy.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^([a-zA-Z0-9])([a-zA-Z0-9- .]+)([a-zA-Z0-9])$`

Required: Yes

port

The port number on which the http/s proxy is listening.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 65535.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DeviceSelectionConfiguration

Represents the device filters used in a test run and the maximum number of devices to be included in the run. It is passed in as the `deviceSelectionConfiguration` request parameter in [ScheduleRun](#).

Contents

filters

Used to dynamically select a set of devices for a test run. A filter is made up of an attribute, an operator, and one or more values.

- **Attribute**

The aspect of a device such as platform or model used as the selection criteria in a device filter.

Allowed values include:

- **ARN**: The Amazon Resource Name (ARN) of the device (for example, `arn:aws:devicefarm:us-west-2::device:12345Example`).
- **PLATFORM**: The device platform. Valid values are `ANDROID` or `IOS`.
- **OS_VERSION**: The operating system version (for example, `10.3.2`).
- **MODEL**: The device model (for example, `iPad 5th Gen`).
- **AVAILABILITY**: The current availability of the device. Valid values are `AVAILABLE`, `HIGHLY_AVAILABLE`, `BUSY`, or `TEMPORARY_NOT_AVAILABLE`.
- **FORM_FACTOR**: The device form factor. Valid values are `PHONE` or `TABLET`.
- **MANUFACTURER**: The device manufacturer (for example, `Apple`).
- **REMOTE_ACCESS_ENABLED**: Whether the device is enabled for remote access. Valid values are `TRUE` or `FALSE`.
- **REMOTE_DEBUG_ENABLED**: Whether the device is enabled for remote debugging. Valid values are `TRUE` or `FALSE`. Because remote debugging is [no longer supported](#), this filter is ignored.
- **INSTANCE_ARN**: The Amazon Resource Name (ARN) of the device instance.
- **INSTANCE_LABELS**: The label of the device instance.

- **FLEET_TYPE**: The fleet type. Valid values are `PUBLIC` or `PRIVATE`.

- **Operator**

The filter operator.

- The EQUALS operator is available for every attribute except INSTANCE_LABELS.
- The CONTAINS operator is available for the INSTANCE_LABELS and MODEL attributes.
- The IN and NOT_IN operators are available for the ARN, OS_VERSION, MODEL, MANUFACTURER, and INSTANCE_ARN attributes.
- The LESS_THAN, GREATER_THAN, LESS_THAN_OR_EQUALS, and GREATER_THAN_OR_EQUALS operators are also available for the OS_VERSION attribute.

- **Values**

An array of one or more filter values.

Operator Values

- The IN and NOT_IN operators can take a values array that has more than one element.
- The other operators require an array with a single element.

Attribute Values

- The PLATFORM attribute can be set to ANDROID or IOS.
- The AVAILABILITY attribute can be set to AVAILABLE, HIGHLY_AVAILABLE, BUSY, or TEMPORARY_NOT_AVAILABLE.
- The FORM_FACTOR attribute can be set to PHONE or TABLET.
- The FLEET_TYPE attribute can be set to PUBLIC or PRIVATE.

Type: Array of [DeviceFilter](#) objects

Required: Yes

maxDevices

The maximum number of devices to be included in a test run.

Type: Integer

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DeviceSelectionResult

Contains the run results requested by the device selection configuration and how many devices were returned. For an example of the JSON response syntax, see [ScheduleRun](#).

Contents

filters

The filters in a device selection result.

Type: Array of [DeviceFilter](#) objects

Required: No

matchedDevicesCount

The number of devices that matched the device filter selection criteria.

Type: Integer

Required: No

maxDevices

The maximum number of devices to be selected by a device filter and included in a test run.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EnvironmentVariable

Information about an environment variable for a project or a run.

Contents

name

The name of the environment variable.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[a-zA-Z_][a-zA-Z_0-9]*`

Required: Yes

value

The value of the environment variable.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ExecutionConfiguration

Represents configuration information about a test run, such as the execution timeout (in minutes).

Contents

accountsCleanup

True if account cleanup is enabled at the beginning of the test. Otherwise, false.

Type: Boolean

Required: No

appPackagesCleanup

True if app package cleanup is enabled at the beginning of the test. Otherwise, false.

Type: Boolean

Required: No

jobTimeoutMinutes

The number of minutes a test run executes before it times out.

Type: Integer

Required: No

skipAppResign

When set to `true`, for private devices, Device Farm does not sign your app again. For public devices, Device Farm always signs your apps again.

For more information about how Device Farm re-signs your apps, see [Do you modify my app?](#) in the *AWS Device Farm FAQs*.

Type: Boolean

Required: No

videoCapture

Set to `true` to enable video capture. Otherwise, set to `false`. The default is `true`.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

IncompatibilityMessage

Represents information about incompatibility.

Contents

message

A message about the incompatibility.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

Required: No

type

The type of incompatibility.

Allowed values include:

- ARN
- FORM_FACTOR (for example, phone or tablet)
- MANUFACTURER
- PLATFORM (for example, Android or iOS)
- REMOTE_ACCESS_ENABLED
- APPIUM_VERSION

Type: String

Valid Values: ARN | PLATFORM | FORM_FACTOR | MANUFACTURER | REMOTE_ACCESS_ENABLED | REMOTE_DEBUG_ENABLED | APPIUM_VERSION | INSTANCE_ARN | INSTANCE_LABELS | FLEET_TYPE | OS_VERSION | MODEL | AVAILABILITY

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InstanceProfile

Represents the instance profile.

Contents

arn

The Amazon Resource Name (ARN) of the instance profile.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

description

The description of the instance profile.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

Required: No

excludeAppPackagesFromCleanup

An array of strings containing the list of app packages that should not be cleaned up from the device after a test run completes.

The list of packages is considered only if you set `packageCleanup` to `true`.

Type: Array of strings

Required: No

name

The name of the instance profile.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

packageCleanup

When set to `true`, Device Farm removes app packages after a test run. The default value is `false` for private devices.

Type: Boolean

Required: No

rebootAfterUse

When set to `true`, Device Farm reboots the instance after a test run. The default value is `true`.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Job

Represents a device.

Contents

arn

The job's ARN.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

counters

The job's result counters.

Type: [Counters](#) object

Required: No

created

When the job was created.

Type: Timestamp

Required: No

device

The device (phone or tablet).

Type: [Device](#) object

Required: No

deviceMinutes

Represents the total (metered or unmetered) minutes used by the job.

Type: [DeviceMinutes](#) object

Required: No

insights

The insights for the job, including the report status and test-level metrics. This field contains data only if you specified `insightsTypes` when you scheduled the run.

Type: [JobInsights](#) object

Required: No

instanceArn

The ARN of the instance.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

message

A message about the job's result.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

Required: No

name

The job's name.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

result

The job's result.

Allowed values include:

- PENDING
- PASSED
- WARNED
- FAILED
- SKIPPED
- ERRORED
- STOPPED

Type: String

Valid Values: PENDING | PASSED | WARNED | FAILED | SKIPPED | ERRORED | STOPPED

Required: No

started

The job's start time.

Type: Timestamp

Required: No

status

The job's status.

Allowed values include:

- PENDING
- PENDING_CONCURRENCY
- PENDING_DEVICE
- PROCESSING
- SCHEDULING
- PREPARING
- RUNNING
- COMPLETED
- STOPPING

Type: String

Valid Values: PENDING | PENDING_CONCURRENCY | PENDING_DEVICE | PROCESSING | SCHEDULING | PREPARING | RUNNING | COMPLETED | STOPPING

Required: No

stopped

The job's stop time.

Type: Timestamp

Required: No

type

The job's type.

Allowed values include the following:

- BUILTIN_FUZZ
- APPIUM_JAVA_JUNIT
- APPIUM_JAVA_TESTNG
- APPIUM_PYTHON
- APPIUM_NODE
- APPIUM_RUBY
- APPIUM_WEB_JAVA_JUNIT
- APPIUM_WEB_JAVA_TESTNG
- APPIUM_WEB_PYTHON
- APPIUM_WEB_NODE
- APPIUM_WEB_RUBY
- INSTRUMENTATION
- XCTEST
- XCTEST_UI

Type: String

Valid Values: BUILTIN_FUZZ | APPIUM_JAVA_JUNIT | APPIUM_JAVA_TESTNG | APPIUM_PYTHON | APPIUM_NODE | APPIUM_RUBY | APPIUM_WEB_JAVA_JUNIT

| APPIUM_WEB_JAVA_TESTNG | APPIUM_WEB_PYTHON | APPIUM_WEB_NODE |
APPIUM_WEB_RUBY | INSTRUMENTATION | XCTEST | XCTEST_UI

Required: No

videoCapture

This value is set to true if video capture is enabled. Otherwise, it is set to false.

Type: Boolean

Required: No

videoEndpoint

The endpoint for streaming device video.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

JobInsights

Contains insights for a job, including report status, and test-level aggregated metrics such as per test execution time and median test execution time.

Contents

status

The status of the insights report for the job.

Type: String

Valid Values: PENDING | RUNNING | COMPLETED | SKIPPED | ERRORED

Required: No

testReport

The test-level aggregated report for the job.

Type: [TestReport](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

JobReport

Contains aggregated job-level metrics for a run.

Contents

jobDetailsUrl

A URL to the detailed job results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 4096.

Required: No

message

A message associated with the job report.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 4096.

Required: No

metrics

The aggregated job-level metrics for the run.

Type: [JobReportMetrics](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

JobReportMetrics

Contains aggregated metrics across all jobs in a run.

Contents

averageJobExecutionDurationSeconds

The average execution duration of jobs in the run, in seconds.

Type: Double

Required: No

jobsErrored

The number of jobs that errored.

Type: Integer

Required: No

jobsFailed

The number of jobs that failed.

Type: Integer

Required: No

jobsPassed

The number of jobs that passed.

Type: Integer

Required: No

jobsPassedPercentage

The percentage of jobs that passed.

Type: Double

Required: No

jobsSkipped

The number of jobs that were skipped.

Type: Integer

Required: No

jobsStopped

The number of jobs that were stopped.

Type: Integer

Required: No

jobsTotal

The total number of jobs in the run.

Type: Integer

Required: No

medianJobExecutionDurationSeconds

The median execution duration of jobs in the run, in seconds.

Type: Double

Required: No

totalJobExecutionDurationSeconds

The total execution duration of all jobs in the run, in seconds.

Type: Double

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ListTestGridProjectsRequest

Contents

maxResult

Return no more than this number of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

nextToken

From a response, used to continue a paginated listing.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ListTestGridSessionsRequest

Contents

projectArn

ARN of a [TestGridProject](#).

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: Yes

creationTimeAfter

Return only sessions created after this time.

Type: Timestamp

Required: No

creationTimeBefore

Return only sessions created before this time.

Type: Timestamp

Required: No

endTimeAfter

Return only sessions that ended after this time.

Type: Timestamp

Required: No

endTimeBefore

Return only sessions that ended before this time.

Type: Timestamp

Required: No

maxResult

Return only this many results at a time.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

nextToken

Pagination token.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 1024.

Required: No

status

Return only sessions in this state.

Type: String

Valid Values: ACTIVE | CLOSED | ERRORRED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Location

Represents a latitude and longitude pair, expressed in geographic coordinate system degrees (for example, 47.6204, -122.3491).

Elevation is currently not supported.

Contents

latitude

The latitude.

Type: Double

Required: Yes

longitude

The longitude.

Type: Double

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MonetaryAmount

A number that represents the monetary amount for an offering or transaction.

Contents

amount

The numerical amount of an offering or transaction.

Type: Double

Required: No

currencyCode

The currency code of a monetary amount. For example, USD means U.S. dollars.

Type: String

Valid Values: USD

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

NetworkProfile

An array of settings that describes characteristics of a network profile.

Contents

arn

The Amazon Resource Name (ARN) of the network profile.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

description

The description of the network profile.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

Required: No

downlinkBandwidthBits

The data throughput rate in bits per second, as an integer from 0 to 104857600.

Type: Long

Required: No

downlinkDelayMs

Delay time for all packets to destination in milliseconds as an integer from 0 to 2000.

Type: Long

Required: No

downlinkJitterMs

Time variation in the delay of received packets in milliseconds as an integer from 0 to 2000.

Type: Long

Required: No

downlinkLossPercent

Proportion of received packets that fail to arrive from 0 to 100 percent.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 100.

Required: No

name

The name of the network profile.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

type

The type of network profile. Valid values are listed here.

Type: String

Valid Values: CURATED | PRIVATE

Required: No

uplinkBandwidthBits

The data throughput rate in bits per second, as an integer from 0 to 104857600.

Type: Long

Required: No

uplinkDelayMs

Delay time for all packets to destination in milliseconds as an integer from 0 to 2000.

Type: Long

Required: No

uplinkJitterMs

Time variation in the delay of received packets in milliseconds as an integer from 0 to 2000.

Type: Long

Required: No

uplinkLossPercent

Proportion of transmitted packets that fail to arrive from 0 to 100 percent.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 100.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Offering

Represents the metadata of a device offering.

Contents

description

A string that describes the offering.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

Required: No

id

The ID that corresponds to a device offering.

Type: String

Length Constraints: Minimum length of 32.

Required: No

platform

The platform of the device (for example, ANDROID or IOS).

Type: String

Valid Values: ANDROID | IOS

Required: No

recurringCharges

Specifies whether there are recurring charges for the offering.

Type: Array of [RecurringCharge](#) objects

Required: No

type

The type of offering (for example, RECURRING) for a device.

Type: String

Valid Values: RECURRING

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OfferingPromotion

Represents information about an offering promotion.

Contents

description

A string that describes the offering promotion.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

Required: No

id

The ID of the offering promotion.

Type: String

Length Constraints: Minimum length of 4.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OfferingStatus

The status of the offering.

Contents

effectiveOn

The date on which the offering is effective.

Type: Timestamp

Required: No

offering

Represents the metadata of an offering status.

Type: [Offering](#) object

Required: No

quantity

The number of available devices in the offering.

Type: Integer

Required: No

type

The type specified for the offering status.

Type: String

Valid Values: PURCHASE | RENEW | SYSTEM

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OfferingTransaction

Represents the metadata of an offering transaction.

Contents

cost

The cost of an offering transaction.

Type: [MonetaryAmount](#) object

Required: No

createdOn

The date on which an offering transaction was created.

Type: Timestamp

Required: No

offeringPromotionId

The ID that corresponds to a device offering promotion.

Type: String

Length Constraints: Minimum length of 4.

Required: No

offeringStatus

The status of an offering transaction.

Type: [OfferingStatus](#) object

Required: No

transactionId

The transaction ID of the offering transaction.

Type: String

Length Constraints: Minimum length of 32.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Problem

Represents a specific warning or failure.

Contents

device

Information about the associated device.

Type: [Device](#) object

Required: No

job

Information about the associated job.

Type: [ProblemDetail](#) object

Required: No

message

A message about the problem's result.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

Required: No

result

The problem's result.

Allowed values include:

- PENDING
- PASSED
- WARNED
- FAILED
- SKIPPED

- ERRORED
- STOPPED

Type: String

Valid Values: PENDING | PASSED | WARNED | FAILED | SKIPPED | ERRORED | STOPPED

Required: No

run

Information about the associated run.

Type: [ProblemDetail](#) object

Required: No

suite

Information about the associated suite.

Type: [ProblemDetail](#) object

Required: No

test

Information about the associated test.

Type: [ProblemDetail](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ProblemDetail

Information about a problem detail.

Contents

arn

The problem detail's ARN.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*+`

Required: No

name

The problem detail's name.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Project

Represents an operating-system neutral workspace for running and managing tests.

Contents

arn

The project's ARN.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

created

When the project was created.

Type: Timestamp

Required: No

defaultJobTimeoutMinutes

The default number of minutes (at the project level) a test run executes before it times out. The default value is 150 minutes.

Type: Integer

Required: No

environmentVariables

Environment variables associated with the project.

Type: Array of [EnvironmentVariable](#) objects

Array Members: Minimum number of 1 item. Maximum number of 32 items.

Required: No

executionRoleArn

The IAM execution role associated with the project.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `^arn:aws:iam:[0-9]{12}:role/.+`

Required: No

name

The project's name.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

vpcConfig

The VPC security groups and subnets that are attached to a project.

Type: [VpcConfig](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Radios

Represents the set of radios and their states on a device. Examples of radios include Wi-Fi, GPS, Bluetooth, and NFC.

Contents

bluetooth

True if Bluetooth is enabled at the beginning of the test. Otherwise, false.

Type: Boolean

Required: No

gps

True if GPS is enabled at the beginning of the test. Otherwise, false.

Type: Boolean

Required: No

nfc

True if NFC is enabled at the beginning of the test. Otherwise, false.

Type: Boolean

Required: No

wifi

True if Wi-Fi is enabled at the beginning of the test. Otherwise, false.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RecurringCharge

Specifies whether charges for devices are recurring.

Contents

cost

The cost of the recurring charge.

Type: [MonetaryAmount](#) object

Required: No

frequency

The frequency in which charges recur.

Type: String

Valid Values: MONTHLY

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RemoteAccessEndpoints

Represents the remote endpoints for viewing and controlling a device during a remote access session.

Contents

interactiveEndpoint

URL for viewing and interacting with the device during the remote access session.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 4096.

Required: No

remoteDriverEndpoint

URL for controlling the device using WebDriver-compliant clients, like Appium, during the remote access session.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 4096.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RemoteAccessSession

Represents information about the remote access session.

Contents

appUpload

The ARN for the app to be installed onto your device.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

arn

The Amazon Resource Name (ARN) of the remote access session.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

billingMethod

The billing method of the remote access session. Possible values include `METERED` or `UNMETERED`. For more information about metered devices, see [AWS Device Farm terminology](#).

Type: String

Valid Values: `METERED` | `UNMETERED`

Required: No

created

The date and time the remote access session was created.

Type: Timestamp

Required: No

device

The device (phone or tablet) used in the remote access session.

Type: [Device](#) object

Required: No

deviceMinutes

The number of minutes a device is used in a remote access session (including setup and teardown minutes).

Type: [DeviceMinutes](#) object

Required: No

deviceProxy

The device proxy configured for the remote access session.

Type: [DeviceProxy](#) object

Required: No

deviceUdid

Unique device identifier for the remote device. Only returned if remote debugging is enabled for the remote access session.

Remote debugging is [no longer supported](#).

Type: String

Required: No

endpoint

The endpoint for the remote access session. This field is deprecated, and is replaced by the new `endpoints.interactiveEndpoint` field.

Type: String

Required: No

endpoints

Represents the remote endpoints for viewing and controlling a device during a remote access session.

Type: [RemoteAccessEndpoints](#) object

Required: No

instanceArn

The ARN of the instance.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

interactionMode

This member has been deprecated.

The interaction mode of the remote access session. Changing the interactive mode of remote access sessions is no longer available.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 64.

Valid Values: INTERACTIVE | NO_VIDEO | VIDEO_ONLY

Required: No

message

A message about the remote access session.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

Required: No

name

The name of the remote access session.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

result

The result of the remote access session. Can be any of the following:

- PENDING.
- PASSED.
- WARNED.
- FAILED.
- SKIPPED.
- ERRORED.
- STOPPED.

Type: String

Valid Values: PENDING | PASSED | WARNED | FAILED | SKIPPED | ERRORED | STOPPED

Required: No

skipAppResign

When set to `true`, for private devices, Device Farm does not sign your app again. For public devices, Device Farm always signs your apps again.

For more information about how Device Farm re-signs your apps, see [Do you modify my app?](#) in the *AWS Device Farm FAQs*.

Type: Boolean

Required: No

started

The date and time the remote access session was started.

Type: Timestamp

Required: No

status

The status of the remote access session. Can be any of the following:

- PENDING.
- PENDING_CONCURRENCY.
- PENDING_DEVICE.
- PROCESSING.
- SCHEDULING.
- PREPARING.
- RUNNING.
- COMPLETED.
- STOPPING.

Type: String

Valid Values: PENDING | PENDING_CONCURRENCY | PENDING_DEVICE | PROCESSING | SCHEDULING | PREPARING | RUNNING | COMPLETED | STOPPING

Required: No

stopped

The date and time the remote access session was stopped.

Type: Timestamp

Required: No

vpcConfig

The VPC security groups and subnets that are attached to a project.

Type: [VpcConfig](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Resolution

Represents the screen resolution of a device in height and width, expressed in pixels.

Contents

height

The screen resolution's height, expressed in pixels.

Type: Integer

Required: No

width

The screen resolution's width, expressed in pixels.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Rule

Represents a condition for a device pool.

Contents

attribute

The rule's stringified attribute. For example, specify the value as `"\"abc\""`.

The supported operators for each attribute are provided in the following list.

APPIUM_VERSION

The Appium version for the test.

Supported operators: CONTAINS

ARN

The Amazon Resource Name (ARN) of the device (for example, `arn:aws:devicefarm:us-west-2::device:12345Example`).

Supported operators: EQUALS, IN, NOT_IN

AVAILABILITY

The current availability of the device. Valid values are AVAILABLE, HIGHLY_AVAILABLE, BUSY, or TEMPORARY_NOT_AVAILABLE.

Supported operators: EQUALS

FLEET_TYPE

The fleet type. Valid values are PUBLIC or PRIVATE.

Supported operators: EQUALS

FORM_FACTOR

The device form factor. Valid values are PHONE or TABLET.

Supported operators: EQUALS, IN, NOT_IN

INSTANCE_ARN

The Amazon Resource Name (ARN) of the device instance.

Supported operators: IN, NOT_IN

INSTANCE_LABELS

The label of the device instance.

Supported operators: CONTAINS

MANUFACTURER

The device manufacturer (for example, Apple).

Supported operators: EQUALS, IN, NOT_IN

MODEL

The device model, such as Apple iPad Air 2 or Google Pixel.

Supported operators: CONTAINS, EQUALS, IN, NOT_IN

OS_VERSION

The operating system version (for example, 10.3.2).

Supported operators: EQUALS, GREATER_THAN, GREATER_THAN_OR_EQUALS, IN, LESS_THAN, LESS_THAN_OR_EQUALS, NOT_IN

PLATFORM

The device platform. Valid values are ANDROID or IOS.

Supported operators: EQUALS, IN, NOT_IN

REMOTE_ACCESS_ENABLED

Whether the device is enabled for remote access. Valid values are TRUE or FALSE.

Supported operators: EQUALS

REMOTE_DEBUG_ENABLED

Whether the device is enabled for remote debugging. Valid values are TRUE or FALSE.

Supported operators: EQUALS

Because remote debugging is [no longer supported](#), this filter is ignored.

Type: String

Valid Values: ARN | PLATFORM | FORM_FACTOR | MANUFACTURER | REMOTE_ACCESS_ENABLED | REMOTE_DEBUG_ENABLED | APPIUM_VERSION | INSTANCE_ARN | INSTANCE_LABELS | FLEET_TYPE | OS_VERSION | MODEL | AVAILABILITY

Required: No

operator

Specifies how Device Farm compares the rule's attribute to the value. For the operators that are supported by each attribute, see the attribute descriptions.

Type: String

Valid Values: EQUALS | LESS_THAN | LESS_THAN_OR_EQUALS | GREATER_THAN | GREATER_THAN_OR_EQUALS | IN | NOT_IN | CONTAINS

Required: No

value

The rule's value.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Run

Represents a test run on a set of devices with a given app package, test parameters, and so on.

Contents

appUpload

An app to upload or that has been uploaded.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

arn

The run's ARN.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

billingMethod

Specifies the billing method for a test run: `metered` or `unmetered`. If the parameter is not specified, the default value is `metered`.

Note

If you have unmetered device slots, you must set this to `unmetered` to use them. Otherwise, the run is counted toward metered device minutes.

Type: String

Valid Values: METERED | UNMETERED

Required: No

completedJobs

The total number of completed jobs.

Type: Integer

Required: No

counters

The run's result counters.

Type: [Counters](#) object

Required: No

created

When the run was created.

Type: Timestamp

Required: No

customerArtifactPaths

Output CustomerArtifactPaths object for the test run.

Type: [CustomerArtifactPaths](#) object

Required: No

deviceMinutes

Represents the total (metered or unmetered) minutes used by the test run.

Type: [DeviceMinutes](#) object

Required: No

devicePoolArn

The ARN of the device pool for the run.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

deviceProxy

The device proxy configured for the devices in the run.

Type: [DeviceProxy](#) object

Required: No

deviceSelectionResult

The results of a device filter used to select the devices for a test run.

Type: [DeviceSelectionResult](#) object

Required: No

environmentVariables

Environment variables associated with the run.

Type: Array of [EnvironmentVariable](#) objects

Array Members: Minimum number of 1 item. Maximum number of 32 items.

Required: No

eventCount

For fuzz tests, this is the number of events, between 1 and 10000, that the UI fuzz test should perform.

Type: Integer

Required: No

executionRoleArn

The IAM role associated with the run.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `^arn:aws:iam:[0-9]{12}:role/.+`

Required: No

insights

The insights for the run, including the report status and job-level metrics. This field contains data only if you specified `insightsTypes` when you scheduled the run.

Type: [RunInsights](#) object

Required: No

insightsTypes

The types of insights requested for the run.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Valid Values: TEST_REPORT

Required: No

jobTimeoutMinutes

The number of minutes the job executes before it times out.

Type: Integer

Required: No

locale

Information about the locale that is used for the run.

Type: String

Required: No

location

Information about the location that is used for the run.

Type: [Location](#) object

Required: No

message

A message about the run's result.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

Required: No

name

The run's name.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

networkProfile

The network profile being used for a test run.

Type: [NetworkProfile](#) object

Required: No

parsingResultUrl

Read-only URL for an object in an S3 bucket where you can get the parsing results of the test package. If the test package doesn't parse, the reason why it doesn't parse appears in the file that this URL points to.

Type: String

Required: No

platform

The run's platform.

Allowed values include:

- ANDROID
- IOS

Type: String

Valid Values: ANDROID | IOS

Required: No

radios

Information about the radio states for the run.

Type: [Radios](#) object

Required: No

result

The run's result.

Allowed values include:

- PENDING
- PASSED
- WARNED
- FAILED
- SKIPPED
- ERRORED
- STOPPED

Type: String

Valid Values: PENDING | PASSED | WARNED | FAILED | SKIPPED | ERRORED | STOPPED

Required: No

resultCode

Supporting field for the result field. Set only if `result` is SKIPPED. `PARSING_FAILED` if the result is skipped because of test package parsing failure.

Type: String

Valid Values: PARSING_FAILED | VPC_ENDPOINT_SETUP_FAILED

Required: No

seed

For fuzz tests, this is a seed to use for randomizing the UI fuzz test. Using the same seed value between tests ensures identical event sequences.

Type: Integer

Required: No

skipAppResign

When set to `true`, for private devices, Device Farm does not sign your app again. For public devices, Device Farm always signs your apps again.

For more information about how Device Farm re-signs your apps, see [Do you modify my app?](#) in the *AWS Device Farm FAQs*.

Type: Boolean

Required: No

started

The run's start time.

Type: Timestamp

Required: No

status

The run's status.

Allowed values include:

- PENDING
- PENDING_CONCURRENCY
- PENDING_DEVICE
- PROCESSING

- SCHEDULING
- PREPARING
- RUNNING
- COMPLETED
- STOPPING

Type: String

Valid Values: PENDING | PENDING_CONCURRENCY | PENDING_DEVICE | PROCESSING | SCHEDULING | PREPARING | RUNNING | COMPLETED | STOPPING

Required: No

stopped

The run's stop time.

Type: Timestamp

Required: No

testSpecArn

The ARN of the YAML-formatted test specification for the run.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: No

totalJobs

The total number of jobs for the run.

Type: Integer

Required: No

type

The run's type.

Must be one of the following values:

- BUILTIN_FUZZ
- APPIUM_JAVA_JUNIT
- APPIUM_JAVA_TESTNG
- APPIUM_PYTHON
- APPIUM_NODE
- APPIUM_RUBY
- APPIUM_WEB_JAVA_JUNIT
- APPIUM_WEB_JAVA_TESTNG
- APPIUM_WEB_PYTHON
- APPIUM_WEB_NODE
- APPIUM_WEB_RUBY
- INSTRUMENTATION
- XCTEST
- XCTEST_UI

Type: String

Valid Values: BUILTIN_FUZZ | APPIUM_JAVA_JUNIT | APPIUM_JAVA_TESTNG | APPIUM_PYTHON | APPIUM_NODE | APPIUM_RUBY | APPIUM_WEB_JAVA_JUNIT | APPIUM_WEB_JAVA_TESTNG | APPIUM_WEB_PYTHON | APPIUM_WEB_NODE | APPIUM_WEB_RUBY | INSTRUMENTATION | XCTEST | XCTEST_UI

Required: No

vpcConfig

The VPC security groups and subnets that are attached to a project.

Type: [VpcConfig](#) object

Required: No

webUrl

The Device Farm console URL for the recording of the run.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RunInsights

Contains insights for a run, including report status, and job-level aggregated metrics such as per job execution time and median job execution time.

Contents

jobReport

The job-level aggregated report for the run.

Type: [JobReport](#) object

Required: No

status

The status of the insights report for the run.

Type: String

Valid Values: PENDING | RUNNING | COMPLETED | SKIPPED | ERRORED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Sample

Represents a sample of performance data.

Contents

arn

The sample's ARN.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

type

The sample's type.

Must be one of the following values:

- CPU: A CPU sample type. This is expressed as the app processing CPU time (including child processes) as reported by process, as a percentage.
- MEMORY: A memory usage sample type. This is expressed as the total proportional set size of an app process, in kilobytes.
- NATIVE_AVG_DRAWTIME
- NATIVE_FPS
- NATIVE_FRAMES
- NATIVE_MAX_DRAWTIME
- NATIVE_MIN_DRAWTIME
- OPENGGL_AVG_DRAWTIME
- OPENGGL_FPS
- OPENGGL_FRAMES
- OPENGGL_MAX_DRAWTIME
- OPENGGL_MIN_DRAWTIME
- RX

- **RX_RATE**: The total number of bytes per second (TCP and UDP) that are sent, by app process.
- **THREADS**: A threads sample type. This is expressed as the total number of threads per app process.
- **TX**
- **TX_RATE**: The total number of bytes per second (TCP and UDP) that are received, by app process.

Type: String

Valid Values: CPU | MEMORY | THREADS | RX_RATE | TX_RATE | RX | TX |
NATIVE_FRAMES | NATIVE_FPS | NATIVE_MIN_DRAWTIME | NATIVE_AVG_DRAWTIME |
NATIVE_MAX_DRAWTIME | OPENGL_FRAMES | OPENGL_FPS | OPENGL_MIN_DRAWTIME |
OPENGL_AVG_DRAWTIME | OPENGL_MAX_DRAWTIME

Required: No

url

The presigned Amazon S3 URL that can be used with a GET request to download the sample's file.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ScheduleRunConfiguration

Represents the settings for a run. Includes things like location, radio states, auxiliary apps, and network profiles.

Contents

auxiliaryApps

A list of upload ARNs for app packages to be installed with your app.

Type: Array of strings

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

billingMethod

Specifies the billing method for a test run: `metered` or `unmetered`. If the parameter is not specified, the default value is `metered`.

Note

If you have purchased unmetered device slots, you must set this parameter to `unmetered` to make use of them. Otherwise, your run counts against your metered time.

Type: String

Valid Values: `METERED` | `UNMETERED`

Required: No

customerArtifactPaths

Input `CustomerArtifactPaths` object for the scheduled run configuration.

Type: [CustomerArtifactPaths](#) object

Required: No

deviceProxy

The device proxy to be configured on the device for the run.

Type: [DeviceProxy](#) object

Required: No

environmentVariables

Environment variables associated with the run.

Type: Array of [EnvironmentVariable](#) objects

Array Members: Minimum number of 1 item. Maximum number of 32 items.

Required: No

executionRoleArn

An IAM role to be assumed by the test host for the run.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `^arn:aws:iam:[0-9]{12}:role/.+`

Required: No

extraDataPackageArn

The ARN of the extra data for the run. The extra data is a .zip file that AWS Device Farm extracts to external data for Android or the app's sandbox for iOS.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

insightsTypes

The types of insights to generate for a run. Specify one or more values to opt in to insights generation when scheduling a run.

Insights are currently supported for custom mode runs with Instrumentation, Appium Java TestNG, and XCTest UI test types.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Valid Values: TEST_REPORT

Required: No

locale

Information about the locale that is used for the run.

Type: String

Required: No

location

Information about the location that is used for the run.

Type: [Location](#) object

Required: No

networkProfileArn

Reserved for internal use.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: No

radios

Information about the radio states for the run.

Type: [Radios](#) object

Required: No

vpceConfigurationArns

An array of ARNs for your VPC endpoint configurations.

Type: Array of strings

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ScheduleRunTest

Represents test settings. This data structure is passed in as the test parameter to `ScheduleRun`. For an example of the JSON request syntax, see [ScheduleRun](#).

Contents

type

The test's type.

Must be one of the following values:

- BUILTIN_FUZZ
- APPIUM_JAVA_JUNIT
- APPIUM_JAVA_TESTNG
- APPIUM_PYTHON
- APPIUM_NODE
- APPIUM_RUBY
- APPIUM_WEB_JAVA_JUNIT
- APPIUM_WEB_JAVA_TESTNG
- APPIUM_WEB_PYTHON
- APPIUM_WEB_NODE
- APPIUM_WEB_RUBY
- INSTRUMENTATION
- XCTEST
- XCTEST_UI

Type: String

Valid Values: BUILTIN_FUZZ | APPIUM_JAVA_JUNIT | APPIUM_JAVA_TESTNG | APPIUM_PYTHON | APPIUM_NODE | APPIUM_RUBY | APPIUM_WEB_JAVA_JUNIT | APPIUM_WEB_JAVA_TESTNG | APPIUM_WEB_PYTHON | APPIUM_WEB_NODE | APPIUM_WEB_RUBY | INSTRUMENTATION | XCTEST | XCTEST_UI

Required: Yes

filter

The test's filter.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 8192.

Required: No

parameters

The test's parameters, such as test framework parameters and fixture settings. Parameters are represented by name-value pairs of strings.

For all tests:

- `app_performance_monitoring`: Performance monitoring is enabled by default. Set this parameter to false to disable it.

For Appium tests (all types):

- `appium_version`: The Appium version. Currently supported values are 1.6.5 (and later), latest, and default.
 - latest runs the latest Appium version supported by Device Farm (1.9.1).
 - For default, Device Farm selects a compatible version of Appium for the device. The current behavior is to run 1.7.2 on Android devices and iOS 9 and earlier and 1.7.2 for iOS 10 and later.
 - This behavior is subject to change.

For fuzz tests (Android only):

- `event_count`: The number of events, between 1 and 10000, that the UI fuzz test should perform.
- `throttle`: The time, in ms, between 0 and 1000, that the UI fuzz test should wait between events.
- `seed`: A seed to use for randomizing the UI fuzz test. Using the same seed value between tests ensures identical event sequences.

For Instrumentation:

- `filter`: A test filter string. Examples:
 - Running a single test case: `com.android.abc.Test1`

- Running a single test: `com.android.abc.Test1#smoke`
- Running multiple tests: `com.android.abc.Test1,com.android.abc.Test2`

For XCTest and XCTestUI:

- filter: A test filter string. Examples:
 - Running a single test class: `LoginTests`
 - Running a multiple test classes: `LoginTests,SmokeTests`
 - Running a single test: `LoginTests/testValid`
 - Running multiple tests: `LoginTests/testValid,LoginTests/testInvalid`

Type: String to string map

Required: No

testPackageArn

The ARN of the uploaded test to be run.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

testSpecArn

The ARN of the YAML-formatted test specification.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Suite

Represents a collection of one or more tests.

Contents

arn

The suite's ARN.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

counters

The suite's result counters.

Type: [Counters](#) object

Required: No

created

When the suite was created.

Type: Timestamp

Required: No

deviceMinutes

Represents the total (metered or unmetered) minutes used by the test suite.

Type: [DeviceMinutes](#) object

Required: No

message

A message about the suite's result.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

Required: No

name

The suite's name.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

result

The suite's result.

Allowed values include:

- PENDING
- PASSED
- WARNED
- FAILED
- SKIPPED
- ERRORED
- STOPPED

Type: String

Valid Values: PENDING | PASSED | WARNED | FAILED | SKIPPED | ERRORED | STOPPED

Required: No

started

The suite's start time.

Type: Timestamp

Required: No

status

The suite's status.

Allowed values include:

- PENDING
- PENDING_CONCURRENCY
- PENDING_DEVICE
- PROCESSING
- SCHEDULING
- PREPARING
- RUNNING
- COMPLETED
- STOPPING

Type: String

Valid Values: PENDING | PENDING_CONCURRENCY | PENDING_DEVICE | PROCESSING | SCHEDULING | PREPARING | RUNNING | COMPLETED | STOPPING

Required: No

stopped

The suite's stop time.

Type: Timestamp

Required: No

type

The suite's type.

Must be one of the following values:

- BUILTIN_FUZZ
- APPIUM_JAVA_JUNIT
- APPIUM_JAVA_TESTNG
- APPIUM_PYTHON

- APPIUM_NODE
- APPIUM_RUBY
- APPIUM_WEB_JAVA_JUNIT
- APPIUM_WEB_JAVA_TESTNG
- APPIUM_WEB_PYTHON
- APPIUM_WEB_NODE
- APPIUM_WEB_RUBY
- INSTRUMENTATION
- XCTEST
- XCTEST_UI

Type: String

Valid Values: BUILTIN_FUZZ | APPIUM_JAVA_JUNIT | APPIUM_JAVA_TESTNG | APPIUM_PYTHON | APPIUM_NODE | APPIUM_RUBY | APPIUM_WEB_JAVA_JUNIT | APPIUM_WEB_JAVA_TESTNG | APPIUM_WEB_PYTHON | APPIUM_WEB_NODE | APPIUM_WEB_RUBY | INSTRUMENTATION | XCTEST | XCTEST_UI

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Tag

The metadata that you apply to a resource to help you categorize and organize it. Each tag consists of a key and an optional value, both of which you define. Tag keys can have a maximum character length of 128 characters. Tag values can have a maximum length of 256 characters.

Contents

Key

One part of a key-value pair that makes up a tag. A key is a general label that acts like a category for more specific tag values.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

Value

The optional part of a key-value pair that makes up a tag. A value acts as a descriptor in a tag category (key).

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Test

Represents a condition that is evaluated.

Contents

arn

The test's ARN.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

counters

The test's result counters.

Type: [Counters](#) object

Required: No

created

When the test was created.

Type: Timestamp

Required: No

deviceMinutes

Represents the total (metered or unmetered) minutes used by the test.

Type: [DeviceMinutes](#) object

Required: No

message

A message about the test's result.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

Required: No

name

The test's name.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

result

The test's result.

Allowed values include:

- PENDING
- PASSED
- WARNED
- FAILED
- SKIPPED
- ERRORED
- STOPPED

Type: String

Valid Values: PENDING | PASSED | WARNED | FAILED | SKIPPED | ERRORED | STOPPED

Required: No

started

The test's start time.

Type: Timestamp

Required: No

status

The test's status.

Allowed values include:

- PENDING
- PENDING_CONCURRENCY
- PENDING_DEVICE
- PROCESSING
- SCHEDULING
- PREPARING
- RUNNING
- COMPLETED
- STOPPING

Type: String

Valid Values: PENDING | PENDING_CONCURRENCY | PENDING_DEVICE | PROCESSING | SCHEDULING | PREPARING | RUNNING | COMPLETED | STOPPING

Required: No

stopped

The test's stop time.

Type: Timestamp

Required: No

type

The test's type.

Must be one of the following values:

- BUILTIN_FUZZ
- APPIUM_JAVA_JUNIT
- APPIUM_JAVA_TESTNG
- APPIUM_PYTHON

- APPIUM_NODE
- APPIUM_RUBY
- APPIUM_WEB_JAVA_JUNIT
- APPIUM_WEB_JAVA_TESTNG
- APPIUM_WEB_PYTHON
- APPIUM_WEB_NODE
- APPIUM_WEB_RUBY
- INSTRUMENTATION
- XCTEST
- XCTEST_UI

Type: String

Valid Values: BUILTIN_FUZZ | APPIUM_JAVA_JUNIT | APPIUM_JAVA_TESTNG | APPIUM_PYTHON | APPIUM_NODE | APPIUM_RUBY | APPIUM_WEB_JAVA_JUNIT | APPIUM_WEB_JAVA_TESTNG | APPIUM_WEB_PYTHON | APPIUM_WEB_NODE | APPIUM_WEB_RUBY | INSTRUMENTATION | XCTEST | XCTEST_UI

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TestGridProject

A Selenium testing project. Projects are used to collect and collate sessions.

Contents

arn

The ARN for the project.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

created

When the project was created.

Type: Timestamp

Required: No

description

A human-readable description for the project.

Type: String

Required: No

name

A human-readable name for the project.

Type: String

Required: No

vpcConfig

The VPC security groups and subnets that are attached to a project.

Type: [TestGridVpcConfig](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TestGridSession

A [TestGridSession](#) is a single instance of a browser launched from the URL provided by a call to [CreateTestGridUrl](#).

Contents

arn

The ARN of the session.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: ^arn:aws:devicefarm:.*+

Required: No

billingMinutes

The number of billed minutes that were used for this session.

Type: Double

Required: No

created

The time that the session was started.

Type: Timestamp

Required: No

ended

The time the session ended.

Type: Timestamp

Required: No

seleniumProperties

A JSON object of options and parameters passed to the Selenium WebDriver.

Type: String

Required: No

status

The state of the session.

Type: String

Valid Values: ACTIVE | CLOSED | ERRORRED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TestGridSessionAction

An action taken by a [TestGridSession](#) browser instance.

Contents

action

The action taken by the session.

Type: String

Required: No

duration

The time, in milliseconds, that the action took to complete in the browser.

Type: Long

Required: No

requestMethod

HTTP method that the browser used to make the request.

Type: String

Required: No

started

The time that the session invoked the action.

Type: Timestamp

Required: No

statusCode

HTTP status code returned to the browser when the action was taken.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TestGridSessionArtifact

Artifacts are video and other files that are produced in the process of running a browser in an automated context.

Note

Video elements might be broken up into multiple artifacts as they grow in size during creation.

Contents

filename

The file name of the artifact.

Type: String

Required: No

type

The kind of artifact.

Type: String

Valid Values: UNKNOWN | VIDEO | SELENIUM_LOG

Required: No

url

A semi-stable URL to the content of the object.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TestGridVpcConfig

The VPC security groups and subnets that are attached to a project.

Contents

securityGroupIds

A list of VPC security group IDs in your Amazon VPC.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: `.*\S.*`

Required: Yes

subnetIds

A list of VPC subnet IDs in your Amazon VPC.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 8 items.

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: `.*\S.*`

Required: Yes

vpcId

The ID of the Amazon VPC.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: `.*\S.*`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TestReport

Contains aggregated test-level metrics for a job.

Contents

message

A message associated with the test report.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 4096.

Required: No

metrics

The aggregated test-level metrics for the job.

Type: [TestReportMetrics](#) object

Required: No

testDetailsUrl

A URL to the detailed test results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 4096.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TestReportMetrics

Contains aggregated metrics across all tests in a job.

Contents

medianTestExecutionDurationSeconds

The median execution duration of tests in the job, in seconds.

Type: Double

Required: No

testsErrored

The number of tests that errored.

Type: Integer

Required: No

testsFailed

The number of tests that failed.

Type: Integer

Required: No

testsOther

The number of tests with other result types.

Type: Integer

Required: No

testsPassed

The number of tests that passed.

Type: Integer

Required: No

testsPassedPercentage

The percentage of tests that passed.

Type: Double

Required: No

testsSkipped

The number of tests that were skipped.

Type: Integer

Required: No

testsTotal

The total number of tests in the job.

Type: Integer

Required: No

totalTestExecutionDurationSeconds

The total execution duration of all tests in the job, in seconds.

Type: Double

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TrialMinutes

Represents information about free trial device minutes for an AWS account.

Contents

remaining

The number of free trial minutes remaining in the account.

Type: Double

Required: No

total

The total number of free trial minutes that the account started with.

Type: Double

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UniqueProblem

A collection of one or more problems, grouped by their result.

Contents

message

A message about the unique problems' result.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

Required: No

problems

Information about the problems.

Type: Array of [Problem](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Upload

An app or a set of one or more tests to upload or that have been uploaded.

Contents

arn

The upload's ARN.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

category

The upload's category. Allowed values include:

- **CURATED**: An upload managed by AWS Device Farm.
- **PRIVATE**: An upload managed by the AWS Device Farm customer.

Type: String

Valid Values: `CURATED` | `PRIVATE`

Required: No

contentType

The upload's content type (for example, `application/octet-stream`).

Type: String

Length Constraints: Minimum length of 0. Maximum length of 64.

Required: No

created

When the upload was created.

Type: Timestamp

Required: No

message

A message about the upload's result.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

Required: No

metadata

The upload's metadata. For example, for Android, this contains information that is parsed from the manifest and is displayed in the AWS Device Farm console after the associated app is uploaded.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 8192.

Required: No

name

The upload's file name.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

status

The upload's status.

Must be one of the following values:

- FAILED
- INITIALIZED
- PROCESSING

- SUCCEEDED

Type: String

Valid Values: INITIALIZED | PROCESSING | SUCCEEDED | FAILED

Required: No

type

The upload's type.

Must be one of the following values:

- ANDROID_APP
- IOS_APP
- WEB_APP
- EXTERNAL_DATA
- APPIUM_JAVA_JUNIT_TEST_PACKAGE
- APPIUM_JAVA_TESTNG_TEST_PACKAGE
- APPIUM_PYTHON_TEST_PACKAGE
- APPIUM_NODE_TEST_PACKAGE
- APPIUM_RUBY_TEST_PACKAGE
- APPIUM_WEB_JAVA_JUNIT_TEST_PACKAGE
- APPIUM_WEB_JAVA_TESTNG_TEST_PACKAGE
- APPIUM_WEB_PYTHON_TEST_PACKAGE
- APPIUM_WEB_NODE_TEST_PACKAGE
- APPIUM_WEB_RUBY_TEST_PACKAGE
- INSTRUMENTATION_TEST_PACKAGE
- XCTEST_TEST_PACKAGE
- XCTEST_UI_TEST_PACKAGE
- APPIUM_JAVA_JUNIT_TEST_SPEC
- APPIUM_JAVA_TESTNG_TEST_SPEC
- APPIUM_PYTHON_TEST_SPEC
- APPIUM_NODE_TEST_SPEC

- APPIUM_RUBY_TEST_SPEC
- APPIUM_WEB_JAVA_JUNIT_TEST_SPEC
- APPIUM_WEB_JAVA_TESTNG_TEST_SPEC
- APPIUM_WEB_PYTHON_TEST_SPEC
- APPIUM_WEB_NODE_TEST_SPEC
- APPIUM_WEB_RUBY_TEST_SPEC
- INSTRUMENTATION_TEST_SPEC
- XCTEST_UI_TEST_SPEC

Type: String

Valid Values: ANDROID_APP | IOS_APP | WEB_APP | EXTERNAL_DATA |
APPIUM_JAVA_JUNIT_TEST_PACKAGE | APPIUM_JAVA_TESTNG_TEST_PACKAGE
| APPIUM_PYTHON_TEST_PACKAGE | APPIUM_NODE_TEST_PACKAGE |
APPIUM_RUBY_TEST_PACKAGE | APPIUM_WEB_JAVA_JUNIT_TEST_PACKAGE |
APPIUM_WEB_JAVA_TESTNG_TEST_PACKAGE | APPIUM_WEB_PYTHON_TEST_PACKAGE
| APPIUM_WEB_NODE_TEST_PACKAGE | APPIUM_WEB_RUBY_TEST_PACKAGE
| CALABASH_TEST_PACKAGE | INSTRUMENTATION_TEST_PACKAGE
| UIAUTOMATION_TEST_PACKAGE | UIAUTOMATOR_TEST_PACKAGE
| XCTEST_TEST_PACKAGE | XCTEST_UI_TEST_PACKAGE |
APPIUM_JAVA_JUNIT_TEST_SPEC | APPIUM_JAVA_TESTNG_TEST_SPEC |
APPIUM_PYTHON_TEST_SPEC | APPIUM_NODE_TEST_SPEC | APPIUM_RUBY_TEST_SPEC
| APPIUM_WEB_JAVA_JUNIT_TEST_SPEC | APPIUM_WEB_JAVA_TESTNG_TEST_SPEC
| APPIUM_WEB_PYTHON_TEST_SPEC | APPIUM_WEB_NODE_TEST_SPEC
| APPIUM_WEB_RUBY_TEST_SPEC | INSTRUMENTATION_TEST_SPEC |
XCTEST_UI_TEST_SPEC

Required: No

url

The presigned Amazon S3 URL that was used to store a file using a PUT request.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 4096.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VpcConfig

Contains the VPC configuration data necessary to interface with AWS Device Farm's services.

Contents

securityGroupIds

An array of one or more security groups IDs in your Amazon VPC.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: `^sg-[0-9a-fA-F]{8,}$`

Required: Yes

subnetIds

An array of one or more subnet IDs in your Amazon VPC.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 8 items.

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: `^subnet-[0-9a-fA-F]{8,}$`

Required: Yes

vpId

The ID of the Amazon VPC.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Pattern: `.*\S.*`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VPCEConfiguration

Represents an Amazon Virtual Private Cloud (VPC) endpoint configuration.

Contents

arn

The Amazon Resource Name (ARN) of the VPC endpoint configuration.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `^arn:aws:devicefarm:.*`

Required: No

serviceDnsName

The DNS name that maps to the private IP address of the service you want to access.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Required: No

vpceConfigurationDescription

An optional description that provides details about your VPC endpoint configuration.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Required: No

vpceConfigurationName

The friendly name you give to your VPC endpoint configuration to manage your configurations more easily.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

vpceServiceName

The name of the VPC endpoint service running in your AWS account that you want Device Farm to test.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Error Types

This section lists common error types that this AWS service may return. Not all services return all error types listed here. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You don't have permission to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 403

ExpiredTokenException

The security token included in the request has expired. Request a new security token and try again.

HTTP Status Code: 403

IncompleteSignature

The request signature doesn't conform to AWS standards. Verify that you're using valid AWS credentials and that your request is properly formatted. If you're using an SDK, ensure it's up to date.

HTTP Status Code: 403

InternalFailure

The request can't be processed right now because of an internal server issue. Try again later. If the problem persists, contact AWS Support.

HTTP Status Code: 500

MalformedHttpRequestException

The request body can't be processed. This typically happens when the request body can't be decompressed using the specified content encoding algorithm. Verify that the content encoding header matches the compression format used.

HTTP Status Code: 400

NotAuthorized

You don't have permissions to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 401

OptInRequired

Your AWS account needs a subscription for this service. Verify that you've enabled the service in your account.

HTTP Status Code: 403

RequestAbortedException

The request was aborted before a response could be returned. This typically happens when the client closes the connection.

HTTP Status Code: 400

RequestEntityTooLargeException

The request entity is too large. Reduce the size of the request body and try again.

HTTP Status Code: 413

RequestTimeoutException

The request timed out. The server didn't receive the complete request within the expected time frame. Try again.

HTTP Status Code: 408

ServiceUnavailable

The service is temporarily unavailable. Try again later.

HTTP Status Code: 503

ThrottlingException

Your request rate is too high. The AWS SDKs automatically retry requests that receive this exception. Reduce the frequency of requests.

HTTP Status Code: 400

UnknownOperationException

The action or operation isn't recognized. Verify that the action name is spelled correctly and that it's supported by the API version you're using.

HTTP Status Code: 404

UnrecognizedClientException

The X.509 certificate or AWS access key ID you provided doesn't exist in our records. Verify that you're using valid credentials and that they haven't expired.

HTTP Status Code: 403

ValidationError

The input doesn't meet the required format or constraints. Check that all required parameters are included and that values are valid.

HTTP Status Code: 400