



API Reference

AWS Elemental Inference



API Version 2018-11-14

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

AWS Elemental Inference: API Reference

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
AssociateFeed	3
Request Syntax	3
URI Request Parameters	3
Request Body	4
Response Syntax	5
Response Elements	5
Errors	5
See Also	6
CreateDictionary	8
Request Syntax	8
URI Request Parameters	8
Request Body	8
Response Syntax	9
Response Elements	10
Errors	11
See Also	12
CreateFeed	13
Request Syntax	13
URI Request Parameters	13
Request Body	13
Response Syntax	14
Response Elements	15
Errors	16
See Also	17
DeleteDictionary	19
Request Syntax	19
URI Request Parameters	19
Request Body	19
Response Syntax	19
Response Elements	19
Errors	20
See Also	21

DeleteFeed	22
Request Syntax	22
URI Request Parameters	22
Request Body	22
Response Syntax	22
Response Elements	23
Errors	23
See Also	24
DisassociateFeed	26
Request Syntax	26
URI Request Parameters	26
Request Body	26
Response Syntax	27
Response Elements	27
Errors	28
See Also	29
ExportDictionaryEntries	30
Request Syntax	30
URI Request Parameters	30
Request Body	30
Response Syntax	30
Response Elements	30
Errors	31
See Also	32
GetDictionary	33
Request Syntax	33
URI Request Parameters	33
Request Body	33
Response Syntax	33
Response Elements	34
Errors	35
See Also	36
GetFeed	37
Request Syntax	37
URI Request Parameters	37
Request Body	37

Response Syntax	37
Response Elements	38
Errors	39
See Also	40
ListDictionaries	41
Request Syntax	41
URI Request Parameters	41
Request Body	41
Response Syntax	41
Response Elements	42
Errors	42
See Also	43
ListFeeds	44
Request Syntax	44
URI Request Parameters	44
Request Body	44
Response Syntax	44
Response Elements	45
Errors	45
See Also	46
ListTagsForResource	48
Request Syntax	48
URI Request Parameters	48
Request Body	48
Response Syntax	48
Response Elements	48
Errors	49
See Also	50
TagResource	51
Request Syntax	51
URI Request Parameters	51
Request Body	51
Response Syntax	52
Response Elements	52
Errors	52
See Also	53

UntagResource	54
Request Syntax	54
URI Request Parameters	54
Request Body	54
Response Syntax	54
Response Elements	54
Errors	55
See Also	56
UpdateDictionary	57
Request Syntax	57
URI Request Parameters	57
Request Body	57
Response Syntax	58
Response Elements	58
Errors	60
See Also	61
UpdateFeed	62
Request Syntax	62
URI Request Parameters	62
Request Body	63
Response Syntax	63
Response Elements	64
Errors	65
See Also	66
Data Types	68
AspectRatio	69
Contents	69
See Also	69
ClippingConfig	70
Contents	70
See Also	70
CreateOutput	71
Contents	71
See Also	72
CroppingConfig	73
Contents	73

See Also	73
DictionarySummary	74
Contents	74
See Also	75
FeedAssociation	76
Contents	76
See Also	76
FeedSummary	77
Contents	77
See Also	78
GetOutput	79
Contents	79
See Also	80
OutputConfig	81
Contents	81
See Also	81
SubtitlingConfig	83
Contents	83
See Also	84
UpdateOutput	85
Contents	85
See Also	86
Common Parameters	87
Common Error Types	90

Welcome

This is the AWS Elemental Inference REST API Reference. It provides information on the URL, request contents, and response contents of each AWS Elemental Inference REST operation.

We assume that you have the IAM permissions that you need to use AWS Elemental Inference via the REST API. We also assume that you are familiar with the features and operations of AWS Elemental Inference as described in *AWS Elemental Inference User Guide*.

This document was last published on October 13, 2026.

Actions

The following actions are supported:

- [AssociateFeed](#)
- [CreateDictionary](#)
- [CreateFeed](#)
- [DeleteDictionary](#)
- [DeleteFeed](#)
- [DisassociateFeed](#)
- [ExportDictionaryEntries](#)
- [GetDictionary](#)
- [GetFeed](#)
- [ListDictionaries](#)
- [ListFeeds](#)
- [ListTagsForResource](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdateDictionary](#)
- [UpdateFeed](#)

AssociateFeed

Associates a resource with the feed. The resource provides the input that Elemental Inference needs in order to perform an Elemental Inference feature, such as cropping video. You always provide the resource by associating it with a feed. You can associate only one resource with each feed. With an association, a specific source media is claiming ownership of the feed.

AssociateFeed is a PATCH operation, which means that you can include only parameters that you want to change. Parameters that you don't include will not be affected by the operation.

Specifically:

- You can add more outputs to the existing outputs. New outputs will be appended.
- You can't modify an existing output (for example to change its name). Instead, use UpdateFeed.
- You can't delete an existing output. Instead, use UpdateFeed.

Also note that you can't change the feed name with AssociateFeed. Instead, use UpdateFeed.

Request Syntax

```
POST /v1/feed/id/associate HTTP/1.1
Content-type: application/json

{
  "associatedResourceName": "string",
  "dryRun": boolean,
  "outputs": [
    {
      "description": "string",
      "name": "string",
      "outputConfig": { ... },
      "status": "string"
    }
  ]
}
```

URI Request Parameters

The request uses the following URI parameters.

id

The ID of the feed.

Pattern: `[a-z0-9]{19}`

Required: Yes

Request Body

The request accepts the following data in JSON format.

associatedResourceName

An identifier for the resource. This name must not resemble an ARN.

The resource is the source media that the feed will process. The name you assign should help you to later identify the source media that belongs to the feed. In this way, you will know which source media to push to the feed (using PutMedia).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[\w \-\. ' , @ : ; / ] *`

Required: Yes

dryRun

Set to true if you want to do a dry run of the associate action.

Elemental Inference will validate that the real request would succeed without actually making any changes. A dry run catches errors such as missing IAM permissions, quota limits exceeded, conflicting outputs, and so on. If the dry run fails, the action returns a 4xx error code. After you've fixed the errors, resubmit the request.

Type: Boolean

Required: No

outputs

An array of one or more outputs that you want to add to this feed now, to supplement any outputs that you specified when you created or updated the feed.

Type: Array of [CreateOutput](#) objects

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "arn": "string",
  "id": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[arn](#)

The ARN of the feed.

Type: String

[id](#)

The ID of the feed.

Type: String

Pattern: `[a-z0-9]{19}`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request could not be completed due to a conflict.

HTTP Status Code: 409

InternalServerErrorException

An internal server error occurred. This is a temporary condition and the request can be retried. If the problem persists, contact AWS Support.

HTTP Status Code: 500

ResourceNotFoundException

The resource specified in the action doesn't exist.

HTTP Status Code: 404

ServiceQuotaExceededException

The request was rejected because it would exceed one or more service quotas for your account. Review your service quotas and either delete unused resources or request a quota increase.

HTTP Status Code: 402

TooManyRequestException

The request was denied due to request throttling. Too many requests have been made within a given time period. Reduce the frequency of requests and use exponential backoff when retrying.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by the service. Check the error message for details about which parameter or field is invalid and correct the request before retrying.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

CreateDictionary

Creates a custom dictionary for improving transcription accuracy. A dictionary contains custom words and phrases that the ASR engine might not recognize, such as brand names, technical terms, or proper nouns. You can reference a dictionary when configuring a smart subtitles output.

Request Syntax

```
POST /v1/dictionary HTTP/1.1
Content-type: application/json
```

```
{
  "entries": "string",
  "language": "string",
  "name": "string",
  "tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

entries

The dictionary entries payload. Contains the custom words and phrases for the dictionary. Maximum size is 40,960 characters.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 40960.

Required: No

language

The language of the dictionary entries. Specify the language using an ISO 639-2/T three-letter code. Supported values: eng, fra, ita, deu, spa, por.

Type: String

Valid Values: eng | fra | ita | deu | spa | por

Required: Yes

name

A user-friendly name for this dictionary.

Type: String

Pattern: `[a-zA-Z0-9]([a-zA-Z0-9-_{0,126}[a-zA-Z0-9])?`

Required: Yes

tags

Optional tags to associate with the dictionary.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 202
Content-type: application/json
```

```
{
  "arn": "string",
  "id": "string",
  "language": "string",
  "name": "string",
  "references": [ "string" ],
  "status": "string",
  "tags": {
    "string" : "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 202 response.

The following data is returned in JSON format by the service.

arn

The ARN of the dictionary.

Type: String

id

A unique ID that Elemental Inference assigns to the dictionary.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 19.

Pattern: `[a-zA-Z0-9]+`

language

The language of the dictionary.

Type: String

Valid Values: `eng | fra | ita | deu | spa | por`

name

The name that you specified in the request.

Type: String

Pattern: `[a-zA-Z0-9]([a-zA-Z0-9-_{0,126}[a-zA-Z0-9])?`

references

A list of feed IDs that reference this dictionary.

Type: Array of strings

Pattern: `[a-z0-9]{19}`

status

The current status of the dictionary. After creation succeeds, the status will be AVAILABLE.

Type: String

Valid Values: CREATING | AVAILABLE | REFERENCED | DELETING | DELETED

tags

Any tags that you included when you created the dictionary.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request could not be completed due to a conflict.

HTTP Status Code: 409

InternalServerErrorException

An internal server error occurred. This is a temporary condition and the request can be retried. If the problem persists, contact AWS Support.

HTTP Status Code: 500

ServiceQuotaExceededException

The request was rejected because it would exceed one or more service quotas for your account. Review your service quotas and either delete unused resources or request a quota increase.

HTTP Status Code: 402

TooManyRequestException

The request was denied due to request throttling. Too many requests have been made within a given time period. Reduce the frequency of requests and use exponential backoff when retrying.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by the service. Check the error message for details about which parameter or field is invalid and correct the request before retrying.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

CreateFeed

Creates a feed. The feed is the target for the live media stream that is being sent by the calling application. An example of a calling application is AWS Elemental MediaLive.

The key contents of the feed is an array of outputs. Each output represents an Elemental Inference feature. After you create the feed, you must associate a resource with the feed. At that point, you will have a useable feed: resource - feed - output or outputs.

Request Syntax

```
POST /v1/feed HTTP/1.1
Content-type: application/json

{
  "name": "string",
  "outputs": [
    {
      "description": "string",
      "name": "string",
      "outputConfig": { ... },
      "status": "string"
    }
  ],
  "tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

name

A user-friendly name for this feed.

Type: String

Pattern: `[a-zA-Z0-9]([a-zA-Z0-9-]{0,126}[a-zA-Z0-9])?`

Required: Yes

outputs

An array of outputs for this feed. Each output represents a specific Elemental Inference feature. For example, there is one output type for the smart crop feature. You must specify at least one output, but you can later add outputs using `AssociateFeed`, or add, modify, and delete outputs using `UpdateFeed`.

Type: Array of [CreateOutput](#) objects

Required: Yes

tags

Optional tags. You can also add tags later, using `TagResource`.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 202
```

```
Content-type: application/json
```

```
{
  "arn": "string",
  "association": {
    "associatedResourceName": "string"
  },
  "dataEndpoints": [ "string" ],
  "id": "string",
  "name": "string",
  "outputs": [
    {
      "description": "string",
```

```
    "fromAssociation": boolean,
    "name": "string",
    "outputConfig": { ... },
    "status": "string"
  }
],
"status": "string",
"tags": {
  "string" : "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 202 response.

The following data is returned in JSON format by the service.

arn

A unique ARN that Elemental Inference assigns to the feed.

Type: String

association

The association for this feed. When you create the feed, this property is empty. You must associate a resource with the feed using AssociateFeed or UpdateFeed.

Type: [FeedAssociation](#) object

dataEndpoints

An array of endpoints for the feed. Typically, there is only one endpoint. The feed receives source media at this endpoint (when the calling application calls PutMedia) and returns the resulting metadata to this endpoint (when the calling application calls GetMetadata).

Type: Array of strings

id

A unique ID that Elemental Inference assigns to the feed.

Type: String

Pattern: `[a-z0-9]{19}`

name

The name that you specified in the request.

Type: String

Pattern: `[a-zA-Z0-9]([a-zA-Z0-9-]{0,126}[a-zA-Z0-9])?`

outputs

Repeats the outputs that you specified in the request.

Type: Array of [GetOutput](#) objects

status

The current status of the feed. After creation of the feed has succeeded, the status will be AVAILABLE.

Type: String

Valid Values: CREATING | AVAILABLE | ACTIVE | UPDATING | DELETING | DELETED
| ARCHIVED

tags

Any tags that you included when you created the feed.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request could not be completed due to a conflict.

HTTP Status Code: 409

InternalServerErrorException

An internal server error occurred. This is a temporary condition and the request can be retried. If the problem persists, contact AWS Support.

HTTP Status Code: 500

ServiceQuotaExceededException

The request was rejected because it would exceed one or more service quotas for your account. Review your service quotas and either delete unused resources or request a quota increase.

HTTP Status Code: 402

TooManyRequestException

The request was denied due to request throttling. Too many requests have been made within a given time period. Reduce the frequency of requests and use exponential backoff when retrying.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by the service. Check the error message for details about which parameter or field is invalid and correct the request before retrying.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DeleteDictionary

Deletes the specified dictionary. You cannot delete a dictionary that is referenced by a feed. You must first remove the dictionary reference from the feed's subtitling configuration.

Request Syntax

```
DELETE /v1/dictionary/id HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

id

The ID of the dictionary to delete.

Length Constraints: Minimum length of 1. Maximum length of 19.

Pattern: [a-zA-Z0-9]+

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 202
Content-type: application/json

{
  "arn": "string",
  "id": "string",
  "status": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 202 response.

The following data is returned in JSON format by the service.

arn

The ARN of the deleted dictionary.

Type: String

id

The ID of the deleted dictionary.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 19.

Pattern: [a-zA-Z0-9]+

status

The status of the dictionary after deletion.

Type: String

Valid Values: CREATING | AVAILABLE | REFERENCED | DELETING | DELETED

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request could not be completed due to a conflict.

HTTP Status Code: 409

InternalServerErrorException

An internal server error occurred. This is a temporary condition and the request can be retried. If the problem persists, contact AWS Support.

HTTP Status Code: 500

ResourceNotFoundException

The resource specified in the action doesn't exist.

HTTP Status Code: 404

TooManyRequestException

The request was denied due to request throttling. Too many requests have been made within a given time period. Reduce the frequency of requests and use exponential backoff when retrying.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by the service. Check the error message for details about which parameter or field is invalid and correct the request before retrying.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DeleteFeed

Deletes the specified feed. You can delete the feed at any time. Elemental Inference doesn't block you from deleting a feed when the calling application is calling PutMedia or GetMetadata on that feed, although both these calls will start to fail. For more information about managing inactive feeds, see the Elemental Inference User Guide.

Request Syntax

```
DELETE /v1/feed/id HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

id

The ID of the feed.

Pattern: `[a-z0-9]{19}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 202
Content-type: application/json

{
  "arn": "string",
  "id": "string",
  "status": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 202 response.

The following data is returned in JSON format by the service.

arn

The ARN of the deleted feed.

Type: String

id

The ID of the deleted feed.

Type: String

Pattern: [a-z0-9]{19}

status

The current status of the feed. When deletion of the feed has succeeded, the status will be DELETED.

Type: String

Valid Values: CREATING | AVAILABLE | ACTIVE | UPDATING | DELETING | DELETED
| ARCHIVED

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request could not be completed due to a conflict.

HTTP Status Code: 409

InternalServerErrorException

An internal server error occurred. This is a temporary condition and the request can be retried. If the problem persists, contact AWS Support.

HTTP Status Code: 500

ResourceNotFoundException

The resource specified in the action doesn't exist.

HTTP Status Code: 404

TooManyRequestException

The request was denied due to request throttling. Too many requests have been made within a given time period. Reduce the frequency of requests and use exponential backoff when retrying.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by the service. Check the error message for details about which parameter or field is invalid and correct the request before retrying.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DisassociateFeed

Releases the resource (the source media) that is associated with this feed. The outputs in the feed become DISABLED.

Request Syntax

```
POST /v1/feed/id/disassociate HTTP/1.1
Content-type: application/json

{
  "associatedResourceName": "string",
  "dryRun": boolean
}
```

URI Request Parameters

The request uses the following URI parameters.

id

The ID of the feed where you want to release the resource.

Pattern: [a-z0-9]{19}

Required: Yes

Request Body

The request accepts the following data in JSON format.

associatedResourceName

The name of the resource currently associated with the feed.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: [\w \-\.\',@:;/]*

Required: Yes

dryRun

Set to true if you want to do a dry run of the disassociate action.

Elemental Inference will validate that the real request would succeed without actually making any changes. A dry run catches errors such as missing IAM permissions. If the dry run fails, the action returns a 4xx error code.

Type: Boolean

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "arn": "string",
  "id": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The ARN of the feed.

Type: String

id

The ID of the feed.

Type: String

Pattern: [a-z0-9]{19}

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request could not be completed due to a conflict.

HTTP Status Code: 409

InternalServerErrorException

An internal server error occurred. This is a temporary condition and the request can be retried. If the problem persists, contact AWS Support.

HTTP Status Code: 500

ResourceNotFoundException

The resource specified in the action doesn't exist.

HTTP Status Code: 404

TooManyRequestException

The request was denied due to request throttling. Too many requests have been made within a given time period. Reduce the frequency of requests and use exponential backoff when retrying.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by the service. Check the error message for details about which parameter or field is invalid and correct the request before retrying.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ExportDictionaryEntries

Exports the entries from the specified dictionary.

Request Syntax

```
GET /v1/dictionary/id/entries/export HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

id

The ID of the dictionary whose entries you want to export.

Length Constraints: Minimum length of 1. Maximum length of 19.

Pattern: [a-zA-Z0-9]+

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "entries": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

entries

The dictionary entries payload.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 40960.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An internal server error occurred. This is a temporary condition and the request can be retried. If the problem persists, contact AWS Support.

HTTP Status Code: 500

ResourceNotFoundException

The resource specified in the action doesn't exist.

HTTP Status Code: 404

TooManyRequestException

The request was denied due to request throttling. Too many requests have been made within a given time period. Reduce the frequency of requests and use exponential backoff when retrying.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by the service. Check the error message for details about which parameter or field is invalid and correct the request before retrying.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetDictionary

Retrieves information about the specified dictionary.

Request Syntax

```
GET /v1/dictionary/id HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

id

The ID of the dictionary to retrieve.

Length Constraints: Minimum length of 1. Maximum length of 19.

Pattern: [a-zA-Z0-9]+

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200  
Content-type: application/json
```

```
{  
  "arn": "string",  
  "id": "string",  
  "language": "string",  
  "name": "string",  
  "references": [ "string " ],  
  "status": "string",  
  "tags": {  
    "string" : "string"  
  }  
}
```

```
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The ARN of the dictionary.

Type: String

id

The ID of the dictionary.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 19.

Pattern: [a-zA-Z0-9]+

language

The language of the dictionary.

Type: String

Valid Values: eng | fra | ita | deu | spa | por

name

The name of the dictionary.

Type: String

Pattern: [a-zA-Z0-9]([a-zA-Z0-9-]{0,126}[a-zA-Z0-9])?

references

A list of feed IDs that reference this dictionary.

Type: Array of strings

Pattern: [a-z0-9]{19}

status

The current status of the dictionary.

Type: String

Valid Values: CREATING | AVAILABLE | REFERENCED | DELETING | DELETED

tags

The tags associated with the dictionary.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An internal server error occurred. This is a temporary condition and the request can be retried. If the problem persists, contact AWS Support.

HTTP Status Code: 500

ResourceNotFoundException

The resource specified in the action doesn't exist.

HTTP Status Code: 404

TooManyRequestException

The request was denied due to request throttling. Too many requests have been made within a given time period. Reduce the frequency of requests and use exponential backoff when retrying.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by the service. Check the error message for details about which parameter or field is invalid and correct the request before retrying.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetFeed

Retrieves information about the specified feed.

Request Syntax

```
GET /v1/feed/id HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

id

The ID of the feed to query.

Pattern: [a-z0-9]{19}

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "arn": "string",
  "association": {
    "associatedResourceName": "string"
  },
  "dataEndpoints": [ "string" ],
  "id": "string",
  "name": "string",
  "outputs": [
    {
      "description": "string",
      "fromAssociation": boolean,
```

```
    "name": "string",
    "outputConfig": { ... },
    "status": "string"
  }
],
"status": "string",
"tags": {
  "string" : "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The ARN of the feed.

Type: String

association

Information about the resource that is associated with the feed. It's possible that there is no associated resource. This is not an error.

Type: [FeedAssociation](#) object

dataEndpoints

The dataEndpoints of the feed.

Type: Array of strings

id

The ID of the feed.

Type: String

Pattern: [a-z0-9]{19}

name

The name of the feed.

Type: String

Pattern: `[a-zA-Z0-9]([a-zA-Z0-9-]{0,126}[a-zA-Z0-9])?`

outputs

An array of the outputs in the feed.

Type: Array of [GetOutput](#) objects

status

The status of the feed.

Type: String

Valid Values: CREATING | AVAILABLE | ACTIVE | UPDATING | DELETING | DELETED
| ARCHIVED

tags

A list of the tags, if any, for the feed.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An internal server error occurred. This is a temporary condition and the request can be retried. If the problem persists, contact AWS Support.

HTTP Status Code: 500

ResourceNotFoundException

The resource specified in the action doesn't exist.

HTTP Status Code: 404

TooManyRequestsException

The request was denied due to request throttling. Too many requests have been made within a given time period. Reduce the frequency of requests and use exponential backoff when retrying.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListDictionaries

Lists the dictionaries in your account.

Request Syntax

```
GET /v1/dictionaries?maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of results to return per API request. Valid range: 1 to 100.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

The token that identifies the next batch of results to return.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "dictionaries": [
    {
      "arn": "string",
      "id": "string",
      "language": "string",
      "name": "string",
      "status": "string"
    }
  ],
}
```

```
"nextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

dictionaries

A list of DictionarySummary objects.

Type: Array of [DictionarySummary](#) objects

nextToken

The token to use to retrieve the next batch of results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An internal server error occurred. This is a temporary condition and the request can be retried. If the problem persists, contact AWS Support.

HTTP Status Code: 500

TooManyRequestException

The request was denied due to request throttling. Too many requests have been made within a given time period. Reduce the frequency of requests and use exponential backoff when retrying.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by the service. Check the error message for details about which parameter or field is invalid and correct the request before retrying.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListFeeds

Displays a list of feeds that belong to this AWS account.

Request Syntax

```
GET /v1/feeds?maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of results to return per API request.

For example, you submit a list request with MaxResults set at 5. Although 20 items match your request, the service returns no more than the first 5 items. (The service also returns a NextToken value that you can use to fetch the next batch of results.)

The service might return fewer results than the MaxResults value. If MaxResults is not included in the request, the service defaults to pagination with a maximum of 10 results per page.

Valid Range: Minimum value of 1. Maximum value of 1000.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

The token that identifies the batch of results that you want to see.

For example, you submit a ListFeeds request with MaxResults set at 5. The service returns the first batch of results (up to 5) and a NextToken value. To see the next batch of results, you can submit the ListFeeds request a second time and specify the NextToken value.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Content-type: application/json

```
{
  "feeds": [
    {
      "arn": "string",
      "association": {
        "associatedResourceName": "string"
      },
      "id": "string",
      "name": "string",
      "status": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

feeds

A list of FeedSummary objects.

Type: Array of [FeedSummary](#) objects

nextToken

The token that identifies the batch of results that you want to see. For example, you submit a list request with MaxResults set at 5. The service returns the first batch of results (up to 5) and a NextToken value. To see the next batch of results, you can submit the list request a second time and specify the NextToken value.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An internal server error occurred. This is a temporary condition and the request can be retried. If the problem persists, contact AWS Support.

HTTP Status Code: 500

ResourceNotFoundException

The resource specified in the action doesn't exist.

HTTP Status Code: 404

TooManyRequestException

The request was denied due to request throttling. Too many requests have been made within a given time period. Reduce the frequency of requests and use exponential backoff when retrying.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by the service. Check the error message for details about which parameter or field is invalid and correct the request before retrying.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

List all tags that are on an Elemental Inference resource in the current region.

Request Syntax

```
GET /v1/tags/resourceArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The ARN of the resource whose tags you want to query.

Pattern: `arn:aws[a-z\-*]:elemental-inference[a-z\-*]:[a-z0-9\-*]+:[0-9]{12}:(feed|dictionary)/[a-zA-Z0-9]{1,19}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "tags": {
    "string" : "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

tags

A list of the tags that belong to this resource.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An internal server error occurred. This is a temporary condition and the request can be retried. If the problem persists, contact AWS Support.

HTTP Status Code: 500

ResourceNotFoundException

The resource specified in the action doesn't exist.

HTTP Status Code: 404

TooManyRequestException

The request was denied due to request throttling. Too many requests have been made within a given time period. Reduce the frequency of requests and use exponential backoff when retrying.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by the service. Check the error message for details about which parameter or field is invalid and correct the request before retrying.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

TagResource

Associates the specified tags to the resource identified by the specified `resourceArn` in the current region. If existing tags on a resource are not specified in the request parameters, they are not changed. When a resource is deleted, the tags associated with that resource are also deleted.

Request Syntax

```
POST /v1/tags/resourceArn HTTP/1.1
Content-type: application/json
```

```
{
  "tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The ARN of the resource where you want to add tags.

Pattern: `arn:aws[a-z\-*]:elemental-inference[a-z\-*]:[a-z0-9\-*]+:[0-9]{12}:(feed|dictionary)/[a-zA-Z0-9]{1,19}`

Required: Yes

Request Body

The request accepts the following data in JSON format.

tags

A list of tags to add to the resource.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: Yes

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request could not be completed due to a conflict.

HTTP Status Code: 409

InternalServerErrorException

An internal server error occurred. This is a temporary condition and the request can be retried. If the problem persists, contact AWS Support.

HTTP Status Code: 500

ResourceNotFoundException

The resource specified in the action doesn't exist.

HTTP Status Code: 404

TooManyRequestException

The request was denied due to request throttling. Too many requests have been made within a given time period. Reduce the frequency of requests and use exponential backoff when retrying.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by the service. Check the error message for details about which parameter or field is invalid and correct the request before retrying.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

UntagResource

Deletes specified tags from the specified resource in the current region.

Request Syntax

```
DELETE /v1/tags/resourceArn?tagKeys=tagKeys HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The ARN of the resource where you want to delete one or more tags.

Pattern: `arn:aws[a-z\-*]:elemental-inference[a-z\-*]:[a-z0-9\-*]+:[0-9]{12}:(feed|dictionary)/[a-zA-Z0-9]{1,19}`

Required: Yes

tagKeys

The keys of the tags to delete.

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request could not be completed due to a conflict.

HTTP Status Code: 409

InternalServerErrorException

An internal server error occurred. This is a temporary condition and the request can be retried. If the problem persists, contact AWS Support.

HTTP Status Code: 500

ResourceNotFoundException

The resource specified in the action doesn't exist.

HTTP Status Code: 404

TooManyRequestException

The request was denied due to request throttling. Too many requests have been made within a given time period. Reduce the frequency of requests and use exponential backoff when retrying.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by the service. Check the error message for details about which parameter or field is invalid and correct the request before retrying.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

UpdateDictionary

Updates the specified dictionary.

Request Syntax

```
PATCH /v1/dictionary/id HTTP/1.1
Content-type: application/json
```

```
{
  "entries": "string",
  "language": "string",
  "name": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

id

The ID of the dictionary to update.

Length Constraints: Minimum length of 1. Maximum length of 19.

Pattern: [a-zA-Z0-9]+

Required: Yes

Request Body

The request accepts the following data in JSON format.

entries

New dictionary entries. If not specified, the entries are not changed.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 40960.

Required: No

language

A new language for the dictionary. If not specified, the language is not changed.

Type: String

Valid Values: eng | fra | ita | deu | spa | por

Required: No

name

A new name for the dictionary. If not specified, the name is not changed.

Type: String

Pattern: [a-zA-Z0-9]([a-zA-Z0-9-_{0,126}[a-zA-Z0-9])?

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "arn": "string",
  "id": "string",
  "language": "string",
  "name": "string",
  "references": [ "string" ],
  "status": "string",
  "tags": {
    "string" : "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The ARN of the dictionary.

Type: String

id

The ID of the dictionary.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 19.

Pattern: [a-zA-Z0-9]+

language

The updated or original language of the dictionary.

Type: String

Valid Values: eng | fra | ita | deu | spa | por

name

The updated or original name of the dictionary.

Type: String

Pattern: [a-zA-Z0-9]([a-zA-Z0-9-_]{0,126}[a-zA-Z0-9])?

references

A list of feed IDs that reference this dictionary.

Type: Array of strings

Pattern: [a-z0-9]{19}

status

The current status of the dictionary.

Type: String

Valid Values: CREATING | AVAILABLE | REFERENCED | DELETING | DELETED

tags

Any tags associated with the dictionary.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request could not be completed due to a conflict.

HTTP Status Code: 409

InternalServerErrorException

An internal server error occurred. This is a temporary condition and the request can be retried. If the problem persists, contact AWS Support.

HTTP Status Code: 500

ResourceNotFoundException

The resource specified in the action doesn't exist.

HTTP Status Code: 404

TooManyRequestException

The request was denied due to request throttling. Too many requests have been made within a given time period. Reduce the frequency of requests and use exponential backoff when retrying.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by the service. Check the error message for details about which parameter or field is invalid and correct the request before retrying.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

UpdateFeed

Updates the name and/or outputs in a feed.

UpdateFeed is a PUT operation, which means that the payload that you specify completely overwrites the existing payload.

This means that if you want to touch the array of outputs, you must pass in the full new list. So you must omit outputs you want to delete, and include outputs you want to add or modify.

If you want to patch the array of outputs to make selective additions, use AssociateFeed.

Request Syntax

```
PUT /v1/feed/id HTTP/1.1
Content-type: application/json

{
  "name": "string",
  "outputs": [
    {
      "description": "string",
      "fromAssociation": boolean,
      "name": "string",
      "outputConfig": { ... },
      "status": "string"
    }
  ]
}
```

URI Request Parameters

The request uses the following URI parameters.

id

The ID of the feed to update.

Pattern: `[a-z0-9]{19}`

Required: Yes

Request Body

The request accepts the following data in JSON format.

name

Required. You can specify the existing name (to leave it unchanged) or a new name.

Type: String

Pattern: `[a-zA-Z0-9]([a-zA-Z0-9-_{0,126}[a-zA-Z0-9])?`

Required: Yes

outputs

Required. You can specify the existing array of outputs (to leave outputs unchanged) or you can specify a new array.

Type: Array of [UpdateOutput](#) objects

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json
```

```
{
  "arn": "string",
  "association": {
    "associatedResourceName": "string"
  },
  "dataEndpoints": [ "string" ],
  "id": "string",
  "name": "string",
  "outputs": [
    {
      "description": "string",
      "fromAssociation": boolean,
      "name": "string",
      "outputConfig": { ... },
      "status": "string"
    }
  ]
}
```

```
    }  
  ],  
  "status": "string",  
  "tags": {  
    "string" : "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The ARN of the feed.

Type: String

association

Information about the resource that is associated with the feed, if any.

Type: [FeedAssociation](#) object

dataEndpoints

The data endpoints of the feed.

Type: Array of strings

id

The ID of the feed.

Type: String

Pattern: [a-z0-9]{19}

name

The updated or original name of the feed.

Type: String

Pattern: `[a-zA-Z0-9]([a-zA-Z0-9-_{0,126}[a-zA-Z0-9])?`

outputs

The array of outputs in the feed. You might have left this array unchanged, or you might have changed it.

Type: Array of [GetOutput](#) objects

status

The status of the feed.

Type: String

Valid Values: CREATING | AVAILABLE | ACTIVE | UPDATING | DELETING | DELETED
| ARCHIVED

tags

The tags associated with the feed.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request could not be completed due to a conflict.

HTTP Status Code: 409

InternalServerErrorException

An internal server error occurred. This is a temporary condition and the request can be retried. If the problem persists, contact AWS Support.

HTTP Status Code: 500

ResourceNotFoundException

The resource specified in the action doesn't exist.

HTTP Status Code: 404

ServiceQuotaExceededException

The request was rejected because it would exceed one or more service quotas for your account. Review your service quotas and either delete unused resources or request a quota increase.

HTTP Status Code: 402

TooManyRequestException

The request was denied due to request throttling. Too many requests have been made within a given time period. Reduce the frequency of requests and use exponential backoff when retrying.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the constraints specified by the service. Check the error message for details about which parameter or field is invalid and correct the request before retrying.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

Data Types

The AWS Elemental Inference API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AspectRatio](#)
- [ClippingConfig](#)
- [CreateOutput](#)
- [CroppingConfig](#)
- [DictionarySummary](#)
- [FeedAssociation](#)
- [FeedSummary](#)
- [GetOutput](#)
- [OutputConfig](#)
- [SubtitlingConfig](#)
- [UpdateOutput](#)

AspectRatio

The width and height of the output video. Used in SubtitlingConfig to determine subtitle layout.

Contents

height

The height component of the aspect ratio (for example, 9 in a 16:9 ratio).

Type: Integer

Required: Yes

width

The width component of the aspect ratio (for example, 16 in a 16:9 ratio).

Type: Integer

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ClippingConfig

A type of OutputConfig, used when the output in a feed is for the clip feature.

Contents

callbackMetadata

A string that you want Elemental Inference to always include in the event clipping metadata for this output. The string might identify the sports event in the source media, for example.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Pattern: `[\w \-\.\ ' ,@: ;]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CreateOutput

Contains configuration information about one output in a feed. It is used in the AssociateFeed and the CreateFeed actions.

Contents

name

A name for the output.

Type: String

Pattern: `[a-zA-Z0-9]([a-zA-Z0-9-]{0,126}[a-zA-Z0-9])?`

Required: Yes

outputConfig

A typed property for an output in a feed. It identifies the action for Elemental Inference to perform. It also provides a repository for the results of that action. For example, CroppingConfig output will contain the metadata for the crop feature.

Type: [OutputConfig](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

status

The status to assign to the output.

Type: String

Valid Values: ENABLED | DISABLED

Required: Yes

description

A description for the output.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Pattern: `[\w \-\.\',@:;]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CroppingConfig

A type of OutputConfig, used when the output in a feed is for the crop feature.

Contents

The members of this exception structure are context-dependent.

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DictionarySummary

Contains summary information about a dictionary. Used in the ListDictionaries response.

Contents

arn

The ARN of the dictionary.

Type: String

Required: Yes

id

The ID of the dictionary.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 19.

Pattern: [a-zA-Z0-9]+

Required: Yes

language

The language of the dictionary.

Type: String

Valid Values: eng | fra | ita | deu | spa | por

Required: Yes

name

The name of the dictionary.

Type: String

Pattern: [a-zA-Z0-9]([a-zA-Z0-9-_{0,126}[a-zA-Z0-9])?

Required: Yes

status

The status of the dictionary.

Type: String

Valid Values: CREATING | AVAILABLE | REFERENCED | DELETING | DELETED

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

FeedAssociation

Contains information about the resource that is associated with a feed. It is used in the FeedSummary that is used in the response of a ListFeeds action.

Contents

associatedResourceName

The name of the associated resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[\w \-\.\ ' ,@:;/]*`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

FeedSummary

Contains configuration information about a feed. It is used in the ListFeeds response.

Contents

arn

The ARN of the feed.

Type: String

Required: Yes

id

The ID of the feed.

Type: String

Pattern: `[a-z0-9]{19}`

Required: Yes

name

The name of the feed

Type: String

Pattern: `[a-zA-Z0-9]([a-zA-Z0-9-_]{0,126}[a-zA-Z0-9])?`

Required: Yes

status

The status of the feed.

Type: String

Valid Values: CREATING | AVAILABLE | ACTIVE | UPDATING | DELETING | DELETED
| ARCHIVED

Required: Yes

association

The resource, if any, associated with the feed.

Type: [FeedAssociation](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

GetOutput

Contains configuration information about one output in a feed. It is used in the GetFeed response.

Contents

name

The name of the output.

Type: String

Pattern: `[a-zA-Z0-9]([a-zA-Z0-9-_{0,126}[a-zA-Z0-9])?`

Required: Yes

outputConfig

A typed property for an output in a feed. It identifies the action for Elemental Inference to perform. It also provides a repository for the results of that action. For example, CroppingConfig output will contain the metadata for the crop feature.

Type: [OutputConfig](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

status

The status of the output.

Type: String

Valid Values: ENABLED | DISABLED

Required: Yes

description

The description of the output.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Pattern: `[\w \-\.\',@:;]*`

Required: No

fromAssociation

True means that the output was originally created in the feed using AssociateFeed. False means it was created using CreateFeed or UpdateFeed.

You will need this value if you use UpdateFeed to modify the list of outputs in the feed.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OutputConfig

Contains one typed output. It is used in the CreateOutput, GetOutput, and Update Output structures.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

clipping

The output config type that applies to the clipping feature.

Type: [ClippingConfig](#) object

Required: No

cropping

The output config type that applies to the cropping feature.

Type: [CroppingConfig](#) object

Required: No

subtitling

The output config type that applies to the smart subtitling feature.

Type: [SubtitlingConfig](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SubtitlingConfig

A type of OutputConfig, used when the output in a feed is for the smart subtitling feature. smart subtitling uses automatic speech recognition (ASR) to generate live TTML subtitles from the audio in your source media.

Contents

language

The language of the audio in the source media. Elemental Inference uses this setting to optimize transcription accuracy. Specify the language using an ISO 639-2/T three-letter code, optionally with a region subtag. Supported values: eng, eng-au, eng-gb, eng-us, fra, ita, deu, spa, por.

Type: String

Valid Values: eng | eng-au | eng-gb | eng-us | fra | ita | deu | spa | por

Required: Yes

aspectRatio

The aspect ratio of the output video, specified as width and height integer values. Elemental Inference uses the aspect ratio to determine subtitle layout and line lengths.

Type: [AspectRatio](#) object

Required: No

dictionary

The ID of a custom dictionary to improve transcription accuracy for domain-specific terminology. Use the CreateDictionary operation to create a dictionary.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 19.

Pattern: [a-zA-Z0-9]+

Required: No

profanityFilter

Controls how profanity is handled in the generated subtitles. Valid values: DISABLED (no filtering, default), CENSOR (replace profanity with asterisks), DROP (remove profanity from the transcript).

Type: String

Valid Values: DISABLED | CENSOR | DROP

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UpdateOutput

Contains configuration information about one output in a feed. It is used in the UpdateFeed action.

Contents

name

The name of the output.

Type: String

Pattern: `[a-zA-Z0-9]([a-zA-Z0-9-_{0,126}[a-zA-Z0-9])?`

Required: Yes

outputConfig

A typed property for an output in a feed. It identifies the action for Elemental Inference to perform. It also provides a repository for the results of that action. For example, CroppingConfig output will contain the metadata for the crop feature.

Type: [OutputConfig](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

status

The status of the output.

Type: String

Valid Values: ENABLED | DISABLED

Required: Yes

description

A description of the output.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Pattern: `[\w \-\.\',@:;]*`

Required: No

fromAssociation

Elemental Inference originally sets this parameter to True if this output was created by AssociateFeed or to False if this output was created by CreateFeed or UpdateFeed.

You must not change this value. Therefore, use GetFeed to determine the current value. Then in the UpdateFeed request, if the current value is True, include this parameter with a value of True. If it's False, omit the parameter.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Error Types

This section lists common error types that this AWS service may return. Not all services return all error types listed here. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You don't have permission to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 403

ExpiredTokenException

The security token included in the request has expired. Request a new security token and try again.

HTTP Status Code: 403

IncompleteSignature

The request signature doesn't conform to AWS standards. Verify that you're using valid AWS credentials and that your request is properly formatted. If you're using an SDK, ensure it's up to date.

HTTP Status Code: 403

InternalFailure

The request can't be processed right now because of an internal server issue. Try again later. If the problem persists, contact AWS Support.

HTTP Status Code: 500

MalformedHttpRequestException

The request body can't be processed. This typically happens when the request body can't be decompressed using the specified content encoding algorithm. Verify that the content encoding header matches the compression format used.

HTTP Status Code: 400

NotAuthorized

You don't have permissions to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 401

OptInRequired

Your AWS account needs a subscription for this service. Verify that you've enabled the service in your account.

HTTP Status Code: 403

RequestAbortedException

The request was aborted before a response could be returned. This typically happens when the client closes the connection.

HTTP Status Code: 400

RequestEntityTooLargeException

The request entity is too large. Reduce the size of the request body and try again.

HTTP Status Code: 413

RequestTimeoutException

The request timed out. The server didn't receive the complete request within the expected time frame. Try again.

HTTP Status Code: 408

ServiceUnavailable

The service is temporarily unavailable. Try again later.

HTTP Status Code: 503

ThrottlingException

Your request rate is too high. The AWS SDKs automatically retry requests that receive this exception. Reduce the frequency of requests.

HTTP Status Code: 400

UnknownOperationException

The action or operation isn't recognized. Verify that the action name is spelled correctly and that it's supported by the API version you're using.

HTTP Status Code: 404

UnrecognizedClientException

The X.509 certificate or AWS access key ID you provided doesn't exist in our records. Verify that you're using valid credentials and that they haven't expired.

HTTP Status Code: 403

ValidationError

The input doesn't meet the required format or constraints. Check that all required parameters are included and that values are valid.

HTTP Status Code: 400