



API Reference

EC2 Image Builder



API Version 2019-12-02

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

EC2 Image Builder: API Reference

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
CancelImageCreation	5
Request Syntax	5
URI Request Parameters	5
Request Body	5
Response Syntax	6
Response Elements	6
Errors	7
See Also	8
CancelLifecycleExecution	9
Request Syntax	9
URI Request Parameters	9
Request Body	9
Response Syntax	10
Response Elements	10
Errors	10
See Also	11
CreateComponent	13
Request Syntax	13
URI Request Parameters	13
Request Body	13
Response Syntax	17
Response Elements	17
Errors	18
See Also	20
CreateContainerRecipe	21
Request Syntax	21
URI Request Parameters	22
Request Body	22
Response Syntax	26
Response Elements	27
Errors	28
See Also	29

CreateDistributionConfiguration	31
Request Syntax	31
URI Request Parameters	33
Request Body	33
Response Syntax	34
Response Elements	34
Errors	35
See Also	37
CreateImage	38
Request Syntax	38
URI Request Parameters	39
Request Body	39
Response Syntax	42
Response Elements	42
Errors	43
See Also	44
CreateImagePipeline	46
Request Syntax	46
URI Request Parameters	47
Request Body	47
Response Syntax	52
Response Elements	52
Errors	53
See Also	54
CreateImageRecipe	56
Request Syntax	56
URI Request Parameters	57
Request Body	57
Response Syntax	61
Response Elements	62
Errors	62
See Also	64
CreateInfrastructureConfiguration	66
Request Syntax	66
URI Request Parameters	67
Request Body	67

Response Syntax	71
Response Elements	71
Errors	72
See Also	73
CreateLifecyclePolicy	75
Request Syntax	75
URI Request Parameters	76
Request Body	76
Response Syntax	79
Response Elements	79
Errors	80
See Also	81
CreateWorkflow	83
Request Syntax	83
URI Request Parameters	83
Request Body	83
Response Syntax	86
Response Elements	87
Errors	88
See Also	89
DeleteComponent	91
Request Syntax	91
URI Request Parameters	91
Request Body	91
Response Syntax	91
Response Elements	91
Errors	92
See Also	93
DeleteContainerRecipe	94
Request Syntax	94
URI Request Parameters	94
Request Body	94
Response Syntax	94
Response Elements	94
Errors	95
See Also	96

DeleteDistributionConfiguration	97
Request Syntax	97
URI Request Parameters	97
Request Body	97
Response Syntax	97
Response Elements	97
Errors	98
See Also	99
DeletelImage	100
Request Syntax	100
URI Request Parameters	100
Request Body	100
Response Syntax	100
Response Elements	101
Errors	101
See Also	102
DeletelImagePipeline	104
Request Syntax	104
URI Request Parameters	104
Request Body	104
Response Syntax	104
Response Elements	104
Errors	105
See Also	106
DeletelImageRecipe	107
Request Syntax	107
URI Request Parameters	107
Request Body	107
Response Syntax	107
Response Elements	107
Errors	108
See Also	109
DeletelInfrastructureConfiguration	110
Request Syntax	110
URI Request Parameters	110
Request Body	110

Response Syntax	110
Response Elements	110
Errors	111
See Also	112
DeleteLifecyclePolicy	113
Request Syntax	113
URI Request Parameters	113
Request Body	113
Response Syntax	113
Response Elements	113
Errors	114
See Also	115
DeleteWorkflow	116
Request Syntax	116
URI Request Parameters	116
Request Body	116
Response Syntax	116
Response Elements	116
Errors	117
See Also	118
DistributeImage	119
Request Syntax	119
URI Request Parameters	119
Request Body	119
Response Syntax	121
Response Elements	121
Errors	122
See Also	124
GetComponent	125
Request Syntax	125
URI Request Parameters	125
Request Body	125
Response Syntax	125
Response Elements	126
Errors	127
See Also	128

GetComponentPolicy	129
Request Syntax	129
URI Request Parameters	129
Request Body	129
Response Syntax	129
Response Elements	129
Errors	130
See Also	131
GetContainerRecipe	132
Request Syntax	132
URI Request Parameters	132
Request Body	132
Response Syntax	132
Response Elements	134
Errors	134
See Also	135
GetContainerRecipePolicy	137
Request Syntax	137
URI Request Parameters	137
Request Body	137
Response Syntax	137
Response Elements	137
Errors	138
See Also	139
GetDistributionConfiguration	140
Request Syntax	140
URI Request Parameters	140
Request Body	140
Response Syntax	140
Response Elements	142
Errors	143
See Also	143
GetImage	145
Request Syntax	145
URI Request Parameters	145
Request Body	145

Response Syntax	145
Response Elements	153
Errors	154
See Also	155
GetImagePipeline	156
Request Syntax	156
URI Request Parameters	156
Request Body	156
Response Syntax	156
Response Elements	158
Errors	158
See Also	159
GetImagePolicy	161
Request Syntax	161
URI Request Parameters	161
Request Body	161
Response Syntax	161
Response Elements	161
Errors	162
See Also	163
GetImageRecipe	164
Request Syntax	164
URI Request Parameters	164
Request Body	164
Response Syntax	164
Response Elements	166
Errors	166
See Also	167
GetImageRecipePolicy	169
Request Syntax	169
URI Request Parameters	169
Request Body	169
Response Syntax	169
Response Elements	169
Errors	170
See Also	171

GetInfrastructureConfiguration	172
Request Syntax	172
URI Request Parameters	172
Request Body	172
Response Syntax	172
Response Elements	173
Errors	174
See Also	175
GetLifecycleExecution	176
Request Syntax	176
URI Request Parameters	176
Request Body	176
Response Syntax	176
Response Elements	177
Errors	177
See Also	178
GetLifecyclePolicy	179
Request Syntax	179
URI Request Parameters	179
Request Body	179
Response Syntax	179
Response Elements	181
Errors	181
See Also	182
GetMarketplaceResource	183
Request Syntax	183
URI Request Parameters	183
Request Body	183
Response Syntax	184
Response Elements	184
Errors	185
See Also	186
GetWorkflow	187
Request Syntax	187
URI Request Parameters	187
Request Body	187

Response Syntax	187
Response Elements	188
Errors	189
See Also	190
GetWorkflowExecution	191
Request Syntax	191
URI Request Parameters	191
Request Body	191
Response Syntax	191
Response Elements	192
Errors	194
See Also	195
GetWorkflowStepExecution	197
Request Syntax	197
URI Request Parameters	197
Request Body	197
Response Syntax	197
Response Elements	198
Errors	201
See Also	202
ImportComponent	204
Request Syntax	204
URI Request Parameters	204
Request Body	204
Response Syntax	207
Response Elements	208
Errors	208
See Also	210
ImportDiskImage	211
Request Syntax	211
URI Request Parameters	211
Request Body	212
Response Syntax	215
Response Elements	215
Errors	215
See Also	216

ImportVmlImage	218
Request Syntax	218
URI Request Parameters	218
Request Body	218
Response Syntax	221
Response Elements	221
Errors	222
See Also	222
ListComponentBuildVersions	224
Request Syntax	224
URI Request Parameters	224
Request Body	224
Response Syntax	225
Response Elements	226
Errors	226
See Also	227
ListComponents	229
Request Syntax	229
URI Request Parameters	229
Request Body	229
Response Syntax	231
Response Elements	232
Errors	232
See Also	233
ListContainerRecipes	235
Request Syntax	235
URI Request Parameters	235
Request Body	235
Response Syntax	236
Response Elements	237
Errors	238
See Also	239
ListDistributionConfigurations	240
Request Syntax	240
URI Request Parameters	240
Request Body	240

Response Syntax	241
Response Elements	241
Errors	242
See Also	243
ListImageBuildVersions	245
Request Syntax	245
URI Request Parameters	245
Request Body	245
Response Syntax	246
Response Elements	249
Errors	249
See Also	250
ListImagePackages	252
Request Syntax	252
URI Request Parameters	252
Request Body	252
Response Syntax	253
Response Elements	253
Errors	254
See Also	255
ListImagePipelineImages	257
Request Syntax	257
URI Request Parameters	257
Request Body	257
Response Syntax	258
Response Elements	261
Errors	261
See Also	263
ListImagePipelines	264
Request Syntax	264
URI Request Parameters	264
Request Body	264
Response Syntax	265
Response Elements	267
Errors	267
See Also	268

ListImageRecipes	270
Request Syntax	270
URI Request Parameters	270
Request Body	270
Response Syntax	271
Response Elements	272
Errors	273
See Also	274
ListImages	275
Request Syntax	275
URI Request Parameters	275
Request Body	275
Response Syntax	277
Response Elements	277
Errors	278
See Also	279
ListImageScanFindingAggregations	281
Request Syntax	281
URI Request Parameters	281
Request Body	281
Response Syntax	282
Response Elements	283
Errors	284
See Also	285
ListImageScanFindings	287
Request Syntax	287
URI Request Parameters	287
Request Body	287
Response Syntax	288
Response Elements	290
Errors	291
See Also	292
ListInfrastructureConfigurations	293
Request Syntax	293
URI Request Parameters	293
Request Body	293

Response Syntax	294
Response Elements	295
Errors	295
See Also	296
ListLifecycleExecutionResources	298
Request Syntax	298
URI Request Parameters	298
Request Body	298
Response Syntax	299
Response Elements	300
Errors	301
See Also	302
ListLifecycleExecutions	303
Request Syntax	303
URI Request Parameters	303
Request Body	303
Response Syntax	304
Response Elements	305
Errors	305
See Also	306
ListLifecyclePolicies	308
Request Syntax	308
URI Request Parameters	308
Request Body	308
Response Syntax	309
Response Elements	309
Errors	310
See Also	311
ListTagsForResource	312
Request Syntax	312
URI Request Parameters	312
Request Body	312
Response Syntax	312
Response Elements	313
Errors	313
See Also	314

ListWaitingWorkflowSteps	315
Request Syntax	315
URI Request Parameters	315
Request Body	315
Response Syntax	316
Response Elements	316
Errors	317
See Also	318
ListWorkflowBuildVersions	319
Request Syntax	319
URI Request Parameters	319
Request Body	319
Response Syntax	320
Response Elements	321
Errors	321
See Also	322
ListWorkflowExecutions	324
Request Syntax	324
URI Request Parameters	324
Request Body	324
Response Syntax	325
Response Elements	326
Errors	327
See Also	328
ListWorkflows	329
Request Syntax	329
URI Request Parameters	329
Request Body	329
Response Syntax	330
Response Elements	331
Errors	331
See Also	332
ListWorkflowStepExecutions	334
Request Syntax	334
URI Request Parameters	334
Request Body	334

Response Syntax	335
Response Elements	336
Errors	337
See Also	338
PutComponentPolicy	340
Request Syntax	340
URI Request Parameters	340
Request Body	340
Response Syntax	341
Response Elements	341
Errors	341
See Also	343
PutContainerRecipePolicy	344
Request Syntax	344
URI Request Parameters	344
Request Body	344
Response Syntax	345
Response Elements	345
Errors	345
See Also	347
PutImagePolicy	348
Request Syntax	348
URI Request Parameters	348
Request Body	348
Response Syntax	349
Response Elements	349
Errors	349
See Also	351
PutImageRecipePolicy	352
Request Syntax	352
URI Request Parameters	352
Request Body	352
Response Syntax	353
Response Elements	353
Errors	353
See Also	355

RetryImage	356
Request Syntax	356
URI Request Parameters	356
Request Body	356
Response Syntax	357
Response Elements	357
Errors	357
See Also	359
SendWorkflowStepAction	360
Request Syntax	360
URI Request Parameters	360
Request Body	360
Response Syntax	361
Response Elements	362
Errors	362
See Also	364
StartImagePipelineExecution	365
Request Syntax	365
URI Request Parameters	365
Request Body	365
Response Syntax	366
Response Elements	366
Errors	367
See Also	368
StartResourceStateUpdate	370
Request Syntax	370
URI Request Parameters	370
Request Body	371
Response Syntax	372
Response Elements	373
Errors	373
See Also	375
TagResource	376
Request Syntax	376
URI Request Parameters	376
Request Body	376

Response Syntax	377
Response Elements	377
Errors	377
See Also	378
UntagResource	379
Request Syntax	379
URI Request Parameters	379
Request Body	379
Response Syntax	380
Response Elements	380
Errors	380
See Also	380
UpdateDistributionConfiguration	382
Request Syntax	382
URI Request Parameters	383
Request Body	384
Response Syntax	385
Response Elements	385
Errors	386
See Also	387
UpdateImagePipeline	388
Request Syntax	388
URI Request Parameters	389
Request Body	389
Response Syntax	393
Response Elements	393
Errors	394
See Also	395
UpdateInfrastructureConfiguration	397
Request Syntax	397
URI Request Parameters	398
Request Body	398
Response Syntax	401
Response Elements	402
Errors	402
See Also	404

UpdateLifecyclePolicy	405
Request Syntax	405
URI Request Parameters	406
Request Body	406
Response Syntax	408
Response Elements	408
Errors	409
See Also	410
Data Types	412
AccountAggregation	416
Contents	416
See Also	416
AdditionalInstanceConfiguration	417
Contents	417
See Also	418
Ami	419
Contents	419
See Also	420
AmiDistributionConfiguration	421
Contents	421
See Also	422
AutoDisablePolicy	423
Contents	423
See Also	423
Component	424
Contents	424
See Also	428
ComponentConfiguration	429
Contents	429
See Also	429
ComponentFailureContext	430
Contents	430
See Also	431
ComponentParameter	432
Contents	432
See Also	432

ComponentParameterDetail	433
Contents	433
See Also	434
ComponentState	435
Contents	435
See Also	435
ComponentSummary	436
Contents	436
See Also	439
ComponentVersion	440
Contents	440
See Also	443
Container	444
Contents	444
See Also	444
ContainerDistributionConfiguration	445
Contents	445
See Also	445
ContainerRecipe	447
Contents	447
See Also	451
ContainerRecipeSummary	453
Contents	453
See Also	455
CvssScore	456
Contents	456
See Also	457
CvssScoreAdjustment	458
Contents	458
See Also	458
CvssScoreDetails	459
Contents	459
See Also	460
Distribution	461
Contents	461
See Also	462

DistributionConfiguration	464
Contents	464
See Also	466
DistributionConfigurationSummary	467
Contents	467
See Also	468
DistributionFailureContext	470
Contents	470
See Also	470
EbsInstanceBlockDeviceSpecification	471
Contents	471
See Also	472
EcrConfiguration	474
Contents	474
See Also	474
FastLaunchConfiguration	475
Contents	475
See Also	476
FastLaunchLaunchTemplateSpecification	477
Contents	477
See Also	478
FastLaunchSnapshotConfiguration	479
Contents	479
See Also	479
Filter	480
Contents	480
See Also	480
Image	481
Contents	481
See Also	487
ImageAggregation	488
Contents	488
See Also	488
ImageFailureContext	489
Contents	489
See Also	490

ImageLoggingConfiguration	492
Contents	492
See Also	492
ImagePackage	493
Contents	493
See Also	493
ImagePipeline	494
Contents	494
See Also	499
ImagePipelineAggregation	500
Contents	500
See Also	500
ImageRecipe	501
Contents	501
See Also	505
ImageRecipeSummary	506
Contents	506
See Also	507
ImageScanFinding	509
Contents	509
See Also	512
ImageScanFindingAggregation	513
Contents	513
See Also	513
ImageScanFindingsFilter	515
Contents	515
See Also	515
ImageScanningConfiguration	516
Contents	516
See Also	516
ImageScanState	517
Contents	517
See Also	517
ImageState	518
Contents	518
See Also	518

ImageSummary	520
Contents	520
See Also	523
ImageTestsConfiguration	525
Contents	525
See Also	525
ImageVersion	526
Contents	526
See Also	529
InfrastructureConfiguration	530
Contents	530
See Also	534
InfrastructureConfigurationSummary	535
Contents	535
See Also	537
InspectorScoreDetails	538
Contents	538
See Also	538
InstanceBlockDeviceMapping	539
Contents	539
See Also	540
InstanceConfiguration	541
Contents	541
See Also	541
InstanceMetadataOptions	542
Contents	542
See Also	543
LatestVersionReferences	544
Contents	544
See Also	545
LaunchPermissionConfiguration	546
Contents	546
See Also	547
LaunchTemplateConfiguration	548
Contents	548
See Also	548

LifecycleExecution	550
Contents	550
See Also	551
LifecycleExecutionResource	552
Contents	552
See Also	554
LifecycleExecutionResourceAction	555
Contents	555
See Also	555
LifecycleExecutionResourcesImpactedSummary	556
Contents	556
See Also	556
LifecycleExecutionResourceState	557
Contents	557
See Also	557
LifecycleExecutionSnapshotResource	558
Contents	558
See Also	558
LifecycleExecutionState	559
Contents	559
See Also	559
LifecyclePolicy	560
Contents	560
See Also	562
LifecyclePolicyDetail	564
Contents	564
See Also	564
LifecyclePolicyDetailAction	565
Contents	565
See Also	565
LifecyclePolicyDetailActionIncludeResources	566
Contents	566
See Also	566
LifecyclePolicyDetailExclusionRules	567
Contents	567
See Also	567

LifecyclePolicyDetailExclusionRulesAmis	568
Contents	568
See Also	569
LifecyclePolicyDetailExclusionRulesAmisLastLaunched	570
Contents	570
See Also	570
LifecyclePolicyDetailFilter	571
Contents	571
See Also	572
LifecyclePolicyResourceSelection	573
Contents	573
See Also	573
LifecyclePolicyResourceSelectionRecipe	575
Contents	575
See Also	575
LifecyclePolicySummary	576
Contents	576
See Also	578
Logging	579
Contents	579
See Also	579
OutputResources	580
Contents	580
See Also	580
PackageVulnerabilityDetails	581
Contents	581
See Also	583
PipelineLoggingConfiguration	584
Contents	584
See Also	584
Placement	586
Contents	586
See Also	587
ProductCodeListItem	588
Contents	588
See Also	588

RegionFailure	589
Contents	589
See Also	590
RegisterImageOptions	591
Contents	591
See Also	591
Remediation	592
Contents	592
See Also	592
RemediationRecommendation	593
Contents	593
See Also	593
ResourceState	594
Contents	594
See Also	594
ResourceStateUpdateExclusionRules	595
Contents	595
See Also	595
ResourceStateUpdateIncludeResources	596
Contents	596
See Also	596
S3ExportConfiguration	597
Contents	597
See Also	598
S3Logs	599
Contents	599
See Also	599
Schedule	600
Contents	600
See Also	601
SeverityCounts	602
Contents	602
See Also	602
SsmParameterConfiguration	604
Contents	604
See Also	605

SystemsManagerAgent	606
Contents	606
See Also	606
TargetContainerRepository	607
Contents	607
See Also	607
VulnerabilityIdAggregation	608
Contents	608
See Also	608
VulnerablePackage	609
Contents	609
See Also	611
WindowsConfiguration	612
Contents	612
See Also	612
Workflow	613
Contents	613
See Also	616
WorkflowConfiguration	617
Contents	617
See Also	618
WorkflowExecutionMetadata	619
Contents	619
See Also	621
WorkflowParameter	623
Contents	623
See Also	623
WorkflowParameterDetail	624
Contents	624
See Also	625
WorkflowState	626
Contents	626
See Also	626
WorkflowStepExecution	627
Contents	627
See Also	628

WorkflowStepMetadata	630
Contents	630
See Also	632
WorkflowSummary	634
Contents	634
See Also	636
WorkflowVersion	637
Contents	637
See Also	638
Common Parameters	639
Common Error Types	642

Welcome

EC2 Image Builder automates the creation, management, and deployment of customized, secure, and up-to-date "golden" server images that are pre-installed and pre-configured with software and settings to meet specific IT standards.

This document was last published on September 21, 2026.

Actions

The following actions are supported:

- [CancelImageCreation](#)
- [CancelLifecycleExecution](#)
- [CreateComponent](#)
- [CreateContainerRecipe](#)
- [CreateDistributionConfiguration](#)
- [CreateImage](#)
- [CreateImagePipeline](#)
- [CreateImageRecipe](#)
- [CreateInfrastructureConfiguration](#)
- [CreateLifecyclePolicy](#)
- [CreateWorkflow](#)
- [DeleteComponent](#)
- [DeleteContainerRecipe](#)
- [DeleteDistributionConfiguration](#)
- [DeleteImage](#)
- [DeleteImagePipeline](#)
- [DeleteImageRecipe](#)
- [DeleteInfrastructureConfiguration](#)
- [DeleteLifecyclePolicy](#)
- [DeleteWorkflow](#)
- [DistributeImage](#)
- [GetComponent](#)
- [GetComponentPolicy](#)
- [GetContainerRecipe](#)
- [GetContainerRecipePolicy](#)
- [GetDistributionConfiguration](#)
- [GetImage](#)

- [GetImagePipeline](#)
- [GetImagePolicy](#)
- [GetImageRecipe](#)
- [GetImageRecipePolicy](#)
- [GetInfrastructureConfiguration](#)
- [GetLifecycleExecution](#)
- [GetLifecyclePolicy](#)
- [GetMarketplaceResource](#)
- [GetWorkflow](#)
- [GetWorkflowExecution](#)
- [GetWorkflowStepExecution](#)
- [ImportComponent](#)
- [ImportDiskImage](#)
- [ImportVmImage](#)
- [ListComponentBuildVersions](#)
- [ListComponents](#)
- [ListContainerRecipes](#)
- [ListDistributionConfigurations](#)
- [ListImageBuildVersions](#)
- [ListImagePackages](#)
- [ListImagePipelineImages](#)
- [ListImagePipelines](#)
- [ListImageRecipes](#)
- [ListImages](#)
- [ListImageScanFindingAggregations](#)
- [ListImageScanFindings](#)
- [ListInfrastructureConfigurations](#)
- [ListLifecycleExecutionResources](#)
- [ListLifecycleExecutions](#)
- [ListLifecyclePolicies](#)

- [ListTagsForResource](#)
- [ListWaitingWorkflowSteps](#)
- [ListWorkflowBuildVersions](#)
- [ListWorkflowExecutions](#)
- [ListWorkflows](#)
- [ListWorkflowStepExecutions](#)
- [PutComponentPolicy](#)
- [PutContainerRecipePolicy](#)
- [PutImagePolicy](#)
- [PutImageRecipePolicy](#)
- [RetryImage](#)
- [SendWorkflowStepAction](#)
- [StartImagePipelineExecution](#)
- [StartResourceStateUpdate](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdateDistributionConfiguration](#)
- [UpdateImagePipeline](#)
- [UpdateInfrastructureConfiguration](#)
- [UpdateLifecyclePolicy](#)

CancelImageCreation

Cancels the creation of an image. This operation can only be used on images in a non-terminal state.

Request Syntax

```
PUT /CancelImageCreation HTTP/1.1
Content-type: application/json

{
  "clientToken": "string",
  "imageBuildVersionArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

clientToken

A unique, case-sensitive identifier you provide to ensure that the operation completes no more than one time. If this token matches a previous request, the service ignores the request, but does not return an error. For more information, see [Ensuring idempotency](#) in the *Amazon EC2 API Reference*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

imageBuildVersionArn

The Amazon Resource Name (ARN) of the image that you want to cancel creation for.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):image/[a-z0-9-_]+/[0-9]+\.[0-9]+\.[0-9]+/[0-9]+$`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "clientToken": "string",
  "imageBuildVersionArn": "string",
  "requestId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[clientToken](#)

The client token that uniquely identifies the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

[imageBuildVersionArn](#)

The Amazon Resource Name (ARN) of the image whose creation this request canceled.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):image/[a-z0-9-_]+/[0-9]+\.[0-9]+\.[0-9]+/[0-9]+$`

[requestId](#)

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

IdempotentParameterMismatchException

You have specified a client token for an operation using parameter values that differ from a previous request that used the same client token.

HTTP Status Code: 400

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ResourceInUseException

The resource that you are trying to operate on is currently in use. Review the message details and retry later.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

CancelLifecycleExecution

Cancels a specific image lifecycle policy runtime instance.

Request Syntax

```
PUT /CancelLifecycleExecution HTTP/1.1
Content-type: application/json

{
  "clientToken": "string",
  "lifecycleExecutionId": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

clientToken

A unique, case-sensitive identifier you provide to ensure that the operation completes no more than one time. If this token matches a previous request, the service ignores the request, but does not return an error. For more information, see [Ensuring idempotency](#) in the *Amazon EC2 API Reference*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

lifecycleExecutionId

Identifies the specific runtime instance of the image lifecycle to cancel.

Type: String

Pattern: `^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}$`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "lifecycleExecutionId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

lifecycleExecutionId

The unique identifier for the image lifecycle runtime instance that was canceled.

Type: String

Pattern: `^lce-[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}$`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

IdempotentParameterMismatchException

You have specified a client token for an operation using parameter values that differ from a previous request that used the same client token.

HTTP Status Code: 400

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ResourceInUseException

The resource that you are trying to operate on is currently in use. Review the message details and retry later.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

CreateComponent

Creates a new component that can be used to build, validate, test, and assess your image. The component is based on a YAML document that you specify using exactly one of the following methods:

- Inline, using the `data` property in the request body.
- A URL that points to a YAML document file stored in Amazon S3, using the `uri` property in the request body.

Request Syntax

```
PUT /CreateComponent HTTP/1.1
Content-type: application/json

{
  "changeDescription": "string",
  "clientToken": "string",
  "data": "string",
  "description": "string",
  "dryRun": boolean,
  "kmsKeyId": "string",
  "name": "string",
  "platform": "string",
  "semanticVersion": "string",
  "supportedOsVersions": [ "string" ],
  "tags": {
    "string" : "string"
  },
  "uri": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

changeDescription

The change description of the component. Describes what change has been made in this version, or what makes this version different from other versions of the component.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

clientToken

A unique, case-sensitive identifier you provide to ensure that the operation completes no more than one time. If this token matches a previous request, the service ignores the request, but does not return an error. For more information, see [Ensuring idempotency](#) in the *Amazon EC2 API Reference*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

data

Component data contains inline YAML document content for the component. Alternatively, you can specify the `uri` of a YAML document file stored in Amazon S3. However, you cannot specify both properties.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 16000.

Pattern: `[^\x00]+`

Required: No

description

Describes the contents of the component.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

dryRun

Validates the required permissions and request parameters without making the request. If validation succeeds, the operation returns a `DryRunOperationException` error response.

Type: Boolean

Required: No

kmsKeyId

The Amazon Resource Name (ARN) that uniquely identifies the KMS key used to encrypt this component. This can be either the Key ARN or the Alias ARN. For more information, see [Key identifiers \(KeyId\)](#) in the *AWS Key Management Service Developer Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

name

The name of the component.

Type: String

Pattern: `^[-_A-Za-z-0-9][-_A-Za-z0-9 ]{1,126}[-_A-Za-z-0-9]$`

Required: Yes

platform

The operating system platform of the component.

Type: String

Valid Values: Windows | Linux | macOS

Required: Yes

semanticVersion

The semantic version of the component. This version follows the semantic version syntax.

Note

The semantic version has four nodes: <major>.<minor>.<patch>/<build>. You can assign values for the first three, and can filter on all of them.

Assignment: For the first three nodes, you can assign any positive integer value, including zero. The upper limit is $2^{30}-1$, or 1073741823, for each node. Image Builder automatically assigns the build number to the fourth node.

Patterns: You can use any numeric pattern that adheres to the assignment requirements for the nodes that you can assign. For example, you might choose a software version pattern, such as 1.0.0, or a date, such as 2021.01.01.

Type: String

Pattern: `^[0-9]+\.[0-9]+\.[0-9]+$`

Required: Yes

supportedOsVersions

The operating system (OS) version supported by the component. If the OS information is available, a prefix match is performed against the base image OS version during image recipe creation.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 25 items.

Length Constraints: Minimum length of 1.

Required: No

tags

The tags that apply to the component.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z0-9\s_.:/=+\-@]*$`

Value Length Constraints: Maximum length of 256.

Required: No

uri

The `uri` of a YAML component document file. This must be an S3 URL (`s3://bucket/key`), and you must have permission to access the S3 bucket it points to. If you use Amazon S3, you can specify component content up to your service quota.

Alternatively, you can specify the YAML document inline, using the `component data` property. You cannot specify both properties.

Type: String

Required: No

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json
```

```
{
  "clientToken": "string",
  "componentBuildVersionArn": "string",
  "latestVersionReferences": {
    "latestMajorVersionArn": "string",
    "latestMinorVersionArn": "string",
    "latestPatchVersionArn": "string",
    "latestVersionArn": "string"
  },
  "requestId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

clientToken

The client token that uniquely identifies the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

componentBuildVersionArn

The Amazon Resource Name (ARN) of the component that the request created.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):component/[a-z0-9-_/][0-9]+\.[0-9]+\.[0-9]+/[0-9]+$`

latestVersionReferences

The resource ARNs with different wildcard variations of semantic versioning.

Type: [LatestVersionReferences](#) object

requestId

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

DryRunOperationException

The dry run operation of the resource was successful, and no resources or mutations were actually performed due to the dry run flag in the request.

HTTP Status Code: 412

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

IdempotentParameterMismatchException

You have specified a client token for an operation using parameter values that differ from a previous request that used the same client token.

HTTP Status Code: 400

InvalidParameterCombinationException

You have specified two or more mutually exclusive parameters. Review the error message for details.

HTTP Status Code: 400

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

InvalidVersionNumberException

Your version number is out of bounds or does not follow the required syntax.

HTTP Status Code: 400

ResourceInUseException

The resource that you are trying to operate on is currently in use. Review the message details and retry later.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceQuotaExceededException

You have exceeded the number of permitted resources or operations for this service. For service quotas, see [EC2 Image Builder endpoints and quotas](#).

HTTP Status Code: 402

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

CreateContainerRecipe

Creates a new container recipe. Container recipes define how images are configured, tested, and assessed.

Request Syntax

PUT /CreateContainerRecipe HTTP/1.1

Content-type: application/json

```
{
  "clientToken": "string",
  "components": [
    {
      "componentArn": "string",
      "parameters": [
        {
          "name": "string",
          "value": [ "string" ]
        }
      ]
    }
  ],
  "containerType": "string",
  "description": "string",
  "dockerfileTemplateData": "string",
  "dockerfileTemplateUri": "string",
  "dryRun": boolean,
  "imageOsVersionOverride": "string",
  "instanceConfiguration": {
    "blockDeviceMappings": [
      {
        "deviceName": "string",
        "ebs": {
          "deleteOnTermination": boolean,
          "encrypted": boolean,
          "iops": number,
          "kmsKeyId": "string",
          "snapshotId": "string",
          "throughput": number,
          "volumeSize": number,
          "volumeType": "string"
        }
      }
    ]
  }
}
```

```
        "noDevice": "string",
        "virtualName": "string"
    },
    ],
    "image": "string"
},
"kmsKeyId": "string",
"name": "string",
"parentImage": "string",
"platformOverride": "string",
"semanticVersion": "string",
"tags": {
    "string" : "string"
},
"targetRepository": {
    "repositoryName": "string",
    "service": "string"
},
"workingDirectory": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

clientToken

A unique, case-sensitive identifier you provide to ensure that the operation completes no more than one time. If this token matches a previous request, the service ignores the request, but does not return an error. For more information, see [Ensuring idempotency](#) in the *Amazon EC2 API Reference*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

components

The components included in the container recipe.

Type: Array of [ComponentConfiguration](#) objects

Array Members: Minimum number of 1 item.

Required: No

containerType

The type of container to create.

Type: String

Valid Values: DOCKER

Required: Yes

description

The description of the container recipe.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

dockerfileTemplateData

The Dockerfile template used to build your image as an inline data blob.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 16000.

Pattern: [^\x00]+

Required: No

dockerfileTemplateUri

The Amazon S3 URI for the Dockerfile that is used to build your container image.

Type: String

Required: No

dryRun

Validates the required permissions and request parameters without making the request. If validation succeeds, the operation returns a `DryRunOperationException` error response.

Type: Boolean

Required: No

imageOsVersionOverride

Specifies the operating system version for the base image.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

instanceConfiguration

A group of options that can be used to configure an instance for building and testing container images.

Type: [InstanceConfiguration](#) object

Required: No

kmsKeyId

The Amazon Resource Name (ARN) that uniquely identifies which KMS key is used to encrypt the Dockerfile template. This can be either the Key ARN or the Alias ARN. For more information, see [Key identifiers \(KeyId\)](#) in the *AWS Key Management Service Developer Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

name

The name of the container recipe.

Type: String

Pattern: `^[-_A-Za-z-0-9][-_A-Za-z0-9 ]{1,126}[-_A-Za-z-0-9]$`

Required: Yes

parentImage

The base image for the container recipe.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: Yes

platformOverride

Specifies the operating system platform when you use a custom base image.

Type: String

Valid Values: Windows | Linux | macOS

Required: No

semanticVersion

The semantic version of the container recipe. This version follows the semantic version syntax.

Note

The semantic version has four nodes: <major>.<minor>.<patch>/<build>. You can assign values for the first three, and can filter on all of them.

Assignment: For the first three nodes, you can assign any positive integer value, including zero. The upper limit is $2^{30}-1$, or 1073741823, for each node. Image Builder automatically assigns the build number to the fourth node.

Patterns: You can use any numeric pattern that adheres to the assignment requirements for the nodes that you can assign. For example, you might choose a software version pattern, such as 1.0.0, or a date, such as 2021.01.01.

Type: String

Pattern: `^(?:[0-9]+|x)\.(?:[0-9]+|x)\.(?:[0-9]+|x)$`

Required: Yes

tags

Tags that are attached to the container recipe.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z0-9\s_.: /+=\ -@]*$`

Value Length Constraints: Maximum length of 256.

Required: No

targetRepository

The destination repository for the container image.

Type: [TargetContainerRepository](#) object

Required: Yes

workingDirectory

The working directory for use during build and test workflows.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
```

```
"clientToken": "string",
"containerRecipeArn": "string",
"latestVersionReferences": {
  "latestMajorVersionArn": "string",
  "latestMinorVersionArn": "string",
  "latestPatchVersionArn": "string",
  "latestVersionArn": "string"
},
"requestId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

clientToken

The client token that uniquely identifies the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

containerRecipeArn

Returns the Amazon Resource Name (ARN) of the container recipe that the request created.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):container-recipe/[a-z0-9-_/]+/(?:[0-9]+|x)\.(?:[0-9]+|x)\.(?:[0-9]+|x)$`

latestVersionReferences

The resource ARNs with different wildcard variations of semantic versioning.

Type: [LatestVersionReferences](#) object

requestId

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

DryRunOperationException

The dry run operation of the resource was successful, and no resources or mutations were actually performed due to the dry run flag in the request.

HTTP Status Code: 412

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

IdempotentParameterMismatchException

You have specified a client token for an operation using parameter values that differ from a previous request that used the same client token.

HTTP Status Code: 400

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

InvalidVersionNumberException

Your version number is out of bounds or does not follow the required syntax.

HTTP Status Code: 400

ResourceAlreadyExistsException

The resource that you are trying to create already exists.

HTTP Status Code: 400

ResourceInUseException

The resource that you are trying to operate on is currently in use. Review the message details and retry later.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceQuotaExceededException

You have exceeded the number of permitted resources or operations for this service. For service quotas, see [EC2 Image Builder endpoints and quotas](#).

HTTP Status Code: 402

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

CreateDistributionConfiguration

Creates a new distribution configuration. Distribution configurations define and configure the outputs of your pipeline.

Request Syntax

PUT /CreateDistributionConfiguration HTTP/1.1

Content-type: application/json

```
{
  "clientToken": "string",
  "description": "string",
  "distributions": [
    {
      "amiDistributionConfiguration": {
        "amiTags": {
          "string": "string"
        },
        "description": "string",
        "kmsKeyId": "string",
        "launchPermission": {
          "organizationalUnitArns": [ "string" ],
          "organizationArns": [ "string" ],
          "userGroups": [ "string" ],
          "userIds": [ "string" ]
        },
        "name": "string",
        "targetAccountIds": [ "string" ]
      },
      "containerDistributionConfiguration": {
        "containerTags": [ "string" ],
        "description": "string",
        "targetRepository": {
          "repositoryName": "string",
          "service": "string"
        }
      },
      "fastLaunchConfigurations": [
        {
          "accountId": "string",
          "enabled": boolean,
          "launchTemplate": {
```

```

        "launchTemplateId": "string",
        "launchTemplateName": "string",
        "launchTemplateVersion": "string"
    },
    "maxParallelLaunches": number,
    "snapshotConfiguration": {
        "targetResourceCount": number
    }
}
],
"launchTemplateConfigurations": [
    {
        "accountId": "string",
        "launchTemplateId": "string",
        "setDefaultVersion": boolean
    }
],
"licenseConfigurationArns": [ "string" ],
"region": "string",
"s3ExportConfiguration": {
    "diskImageFormat": "string",
    "roleName": "string",
    "s3Bucket": "string",
    "s3Prefix": "string"
},
"ssmParameterConfigurations": [
    {
        "amiAccountId": "string",
        "dataType": "string",
        "parameterName": "string"
    }
]
}
],
"dryRun": boolean,
"name": "string",
"tags": {
    "string" : "string"
}
}

```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

clientToken

A unique, case-sensitive identifier you provide to ensure that the operation completes no more than one time. If this token matches a previous request, the service ignores the request, but does not return an error. For more information, see [Ensuring idempotency](#) in the *Amazon EC2 API Reference*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

description

The description of the distribution configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

distributions

The distributions of the distribution configuration.

Type: Array of [Distribution](#) objects

Required: Yes

dryRun

Validates the required permissions and request parameters without making the request. If validation succeeds, the operation returns a `DryRunOperationException` error response.

Type: Boolean

Required: No

name

The name of the distribution configuration.

Type: String

Pattern: `^[-_A-Za-z-0-9][-_A-Za-z0-9 ]{1,126}[-_A-Za-z-0-9]$`

Required: Yes

tags

The tags of the distribution configuration.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z0-9\s_.:/=+\-@]*$`

Value Length Constraints: Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "clientToken": "string",
  "distributionConfigurationArn": "string",
  "requestId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

clientToken

The client token that uniquely identifies the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

distributionConfigurationArn

The Amazon Resource Name (ARN) of the distribution configuration that was created by this request.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):distribution-configuration/[a-z0-9-_]+$`

requestId

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

DryRunOperationException

The dry run operation of the resource was successful, and no resources or mutations were actually performed due to the dry run flag in the request.

HTTP Status Code: 412

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

IdempotentParameterMismatchException

You have specified a client token for an operation using parameter values that differ from a previous request that used the same client token.

HTTP Status Code: 400

InvalidParameterCombinationException

You have specified two or more mutually exclusive parameters. Review the error message for details.

HTTP Status Code: 400

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ResourceAlreadyExistsException

The resource that you are trying to create already exists.

HTTP Status Code: 400

ResourceInUseException

The resource that you are trying to operate on is currently in use. Review the message details and retry later.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceQuotaExceededException

You have exceeded the number of permitted resources or operations for this service. For service quotas, see [EC2 Image Builder endpoints and quotas](#).

HTTP Status Code: 402

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

CreateImage

Creates a new image along with all configured output resources defined in the distribution configuration. You must specify exactly one recipe for your image, using either a ContainerRecipeArn or an ImageRecipeArn.

Request Syntax

```
PUT /CreateImage HTTP/1.1
Content-type: application/json

{
  "clientToken": "string",
  "containerRecipeArn": "string",
  "distributionConfigurationArn": "string",
  "enhancedImageMetadataEnabled": boolean,
  "executionRole": "string",
  "imageRecipeArn": "string",
  "imageScanningConfiguration": {
    "ecrConfiguration": {
      "containerTags": [ "string" ],
      "repositoryName": "string"
    },
    "imageScanningEnabled": boolean
  },
  "imageTestsConfiguration": {
    "imageTestsEnabled": boolean,
    "timeoutMinutes": number
  },
  "infrastructureConfigurationArn": "string",
  "loggingConfiguration": {
    "logGroupName": "string"
  },
  "tags": {
    "string" : "string"
  },
  "workflows": [
    {
      "onFailure": "string",
      "parallelGroup": "string",
      "parameters": [
        {
```

```
        "name": "string",
        "value": [ "string" ]
      }
    ],
    "workflowArn": "string"
  }
]
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

clientToken

A unique, case-sensitive identifier you provide to ensure that the operation completes no more than one time. If this token matches a previous request, the service ignores the request, but does not return an error. For more information, see [Ensuring idempotency](#) in the *Amazon EC2 API Reference*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

containerRecipeArn

The Amazon Resource Name (ARN) of the container recipe that defines how images are configured and tested.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):container-recipe/[a-z0-9-_/]+/(?:[0-9]+|x)\.(?:[0-9]+|x)\.(?:[0-9]+|x)$`

Required: No

distributionConfigurationArn

The Amazon Resource Name (ARN) of the distribution configuration that defines and configures the outputs of your pipeline.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):distribution-configuration/[a-z0-9-_]+$`

Required: No

enhancedImageMetadataEnabled

Specifies whether to collect additional information about the image being created, including the operating system (OS) version and package list. Defaults to true.

Type: Boolean

Required: No

executionRole

The name or Amazon Resource Name (ARN) for the IAM role you create that grants Image Builder access to perform workflow actions.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^(?:arn:aws(?:-[a-z]+)*:iam:[0-9]{12}:role/)?[a-zA-Z_0-9+=,.\@_-/_]+$`

Required: No

imageRecipeArn

The Amazon Resource Name (ARN) of the image recipe that defines how images are configured, tested, and assessed.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):image-recipe/[a-z0-9-_]+/(?:[0-9]+|x)\.(?:[0-9]+|x)\.(?:[0-9]+|x)$`

Required: No

[imageScanningConfiguration](#)

Contains settings for vulnerability scans.

Type: [ImageScanningConfiguration](#) object

Required: No

[imageTestsConfiguration](#)

The image tests configuration of the image.

Type: [ImageTestsConfiguration](#) object

Required: No

[infrastructureConfigurationArn](#)

The Amazon Resource Name (ARN) of the infrastructure configuration that defines the environment in which your image will be built and tested.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):infrastructure-configuration/[a-z0-9-_]+$`

Required: Yes

[loggingConfiguration](#)

The logging configuration for the image build process.

Type: [ImageLoggingConfiguration](#) object

Required: No

[tags](#)

The tags of the image.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z0-9\s_.: /+=\ -@]*$`

Value Length Constraints: Maximum length of 256.

Required: No

[workflows](#)

Contains an array of workflow configuration objects.

Type: Array of [WorkflowConfiguration](#) objects

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "clientToken": "string",
  "imageBuildVersionArn": "string",
  "latestVersionReferences": {
    "latestMajorVersionArn": "string",
    "latestMinorVersionArn": "string",
    "latestPatchVersionArn": "string",
    "latestVersionArn": "string"
  },
  "requestId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[clientToken](#)

The client token that uniquely identifies the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

imageBuildVersionArn

The Amazon Resource Name (ARN) of the image that the request created.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):image/[a-z0-9-_]+/[0-9]+\.[0-9]+\.[0-9]+/[0-9]+$`

latestVersionReferences

The resource ARNs with different wildcard variations of semantic versioning.

Type: [LatestVersionReferences](#) object

requestId

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

IdempotentParameterMismatchException

You have specified a client token for an operation using parameter values that differ from a previous request that used the same client token.

HTTP Status Code: 400

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ResourceInUseException

The resource that you are trying to operate on is currently in use. Review the message details and retry later.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceQuotaExceededException

You have exceeded the number of permitted resources or operations for this service. For service quotas, see [EC2 Image Builder endpoints and quotas](#).

HTTP Status Code: 402

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

CreateImagePipeline

Creates a new image pipeline. Use image pipelines to automate the creation and distribution of images.

Request Syntax

PUT /CreateImagePipeline HTTP/1.1

Content-type: application/json

```
{
  "clientToken": "string",
  "containerRecipeArn": "string",
  "description": "string",
  "distributionConfigurationArn": "string",
  "dryRun": boolean,
  "enhancedImageMetadataEnabled": boolean,
  "executionRole": "string",
  "imageRecipeArn": "string",
  "imageScanningConfiguration": {
    "ecrConfiguration": {
      "containerTags": [ "string" ],
      "repositoryName": "string"
    },
    "imageScanningEnabled": boolean
  },
  "imageTags": {
    "string" : "string"
  },
  "imageTestsConfiguration": {
    "imageTestsEnabled": boolean,
    "timeoutMinutes": number
  },
  "infrastructureConfigurationArn": "string",
  "loggingConfiguration": {
    "imageLogGroupName": "string",
    "pipelineLogGroupName": "string"
  },
  "name": "string",
  "schedule": {
    "autoDisablePolicy": {
      "failureCount": number
    }
  },
}
```

```
    "pipelineExecutionStartCondition": "string",
    "scheduleExpression": "string",
    "timezone": "string"
  },
  "status": "string",
  "tags": {
    "string" : "string"
  },
  "workflows": [
    {
      "onFailure": "string",
      "parallelGroup": "string",
      "parameters": [
        {
          "name": "string",
          "value": [ "string" ]
        }
      ],
      "workflowArn": "string"
    }
  ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

clientToken

A unique, case-sensitive identifier you provide to ensure that the operation completes no more than one time. If this token matches a previous request, the service ignores the request, but does not return an error. For more information, see [Ensuring idempotency](#) in the *Amazon EC2 API Reference*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

containerRecipeArn

The Amazon Resource Name (ARN) of the container recipe that is used to configure images created by this container pipeline.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):container-recipe/[a-z0-9-_/]+(?:[0-9]+|x)\.(?:[0-9]+|x)\.(?:[0-9]+|x)$`

Required: No

description

The description of the image pipeline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

distributionConfigurationArn

The Amazon Resource Name (ARN) of the distribution configuration that configures and distributes images created by this image pipeline.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):distribution-configuration/[a-z0-9-_/]+$`

Required: No

dryRun

Validates the required permissions and request parameters without making the request. If validation succeeds, the operation returns a `DryRunOperationException` error response.

Type: Boolean

Required: No

enhancedImageMetadataEnabled

Specifies whether to collect additional information about the image being created, including the operating system (OS) version and package list. Defaults to `true`.

Type: Boolean

Required: No

executionRole

The name or Amazon Resource Name (ARN) for the IAM role you create that grants Image Builder access to perform workflow actions.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^(?:arn:aws(?:-[a-z]+)*:iam::[0-9]{12}:role/)?[a-zA-Z0-9+=,.\@\_/-_]/]+$`

Required: No

imageRecipeArn

The Amazon Resource Name (ARN) of the image recipe that configures images created by this image pipeline.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):image-recipe/[a-zA-Z0-9-_\+]/(?:[0-9]+|x)\.(?:[0-9]+|x)\.(?:[0-9]+|x)$`

Required: No

imageScanningConfiguration

Contains settings for vulnerability scans.

Type: [ImageScanningConfiguration](#) object

Required: No

imageTags

The tags to be applied to the images produced by this pipeline.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z0-9\s_.:/+\\-@]*$`

Value Length Constraints: Maximum length of 256.

Required: No

imageTestsConfiguration

The image test configuration of the image pipeline.

Type: [ImageTestsConfiguration](#) object

Required: No

infrastructureConfigurationArn

The Amazon Resource Name (ARN) of the infrastructure configuration that builds images created by this image pipeline.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):infrastructure-configuration/[a-z0-9-_]+$`

Required: Yes

loggingConfiguration

Specifies the logging configuration for the image pipeline. Use this to define custom CloudWatch Logs log groups for your pipeline execution logs and image build logs. The service manages log groups with names starting with `/aws/imagebuilder/` using the service-linked role. For custom log group names outside of this prefix, you must also provide an `executionRole`.

Type: [PipelineLoggingConfiguration](#) object

Required: No

name

The name of the image pipeline.

Type: String

Pattern: `^[-_A-Za-z-0-9][-_A-Za-z0-9 ]{1,126}[-_A-Za-z-0-9]$`

Required: Yes

schedule

The schedule of the image pipeline.

Type: [Schedule](#) object

Required: No

status

The status of the image pipeline.

Type: String

Valid Values: DISABLED | ENABLED

Required: No

tags

The tags of the image pipeline.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z0-9\s_./=+\-@]*$`

Value Length Constraints: Maximum length of 256.

Required: No

workflows

Contains an array of workflow configuration objects.

Type: Array of [WorkflowConfiguration](#) objects

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "clientToken": "string",
  "imagePipelineArn": "string",
  "requestId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[clientToken](#)

The client token that uniquely identifies the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

[imagePipelineArn](#)

The Amazon Resource Name (ARN) of the image pipeline that was created by this request.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):image-pipeline/[a-z0-9-_]+$`

[requestId](#)

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

DryRunOperationException

The dry run operation of the resource was successful, and no resources or mutations were actually performed due to the dry run flag in the request.

HTTP Status Code: 412

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

IdempotentParameterMismatchException

You have specified a client token for an operation using parameter values that differ from a previous request that used the same client token.

HTTP Status Code: 400

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ResourceAlreadyExistsException

The resource that you are trying to create already exists.

HTTP Status Code: 400

ResourceInUseException

The resource that you are trying to operate on is currently in use. Review the message details and retry later.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceQuotaExceededException

You have exceeded the number of permitted resources or operations for this service. For service quotas, see [EC2 Image Builder endpoints and quotas](#).

HTTP Status Code: 402

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

CreateImageRecipe

Creates a new image recipe. Image recipes define how images are configured, tested, and assessed.

Request Syntax

PUT /CreateImageRecipe HTTP/1.1

Content-type: application/json

```
{
  "additionalInstanceConfiguration": {
    "systemsManagerAgent": {
      "uninstallAfterBuild": boolean
    },
    "userDataOverride": "string"
  },
  "amiTags": {
    "string" : "string"
  },
  "amiWatermarks": [ "string" ],
  "blockDeviceMappings": [
    {
      "deviceName": "string",
      "ebs": {
        "deleteOnTermination": boolean,
        "encrypted": boolean,
        "iops": number,
        "kmsKeyId": "string",
        "snapshotId": "string",
        "throughput": number,
        "volumeSize": number,
        "volumeType": "string"
      },
      "noDevice": "string",
      "virtualName": "string"
    }
  ],
  "clientToken": "string",
  "components": [
    {
      "componentArn": "string",
      "parameters": [
        {
```

```
        "name": "string",
        "value": [ "string" ]
      }
    ]
  },
  "description": "string",
  "dryRun": boolean,
  "name": "string",
  "parentImage": "string",
  "semanticVersion": "string",
  "tags": {
    "string" : "string"
  },
  "workingDirectory": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

additionalInstanceConfiguration

The additional settings and launch scripts for your build instances.

Type: [AdditionalInstanceConfiguration](#) object

Required: No

amiTags

Tags that are applied to the AMI that Image Builder creates during the Build phase prior to image distribution.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z0-9\s_.: /+=\ -]*$`

Value Length Constraints: Maximum length of 256.

Required: No

amiWatermarks

The AMI watermark names to attach to the output AMI from this recipe. AMI watermarks are lineage markers. They automatically propagate to derivative AMIs when the source AMI is copied or distributed across Regions or accounts.

Note

AMI watermarks are supported only for image recipes. AMIs with watermarks cannot be made public.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: `^[A-Za-z0-9()\\[\]./'@_\-][A-Za-z0-9 ()\\[\]./'@_\-]{1,126}[A-Za-z0-9()\\[\]./'@_\-]$`

Required: No

blockDeviceMappings

The block device mappings of the image recipe.

Type: Array of [InstanceBlockDeviceMapping](#) objects

Required: No

clientToken

A unique, case-sensitive identifier you provide to ensure that the operation completes no more than one time. If this token matches a previous request, the service ignores the request, but does not return an error. For more information, see [Ensuring idempotency](#) in the *Amazon EC2 API Reference*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

components

The components included in the image recipe.

Type: Array of [ComponentConfiguration](#) objects

Array Members: Minimum number of 1 item.

Required: No

description

The description of the image recipe.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

dryRun

Validates the required permissions and request parameters without making the request. If validation succeeds, the operation returns a `DryRunOperationException` error response.

Type: Boolean

Required: No

name

The name of the image recipe.

Type: String

Pattern: `^[_A-Za-z0-9][_A-Za-z0-9 ]{1,126}[_A-Za-z0-9]$`

Required: Yes

parentImage

The base image for customizations specified in the image recipe. You can specify the parent image using one of the following options:

- AMI ID
- Image Builder image Amazon Resource Name (ARN)
- AWS Systems Manager (SSM) Parameter Store Parameter, prefixed by `ssm:`, followed by the parameter name or ARN.
- AWS Marketplace product ID

If you enter an AMI ID or an SSM parameter that contains the AMI ID, you must have access to the AMI, and the AMI must be in the source Region.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: Yes

semanticVersion

The semantic version of the image recipe. This version follows the semantic version syntax.

Note

The semantic version has four nodes: `<major>.<minor>.<patch>/<build>`. You can assign values for the first three, and can filter on all of them.

Assignment: For the first three nodes, you can assign any positive integer value, including zero. The upper limit is $2^{30}-1$, or 1073741823, for each node. Image Builder automatically assigns the build number to the fourth node.

Patterns: You can use any numeric pattern that adheres to the assignment requirements for the nodes that you can assign. For example, you might choose a software version pattern, such as 1.0.0, or a date, such as 2021.01.01.

Type: String

Pattern: `^(?:[0-9]+|x)\.(?:[0-9]+|x)\.(?:[0-9]+|x)$`

Required: Yes

[tags](#)

The tags of the image recipe.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z0-9\s_.:/+@]*$`

Value Length Constraints: Maximum length of 256.

Required: No

[workingDirectory](#)

The working directory used during build and test workflows.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "clientToken": "string",
  "imageRecipeArn": "string",
  "latestVersionReferences": {
    "latestMajorVersionArn": "string",
    "latestMinorVersionArn": "string",
    "latestPatchVersionArn": "string",
    "latestVersionArn": "string"
  },
  "requestId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

clientToken

The client token that uniquely identifies the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

imageRecipeArn

The Amazon Resource Name (ARN) of the image recipe that was created by this request.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):image-recipe/[a-z0-9-_.+/(?:[0-9]+|x)\.(?:[0-9]+|x)\.(?:[0-9]+|x)$`

latestVersionReferences

The resource ARNs with different wildcard variations of semantic versioning.

Type: [LatestVersionReferences](#) object

requestId

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

DryRunOperationException

The dry run operation of the resource was successful, and no resources or mutations were actually performed due to the dry run flag in the request.

HTTP Status Code: 412

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

IdempotentParameterMismatchException

You have specified a client token for an operation using parameter values that differ from a previous request that used the same client token.

HTTP Status Code: 400

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

InvalidVersionNumberException

Your version number is out of bounds or does not follow the required syntax.

HTTP Status Code: 400

ResourceAlreadyExistsException

The resource that you are trying to create already exists.

HTTP Status Code: 400

ResourceInUseException

The resource that you are trying to operate on is currently in use. Review the message details and retry later.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceQuotaExceededException

You have exceeded the number of permitted resources or operations for this service. For service quotas, see [EC2 Image Builder endpoints and quotas](#).

HTTP Status Code: 402

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)

- [AWS SDK for Ruby V3](#)

CreateInfrastructureConfiguration

Creates a new infrastructure configuration. An infrastructure configuration defines the environment in which your image will be built and tested.

Request Syntax

PUT /CreateInfrastructureConfiguration HTTP/1.1

Content-type: application/json

```
{
  "clientToken": "string",
  "description": "string",
  "dryRun": boolean,
  "instanceMetadataOptions": {
    "httpPutResponseHopLimit": number,
    "httpTokens": "string"
  },
  "instanceProfileName": "string",
  "instanceTypes": [ "string" ],
  "keyPair": "string",
  "logging": {
    "s3Logs": {
      "s3BucketName": "string",
      "s3KeyPrefix": "string"
    }
  },
  "name": "string",
  "placement": {
    "availabilityZone": "string",
    "hostId": "string",
    "hostResourceGroupArn": "string",
    "tenancy": "string"
  },
  "resourceTags": {
    "string" : "string"
  },
  "securityGroupIds": [ "string" ],
  "snsTopicArn": "string",
  "subnetId": "string",
  "tags": {
    "string" : "string"
  },
}
```

```
"terminateInstanceOnFailure": boolean
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

clientToken

A unique, case-sensitive identifier you provide to ensure that the operation completes no more than one time. If this token matches a previous request, the service ignores the request, but does not return an error. For more information, see [Ensuring idempotency](#) in the *Amazon EC2 API Reference*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

description

The description of the infrastructure configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

dryRun

Validates the required permissions and request parameters without making the request. If validation succeeds, the operation returns a `DryRunOperationException` error response.

Type: Boolean

Required: No

instanceMetadataOptions

The instance metadata options that you can set for the HTTP requests that pipeline builds use to launch EC2 build and test instances.

Type: [InstanceMetadataOptions](#) object

Required: No

instanceProfileName

The instance profile to associate with the instance used to customize your Amazon EC2 AMI.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^[\\w+=, .@- ]+$`

Required: Yes

instanceTypes

The instance types of the infrastructure configuration. You can specify one or more instance types to use for this build. Image Builder picks one of these instance types based on availability.

Type: Array of strings

Required: No

keyPair

The key pair of the infrastructure configuration. You can use this to log on to and debug the instance used to create your image.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

logging

The logging configuration of the infrastructure configuration.

Type: [Logging](#) object

Required: No

name

The name of the infrastructure configuration.

Type: String

Pattern: `^[-_A-Za-z-0-9][-_A-Za-z0-9 ]{1,126}[-_A-Za-z-0-9]$`

Required: Yes

placement

The instance placement settings that define where the instances that are launched from your image run.

Type: [Placement](#) object

Required: No

resourceTags

The metadata tags to assign to the Amazon EC2 instance that Image Builder launches during the build process. Tags are formatted as key value pairs.

Type: String to string map

Map Entries: Maximum number of 30 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z0-9\s_.:/+=\-\@]*$`

Value Length Constraints: Maximum length of 256.

Required: No

securityGroupIds

The security group IDs to associate with the instance used to customize your Amazon EC2 AMI.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

snsTopicArn

The Amazon Resource Name (ARN) of the SNS topic to which Image Builder sends image build event notifications.

Note

EC2 Image Builder is unable to send notifications to SNS topics that are encrypted using keys from other accounts. The key that is used to encrypt the SNS topic must reside in the account that the Image Builder service runs under.

Type: String

Pattern: `^arn:aws[^:]*:sns:[^:]+:[0-9]{12}:[a-zA-Z0-9-_{1,256}]$`

Required: No

subnetId

The subnet ID in which to place the instance used to customize your Amazon EC2 AML.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

tags

The metadata tags to assign to the infrastructure configuration resource that Image Builder creates as output. Tags are formatted as key value pairs.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z0-9\s_.:/+=\-\@]*$`

Value Length Constraints: Maximum length of 256.

Required: No

terminateInstanceOnFailure

Specifies whether to terminate the instance on failure. Set to false if you want Image Builder to retain the instance used to configure your AMI if the build or test phase of your workflow fails. Defaults to true.

Type: Boolean

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "clientToken": "string",
  "infrastructureConfigurationArn": "string",
  "requestId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

clientToken

The client token that uniquely identifies the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

infrastructureConfigurationArn

The Amazon Resource Name (ARN) of the infrastructure configuration that was created by this request.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):infrastructure-configuration/[a-z0-9-_]+$`

requestId

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

DryRunOperationException

The dry run operation of the resource was successful, and no resources or mutations were actually performed due to the dry run flag in the request.

HTTP Status Code: 412

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

IdempotentParameterMismatchException

You have specified a client token for an operation using parameter values that differ from a previous request that used the same client token.

HTTP Status Code: 400

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ResourceAlreadyExistsException

The resource that you are trying to create already exists.

HTTP Status Code: 400

ResourceInUseException

The resource that you are trying to operate on is currently in use. Review the message details and retry later.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceQuotaExceededException

You have exceeded the number of permitted resources or operations for this service. For service quotas, see [EC2 Image Builder endpoints and quotas](#).

HTTP Status Code: 402

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

CreateLifecyclePolicy

Creates a lifecycle policy resource.

Request Syntax

PUT /CreateLifecyclePolicy HTTP/1.1

Content-type: application/json

```
{
  "clientToken": "string",
  "description": "string",
  "dryRun": boolean,
  "executionRole": "string",
  "name": "string",
  "policyDetails": [
    {
      "action": {
        "includeResources": {
          "amis": boolean,
          "containers": boolean,
          "snapshots": boolean
        },
        "type": "string"
      },
      "exclusionRules": {
        "amis": {
          "isPublic": boolean,
          "lastLaunched": {
            "unit": "string",
            "value": number
          },
          "regions": [ "string" ],
          "sharedAccounts": [ "string" ],
          "tagMap": {
            "string" : "string"
          }
        },
        "tagMap": {
          "string" : "string"
        }
      },
      "filter": {
```

```
        "retainAtLeast": number,
        "type": "string",
        "unit": "string",
        "value": number
    }
}
],
"resourceSelection": {
    "recipes": [
        {
            "name": "string",
            "semanticVersion": "string"
        }
    ],
    "tagMap": {
        "string" : "string"
    }
},
"resourceType": "string",
"status": "string",
"tags": {
    "string" : "string"
}
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

clientToken

A unique, case-sensitive identifier you provide to ensure that the operation completes no more than one time. If this token matches a previous request, the service ignores the request, but does not return an error. For more information, see [Ensuring idempotency](#) in the *Amazon EC2 API Reference*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

description

Optional description for the lifecycle policy.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

dryRun

Validates the required permissions and request parameters without making the request. If validation succeeds, the operation returns a `DryRunOperationException` error response.

Type: Boolean

Required: No

executionRole

The name or Amazon Resource Name (ARN) for the IAM role you create that grants Image Builder access to run lifecycle actions.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^(?:arn:aws(?:-[a-z]+)*:iam:[0-9]{12}:role/)?[a-zA-Z0-9+=,.\@\_/-]+`

Required: Yes

name

The name of the lifecycle policy to create.

Type: String

Pattern: `^[-_A-Za-z0-9][-_A-Za-z0-9 ]{1,126}[-_A-Za-z0-9]$`

Required: Yes

policyDetails

Configuration details for the lifecycle policy rules.

Type: Array of [LifecyclePolicyDetail](#) objects

Array Members: Minimum number of 1 item. Maximum number of 3 items.

Required: Yes

resourceSelection

Selection criteria for the resources that the lifecycle policy applies to.

Type: [LifecyclePolicyResourceSelection](#) object

Required: Yes

resourceType

The type of Image Builder resource that the lifecycle policy applies to.

Type: String

Valid Values: AMI_IMAGE | CONTAINER_IMAGE

Required: Yes

status

Indicates whether the lifecycle policy resource is enabled.

Type: String

Valid Values: DISABLED | ENABLED

Required: No

tags

Tags to apply to the lifecycle policy resource.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z0-9\s_.:/+=\-\@]*$`

Value Length Constraints: Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "clientToken": "string",
  "lifecyclePolicyArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[clientToken](#)

The client token that uniquely identifies the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

[lifecyclePolicyArn](#)

The Amazon Resource Name (ARN) of the lifecycle policy that the request created.

Type: String

Length Constraints: Maximum length of 1024.

Pattern: `^arn:aws(?:-[a-z]+)*:imagebuilder:[a-z]{2,}(?:-[a-z]+)+-[0-9]+:(?:[0-9]{12}|aws):lifecycle-policy/[a-z0-9-_\@]*$`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

DryRunOperationException

The dry run operation of the resource was successful, and no resources or mutations were actually performed due to the dry run flag in the request.

HTTP Status Code: 412

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

IdempotentParameterMismatchException

You have specified a client token for an operation using parameter values that differ from a previous request that used the same client token.

HTTP Status Code: 400

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ResourceAlreadyExistsException

The resource that you are trying to create already exists.

HTTP Status Code: 400

ResourceInUseException

The resource that you are trying to operate on is currently in use. Review the message details and retry later.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceQuotaExceededException

You have exceeded the number of permitted resources or operations for this service. For service quotas, see [EC2 Image Builder endpoints and quotas](#).

HTTP Status Code: 402

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

CreateWorkflow

Creates a new workflow or a new version of an existing workflow.

Request Syntax

```
PUT /CreateWorkflow HTTP/1.1
Content-type: application/json

{
  "changeDescription": "string",
  "clientToken": "string",
  "data": "string",
  "description": "string",
  "dryRun": boolean,
  "kmsKeyId": "string",
  "name": "string",
  "semanticVersion": "string",
  "tags": {
    "string" : "string"
  },
  "type": "string",
  "uri": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

changeDescription

Describes what change has been made in this version of the workflow, or what makes this version different from other versions of the workflow.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

clientToken

A unique, case-sensitive identifier you provide to ensure that the operation completes no more than one time. If this token matches a previous request, the service ignores the request, but does not return an error. For more information, see [Ensuring idempotency](#) in the *Amazon EC2 API Reference*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

data

Contains the UTF-8 encoded YAML document content for the workflow. Alternatively, you can specify the `uri` of a YAML document file stored in Amazon S3. However, you cannot specify both properties.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 16000.

Pattern: `[^\x00]+`

Required: No

description

Describes the workflow.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

dryRun

Validates the required permissions and request parameters without making the request. If validation succeeds, the operation returns a `DryRunOperationException` error response.

Type: Boolean

Required: No

kmsKeyId

The Amazon Resource Name (ARN) that uniquely identifies the KMS key used to encrypt this workflow resource. This can be either the Key ARN or the Alias ARN. For more information, see [Key identifiers \(KeyId\)](#) in the *AWS Key Management Service Developer Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

name

The name of the workflow to create.

Type: String

Pattern: `^[-_A-Za-z-0-9][-_A-Za-z0-9 ]{1,126}[-_A-Za-z-0-9]$`

Required: Yes

semanticVersion

The semantic version of this workflow resource. The semantic version syntax adheres to the following rules.

Note

The semantic version has four nodes: <major>.<minor>.<patch>/<build>. You can assign values for the first three, and can filter on all of them.

Assignment: For the first three nodes, you can assign any positive integer value, including zero. The upper limit is $2^{30}-1$, or 1073741823, for each node. Image Builder automatically assigns the build number to the fourth node.

Patterns: You can use any numeric pattern that adheres to the assignment requirements for the nodes that you can assign. For example, you might choose a software version pattern, such as 1.0.0, or a date, such as 2021.01.01.

Type: String

Pattern: `^[0-9]+\.[0-9]+\.[0-9]+$`

Required: Yes

tags

Tags that apply to the workflow resource.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z0-9\s_.: /+=\ -@]*$`

Value Length Constraints: Maximum length of 256.

Required: No

type

The phase in the image build process for which the workflow resource is responsible.

Type: String

Valid Values: BUILD | TEST | DISTRIBUTION

Required: Yes

uri

The `uri` of a YAML component document file. This must be an S3 URL (`s3://bucket/key`), and you must have permission to access the S3 bucket it points to. If you use Amazon S3, you can specify component content up to your service quota.

Alternatively, you can specify the YAML document inline, using the `component data` property. You cannot specify both properties.

Type: String

Required: No

Response Syntax

```
HTTP/1.1 200
```

Content-type: application/json

```
{
  "clientToken": "string",
  "latestVersionReferences": {
    "latestMajorVersionArn": "string",
    "latestMinorVersionArn": "string",
    "latestPatchVersionArn": "string",
    "latestVersionArn": "string"
  },
  "workflowBuildVersionArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[clientToken](#)

The client token that uniquely identifies the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

[latestVersionReferences](#)

The resource ARNs with different wildcard variations of semantic versioning.

Type: [LatestVersionReferences](#) object

[workflowBuildVersionArn](#)

The Amazon Resource Name (ARN) of the workflow resource that the request created.

Type: String

Length Constraints: Maximum length of 1024.

Pattern: `^arn:aws(?:-[a-z]+)*:imagebuilder:[a-z]{2,}(?:-[a-z]+)+-[0-9]+(?:[0-9]{12}|aws(?:-[a-z-]+)?):workflow/(build|test|distribution)/[a-z0-9-_.]+/[0-9]+\.[0-9]+\.[0-9]+/[0-9]+$`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

DryRunOperationException

The dry run operation of the resource was successful, and no resources or mutations were actually performed due to the dry run flag in the request.

HTTP Status Code: 412

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

IdempotentParameterMismatchException

You have specified a client token for an operation using parameter values that differ from a previous request that used the same client token.

HTTP Status Code: 400

InvalidParameterCombinationException

You have specified two or more mutually exclusive parameters. Review the error message for details.

HTTP Status Code: 400

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

InvalidVersionNumberException

Your version number is out of bounds or does not follow the required syntax.

HTTP Status Code: 400

ResourceInUseException

The resource that you are trying to operate on is currently in use. Review the message details and retry later.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceQuotaExceededException

You have exceeded the number of permitted resources or operations for this service. For service quotas, see [EC2 Image Builder endpoints and quotas](#).

HTTP Status Code: 402

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DeleteComponent

Deletes a component build version.

Request Syntax

```
DELETE /DeleteComponent?componentBuildVersionArn=componentBuildVersionArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

componentBuildVersionArn

The Amazon Resource Name (ARN) of the component build version to delete.

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?)?:component/[a-z0-9-_]+/[0-9]+\.[0-9]+\.[0-9]+/[0-9]+$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "componentBuildVersionArn": "string",
  "requestId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

componentBuildVersionArn

The Amazon Resource Name (ARN) of the component build version that this request deleted.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):component/[a-z0-9-_]+/[0-9]+\.[0-9]+\.[0-9]+/[0-9]+$`

requestId

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ResourceDependencyException

You have attempted to mutate or delete a resource with a dependency that prohibits this action. See the error message for more details.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DeleteContainerRecipe

Deletes a container recipe.

Request Syntax

```
DELETE /DeleteContainerRecipe?containerRecipeArn=containerRecipeArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

containerRecipeArn

The Amazon Resource Name (ARN) of the container recipe to delete.

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):container-recipe/[a-z0-9-_]+/(?:[0-9]+|x)\.(?:[0-9]+|x)\.(?:[0-9]+|x)$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "containerRecipeArn": "string",
  "requestId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

containerRecipeArn

The Amazon Resource Name (ARN) of the container recipe that was deleted.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):container-recipe/[a-z0-9-_/]+(?:[0-9]+|x)\.(?:[0-9]+|x)\.(?:[0-9]+|x)$`

requestId

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ResourceDependencyException

You have attempted to mutate or delete a resource with a dependency that prohibits this action. See the error message for more details.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DeleteDistributionConfiguration

Deletes a distribution configuration.

Request Syntax

```
DELETE /DeleteDistributionConfiguration?  
distributionConfigurationArn=distributionConfigurationArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

distributionConfigurationArn

The Amazon Resource Name (ARN) of the distribution configuration to delete.

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):distribution-configuration/[a-z0-9-_]+$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200  
Content-type: application/json  
  
{  
  "distributionConfigurationArn": "string",  
  "requestId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

distributionConfigurationArn

The Amazon Resource Name (ARN) of the distribution configuration that was deleted.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):distribution-configuration/[a-z0-9- _]+$`

requestId

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ResourceDependencyException

You have attempted to mutate or delete a resource with a dependency that prohibits this action. See the error message for more details.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DeleteImage

Deletes an Image Builder image resource. This does not delete any EC2 AMIs or ECR container images that are created during the image build process. You must clean those up separately, using the appropriate Amazon EC2 or Amazon ECR console actions, or API or AWS CLI commands.

- To deregister an EC2 Linux AMI, see [Deregister your Linux AMI](#) in the *Amazon EC2 User Guide*.
- To deregister an EC2 Windows AMI, see [Deregister your Windows AMI](#) in the *Amazon EC2 Windows Guide*.
- To delete a container image from Amazon ECR, see [Deleting an image](#) in the *Amazon ECR User Guide*.

Request Syntax

```
DELETE /DeleteImage?imageBuildVersionArn=imageBuildVersionArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[imageBuildVersionArn](#)

The Amazon Resource Name (ARN) of the Image Builder image resource to delete.

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):image/[a-z0-9-_/]+/[0-9]+\.[0-9]+\.[0-9]+/[0-9]+$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "imageBuildVersionArn": "string",
  "requestId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

imageBuildVersionArn

The Amazon Resource Name (ARN) of the Image Builder image resource that this request deleted.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):image/[a-z0-9-_]+/[0-9]+\.[0-9]+\.[0-9]+/[0-9]+$`

requestId

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ResourceDependencyException

You have attempted to mutate or delete a resource with a dependency that prohibits this action. See the error message for more details.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DeleteImagePipeline

Deletes an image pipeline.

Request Syntax

```
DELETE /DeleteImagePipeline?imagePipelineArn=imagePipelineArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

imagePipelineArn

The Amazon Resource Name (ARN) of the image pipeline to delete.

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):image-pipeline/[a-z0-9-_$]+$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "imagePipelineArn": "string",
  "requestId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

imagePipelineArn

The Amazon Resource Name (ARN) of the image pipeline that was deleted.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):image-pipeline/[a-z0-9-_$]+$`

requestId

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ResourceDependencyException

You have attempted to mutate or delete a resource with a dependency that prohibits this action. See the error message for more details.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DeleteImageRecipe

Deletes an image recipe.

Request Syntax

```
DELETE /DeleteImageRecipe?imageRecipeArn=imageRecipeArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

imageRecipeArn

The Amazon Resource Name (ARN) of the image recipe to delete.

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):image-recipe/[a-z0-9-_.]+/(?:[0-9]+|x)\.(?:[0-9]+|x)\.(?:[0-9]+|x)$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "imageRecipeArn": "string",
  "requestId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

imageRecipeArn

The Amazon Resource Name (ARN) of the image recipe that was deleted.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):image-recipe/[a-z0-9-_\+]/(?:[0-9]+\|x)\.(?:[0-9]+\|x)\.(?:[0-9]+\|x)$`

requestId

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ResourceDependencyException

You have attempted to mutate or delete a resource with a dependency that prohibits this action. See the error message for more details.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DeleteInfrastructureConfiguration

Deletes an infrastructure configuration.

Request Syntax

```
DELETE /DeleteInfrastructureConfiguration?  
infrastructureConfigurationArn=infrastructureConfigurationArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

infrastructureConfigurationArn

The Amazon Resource Name (ARN) of the infrastructure configuration to delete.

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):infrastructure-configuration/[a-z0-9-_]+$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200  
Content-type: application/json  
  
{  
  "infrastructureConfigurationArn": "string",  
  "requestId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

infrastructureConfigurationArn

The Amazon Resource Name (ARN) of the infrastructure configuration that was deleted.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):infrastructure-configuration/[a-z0-9-_]+$`

requestId

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ResourceDependencyException

You have attempted to mutate or delete a resource with a dependency that prohibits this action. See the error message for more details.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DeleteLifecyclePolicy

Deletes the specified lifecycle policy resource.

Request Syntax

```
DELETE /DeleteLifecyclePolicy?lifecyclePolicyArn=lifecyclePolicyArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

lifecyclePolicyArn

The Amazon Resource Name (ARN) of the lifecycle policy resource to delete.

Length Constraints: Maximum length of 1024.

Pattern: `^arn:aws(?:-[a-z]+)*:imagebuilder:[a-z]{2,}(?:-[a-z]+)+-[0-9]+:(?:[0-9]{12}|aws):lifecycle-policy/[a-z0-9-_]+$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "lifecyclePolicyArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

lifecyclePolicyArn

The Amazon Resource Name (ARN) of the lifecycle policy that was deleted.

Type: String

Length Constraints: Maximum length of 1024.

Pattern: `^arn:aws(?:-[a-z]+)*:imagebuilder:[a-z]{2,}(?:-[a-z]+)+-[0-9]+:(?:[0-9]{12}|aws):lifecycle-policy/[a-z0-9-_]+$`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ResourceDependencyException

You have attempted to mutate or delete a resource with a dependency that prohibits this action. See the error message for more details.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DeleteWorkflow

Deletes a specific workflow resource.

Request Syntax

```
DELETE /DeleteWorkflow?workflowBuildVersionArn=workflowBuildVersionArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

workflowBuildVersionArn

The Amazon Resource Name (ARN) of the workflow resource to delete.

Length Constraints: Maximum length of 1024.

Pattern: `^arn:aws(?:-[a-z]+)*:imagebuilder:[a-z]{2,}(?:-[a-z]+)-[0-9]+:(?:[0-9]{12}|aws(?:-[a-z]+)?):workflow/(build|test|distribution)/[a-z0-9-_.]+/[0-9]+\.[0-9]+\.[0-9]+/[0-9]+$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "workflowBuildVersionArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

workflowBuildVersionArn

The Amazon Resource Name (ARN) of the workflow resource that this request deleted.

Type: String

Length Constraints: Maximum length of 1024.

Pattern: `^arn:aws(?:-[a-z]+)*:imagebuilder:[a-z]{2,}(?:-[a-z]+)-[0-9]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):workflow/(build|test|distribution)/[a-z0-9-_/][0-9]+\.[0-9]+\.[0-9]+/[0-9]+$`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ResourceDependencyException

You have attempted to mutate or delete a resource with a dependency that prohibits this action. See the error message for more details.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DistributeImage

Distributes an existing AMI to target Regions and accounts without running the full image build process. This operation only runs the distribution phase on an image that has already been built.

Request Syntax

```
PUT /DistributeImage HTTP/1.1
Content-type: application/json

{
  "clientToken": "string",
  "distributionConfigurationArn": "string",
  "executionRole": "string",
  "loggingConfiguration": {
    "logGroupName": "string"
  },
  "sourceImage": "string",
  "tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

clientToken

A unique, case-sensitive identifier you provide to ensure that the operation completes no more than one time. If this token matches a previous request, the service ignores the request, but does not return an error. For more information, see [Ensuring idempotency](#) in the *Amazon EC2 API Reference*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

[distributionConfigurationArn](#)

The Amazon Resource Name (ARN) of the distribution configuration. The configuration defines target Regions, accounts, and AMI settings. The distribution configuration must be in the same Region as this operation.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):distribution-configuration/[a-z0-9-_]+$`

Required: Yes

[executionRole](#)

The name or Amazon Resource Name (ARN) of the IAM role that Image Builder assumes to distribute the image.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^(?:arn:aws(?:-[a-z]+)*:iam:[0-9]{12}:role/)?[a-zA-Z_0-9+=,.\@_-/_]+$`

Required: Yes

[loggingConfiguration](#)

The logging configuration for the distribution.

Type: [ImageLoggingConfiguration](#) object

Required: No

[sourceImage](#)

The source image to distribute. Specify an AMI identifier, SSM parameter path, or Image Builder image Amazon Resource Name (ARN). When you specify an Image Builder image Amazon Resource Name (ARN), the image must be in the AVAILABLE state.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: Yes

[tags](#)

The tags to apply to the distributed image.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z0-9\s_.:/=\-@]*$`

Value Length Constraints: Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "clientToken": "string",
  "imageBuildVersionArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[clientToken](#)

The client token that uniquely identifies the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

imageBuildVersionArn

The Amazon Resource Name (ARN) of the image to be distributed.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):image/[a-z0-9-_]+/[0-9]+\.[0-9]+\.[0-9]+/[0-9]+$`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have permissions to perform the requested operation.

HTTP Status Code: 403

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

IdempotentParameterMismatchException

You have specified a client token for an operation using parameter values that differ from a previous request that used the same client token.

HTTP Status Code: 400

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ResourceInUseException

The resource that you are trying to operate on is currently in use. Review the message details and retry later.

HTTP Status Code: 400

ResourceNotFoundException

At least one of the resources referenced by your request does not exist.

HTTP Status Code: 404

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceQuotaExceededException

You have exceeded the number of permitted resources or operations for this service. For service quotas, see [EC2 Image Builder endpoints and quotas](#).

HTTP Status Code: 402

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

TooManyRequestsException

You have attempted too many requests for the specific operation.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetComponent

Retrieves a component object.

Request Syntax

```
GET /GetComponent?componentBuildVersionArn=componentBuildVersionArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

componentBuildVersionArn

The Amazon Resource Name (ARN) of the component that you want to get. Regex requires the suffix `/\d+$`.

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):component/[a-z0-9-_]+/(?:((?:([0-9]+|x)\.([0-9]+|x)\.([0-9]+|x)))|([0-9]+\.[0-9]+\.[0-9]+/[0-9]+))$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "component": {
    "arn": "string",
    "changeDescription": "string",
    "data": "string",
    "dateCreated": "string",
    "description": "string",
    "encrypted": boolean,
```

```

    "kmsKeyId": "string",
    "name": "string",
    "obfuscate": boolean,
    "owner": "string",
    "parameters": [
      {
        "defaultValue": [ "string" ],
        "description": "string",
        "name": "string",
        "type": "string"
      }
    ],
    "platform": "string",
    "productCodes": [
      {
        "productCodeId": "string",
        "productCodeType": "string"
      }
    ],
    "publisher": "string",
    "state": {
      "reason": "string",
      "status": "string"
    },
    "supportedOsVersions": [ "string" ],
    "tags": {
      "string" : "string"
    },
    "type": "string",
    "version": "string"
  },
  "latestVersionReferences": {
    "latestMajorVersionArn": "string",
    "latestMinorVersionArn": "string",
    "latestPatchVersionArn": "string",
    "latestVersionArn": "string"
  },
  "requestId": "string"
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

component

The component object specified in the request.

Type: [Component](#) object

latestVersionReferences

The resource ARNs with different wildcard variations of semantic versioning.

Type: [LatestVersionReferences](#) object

requestId

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetComponentPolicy

Retrieves a component policy.

Request Syntax

```
GET /GetComponentPolicy?componentArn=componentArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

componentArn

The Amazon Resource Name (ARN) of the component whose policy you want to retrieve.

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):component/[a-z0-9-_]+/[0-9]+\.[0-9]+\.[0-9]+/[0-9]+$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "policy": "string",
  "requestId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

policy

The component policy.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 30000.

requestId

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ResourceNotFoundException

At least one of the resources referenced by your request does not exist.

HTTP Status Code: 404

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetContainerRecipe

Retrieves a container recipe.

Request Syntax

```
GET /GetContainerRecipe?containerRecipeArn=containerRecipeArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

containerRecipeArn

The Amazon Resource Name (ARN) of the container recipe to retrieve.

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):container-recipe/[a-z0-9-_/]+/(?:[0-9]+|x)\.(?:[0-9]+|x)\.(?:[0-9]+|x)$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

HTTP/1.1 200

Content-type: application/json

```
{
  "containerRecipe": {
    "arn": "string",
    "components": [
      {
        "componentArn": "string",
        "parameters": [
          {
            "name": "string",
            "value": [ "string" ]
          }
        ]
      }
    ]
  }
}
```

```

    ]
  }
],
  "containerType": "string",
  "dateCreated": "string",
  "description": "string",
  "dockerfileTemplateData": "string",
  "encrypted": boolean,
  "instanceConfiguration": {
    "blockDeviceMappings": [
      {
        "deviceName": "string",
        "ebs": {
          "deleteOnTermination": boolean,
          "encrypted": boolean,
          "iops": number,
          "kmsKeyId": "string",
          "snapshotId": "string",
          "throughput": number,
          "volumeSize": number,
          "volumeType": "string"
        },
        "noDevice": "string",
        "virtualName": "string"
      }
    ],
    "image": "string"
  },
  "kmsKeyId": "string",
  "name": "string",
  "owner": "string",
  "parentImage": "string",
  "platform": "string",
  "tags": {
    "string" : "string"
  },
  "targetRepository": {
    "repositoryName": "string",
    "service": "string"
  },
  "version": "string",
  "workingDirectory": "string"
},
"latestVersionReferences": {

```

```
    "latestMajorVersionArn": "string",
    "latestMinorVersionArn": "string",
    "latestPatchVersionArn": "string",
    "latestVersionArn": "string"
  },
  "requestId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

containerRecipe

The container recipe object that is returned.

Type: [ContainerRecipe](#) object

latestVersionReferences

The resource ARNs with different wildcard variations of semantic versioning.

Type: [LatestVersionReferences](#) object

requestId

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetContainerRecipePolicy

Retrieves the policy for a container recipe.

Request Syntax

```
GET /GetContainerRecipePolicy?containerRecipeArn=containerRecipeArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

containerRecipeArn

The Amazon Resource Name (ARN) of the container recipe for the policy being requested.

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):container-recipe/[a-z0-9-_/]+(?:[0-9]+|x)\.(?:[0-9]+|x)\.(?:[0-9]+|x)$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "policy": "string",
  "requestId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

policy

The container recipe policy object that is returned.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 30000.

requestId

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ResourceNotFoundException

At least one of the resources referenced by your request does not exist.

HTTP Status Code: 404

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetDistributionConfiguration

Retrieves a distribution configuration.

Request Syntax

```
GET /GetDistributionConfiguration?  
distributionConfigurationArn=distributionConfigurationArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

distributionConfigurationArn

The Amazon Resource Name (ARN) of the distribution configuration that you want to retrieve.

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):distribution-configuration/[a-z0-9-_]+$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200  
Content-type: application/json  
  
{  
  "distributionConfiguration": {  
    "arn": "string",  
    "dateCreated": "string",  
    "dateUpdated": "string",  
    "description": "string",  
    "distributions": [  
      {  
        "amiDistributionConfiguration": {  
          "amiTags": {
```

```

        "string" : "string"
    },
    "description": "string",
    "kmsKeyId": "string",
    "launchPermission": {
        "organizationalUnitArns": [ "string" ],
        "organizationArns": [ "string" ],
        "userGroups": [ "string" ],
        "userIds": [ "string" ]
    },
    "name": "string",
    "targetAccountIds": [ "string" ]
},
"containerDistributionConfiguration": {
    "containerTags": [ "string" ],
    "description": "string",
    "targetRepository": {
        "repositoryName": "string",
        "service": "string"
    }
},
"fastLaunchConfigurations": [
    {
        "accountId": "string",
        "enabled": boolean,
        "launchTemplate": {
            "launchTemplateId": "string",
            "launchTemplateName": "string",
            "launchTemplateVersion": "string"
        },
        "maxParallelLaunches": number,
        "snapshotConfiguration": {
            "targetResourceCount": number
        }
    }
],
"launchTemplateConfigurations": [
    {
        "accountId": "string",
        "launchTemplateId": "string",
        "setDefaultVersion": boolean
    }
],
"licenseConfigurationArns": [ "string" ],

```

```

    "region": "string",
    "s3ExportConfiguration": {
      "diskImageFormat": "string",
      "roleName": "string",
      "s3Bucket": "string",
      "s3Prefix": "string"
    },
    "ssmParameterConfigurations": [
      {
        "amiAccountId": "string",
        "dataType": "string",
        "parameterName": "string"
      }
    ]
  },
  "name": "string",
  "tags": {
    "string" : "string"
  },
  "timeoutMinutes": number
},
"requestId": "string"
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

distributionConfiguration

The distribution configuration object.

Type: [DistributionConfiguration](#) object

requestId

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetImage

Retrieves an image.

Request Syntax

```
GET /GetImage?imageBuildVersionArn=imageBuildVersionArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

imageBuildVersionArn

The Amazon Resource Name (ARN) of the image that you want to get.

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):image/[a-z0-9-_]+/(?:((?:([0-9]+|x)\.([0-9]+|x)\.([0-9]+|x))|([0-9]+\.[0-9]+\.[0-9]+/[0-9]+)))$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json
```

```
{
  "image": {
    "arn": "string",
    "buildType": "string",
    "containerRecipe": {
      "arn": "string",
      "components": [
        {
          "componentArn": "string",
          "parameters": [
```

```

        {
            "name": "string",
            "value": [ "string" ]
        }
    ]
}
],
"containerType": "string",
"dateCreated": "string",
"description": "string",
"dockerfileTemplateData": "string",
"encrypted": boolean,
"instanceConfiguration": {
    "blockDeviceMappings": [
        {
            "deviceName": "string",
            "ebs": {
                "deleteOnTermination": boolean,
                "encrypted": boolean,
                "iops": number,
                "kmsKeyId": "string",
                "snapshotId": "string",
                "throughput": number,
                "volumeSize": number,
                "volumeType": "string"
            },
            "noDevice": "string",
            "virtualName": "string"
        }
    ],
    "image": "string"
},
"kmsKeyId": "string",
"name": "string",
"owner": "string",
"parentImage": "string",
"platform": "string",
"tags": {
    "string" : "string"
},
"targetRepository": {
    "repositoryName": "string",
    "service": "string"
},

```

```

    "version": "string",
    "workingDirectory": "string"
  },
  "dateCreated": "string",
  "deprecationTime": number,
  "distributionConfiguration": {
    "arn": "string",
    "dateCreated": "string",
    "dateUpdated": "string",
    "description": "string",
    "distributions": [
      {
        "amiDistributionConfiguration": {
          "amiTags": {
            "string": "string"
          },
          "description": "string",
          "kmsKeyId": "string",
          "launchPermission": {
            "organizationalUnitArns": [ "string" ],
            "organizationArns": [ "string" ],
            "userGroups": [ "string" ],
            "userIds": [ "string" ]
          },
          "name": "string",
          "targetAccountIds": [ "string" ]
        },
        "containerDistributionConfiguration": {
          "containerTags": [ "string" ],
          "description": "string",
          "targetRepository": {
            "repositoryName": "string",
            "service": "string"
          }
        }
      }
    ],
    "fastLaunchConfigurations": [
      {
        "accountId": "string",
        "enabled": boolean,
        "launchTemplate": {
          "launchTemplateId": "string",
          "launchTemplateName": "string",
          "launchTemplateVersion": "string"
        }
      }
    ]
  }
}

```

```

        "maxParallelLaunches": number,
        "snapshotConfiguration": {
            "targetResourceCount": number
        }
    },
    ],
    "launchTemplateConfigurations": [
        {
            "accountId": "string",
            "launchTemplateId": "string",
            "setDefaultVersion": boolean
        }
    ],
    "licenseConfigurationArns": [ "string" ],
    "region": "string",
    "s3ExportConfiguration": {
        "diskImageFormat": "string",
        "roleName": "string",
        "s3Bucket": "string",
        "s3Prefix": "string"
    },
    "ssmParameterConfigurations": [
        {
            "amiAccountId": "string",
            "dataType": "string",
            "parameterName": "string"
        }
    ]
},
    ],
    "name": "string",
    "tags": {
        "string" : "string"
    },
    "timeoutMinutes": number
},
    "enhancedImageMetadataEnabled": boolean,
    "executionRole": "string",
    "imageRecipe": {
        "additionalInstanceConfiguration": {
            "systemsManagerAgent": {
                "uninstallAfterBuild": boolean
            },
            "userDataOverride": "string"
        }
    }
}

```

```

    },
    "amiTags": {
      "string" : "string"
    },
    "amiWatermarks": [ "string" ],
    "arn": "string",
    "blockDeviceMappings": [
      {
        "deviceName": "string",
        "ebs": {
          "deleteOnTermination": boolean,
          "encrypted": boolean,
          "iops": number,
          "kmsKeyId": "string",
          "snapshotId": "string",
          "throughput": number,
          "volumeSize": number,
          "volumeType": "string"
        },
        "noDevice": "string",
        "virtualName": "string"
      }
    ],
    "components": [
      {
        "componentArn": "string",
        "parameters": [
          {
            "name": "string",
            "value": [ "string" ]
          }
        ]
      }
    ],
    "dateCreated": "string",
    "description": "string",
    "name": "string",
    "owner": "string",
    "parentImage": "string",
    "platform": "string",
    "tags": {
      "string" : "string"
    },
    "type": "string",

```

```

    "version": "string",
    "workingDirectory": "string"
  },
  "imageScanningConfiguration": {
    "ecrConfiguration": {
      "containerTags": [ "string" ],
      "repositoryName": "string"
    },
    "imageScanningEnabled": boolean
  },
  "imageSource": "string",
  "imageTestsConfiguration": {
    "imageTestsEnabled": boolean,
    "timeoutMinutes": number
  },
  "infrastructureConfiguration": {
    "arn": "string",
    "dateCreated": "string",
    "dateUpdated": "string",
    "description": "string",
    "instanceMetadataOptions": {
      "httpPutResponseHopLimit": number,
      "httpTokens": "string"
    },
    "instanceProfileName": "string",
    "instanceTypes": [ "string" ],
    "keyPair": "string",
    "logging": {
      "s3Logs": {
        "s3BucketName": "string",
        "s3KeyPrefix": "string"
      }
    },
    "name": "string",
    "placement": {
      "availabilityZone": "string",
      "hostId": "string",
      "hostResourceGroupArn": "string",
      "tenancy": "string"
    },
    "resourceTags": {
      "string" : "string"
    },
    "securityGroupIds": [ "string" ],

```

```

    "snsTopicArn": "string",
    "subnetId": "string",
    "tags": {
        "string" : "string"
    },
    "terminateInstanceOnFailure": boolean
},
"lifecycleExecutionId": "string",
"loggingConfiguration": {
    "logGroupName": "string"
},
"name": "string",
"osVersion": "string",
"outputResources": {
    "amis": [
        {
            "accountId": "string",
            "description": "string",
            "image": "string",
            "name": "string",
            "region": "string",
            "state": {
                "failureContext": {
                    "componentFailure": {
                        "action": "string",
                        "componentArn": "string",
                        "errorMessage": "string",
                        "phaseName": "string",
                        "stepName": "string"
                    },
                    "distributionFailure": {
                        "errorMessage": "string",
                        "regionFailures": [
                            {
                                "errorMessage": "string",
                                "imageConfigurationStep": "string",
                                "region": "string",
                                "status": "string",
                                "targetAccountId": "string"
                            }
                        ]
                    }
                }
            },
            "failedStep": "string",
            "imageStatus": "string",

```

```

        "stepExecutionId": "string",
        "workflowArn": "string",
        "workflowExecutionId": "string"
    },
    "reason": "string",
    "status": "string"
}
],
"containers": [
    {
        "imageUris": [ "string" ],
        "region": "string"
    }
]
},
"platform": "string",
"scanState": {
    "reason": "string",
    "status": "string"
},
"sourcePipelineArn": "string",
"sourcePipelineName": "string",
"state": {
    "failureContext": {
        "componentFailure": {
            "action": "string",
            "componentArn": "string",
            "errorMessage": "string",
            "phaseName": "string",
            "stepName": "string"
        },
        "distributionFailure": {
            "errorMessage": "string",
            "regionFailures": [
                {
                    "errorMessage": "string",
                    "imageConfigurationStep": "string",
                    "region": "string",
                    "status": "string",
                    "targetAccountId": "string"
                }
            ]
        }
    }
},

```

```

        "failedStep": "string",
        "imageStatus": "string",
        "stepExecutionId": "string",
        "workflowArn": "string",
        "workflowExecutionId": "string"
    },
    "reason": "string",
    "status": "string"
},
"tags": {
    "string" : "string"
},
"type": "string",
"version": "string",
"workflows": [
    {
        "onFailure": "string",
        "parallelGroup": "string",
        "parameters": [
            {
                "name": "string",
                "value": [ "string" ]
            }
        ],
        "workflowArn": "string"
    }
]
},
"latestVersionReferences": {
    "latestMajorVersionArn": "string",
    "latestMinorVersionArn": "string",
    "latestPatchVersionArn": "string",
    "latestVersionArn": "string"
},
"requestId": "string"
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

image

The image object.

Type: [Image](#) object

latestVersionReferences

The resource ARNs with different wildcard variations of semantic versioning.

Type: [LatestVersionReferences](#) object

requestId

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetImagePipeline

Retrieves an image pipeline.

Request Syntax

```
GET /GetImagePipeline?imagePipelineArn=imagePipelineArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

imagePipelineArn

The Amazon Resource Name (ARN) of the image pipeline that you want to retrieve.

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):image-pipeline/[a-z0-9-_$]+`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json
```

```
{
  "imagePipeline": {
    "arn": "string",
    "consecutiveFailures": number,
    "containerRecipeArn": "string",
    "dateCreated": "string",
    "dateLastRun": "string",
    "dateNextRun": "string",
    "dateUpdated": "string",
    "description": "string",
    "distributionConfigurationArn": "string",
```

```

    "enhancedImageMetadataEnabled": boolean,
    "executionRole": "string",
    "imageRecipeArn": "string",
    "imageScanningConfiguration": {
        "ecrConfiguration": {
            "containerTags": [ "string " ],
            "repositoryName": "string"
        },
        "imageScanningEnabled": boolean
    },
    "imageTags": {
        "string" : "string"
    },
    "imageTestsConfiguration": {
        "imageTestsEnabled": boolean,
        "timeoutMinutes": number
    },
    "infrastructureConfigurationArn": "string",
    "lastRunStatus": "string",
    "loggingConfiguration": {
        "imageLogGroupName": "string",
        "pipelineLogGroupName": "string"
    },
    "name": "string",
    "platform": "string",
    "schedule": {
        "autoDisablePolicy": {
            "failureCount": number
        },
        "pipelineExecutionStartCondition": "string",
        "scheduleExpression": "string",
        "timezone": "string"
    },
    "status": "string",
    "tags": {
        "string" : "string"
    },
    "workflows": [
        {
            "onFailure": "string",
            "parallelGroup": "string",
            "parameters": [
                {
                    "name": "string",

```

```
        "value": [ "string" ]
      },
    ],
    "workflowArn": "string"
  }
],
},
"requestId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

imagePipeline

The image pipeline object.

Type: [ImagePipeline](#) object

requestId

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetImagePolicy

Retrieves an image policy.

Request Syntax

```
GET /GetImagePolicy?imageArn=imageArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

imageArn

The Amazon Resource Name (ARN) of the image whose policy you want to retrieve.

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):image/[a-z0-9-_]+/[0-9]+\.[0-9]+\.[0-9]+/[0-9]+$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "policy": "string",
  "requestId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

policy

The image policy object.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 30000.

requestId

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ResourceNotFoundException

At least one of the resources referenced by your request does not exist.

HTTP Status Code: 404

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetImageRecipe

Retrieves an image recipe.

Request Syntax

```
GET /GetImageRecipe?imageRecipeArn=imageRecipeArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

imageRecipeArn

The Amazon Resource Name (ARN) of the image recipe that you want to retrieve.

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):image-recipe/[a-z0-9-_\u002B]+/(?:[0-9]+|x)\\. (?:[0-9]+|x)\\. (?:[0-9]+|x)$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "imageRecipe": {
    "additionalInstanceConfiguration": {
      "systemsManagerAgent": {
        "uninstallAfterBuild": boolean
      },
      "userDataOverride": "string"
    },
    "amiTags": {
      "string" : "string"
    },
  },
}
```

```

    "amiWatermarks": [ "string" ],
    "arn": "string",
    "blockDeviceMappings": [
      {
        "deviceName": "string",
        "ebs": {
          "deleteOnTermination": boolean,
          "encrypted": boolean,
          "iops": number,
          "kmsKeyId": "string",
          "snapshotId": "string",
          "throughput": number,
          "volumeSize": number,
          "volumeType": "string"
        },
        "noDevice": "string",
        "virtualName": "string"
      }
    ],
    "components": [
      {
        "componentArn": "string",
        "parameters": [
          {
            "name": "string",
            "value": [ "string" ]
          }
        ]
      }
    ],
    "dateCreated": "string",
    "description": "string",
    "name": "string",
    "owner": "string",
    "parentImage": "string",
    "platform": "string",
    "tags": {
      "string" : "string"
    },
    "type": "string",
    "version": "string",
    "workingDirectory": "string"
  },
  "latestVersionReferences": {

```

```
    "latestMajorVersionArn": "string",
    "latestMinorVersionArn": "string",
    "latestPatchVersionArn": "string",
    "latestVersionArn": "string"
  },
  "requestId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[imageRecipe](#)

The image recipe object.

Type: [ImageRecipe](#) object

[latestVersionReferences](#)

The resource ARNs with different wildcard variations of semantic versioning.

Type: [LatestVersionReferences](#) object

[requestId](#)

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetImageRecipePolicy

Retrieves an image recipe policy.

Request Syntax

```
GET /GetImageRecipePolicy?imageRecipeArn=imageRecipeArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

imageRecipeArn

The Amazon Resource Name (ARN) of the image recipe whose policy you want to retrieve.

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):image-recipe/[a-z0-9-_]+/(?:[0-9]+|x)\.(?:[0-9]+|x)\.(?:[0-9]+|x)$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "policy": "string",
  "requestId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

policy

The image recipe policy object.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 30000.

requestId

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ResourceNotFoundException

At least one of the resources referenced by your request does not exist.

HTTP Status Code: 404

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetInfrastructureConfiguration

Retrieves an infrastructure configuration.

Request Syntax

```
GET /GetInfrastructureConfiguration?
infrastructureConfigurationArn=infrastructureConfigurationArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

infrastructureConfigurationArn

The Amazon Resource Name (ARN) of the infrastructure configuration that you want to retrieve.

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):infrastructure-configuration/[a-z0-9-_]+$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "infrastructureConfiguration": {
    "arn": "string",
    "dateCreated": "string",
    "dateUpdated": "string",
    "description": "string",
    "instanceMetadataOptions": {
      "httpPutResponseHopLimit": number,
```

```

    "httpTokens": "string"
  },
  "instanceProfileName": "string",
  "instanceTypes": [ "string" ],
  "keyPair": "string",
  "logging": {
    "s3Logs": {
      "s3BucketName": "string",
      "s3KeyPrefix": "string"
    }
  },
  "name": "string",
  "placement": {
    "availabilityZone": "string",
    "hostId": "string",
    "hostResourceGroupArn": "string",
    "tenancy": "string"
  },
  "resourceTags": {
    "string" : "string"
  },
  "securityGroupIds": [ "string" ],
  "snsTopicArn": "string",
  "subnetId": "string",
  "tags": {
    "string" : "string"
  },
  "terminateInstanceOnFailure": boolean
},
"requestId": "string"
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

infrastructureConfiguration

The infrastructure configuration object.

Type: InfrastructureConfiguration object

requestId

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetLifecycleExecution

Retrieves the runtime information for a specific runtime instance of the lifecycle policy.

Request Syntax

```
GET /GetLifecycleExecution?lifecycleExecutionId=lifecycleExecutionId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[lifecycleExecutionId](#)

The unique identifier for a runtime instance of the lifecycle policy.

Pattern: `^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "lifecycleExecution": {
    "endTime": number,
    "lifecycleExecutionId": "string",
    "lifecyclePolicyArn": "string",
    "resourcesImpactedSummary": {
      "hasImpactedResources": boolean
    },
    "startTime": number,
```

```
    "state": {  
      "reason": "string",  
      "status": "string"  
    }  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

lifecycleExecution

Runtime details for the specified runtime instance of the lifecycle policy.

Type: [LifecycleExecution](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetLifecyclePolicy

Retrieves details for the specified image lifecycle policy.

Request Syntax

```
GET /GetLifecyclePolicy?lifecyclePolicyArn=lifecyclePolicyArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[lifecyclePolicyArn](#)

Specifies the Amazon Resource Name (ARN) of the image lifecycle policy resource to get.

Length Constraints: Maximum length of 1024.

Pattern: `^arn:aws(?:-[a-z]+)*:imagebuilder:[a-z]{2,}(?:-[a-z]+)+-[0-9]+:(?:[0-9]{12}|aws):lifecycle-policy/[a-z0-9-_]+$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "lifecyclePolicy": {
    "arn": "string",
    "dateCreated": number,
    "dateLastRun": number,
    "dateUpdated": number,
    "description": "string",
    "executionRole": "string",
    "name": "string",
```

```

    "policyDetails": [
      {
        "action": {
          "includeResources": {
            "amis": boolean,
            "containers": boolean,
            "snapshots": boolean
          },
          "type": "string"
        },
        "exclusionRules": {
          "amis": {
            "isPublic": boolean,
            "lastLaunched": {
              "unit": "string",
              "value": number
            },
            "regions": [ "string " ],
            "sharedAccounts": [ "string " ],
            "tagMap": {
              "string": "string"
            }
          },
          "tagMap": {
            "string": "string"
          }
        },
        "filter": {
          "retainAtLeast": number,
          "type": "string",
          "unit": "string",
          "value": number
        }
      }
    ],
    "resourceSelection": {
      "recipes": [
        {
          "name": "string",
          "semanticVersion": "string"
        }
      ],
      "tagMap": {
        "string": "string"
      }
    }
  }

```

```
    }  
  },  
  "resourceType": "string",  
  "status": "string",  
  "tags": {  
    "string" : "string"  
  }  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

lifecyclePolicy

The Amazon Resource Name (ARN) of the image lifecycle policy resource that was returned.

Type: [LifecyclePolicy](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetMarketplaceResource

Verifies the subscription and performs resource dependency checks on the requested AWS Marketplace resource. For AWS Marketplace components, the response contains fields to download the components and their artifacts.

Request Syntax

```
POST /GetMarketplaceResource HTTP/1.1
Content-type: application/json
```

```
{
  "resourceArn": "string",
  "resourceLocation": "string",
  "resourceType": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[resourceArn](#)

The Amazon Resource Name (ARN) that uniquely identifies an AWS Marketplace resource.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?)?:(?:image-recipe|container-recipe|infrastructure-configuration|distribution-configuration|component|image|image-pipeline|lifecycle-policy|workflow\/(?:build|test|distribution))\/[a-z0-9-_\]+(?:\/(?:?:x|[0-9]+)\.?:x|[0-9]+)\.?:x|[0-9]+))(?:\/[0-9]+)??$`

Required: Yes

[resourceLocation](#)

The bucket path that you can specify to download the resource from Amazon S3.

Type: String

Length Constraints: Maximum length of 1024.

Pattern: `^s3://[^\s]+/\.[^\s]*$`

Required: No

resourceType

Specifies which type of AWS Marketplace resource Image Builder retrieves.

Type: String

Valid Values: `COMPONENT_DATA` | `COMPONENT_ARTIFACT`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "data": "string",
  "resourceArn": "string",
  "url": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

data

Returns obfuscated data that contains the YAML content of the component.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetWorkflow

Retrieves a workflow resource object.

Request Syntax

```
GET /GetWorkflow?workflowBuildVersionArn=workflowBuildVersionArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

workflowBuildVersionArn

The Amazon Resource Name (ARN) of the workflow resource that you want to get.

Pattern: `^arn:aws(?:-[a-z]+)*:imagebuilder:[a-z]{2,}(?:-[a-z]+)-[0-9]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):workflow/(build|test|distribution)/[a-z0-9-_.]+/(?:((?:([0-9]+|x)\.([0-9]+|x)\.([0-9]+|x))|(?:[0-9]+\.[0-9]+\.[0-9]+/[0-9]+))$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json
```

```
{
  "latestVersionReferences": {
    "latestMajorVersionArn": "string",
    "latestMinorVersionArn": "string",
    "latestPatchVersionArn": "string",
    "latestVersionArn": "string"
  },
}
```

```
{
  "workflow": {
    "arn": "string",
    "changeDescription": "string",
    "data": "string",
    "dateCreated": "string",
    "description": "string",
    "kmsKeyId": "string",
    "name": "string",
    "owner": "string",
    "parameters": [
      {
        "defaultValue": [ "string" ],
        "description": "string",
        "name": "string",
        "type": "string"
      }
    ],
    "state": {
      "reason": "string",
      "status": "string"
    },
    "tags": {
      "string" : "string"
    },
    "type": "string",
    "version": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

latestVersionReferences

The resource ARNs with different wildcard variations of semantic versioning.

Type: [LatestVersionReferences](#) object

workflow

The workflow resource specified in the request.

Type: [Workflow](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetWorkflowExecution

Retrieves runtime information for a specific runtime instance of the workflow.

Request Syntax

```
GET /GetWorkflowExecution?workflowExecutionId=workflowExecutionId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

workflowExecutionId

Use the unique identifier for a runtime instance of the workflow to get runtime details.

Pattern: `^wf-[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "endTime": "string",
  "imageBuildVersionArn": "string",
  "message": "string",
  "parallelGroup": "string",
  "requestId": "string",
  "startTime": "string",
  "status": "string",
  "totalStepCount": number,
```

```
"totalStepsFailed": number,  
"totalStepsSkipped": number,  
"totalStepsSucceeded": number,  
"type": "string",  
"workflowBuildVersionArn": "string",  
"workflowExecutionId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

endTime

The timestamp when the specified runtime instance of the workflow finished.

Type: String

imageBuildVersionArn

The Amazon Resource Name (ARN) of the image resource build version that the specified runtime instance of the workflow created.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):image/[a-z0-9-_]+/[0-9]+\.[0-9]+\.[0-9]+/[0-9]+$`

message

The output message from the specified runtime instance of the workflow, if applicable.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

parallelGroup

Test workflows are defined within named runtime groups. The parallel group is a named group that contains one or more test workflows.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `^[A-Za-z0-9][A-Za-z0-9-_+#{0,99}]$`

requestId

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

startTime

The timestamp when the specified runtime instance of the workflow started.

Type: String

status

The current runtime status for the specified runtime instance of the workflow.

Type: String

Valid Values: PENDING | SKIPPED | RUNNING | COMPLETED | FAILED |
ROLLBACK_IN_PROGRESS | ROLLBACK_COMPLETED | CANCELLED

totalStepCount

The total number of steps in the specified runtime instance of the workflow that ran. This number should equal the sum of the step counts for steps that succeeded, were skipped, and failed.

Type: Integer

totalStepsFailed

A runtime count for the number of steps that failed in the specified runtime instance of the workflow.

Type: Integer

totalStepsSkipped

A runtime count for the number of steps that were skipped in the specified runtime instance of the workflow.

Type: Integer

totalStepsSucceeded

A runtime count for the number of steps that ran successfully in the specified runtime instance of the workflow.

Type: Integer

type

The type of workflow that Image Builder ran for the specified runtime instance of the workflow.

Type: String

Valid Values: BUILD | TEST | DISTRIBUTION

workflowBuildVersionArn

The Amazon Resource Name (ARN) of the build version for the Image Builder workflow resource that defines the specified runtime instance of the workflow.

Type: String

Length Constraints: Maximum length of 1024.

Pattern: `^arn:aws(?:-[a-z]+)*:imagebuilder:[a-z]{2,}(?:-[a-z]+)-[0-9]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):workflow/(build|test|distribution)/[a-z0-9-_/][0-9]+\.[0-9]+\.[0-9]+/[0-9]+$`

workflowExecutionId

The unique identifier that Image Builder assigned to keep track of runtime details when it ran the workflow.

Type: String

Pattern: `^wf-[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}$`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidRequestException

You have requested an action that that the service doesn't support.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetWorkflowStepExecution

Retrieves runtime information for a specific runtime instance of the workflow step.

Request Syntax

```
GET /GetWorkflowStepExecution?stepExecutionId=stepExecutionId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

stepExecutionId

Use the unique identifier for a specific runtime instance of the workflow step to get runtime details for that step.

Pattern: `^step-[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "action": "string",
  "attemptNumber": number,
  "description": "string",
  "endTime": "string",
  "imageBuildVersionArn": "string",
  "inputs": "string",
  "maxAttempts": number,
```

```
"message": "string",
"name": "string",
"onFailure": "string",
"outputs": "string",
"requestId": "string",
"rollbackStatus": "string",
"startTime": "string",
"status": "string",
"stepExecutionId": "string",
"timeoutSeconds": number,
"workflowBuildVersionArn": "string",
"workflowExecutionId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

action

The name of the action that the specified step performs.

Type: String

Pattern: `^[A-Za-z][A-Za-z0-9-_{1,99}]$`

attemptNumber

The current attempt number for the specified runtime instance of the workflow step. The first run is attempt one. The number increases by one for each retry.

Type: Integer

Valid Range: Minimum value of 1.

description

Describes the specified workflow step.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

endTime

The timestamp when the specified runtime instance of the workflow step finished.

Type: String

imageBuildVersionArn

The Amazon Resource Name (ARN) of the image resource build version that the specified runtime instance of the workflow step creates.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):image/[a-z0-9-_]+/[0-9]+\.[0-9]+\.[0-9]+/[0-9]+$`

inputs

Input parameters that Image Builder provided for the specified runtime instance of the workflow step.

Type: String

maxAttempts

The maximum number of attempts allowed for the specified runtime instance of the workflow step, based on the retry configuration in the workflow document. If the step doesn't configure retries, the maximum is one attempt.

Type: Integer

Valid Range: Minimum value of 1.

message

The output message from the specified runtime instance of the workflow step, if applicable.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

name

The name of the specified runtime instance of the workflow step.

Type: String

Pattern: `^[A-Za-z][A-Za-z0-9-_{1,99}]$`

onFailure

The action to perform if the workflow step fails.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

outputs

The file names that the specified runtime version of the workflow step created as output.

Type: String

requestId

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

rollbackStatus

Reports on the rollback status of the specified runtime version of the workflow step, if applicable.

Type: String

Valid Values: RUNNING | COMPLETED | SKIPPED | FAILED

startTime

The timestamp when the specified runtime version of the workflow step started.

Type: String

status

The current status for the specified runtime version of the workflow step.

Type: String

Valid Values: PENDING | SKIPPED | RUNNING | COMPLETED | FAILED | CANCELLED

stepExecutionId

The unique identifier for the runtime version of the workflow step that you specified in the request.

Type: String

Pattern: `^step-[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}$`

timeoutSeconds

The maximum duration in seconds for this step to complete its action.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 43200.

workflowBuildVersionArn

The Amazon Resource Name (ARN) of the build version for the Image Builder workflow resource that defines this workflow step.

Type: String

Length Constraints: Maximum length of 1024.

Pattern: `^arn:aws(?:-[a-z]+)*:imagebuilder:[a-z]{2,}(?:-[a-z]+)+-[0-9]+(?::[0-9]{12}|aws(?:-[a-z-]+)?):workflow/(build|test|distribution)/[a-z0-9-_.+[/[0-9]+\.[0-9]+\.[0-9]+/[0-9]+$`

workflowExecutionId

The unique identifier that Image Builder assigned to keep track of runtime details when it ran the workflow.

Type: String

Pattern: `^wf-[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}$`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidRequestException

You have requested an action that that the service doesn't support.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ImportComponent

Imports a component and transforms its data into a component document.

Request Syntax

```
PUT /ImportComponent HTTP/1.1
Content-type: application/json

{
  "changeDescription": "string",
  "clientToken": "string",
  "data": "string",
  "description": "string",
  "format": "string",
  "kmsKeyId": "string",
  "name": "string",
  "platform": "string",
  "semanticVersion": "string",
  "tags": {
    "string" : "string"
  },
  "type": "string",
  "uri": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

changeDescription

The change description of the component. This description indicates the change that has been made in this version, or what makes this version different from other versions of the component.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

clientToken

A unique, case-sensitive identifier you provide to ensure that the operation completes no more than one time. If this token matches a previous request, the service ignores the request, but does not return an error. For more information, see [Ensuring idempotency](#) in the *Amazon EC2 API Reference*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

data

The data of the component. Used to specify the data inline. Either `data` or `uri` can be used to specify the data within the component.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

description

The description of the component. Describes the contents of the component.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

format

The format of the resource that you want to import as a component.

Type: String

Valid Values: SHELL

Required: Yes

kmsKeyId

The Amazon Resource Name (ARN) that uniquely identifies the KMS key used to encrypt this component. This can be either the Key ARN or the Alias ARN. For more information, see [Key identifiers \(KeyId\)](#) in the *AWS Key Management Service Developer Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

name

The name of the component.

Type: String

Pattern: `^[-_A-Za-z-0-9][-_A-Za-z0-9 ]{1,126}[-_A-Za-z-0-9]$`

Required: Yes

platform

The platform of the component.

Type: String

Valid Values: Windows | Linux | macOS

Required: Yes

semanticVersion

The semantic version of the component. This version follows the semantic version syntax.

Note

The semantic version has four nodes: <major>.<minor>.<patch>/<build>. You can assign values for the first three, and can filter on all of them.

Filtering: You can use wildcards (x) to specify the most recent versions or nodes when selecting the base image or components for your recipe. When you use a wildcard in any node, all nodes to the right of the first wildcard must also be wildcards.

Type: String

Pattern: `^[0-9]+\.[0-9]+\.[0-9]+$`

Required: Yes

tags

The tags of the component.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z0-9\s_.: /+=\ -@]*$`

Value Length Constraints: Maximum length of 256.

Required: No

type

The type of the component denotes whether the component is used to build the image, or only to test it.

Type: String

Valid Values: BUILD | TEST

Required: Yes

uri

The uri of the component. Must be an Amazon S3 URL and you must have permission to access the Amazon S3 bucket. If you use Amazon S3, you can specify component content up to your service quota. Either `data` or `uri` can be used to specify the data within the component.

Type: String

Required: No

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json

{
  "clientToken": "string",
  "componentBuildVersionArn": "string",
  "requestId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[clientToken](#)

The client token that uniquely identifies the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

[componentBuildVersionArn](#)

The Amazon Resource Name (ARN) of the imported component.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):component/[a-z0-9-_/][0-9]+\.[0-9]+\.[0-9]+/[0-9]+$`

[requestId](#)

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

IdempotentParameterMismatchException

You have specified a client token for an operation using parameter values that differ from a previous request that used the same client token.

HTTP Status Code: 400

InvalidParameterCombinationException

You have specified two or more mutually exclusive parameters. Review the error message for details.

HTTP Status Code: 400

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

InvalidVersionNumberException

Your version number is out of bounds or does not follow the required syntax.

HTTP Status Code: 400

ResourceInUseException

The resource that you are trying to operate on is currently in use. Review the message details and retry later.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ImportDiskImage

Imports a Windows operating system image from a verified Microsoft ISO disk file. The following disk images are supported:

- Windows 11 Enterprise

Request Syntax

```
PUT /ImportDiskImage HTTP/1.1
Content-type: application/json

{
  "clientToken": "string",
  "description": "string",
  "executionRole": "string",
  "infrastructureConfigurationArn": "string",
  "loggingConfiguration": {
    "logGroupName": "string"
  },
  "name": "string",
  "osVersion": "string",
  "platform": "string",
  "registerImageOptions": {
    "secureBootEnabled": boolean,
    "uefiData": "string"
  },
  "semanticVersion": "string",
  "tags": {
    "string" : "string"
  },
  "uri": "string",
  "windowsConfiguration": {
    "imageIndex": number
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

clientToken

A unique, case-sensitive identifier you provide to ensure that the operation completes no more than one time. If this token matches a previous request, the service ignores the request, but does not return an error. For more information, see [Ensuring idempotency](#) in the *Amazon EC2 API Reference*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

description

The description for your disk image import.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

executionRole

The name or Amazon Resource Name (ARN) for the IAM role you create that grants Image Builder access to perform workflow actions to import an image from a Microsoft ISO file.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^(?:arn:aws(?:-[a-z]+)*:iam:[0-9]{12}:role/)?[a-zA-Z_0-9+=,.\@\\-_/]+$`

Required: No

infrastructureConfigurationArn

The Amazon Resource Name (ARN) of the infrastructure configuration resource that's used for launching the EC2 instance on which the ISO image is built.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):infrastructure-configuration/[a-z0-9-_]+$`

Required: Yes

loggingConfiguration

The logging configuration for the image build process.

Type: [ImageLoggingConfiguration](#) object

Required: No

name

The name of the image resource that's created from the import.

Type: String

Pattern: `^[-_A-Za-z-0-9][-_A-Za-z0-9 ]{1,126}[-_A-Za-z-0-9]$`

Required: Yes

osVersion

The operating system version for the imported image. Allowed values include the following:
Microsoft Windows 11.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

platform

The operating system platform for the imported image. Allowed values include the following:
Windows.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: Yes

registerImageOptions

Configures Secure Boot and UEFI settings for the imported image.

Type: [RegisterImageOptions](#) object

Required: No

semanticVersion

The semantic version to attach to the image that's created during the import process. This version follows the semantic version syntax.

Type: String

Pattern: `^[0-9]+\.[0-9]+\.[0-9]+$`

Required: Yes

tags

Tags that are attached to image resources created from the import.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z0-9\s_.:/+=\-\@]*$`

Value Length Constraints: Maximum length of 256.

Required: No

uri

The `uri` of the ISO disk file that's stored in Amazon S3.

Type: String

Required: Yes

windowsConfiguration

Specifies Windows settings for ISO imports.

Type: [WindowsConfiguration](#) object

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "clientToken": "string",
  "imageBuildVersionArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[clientToken](#)

The client token that uniquely identifies the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

[imageBuildVersionArn](#)

The Amazon Resource Name (ARN) of the output AMI that was created from the ISO disk file.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):image/[a-z0-9-_]+/[0-9]+\.[0-9]+\.[0-9]+/[0-9]+$`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You do not have permissions to perform the requested operation.

HTTP Status Code: 403

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

TooManyRequestsException

You have attempted too many requests for the specific operation.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ImportVmImage

When you export your virtual machine (VM) from its virtualization environment, that process creates a set of one or more disk container files that act as snapshots of your VM's environment, settings, and data. The Amazon EC2 API [ImportImage](#) action uses those files to import your VM and create an AMI. To import using the AWS CLI command, see [import-image](#)

You can reference the task ID from the VM import to pull in the AMI that the import created as the base image for your Image Builder recipe.

Request Syntax

```
PUT /ImportVmImage HTTP/1.1
Content-type: application/json

{
  "clientToken": "string",
  "description": "string",
  "loggingConfiguration": {
    "logGroupName": "string"
  },
  "name": "string",
  "osVersion": "string",
  "platform": "string",
  "semanticVersion": "string",
  "tags": {
    "string" : "string"
  },
  "vmImportTaskId": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

clientToken

A unique, case-sensitive identifier you provide to ensure that the operation completes no more than one time. If this token matches a previous request, the service ignores the request, but does not return an error. For more information, see [Ensuring idempotency](#) in the *Amazon EC2 API Reference*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

description

The description for the base image that is created by the import process.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

loggingConfiguration

The logging configuration for the image build process.

Type: [ImageLoggingConfiguration](#) object

Required: No

name

The name of the base image that is created by the import process.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: Yes

osVersion

The operating system version for the imported VM.

Type: String

Length Constraints: Minimum length of 1.

Required: No

platform

The operating system platform for the imported VM.

Type: String

Valid Values: Windows | Linux | macOS

Required: Yes

semanticVersion

The semantic version to attach to the base image that was created during the import process. This version follows the semantic version syntax.

Note

The semantic version has four nodes: <major>.<minor>.<patch>/<build>. You can assign values for the first three, and can filter on all of them.

Assignment: For the first three nodes, you can assign any positive integer value, including zero. The upper limit is $2^{30}-1$, or 1073741823, for each node. Image Builder automatically assigns the build number to the fourth node.

Patterns: You can use any numeric pattern that adheres to the assignment requirements for the nodes that you can assign. For example, you might choose a software version pattern, such as 1.0.0, or a date, such as 2021.01.01.

Type: String

Pattern: `^[0-9]+\.[0-9]+\.[0-9]+$`

Required: Yes

tags

Tags that are attached to the import resources.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z0-9\s_.: /+=\ -@]*$`

Value Length Constraints: Maximum length of 256.

Required: No

[vmImportTaskId](#)

The `importTaskId` (API) or `ImportTaskId` (AWS CLI) from the Amazon EC2 VM import process. Image Builder retrieves information from the import process to pull in the AMI that is created from the VM source as the base image for your recipe.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "clientToken": "string",
  "imageArn": "string",
  "requestId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[clientToken](#)

The client token that uniquely identifies the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

imageArn

The Amazon Resource Name (ARN) of the AMI that was created during the VM import process. This AMI is used as the base image for the recipe that imported the VM.

Type: String

requestId

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListComponentBuildVersions

Returns the list of component build versions for the specified component version Amazon Resource Name (ARN).

Request Syntax

```
POST /ListComponentBuildVersions HTTP/1.1
Content-type: application/json
```

```
{
  "componentVersionArn": "string",
  "maxResults": number,
  "nextToken": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

componentVersionArn

The component version Amazon Resource Name (ARN) whose versions you want to list.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):component/[a-z0-9-_[\]]+/[0-9]+\.[0-9]+\.[0-9]+$`

Required: No

maxResults

The maximum number of items to return in a single request.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 25.

Required: No

nextToken

A token to specify where to start paginating. Use the `nextToken` value from a previously truncated response.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "componentSummaryList": [
    {
      "arn": "string",
      "changeDescription": "string",
      "dateCreated": "string",
      "description": "string",
      "name": "string",
      "obfuscate": boolean,
      "owner": "string",
      "platform": "string",
      "publisher": "string",
      "state": {
        "reason": "string",
        "status": "string"
      },
      "supportedOsVersions": [ "string" ],
      "tags": {
        "string" : "string"
      },
      "type": "string",
      "version": "string"
    }
  ],
  "nextToken": "string",
```

```
"requestId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[componentSummaryList](#)

The list of component summaries for the specified semantic version.

Type: Array of [ComponentSummary](#) objects

[nextToken](#)

The next token used for paginated responses. When this field isn't empty, there are additional elements that the service hasn't included in this request. Use this token with the next request to retrieve additional objects.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

[requestId](#)

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidPaginationTokenException

You have provided an invalid pagination token in your request.

HTTP Status Code: 400

InvalidRequestException

You have requested an action that that the service doesn't support.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListComponents

Returns the list of components that can be filtered by name, or by using the listed `filters` to streamline results. Newly created components can take up to two minutes to appear in the ListComponents API Results.

Note

The semantic version has four nodes: `<major>.<minor>.<patch>/<build>`. You can assign values for the first three, and can filter on all of them.

Filtering: You can use wildcards (x) to specify the most recent versions or nodes when selecting the base image or components for your recipe. When you use a wildcard in any node, all nodes to the right of the first wildcard must also be wildcards.

Request Syntax

```
POST /ListComponents HTTP/1.1
Content-type: application/json
```

```
{
  "byName": boolean,
  "filters": [
    {
      "name": "string",
      "values": [ "string" ]
    }
  ],
  "maxResults": number,
  "nextToken": "string",
  "owner": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

byName

Returns the list of components for the specified name.

Type: Boolean

Required: No

filters

Use the following filters to streamline results:

- description
- name
- platform
- supportedOsVersion
- type
- version

Type: Array of [Filter](#) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: No

maxResults

The maximum number of items to return in a single request.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 25.

Required: No

nextToken

A token to specify where to start paginating. Use the `nextToken` value from a previously truncated response.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Required: No

owner

Filters results based on the type of owner for the component. By default, this request returns a list of components that your account owns. To see results for other types of owners, you can specify components that Amazon manages, third party components, or components that other accounts have shared with you.

Type: String

Valid Values: Self | Shared | Amazon | ThirdParty | AWSMarketplace

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "componentVersionList": [
    {
      "arn": "string",
      "dateCreated": "string",
      "description": "string",
      "name": "string",
      "owner": "string",
      "platform": "string",
      "productCodes": [
        {
          "productCodeId": "string",
          "productCodeType": "string"
        }
      ],
      "status": "string",
      "supportedOsVersions": [ "string " ],
      "type": "string",
      "version": "string"
    }
  ],
  "nextToken": "string",
  "requestId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

componentVersionList

The list of component semantic versions.

Note

The semantic version has four nodes: <major>.<minor>.<patch>/<build>. You can assign values for the first three, and can filter on all of them.

Type: Array of [ComponentVersion](#) objects

nextToken

The next token used for paginated responses. When this field isn't empty, there are additional elements that the service hasn't included in this request. Use this token with the next request to retrieve additional objects.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

requestId

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidPaginationTokenException

You have provided an invalid pagination token in your request.

HTTP Status Code: 400

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListContainerRecipes

Returns a list of container recipes.

Request Syntax

```
POST /ListContainerRecipes HTTP/1.1
Content-type: application/json
```

```
{
  "filters": [
    {
      "name": "string",
      "values": [ "string" ]
    }
  ],
  "maxResults": number,
  "nextToken": "string",
  "owner": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

filters

Use the following filters to streamline results:

- containerType
- name
- parentImage
- platform

Type: Array of [Filter](#) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: No

maxResults

The maximum number of items to return in a single request.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 25.

Required: No

nextToken

A token to specify where to start paginating. Use the nextToken value from a previously truncated response.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Required: No

owner

Returns container recipes belonging to the specified owner, that have been shared with you. You can omit this field to return container recipes belonging to your account.

Type: String

Valid Values: Self | Shared | Amazon | ThirdParty | AWSMarketplace

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "containerRecipeSummaryList": [
    {
      "arn": "string",
      "containerType": "string",
```

```
    "dateCreated": "string",
    "instanceImage": "string",
    "name": "string",
    "owner": "string",
    "parentImage": "string",
    "platform": "string",
    "tags": {
        "string" : "string"
    }
},
"nextToken": "string",
"requestId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

containerRecipeSummaryList

The list of container recipes returned for the request.

Type: Array of [ContainerRecipeSummary](#) objects

nextToken

The next token used for paginated responses. When this field isn't empty, there are additional elements that the service hasn't included in this request. Use this token with the next request to retrieve additional objects.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

requestId

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidPaginationTokenException

You have provided an invalid pagination token in your request.

HTTP Status Code: 400

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListDistributionConfigurations

Returns a list of distribution configurations.

Request Syntax

```
POST /ListDistributionConfigurations HTTP/1.1
Content-type: application/json
```

```
{
  "filters": [
    {
      "name": "string",
      "values": [ "string" ]
    }
  ],
  "maxResults": number,
  "nextToken": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

filters

You can filter on name to streamline results.

Type: Array of [Filter](#) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: No

maxResults

The maximum number of items to return in a single request.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 25.

Required: No

nextToken

A token to specify where to start paginating. Use the nextToken value from a previously truncated response.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "distributionConfigurationSummaryList": [
    {
      "arn": "string",
      "dateCreated": "string",
      "dateUpdated": "string",
      "description": "string",
      "name": "string",
      "regions": [ "string" ],
      "tags": {
        "string" : "string"
      }
    }
  ],
  "nextToken": "string",
  "requestId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[distributionConfigurationSummaryList](#)

The list of distributions.

Type: Array of [DistributionConfigurationSummary](#) objects

[nextToken](#)

The next token used for paginated responses. When this field isn't empty, there are additional elements that the service hasn't included in this request. Use this token with the next request to retrieve additional objects.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

[requestId](#)

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidPaginationTokenException

You have provided an invalid pagination token in your request.

HTTP Status Code: 400

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListImageBuildVersions

Returns a list of image build versions.

Request Syntax

```
POST /ListImageBuildVersions HTTP/1.1
Content-type: application/json
```

```
{
  "filters": [
    {
      "name": "string",
      "values": [ "string" ]
    }
  ],
  "imageVersionArn": "string",
  "maxResults": number,
  "nextToken": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

filters

Use the following filters to streamline results:

- name
- osVersion
- platform
- type
- version

Type: Array of [Filter](#) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: No

[imageVersionArn](#)

The Amazon Resource Name (ARN) of the image whose build versions you want to retrieve.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):image/[a-z0-9-_]+/[0-9]+\.[0-9]+\.[0-9]+$`

Required: No

[maxResults](#)

The maximum number of items to return in a single request.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 25.

Required: No

[nextToken](#)

A token to specify where to start paginating. Use the `nextToken` value from a previously truncated response.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "imageSummaryList": [
    {
      "arn": "string",
      "buildType": "string",
```

```

    "dateCreated": "string",
    "deprecationTime": number,
    "imageSource": "string",
    "lifecycleExecutionId": "string",
    "loggingConfiguration": {
        "logGroupName": "string"
    },
    "name": "string",
    "osVersion": "string",
    "outputResources": {
        "amis": [
            {
                "accountId": "string",
                "description": "string",
                "image": "string",
                "name": "string",
                "region": "string",
                "state": {
                    "failureContext": {
                        "componentFailure": {
                            "action": "string",
                            "componentArn": "string",
                            "errorMessage": "string",
                            "phaseName": "string",
                            "stepName": "string"
                        },
                        "distributionFailure": {
                            "errorMessage": "string",
                            "regionFailures": [
                                {
                                    "errorMessage": "string",
                                    "imageConfigurationStep": "string",
                                    "region": "string",
                                    "status": "string",
                                    "targetAccountId": "string"
                                }
                            ]
                        }
                    }
                },
                "failedStep": "string",
                "imageStatus": "string",
                "stepExecutionId": "string",
                "workflowArn": "string",
                "workflowExecutionId": "string"
            }
        ]
    },

```

```

        "reason": "string",
        "status": "string"
    }
}
],
"containers": [
    {
        "imageUri": [ "string" ],
        "region": "string"
    }
]
},
"owner": "string",
"platform": "string",
"state": {
    "failureContext": {
        "componentFailure": {
            "action": "string",
            "componentArn": "string",
            "errorMessage": "string",
            "phaseName": "string",
            "stepName": "string"
        },
        "distributionFailure": {
            "errorMessage": "string",
            "regionFailures": [
                {
                    "errorMessage": "string",
                    "imageConfigurationStep": "string",
                    "region": "string",
                    "status": "string",
                    "targetAccountId": "string"
                }
            ]
        }
    },
    "failedStep": "string",
    "imageStatus": "string",
    "stepExecutionId": "string",
    "workflowArn": "string",
    "workflowExecutionId": "string"
},
"reason": "string",
"status": "string"
},

```

```
    "tags": {
      "string" : "string"
    },
    "type": "string",
    "version": "string"
  },
  "nextToken": "string",
  "requestId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[imageSummaryList](#)

The list of image build versions.

Type: Array of [ImageSummary](#) objects

[nextToken](#)

The next token used for paginated responses. When this field isn't empty, there are additional elements that the service hasn't included in this request. Use this token with the next request to retrieve additional objects.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

[requestId](#)

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidPaginationTokenException

You have provided an invalid pagination token in your request.

HTTP Status Code: 400

InvalidRequestException

You have requested an action that that the service doesn't support.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListImagePackages

Lists the packages that are associated with an image build version, as determined by AWS Systems Manager Inventory at build time.

Request Syntax

```
POST /ListImagePackages HTTP/1.1
Content-type: application/json

{
  "imageBuildVersionArn": "string",
  "maxResults": number,
  "nextToken": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

imageBuildVersionArn

Filter results for the ListImagePackages request by the Image Build Version ARN

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?)?:image/[a-z0-9-_]+/[0-9]+\.[0-9]+\.[0-9]+/[0-9]+$`

Required: Yes

maxResults

The maximum number of items to return in a single request.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 25.

Required: No

nextToken

A token to specify where to start paginating. Use the nextToken value from a previously truncated response.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "imagePackageList": [
    {
      "packageName": "string",
      "packageVersion": "string"
    }
  ],
  "nextToken": "string",
  "requestId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

imagePackageList

The list of Image Packages returned in the response.

Type: Array of [ImagePackage](#) objects

nextToken

The next token used for paginated responses. When this field isn't empty, there are additional elements that the service hasn't included in this request. Use this token with the next request to retrieve additional objects.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

requestId

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidPaginationTokenException

You have provided an invalid pagination token in your request.

HTTP Status Code: 400

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ResourceNotFoundException

At least one of the resources referenced by your request does not exist.

HTTP Status Code: 404

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListImagePipelineImages

Returns a list of images created by the specified pipeline.

Request Syntax

```
POST /ListImagePipelineImages HTTP/1.1
Content-type: application/json
```

```
{
  "filters": [
    {
      "name": "string",
      "values": [ "string" ]
    }
  ],
  "imagePipelineArn": "string",
  "maxResults": number,
  "nextToken": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

filters

Use the following filters to streamline results:

- name
- version

Type: Array of [Filter](#) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: No

imagePipelineArn

The Amazon Resource Name (ARN) of the image pipeline whose images you want to view.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):image-pipeline/[a-z0-9-_$]+$`

Required: Yes

maxResults

The maximum number of items to return in a single request.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 25.

Required: No

nextToken

A token to specify where to start paginating. Use the `nextToken` value from a previously truncated response.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Required: No

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json
```

```
{
  "imageSummaryList": [
    {
      "arn": "string",
      "buildType": "string",
      "dateCreated": "string",
      "deprecationTime": number,
      "imageSource": "string",
```

```

    "lifecycleExecutionId": "string",
    "loggingConfiguration": {
        "logGroupName": "string"
    },
    "name": "string",
    "osVersion": "string",
    "outputResources": {
        "amis": [
            {
                "accountId": "string",
                "description": "string",
                "image": "string",
                "name": "string",
                "region": "string",
                "state": {
                    "failureContext": {
                        "componentFailure": {
                            "action": "string",
                            "componentArn": "string",
                            "errorMessage": "string",
                            "phaseName": "string",
                            "stepName": "string"
                        },
                        "distributionFailure": {
                            "errorMessage": "string",
                            "regionFailures": [
                                {
                                    "errorMessage": "string",
                                    "imageConfigurationStep": "string",
                                    "region": "string",
                                    "status": "string",
                                    "targetAccountId": "string"
                                }
                            ]
                        }
                    },
                    "failedStep": "string",
                    "imageStatus": "string",
                    "stepExecutionId": "string",
                    "workflowArn": "string",
                    "workflowExecutionId": "string"
                },
                "reason": "string",
                "status": "string"
            }
        ]
    }
}

```

```

    }
  ],
  "containers": [
    {
      "imageUri": [ "string" ],
      "region": "string"
    }
  ]
},
"owner": "string",
"platform": "string",
"state": {
  "failureContext": {
    "componentFailure": {
      "action": "string",
      "componentArn": "string",
      "errorMessage": "string",
      "phaseName": "string",
      "stepName": "string"
    },
    "distributionFailure": {
      "errorMessage": "string",
      "regionFailures": [
        {
          "errorMessage": "string",
          "imageConfigurationStep": "string",
          "region": "string",
          "status": "string",
          "targetAccountId": "string"
        }
      ]
    },
    "failedStep": "string",
    "imageStatus": "string",
    "stepExecutionId": "string",
    "workflowArn": "string",
    "workflowExecutionId": "string"
  },
  "reason": "string",
  "status": "string"
},
"tags": {
  "string" : "string"
},

```

```
    "type": "string",  
    "version": "string"  
  },  
  ],  
  "nextToken": "string",  
  "requestId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[imageSummaryList](#)

The list of images built by this pipeline.

Type: Array of [ImageSummary](#) objects

[nextToken](#)

The next token used for paginated responses. When this field isn't empty, there are additional elements that the service hasn't included in this request. Use this token with the next request to retrieve additional objects.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

[requestId](#)

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidPaginationTokenException

You have provided an invalid pagination token in your request.

HTTP Status Code: 400

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ResourceNotFoundException

At least one of the resources referenced by your request does not exist.

HTTP Status Code: 404

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListImagePipelines

Returns a list of image pipelines.

Request Syntax

```
POST /ListImagePipelines HTTP/1.1
Content-type: application/json
```

```
{
  "filters": [
    {
      "name": "string",
      "values": [ "string" ]
    }
  ],
  "maxResults": number,
  "nextToken": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

filters

Use the following filters to streamline results:

- description
- distributionConfigurationArn
- imageRecipeArn
- infrastructureConfigurationArn
- name
- status

Type: Array of [Filter](#) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: No

[maxResults](#)

The maximum number of items to return in a single request.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 25.

Required: No

[nextToken](#)

A token to specify where to start paginating. Use the nextToken value from a previously truncated response.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Required: No

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json
```

```
{
  "imagePipelineList": [
    {
      "arn": "string",
      "consecutiveFailures": number,
      "containerRecipeArn": "string",
      "dateCreated": "string",
      "dateLastRun": "string",
      "dateNextRun": "string",
      "dateUpdated": "string",
      "description": "string",
      "distributionConfigurationArn": "string",
      "enhancedImageMetadataEnabled": boolean,
      "executionRole": "string",
      "imageRecipeArn": "string",
```

```
"imageScanningConfiguration": {
  "ecrConfiguration": {
    "containerTags": [ "string" ],
    "repositoryName": "string"
  },
  "imageScanningEnabled": boolean
},
"imageTags": {
  "string" : "string"
},
"imageTestsConfiguration": {
  "imageTestsEnabled": boolean,
  "timeoutMinutes": number
},
"infrastructureConfigurationArn": "string",
"lastRunStatus": "string",
"loggingConfiguration": {
  "imageLogGroupName": "string",
  "pipelineLogGroupName": "string"
},
"name": "string",
"platform": "string",
"schedule": {
  "autoDisablePolicy": {
    "failureCount": number
  },
  "pipelineExecutionStartCondition": "string",
  "scheduleExpression": "string",
  "timezone": "string"
},
"status": "string",
"tags": {
  "string" : "string"
},
"workflows": [
  {
    "onFailure": "string",
    "parallelGroup": "string",
    "parameters": [
      {
        "name": "string",
        "value": [ "string" ]
      }
    ]
  }
],
```

```
        "workflowArn": "string"  
      }  
    ]  
  },  
  "nextToken": "string",  
  "requestId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

imagePipelineList

The list of image pipelines.

Type: Array of [ImagePipeline](#) objects

nextToken

The next token used for paginated responses. When this field isn't empty, there are additional elements that the service hasn't included in this request. Use this token with the next request to retrieve additional objects.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

requestId

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidPaginationTokenException

You have provided an invalid pagination token in your request.

HTTP Status Code: 400

InvalidRequestException

You have requested an action that that the service doesn't support.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListImageRecipes

Returns a list of image recipes.

Request Syntax

```
POST /ListImageRecipes HTTP/1.1
Content-type: application/json
```

```
{
  "filters": [
    {
      "name": "string",
      "values": [ "string" ]
    }
  ],
  "maxResults": number,
  "nextToken": "string",
  "owner": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

filters

Use the following filters to streamline results:

- name
- parentImage
- platform

Type: Array of [Filter](#) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: No

maxResults

The maximum number of items to return in a single request.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 25.

Required: No

nextToken

A token to specify where to start paginating. Use the `nextToken` value from a previously truncated response.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Required: No

owner

You can specify the recipe owner to filter results by that owner. By default, this request will only show image recipes owned by your account. To filter by a different owner, specify one of the `Valid Values` that are listed for this parameter.

Type: String

Valid Values: `Self` | `Shared` | `Amazon` | `ThirdParty` | `AWSMarketplace`

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "imageRecipeSummaryList": [
    {
      "arn": "string",
      "dateCreated": "string",
```

```
    "name": "string",
    "owner": "string",
    "parentImage": "string",
    "platform": "string",
    "tags": {
        "string" : "string"
    }
},
"nextToken": "string",
"requestId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

imageRecipeSummaryList

A list of ImageRecipeSummary objects that contain identifying characteristics for the image recipe, such as the name, the Amazon Resource Name (ARN), and the date created, along with other key details.

Type: Array of [ImageRecipeSummary](#) objects

nextToken

The next token used for paginated responses. When this field isn't empty, there are additional elements that the service hasn't included in this request. Use this token with the next request to retrieve additional objects.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

requestId

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidPaginationTokenException

You have provided an invalid pagination token in your request.

HTTP Status Code: 400

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListImages

Returns the list of images that you have access to. Newly created images can take up to two minutes to appear in the ListImages API Results.

Request Syntax

```
POST /ListImages HTTP/1.1
Content-type: application/json

{
  "byName": boolean,
  "filters": [
    {
      "name": "string",
      "values": [ "string" ]
    }
  ],
  "includeDeprecated": boolean,
  "maxResults": number,
  "nextToken": "string",
  "owner": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

byName

Requests a list of images with a specific recipe name.

Type: Boolean

Required: No

filters

Use the following filters to streamline results:

- name
- osVersion
- platform
- type
- version

Type: Array of [Filter](#) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: No

[**includeDeprecated**](#)

Includes deprecated images in the response list.

Type: Boolean

Required: No

[**maxResults**](#)

The maximum number of items to return in a single request.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 25.

Required: No

[**nextToken**](#)

A token to specify where to start paginating. Use the nextToken value from a previously truncated response.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Required: No

[**owner**](#)

Filters the list to images owned by you, by Amazon, or shared with you by other accounts. By default, only your account's images are returned.

Type: String

Valid Values: Self | Shared | Amazon | ThirdParty | AWSMarketplace

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "imageVersionList": [
    {
      "arn": "string",
      "buildType": "string",
      "dateCreated": "string",
      "imageSource": "string",
      "name": "string",
      "osVersion": "string",
      "owner": "string",
      "platform": "string",
      "type": "string",
      "version": "string"
    }
  ],
  "nextToken": "string",
  "requestId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

imageVersionList

The list of image semantic versions.

Note

The semantic version has four nodes: <major>.<minor>.<patch>/<build>. You can assign values for the first three, and can filter on all of them.

Filtering: You can use wildcards (x) to specify the most recent versions or nodes when selecting the base image or components for your recipe. When you use a wildcard in any node, all nodes to the right of the first wildcard must also be wildcards.

Type: Array of [ImageVersion](#) objects

[nextToken](#)

The next token used for paginated responses. When this field isn't empty, there are additional elements that the service hasn't included in this request. Use this token with the next request to retrieve additional objects.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

[requestId](#)

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidPaginationTokenException

You have provided an invalid pagination token in your request.

HTTP Status Code: 400

InvalidRequestException

You have requested an action that that the service doesn't support.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListImageScanFindingAggregations

Returns a list of image scan aggregations for your account. You can filter by the type of key that Image Builder uses to group results. For example, if you want to get a list of findings by severity level for one of your pipelines, you might specify your pipeline with the `imagePipelineArn` filter. If you don't specify a filter, Image Builder returns an aggregation for your account.

To streamline results, you can use the following filters in your request:

- `accountId`
- `imageBuildVersionArn`
- `imagePipelineArn`
- `vulnerabilityId`

Request Syntax

```
POST /ListImageScanFindingAggregations HTTP/1.1
Content-type: application/json
```

```
{
  "filter": {
    "name": "string",
    "values": [ "string" ]
  },
  "nextToken": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

filter

A filter name and value pair that is used to return a more specific list of results from a list operation. Filters can be used to match a set of resources by specific criteria, such as tags, attributes, or IDs.

Type: [Filter](#) object

Required: No

nextToken

A token to specify where to start paginating. Use the `nextToken` value from a previously truncated response.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "aggregationType": "string",
  "nextToken": "string",
  "requestId": "string",
  "responses": [
    {
      "accountAggregation": {
        "accountId": "string",
        "severityCounts": {
          "all": number,
          "critical": number,
          "high": number,
          "medium": number
        }
      },
      "imageAggregation": {
        "imageBuildVersionArn": "string",
```

```

        "severityCounts": {
            "all": number,
            "critical": number,
            "high": number,
            "medium": number
        }
    },
    "imagePipelineAggregation": {
        "imagePipelineArn": "string",
        "severityCounts": {
            "all": number,
            "critical": number,
            "high": number,
            "medium": number
        }
    },
    "vulnerabilityIdAggregation": {
        "severityCounts": {
            "all": number,
            "critical": number,
            "high": number,
            "medium": number
        },
        "vulnerabilityId": "string"
    }
}
]
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

aggregationType

The aggregation type specifies what type of key is used to group the image scan findings. Image Builder returns results based on the request filter. If you didn't specify a filter in the request, the type defaults to `accountId`.

Aggregation types

- `accountId`

- imageBuildVersionArn
- imagePipelineArn
- vulnerabilityId

Each aggregation includes counts by severity level for medium severity and higher level findings, plus a total for all of the findings for each key value.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

nextToken

The next token used for paginated responses. When this field isn't empty, there are additional elements that the service hasn't included in this request. Use this token with the next request to retrieve additional objects.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

requestId

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

responses

An array of image scan finding aggregations that match the filter criteria.

Type: Array of [ImageScanFindingAggregation](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidPaginationTokenException

You have provided an invalid pagination token in your request.

HTTP Status Code: 400

InvalidRequestException

You have requested an action that that the service doesn't support.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListImageScanFindings

Returns a list of image scan findings for your account.

Request Syntax

```
POST /ListImageScanFindings HTTP/1.1
Content-type: application/json
```

```
{
  "filters": [
    {
      "name": "string",
      "values": [ "string" ]
    }
  ],
  "maxResults": number,
  "nextToken": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

filters

An array of name value pairs that you can use to filter your results. You can use the following filters to streamline results:

- `imageBuildVersionArn`
- `imagePipelineArn`
- `vulnerabilityId`
- `severity`

If you don't request a filter, then all findings in your account are listed.

Type: Array of [ImageScanFindingsFilter](#) objects

Array Members: Fixed number of 1 item.

Required: No

[maxResults](#)

The maximum number of items to return in a single request.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 25.

Required: No

[nextToken](#)

A token to specify where to start paginating. Use the nextToken value from a previously truncated response.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "findings": [
    {
      "awsAccountId": "string",
      "description": "string",
      "firstObservedAt": number,
      "fixAvailable": "string",
      "imageBuildVersionArn": "string",
      "imagePipelineArn": "string",
      "inspectorScore": number,
      "inspectorScoreDetails": {
        "adjustedCvss": {
          "adjustments": [
            {
              "metric": "string",
```

```

        "reason": "string"
    }
],
"cvssSource": "string",
"score": number,
"scoreSource": "string",
"scoringVector": "string",
"version": "string"
}
},
"packageVulnerabilityDetails": {
    "cvss": [
        {
            "baseScore": number,
            "scoringVector": "string",
            "source": "string",
            "version": "string"
        }
    ],
    "referenceUrls": [ "string" ],
    "relatedVulnerabilities": [ "string" ],
    "source": "string",
    "sourceUrl": "string",
    "vendorCreatedAt": number,
    "vendorSeverity": "string",
    "vendorUpdatedAt": number,
    "vulnerabilityId": "string",
    "vulnerablePackages": [
        {
            "arch": "string",
            "epoch": number,
            "filePath": "string",
            "fixedInVersion": "string",
            "name": "string",
            "packageManager": "string",
            "release": "string",
            "remediation": "string",
            "sourceLayerHash": "string",
            "version": "string"
        }
    ]
},
"remediation": {
    "recommendation": {

```

```
        "text": "string",
        "url": "string"
    },
    "severity": "string",
    "title": "string",
    "type": "string",
    "updatedAt": number
}
],
"nextToken": "string",
"requestId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

findings

The image scan findings for your account that meet your request filter criteria.

Type: Array of [ImageScanFinding](#) objects

Array Members: Maximum number of 25 items.

nextToken

The next token used for paginated responses. When this field isn't empty, there are additional elements that the service hasn't included in this request. Use this token with the next request to retrieve additional objects.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

requestId

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidPaginationTokenException

You have provided an invalid pagination token in your request.

HTTP Status Code: 400

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListInfrastructureConfigurations

Returns a list of infrastructure configurations.

Request Syntax

```
POST /ListInfrastructureConfigurations HTTP/1.1
Content-type: application/json
```

```
{
  "filters": [
    {
      "name": "string",
      "values": [ "string" ]
    }
  ],
  "maxResults": number,
  "nextToken": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

filters

You can filter on name to streamline results.

Type: Array of [Filter](#) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: No

maxResults

The maximum number of items to return in a single request.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 25.

Required: No

nextToken

A token to specify where to start paginating. Use the nextToken value from a previously truncated response.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Required: No

Response Syntax

HTTP/1.1 200

Content-type: application/json

```
{
  "infrastructureConfigurationSummaryList": [
    {
      "arn": "string",
      "dateCreated": "string",
      "dateUpdated": "string",
      "description": "string",
      "instanceProfileName": "string",
      "instanceTypes": [ "string" ],
      "name": "string",
      "placement": {
        "availabilityZone": "string",
        "hostId": "string",
        "hostResourceGroupArn": "string",
        "tenancy": "string"
      },
      "resourceTags": {
        "string" : "string"
      },
      "tags": {
        "string" : "string"
      }
    }
  ]
}
```

```
] ,
  "nextToken": "string",
  "requestId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[infrastructureConfigurationSummaryList](#)

The list of infrastructure configurations.

Type: Array of [InfrastructureConfigurationSummary](#) objects

[nextToken](#)

The next token used for paginated responses. When this field isn't empty, there are additional elements that the service hasn't included in this request. Use this token with the next request to retrieve additional objects.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

[requestId](#)

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidPaginationTokenException

You have provided an invalid pagination token in your request.

HTTP Status Code: 400

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListLifecycleExecutionResources

Lists resources that the runtime instance of the image lifecycle identified for lifecycle actions.

Request Syntax

```
POST /ListLifecycleExecutionResources HTTP/1.1
Content-type: application/json
```

```
{
  "lifecycleExecutionId": "string",
  "maxResults": number,
  "nextToken": "string",
  "parentResourceId": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

lifecycleExecutionId

The unique identifier for a runtime instance of the lifecycle policy.

Type: String

Pattern: `^lce-[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}$`

Required: Yes

maxResults

The maximum number of items to return in a single request.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 25.

Required: No

nextToken

A token to specify where to start paginating. Use the `nextToken` value from a previously truncated response.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Required: No

parentResourceId

You can leave this empty to get a list of Image Builder resources that were identified for lifecycle actions.

To get a list of associated resources that are impacted for an individual resource (the parent), specify its Amazon Resource Name (ARN). Associated resources are produced from your image and distributed when you run a build, such as AMIs or container images stored in ECR repositories.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

Response Syntax

HTTP/1.1 200

Content-type: application/json

```
{
  "lifecycleExecutionId": "string",
  "lifecycleExecutionState": {
    "reason": "string",
    "status": "string"
  },
  "nextToken": "string",
  "resources": [
    {
      "accountId": "string",
```

```

    "action": {
      "name": "string",
      "reason": "string"
    },
    "endTime": number,
    "imageUri": [ "string" ],
    "region": "string",
    "resourceId": "string",
    "snapshots": [
      {
        "snapshotId": "string",
        "state": {
          "reason": "string",
          "status": "string"
        }
      }
    ],
    "startTime": number,
    "state": {
      "reason": "string",
      "status": "string"
    }
  }
]
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

lifecycleExecutionId

Runtime details for the specified runtime instance of the lifecycle policy.

Type: String

Pattern: `^lce-[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}$`

lifecycleExecutionState

The current state of the lifecycle runtime instance.

Type: [LifecycleExecutionState](#) object

[nextToken](#)

The next token used for paginated responses. When this field isn't empty, there are additional elements that the service hasn't included in this request. Use this token with the next request to retrieve additional objects.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

[resources](#)

A list of resources that were identified for lifecycle actions.

Type: Array of [LifecycleExecutionResource](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidPaginationTokenException

You have provided an invalid pagination token in your request.

HTTP Status Code: 400

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListLifecycleExecutions

Retrieves the lifecycle runtime history for the specified resource.

Request Syntax

```
POST /ListLifecycleExecutions HTTP/1.1
Content-type: application/json
```

```
{
  "maxResults": number,
  "nextToken": "string",
  "resourceArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

maxResults

The maximum number of items to return in a single request.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 25.

Required: No

nextToken

A token to specify where to start paginating. Use the nextToken value from a previously truncated response.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

lifecycleExecutions

A list of lifecycle runtime instances for the specified resource.

Type: Array of [LifecycleExecution](#) objects

nextToken

The next token used for paginated responses. When this field isn't empty, there are additional elements that the service hasn't included in this request. Use this token with the next request to retrieve additional objects.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidPaginationTokenException

You have provided an invalid pagination token in your request.

HTTP Status Code: 400

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListLifecyclePolicies

Retrieves a list of lifecycle policies in your AWS account.

Request Syntax

```
POST /ListLifecyclePolicies HTTP/1.1
Content-type: application/json

{
  "filters": [
    {
      "name": "string",
      "values": [ "string" ]
    }
  ],
  "maxResults": number,
  "nextToken": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

filters

Streamline results based on one of the following values: Name, Status.

Type: Array of [Filter](#) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: No

maxResults

The maximum number of items to return in a single request.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 25.

Required: No

nextToken

A token to specify where to start paginating. Use the nextToken value from a previously truncated response.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Required: No

Response Syntax

HTTP/1.1 200

Content-type: application/json

```
{
  "lifecyclePolicySummaryList": [
    {
      "arn": "string",
      "dateCreated": number,
      "dateLastRun": number,
      "dateUpdated": number,
      "description": "string",
      "executionRole": "string",
      "name": "string",
      "resourceType": "string",
      "status": "string",
      "tags": {
        "string" : "string"
      }
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[lifecyclePolicySummaryList](#)

A list of lifecycle policies in your AWS account that meet the criteria specified in the request.

Type: Array of [LifecyclePolicySummary](#) objects

[nextToken](#)

The next token used for paginated responses. When this field isn't empty, there are additional elements that the service hasn't included in this request. Use this token with the next request to retrieve additional objects.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidPaginationTokenException

You have provided an invalid pagination token in your request.

HTTP Status Code: 400

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

Returns the list of tags for the specified resource.

Request Syntax

```
GET /tags/resourceArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The Amazon Resource Name (ARN) of the resource whose tags you want to retrieve.

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):(?:image-recipe|container-recipe|infrastructure-configuration|distribution-configuration|component|image|image-pipeline|lifecycle-policy|workflow\/(?:build|test|distribution))\/[a-z0-9-_]+(?:\/(?:?:x|[0-9]+)\.?:x|[0-9]+)\.?:x|[0-9]+))(?:\/[0-9]+)?)?$`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "tags": {
    "string" : "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

tags

The tags for the specified resource.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z0-9\s_.: /+=\ -@]*$`

Value Length Constraints: Maximum length of 256.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

ResourceNotFoundException

At least one of the resources referenced by your request does not exist.

HTTP Status Code: 404

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListWaitingWorkflowSteps

Retrieves a list of workflow steps that are waiting for action for workflows in your AWS account.

Request Syntax

```
POST /ListWaitingWorkflowSteps HTTP/1.1
Content-type: application/json
```

```
{
  "maxResults": number,
  "nextToken": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

maxResults

The maximum number of items to return in a single request.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 25.

Required: No

nextToken

A token to specify where to start paginating. Use the `nextToken` value from a previously truncated response.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextToken": "string",
  "steps": [
    {
      "action": "string",
      "imageBuildVersionArn": "string",
      "name": "string",
      "startTime": "string",
      "stepExecutionId": "string",
      "workflowBuildVersionArn": "string",
      "workflowExecutionId": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

The next token used for paginated responses. When this field isn't empty, there are additional elements that the service hasn't included in this request. Use this token with the next request to retrieve additional objects.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

steps

An array of the workflow steps that are waiting for action in your AWS account.

Type: Array of [WorkflowStepExecution](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidPaginationTokenException

You have provided an invalid pagination token in your request.

HTTP Status Code: 400

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListWorkflowBuildVersions

Returns a list of build versions for a specific workflow resource.

Request Syntax

```
POST /ListWorkflowBuildVersions HTTP/1.1
Content-type: application/json
```

```
{
  "maxResults": number,
  "nextToken": "string",
  "workflowVersionArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

maxResults

The maximum number of items to return in a single request.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 25.

Required: No

nextToken

A token to specify where to start paginating. Use the nextToken value from a previously truncated response.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Required: No

workflowVersionArn

The Amazon Resource Name (ARN) of the workflow resource for which to get a list of build versions.

Type: String

Pattern: `^arn:aws(?:-[a-z]+)*:imagebuilder:[a-z]{2,}(?:-[a-z]+)+-[0-9]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):workflow/(build|test|distribution)/[a-z0-9-_.]+/(?:[0-9]+|x)\.(?:[0-9]+|x)\.(?:[0-9]+|x)$`

Required: No

Response Syntax

HTTP/1.1 200

Content-type: application/json

```
{
  "nextToken": "string",
  "workflowSummaryList": [
    {
      "arn": "string",
      "changeDescription": "string",
      "dateCreated": "string",
      "description": "string",
      "name": "string",
      "owner": "string",
      "state": {
        "reason": "string",
        "status": "string"
      },
      "tags": {
        "string" : "string"
      },
      "type": "string",
      "version": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[nextToken](#)

The next token used for paginated responses. When this field isn't empty, there are additional elements that the service hasn't included in this request. Use this token with the next request to retrieve additional objects.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

[workflowSummaryList](#)

A list that contains metadata for the workflow builds that have run for the workflow resource specified in the request.

Type: Array of [WorkflowSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidPaginationTokenException

You have provided an invalid pagination token in your request.

HTTP Status Code: 400

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListWorkflowExecutions

Returns a list of workflow runtime instance metadata objects for a specific image build version.

Request Syntax

```
POST /ListWorkflowExecutions HTTP/1.1
Content-type: application/json
```

```
{
  "imageBuildVersionArn": "string",
  "maxResults": number,
  "nextToken": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

imageBuildVersionArn

List all workflow runtime instances for the specified image build version resource ARN.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):image/[a-z0-9-_]+/[0-9]+\.[0-9]+\.[0-9]+/[0-9]+$`

Required: Yes

maxResults

The maximum number of items to return in a single request.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 25.

Required: No

nextToken

A token to specify where to start paginating. Use the `nextToken` value from a previously truncated response.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "imageBuildVersionArn": "string",
  "message": "string",
  "nextToken": "string",
  "requestId": "string",
  "workflowExecutions": [
    {
      "endTime": "string",
      "message": "string",
      "parallelGroup": "string",
      "retried": boolean,
      "startTime": "string",
      "status": "string",
      "totalStepCount": number,
      "totalStepsFailed": number,
      "totalStepsSkipped": number,
      "totalStepsSucceeded": number,
      "type": "string",
      "workflowBuildVersionArn": "string",
      "workflowExecutionId": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

imageBuildVersionArn

The resource Amazon Resource Name (ARN) of the image build version for which you requested a list of workflow runtime details.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):image/[a-z0-9-_]+/[0-9]+\.[0-9]+\.[0-9]+/[0-9]+$`

message

The output message from the list action, if applicable.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

nextToken

The next token used for paginated responses. When this field isn't empty, there are additional elements that the service hasn't included in this request. Use this token with the next request to retrieve additional objects.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

requestId

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

workflowExecutions

Contains an array of runtime details that represents each time a workflow ran for the requested image build version.

Type: Array of [WorkflowExecutionMetadata](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidPaginationTokenException

You have provided an invalid pagination token in your request.

HTTP Status Code: 400

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListWorkflows

Lists workflow build versions based on filtering parameters.

Request Syntax

```
POST /ListWorkflows HTTP/1.1
Content-type: application/json
```

```
{
  "byName": boolean,
  "filters": [
    {
      "name": "string",
      "values": [ "string" ]
    }
  ],
  "maxResults": number,
  "nextToken": "string",
  "owner": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

byName

Specify all or part of the workflow name to streamline results.

Type: Boolean

Required: No

filters

Used to streamline search results.

Type: Array of [Filter](#) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: No

maxResults

The maximum number of items to return in a single request.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 25.

Required: No

nextToken

A token to specify where to start paginating. Use the `nextToken` value from a previously truncated response.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Required: No

owner

Used to get a list of workflow build version filtered by the identity of the creator.

Type: String

Valid Values: Self | Shared | Amazon | ThirdParty | AWSMarketplace

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextToken": "string",
  "workflowVersionList": [
    {
```

```
    "arn": "string",
    "dateCreated": "string",
    "description": "string",
    "name": "string",
    "owner": "string",
    "type": "string",
    "version": "string"
  }
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

The next token used for paginated responses. When this field isn't empty, there are additional elements that the service hasn't included in this request. Use this token with the next request to retrieve additional objects.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

workflowVersionList

A list of workflow build versions that match the request criteria.

Type: Array of [WorkflowVersion](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidPaginationTokenException

You have provided an invalid pagination token in your request.

HTTP Status Code: 400

InvalidRequestException

You have requested an action that that the service doesn't support.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListWorkflowStepExecutions

Returns runtime data for each step in a runtime instance of the workflow that you specify in the request.

Request Syntax

```
POST /ListWorkflowStepExecutions HTTP/1.1
Content-type: application/json
```

```
{
  "maxResults": number,
  "nextToken": "string",
  "workflowExecutionId": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

maxResults

The maximum number of items to return in a single request.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 25.

Required: No

nextToken

A token to specify where to start paginating. Use the nextToken value from a previously truncated response.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Required: No

workflowExecutionId

The unique identifier that Image Builder assigned to keep track of runtime details when it ran the workflow.

Type: String

Pattern: ^wf-[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "imageBuildVersionArn": "string",
  "message": "string",
  "nextToken": "string",
  "requestId": "string",
  "steps": [
    {
      "action": "string",
      "attemptNumber": number,
      "description": "string",
      "endTime": "string",
      "inputs": "string",
      "maxAttempts": number,
      "message": "string",
      "name": "string",
      "outputs": "string",
      "rollbackStatus": "string",
      "startTime": "string",
      "status": "string",
      "stepExecutionId": "string"
    }
  ],
  "workflowBuildVersionArn": "string",
  "workflowExecutionId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

imageBuildVersionArn

The image build version resource Amazon Resource Name (ARN) that's associated with the specified runtime instance of the workflow.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):image/[a-z0-9-_]+/[0-9]+\.[0-9]+\.[0-9]+/[0-9]+$`

message

The output message from the list action, if applicable.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

nextToken

The next token used for paginated responses. When this field isn't empty, there are additional elements that the service hasn't included in this request. Use this token with the next request to retrieve additional objects.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

requestId

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

steps

Contains an array of runtime details that represents each step in this runtime instance of the workflow.

Type: Array of [WorkflowStepMetadata](#) objects

[workflowBuildVersionArn](#)

The build version Amazon Resource Name (ARN) for the Image Builder workflow resource that defines the steps for this runtime instance of the workflow.

Type: String

Length Constraints: Maximum length of 1024.

Pattern: `^arn:aws(?:-[a-z]+)*:imagebuilder:[a-z]{2,}(?:-[a-z]+)-[0-9]+(?:-[0-9]{12}|aws(?:-[a-z]+)?):workflow/(build|test|distribution)/[a-z0-9-_/]+/[0-9]+\.[0-9]+\.[0-9]+/[0-9]+$`

[workflowExecutionId](#)

The unique identifier that Image Builder assigned to keep track of runtime details when it ran the workflow.

Type: String

Pattern: `^wf-[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}$`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidPaginationTokenException

You have provided an invalid pagination token in your request.

HTTP Status Code: 400

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

PutComponentPolicy

Applies a policy to a component. To share resources, call the RAM API [CreateResourceShare](#). If you call this API, you must also call the RAM API [PromoteResourceShareCreatedFromPolicy](#) so that the resource is visible to all principals with whom the resource is shared.

Request Syntax

```
PUT /PutComponentPolicy HTTP/1.1
Content-type: application/json

{
  "componentArn": "string",
  "policy": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[componentArn](#)

The Amazon Resource Name (ARN) of the component that this policy should be applied to.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):component/[a-z0-9-_/][0-9]+\.[0-9]+\.[0-9]+/[0-9]+$`

Required: Yes

[policy](#)

The policy to apply.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 30000.

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "componentArn": "string",
  "requestId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[componentArn](#)

The Amazon Resource Name (ARN) of the component that this policy was applied to.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):component/[a-z0-9-_/][0-9]+\.[0-9]+\.[0-9]+/[0-9]+$`

[requestId](#)

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidParameterValueException

The value that you provided for the specified parameter is invalid.

HTTP Status Code: 400

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ResourceNotFoundException

At least one of the resources referenced by your request does not exist.

HTTP Status Code: 404

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

PutContainerRecipePolicy

Applies a policy to a container image. To share resources, call the RAM API [CreateResourceShare](#). If you call this API, you must also call the RAM API [PromoteResourceShareCreatedFromPolicy](#) so that the resource is visible to all principals with whom the resource is shared.

Request Syntax

```
PUT /PutContainerRecipePolicy HTTP/1.1
Content-type: application/json

{
  "containerRecipeArn": "string",
  "policy": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[containerRecipeArn](#)

The Amazon Resource Name (ARN) of the container recipe that this policy should be applied to.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):container-recipe/[a-z0-9-_]+/(?:[0-9]+|x)\.(?:[0-9]+|x)\.(?:[0-9]+|x)$`

Required: Yes

[policy](#)

The policy to apply to the container recipe.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 30000.

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "containerRecipeArn": "string",
  "requestId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[containerRecipeArn](#)

The Amazon Resource Name (ARN) of the container recipe that this policy was applied to.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):container-recipe/[a-z0-9-_/]+/(?:[0-9]+|x)\.(?:[0-9]+|x)\.(?:[0-9]+|x)$`

[requestId](#)

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidParameterValueException

The value that you provided for the specified parameter is invalid.

HTTP Status Code: 400

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ResourceNotFoundException

At least one of the resources referenced by your request does not exist.

HTTP Status Code: 404

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

PutImagePolicy

Applies a policy to an image. To share resources, call the RAM API [CreateResourceShare](#). If you call this API, you must also call the RAM API [PromoteResourceShareCreatedFromPolicy](#) so that the resource is visible to all principals with whom the resource is shared.

Request Syntax

```
PUT /PutImagePolicy HTTP/1.1
Content-type: application/json

{
  "imageArn": "string",
  "policy": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[imageArn](#)

The Amazon Resource Name (ARN) of the image that this policy should be applied to.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?)?:image/[a-z0-9-_]+/[0-9]+\.[0-9]+\.[0-9]+/[0-9]+$`

Required: Yes

[policy](#)

The policy to apply.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 30000.

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "imageArn": "string",
  "requestId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[imageArn](#)

The Amazon Resource Name (ARN) of the image that this policy was applied to.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):image/[a-z0-9-_]+/[0-9]+\.[0-9]+\.[0-9]+/[0-9]+$`

[requestId](#)

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidParameterValueException

The value that you provided for the specified parameter is invalid.

HTTP Status Code: 400

InvalidRequestException

You have requested an action that that the service doesn't support.

HTTP Status Code: 400

ResourceNotFoundException

At least one of the resources referenced by your request does not exist.

HTTP Status Code: 404

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

PutImageRecipePolicy

Applies a policy to an image recipe. To share resources, call the RAM API [CreateResourceShare](#). If you call this API, you must also call the RAM API [PromoteResourceShareCreatedFromPolicy](#) so that the resource is visible to all principals with whom the resource is shared.

Request Syntax

```
PUT /PutImageRecipePolicy HTTP/1.1
Content-type: application/json

{
  "imageRecipeArn": "string",
  "policy": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[imageRecipeArn](#)

The Amazon Resource Name (ARN) of the image recipe that this policy should be applied to.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):image-recipe/[a-z0-9-_.+/(?:[0-9]+|x)\.(?:[0-9]+|x)\.(?:[0-9]+|x)$`

Required: Yes

[policy](#)

The policy to apply.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 30000.

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "imageRecipeArn": "string",
  "requestId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[imageRecipeArn](#)

The Amazon Resource Name (ARN) of the image recipe that this policy was applied to.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):image-recipe/[a-z0-9-_.]+/(?:[0-9]+|x)\.(?:[0-9]+|x)\.(?:[0-9]+|x)$`

[requestId](#)

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

InvalidParameterValueException

The value that you provided for the specified parameter is invalid.

HTTP Status Code: 400

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ResourceNotFoundException

At least one of the resources referenced by your request does not exist.

HTTP Status Code: 404

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

RetryImage

Retries an image distribution or test without rebuilding the image.

Request Syntax

```
PUT /RetryImage HTTP/1.1
Content-type: application/json

{
  "clientToken": "string",
  "imageBuildVersionArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[clientToken](#)

A unique, case-sensitive identifier you provide to ensure that the operation completes no more than one time. If this token matches a previous request, the service ignores the request, but does not return an error. For more information, see [Ensuring idempotency](#) in the *Amazon EC2 API Reference*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

[imageBuildVersionArn](#)

The source image Amazon Resource Name (ARN) to retry.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):image/[a-z0-9-_]+/[0-9]+\.[0-9]+\.[0-9]+/[0-9]+$`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "clientToken": "string",
  "imageBuildVersionArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[clientToken](#)

The client token that uniquely identifies the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

[imageBuildVersionArn](#)

The ARN of the image to be retried.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):image/[a-z0-9-_]+/[0-9]+\.[0-9]+\.[0-9]+/[0-9]+$`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

IdempotentParameterMismatchException

You have specified a client token for an operation using parameter values that differ from a previous request that used the same client token.

HTTP Status Code: 400

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ResourceInUseException

The resource that you are trying to operate on is currently in use. Review the message details and retry later.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

SendWorkflowStepAction

Pauses or resumes image creation when the associated workflow runs a `WaitForAction` step.

Request Syntax

```
PUT /SendWorkflowStepAction HTTP/1.1
Content-type: application/json
```

```
{
  "action": "string",
  "clientToken": "string",
  "imageBuildVersionArn": "string",
  "reason": "string",
  "stepExecutionId": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

action

The action to perform on the paused workflow step. The workflow step must be in a waiting state to accept an action. The request fails if the step has already timed out or been actioned.

Type: String

Valid Values: RESUME | STOP

Required: Yes

clientToken

A unique, case-sensitive identifier you provide to ensure that the operation completes no more than one time. If this token matches a previous request, the service ignores the request, but does not return an error. For more information, see [Ensuring idempotency](#) in the *Amazon EC2 API Reference*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

imageBuildVersionArn

The Amazon Resource Name (ARN) of the image build version associated with the workflow step execution. This value must match the image that owns the waiting step. If the ARN does not correspond to the image running the workflow, then the request fails with a validation error.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):image/[a-z0-9-_]+/[0-9]+\.[0-9]+\.[0-9]+/[0-9]+$`

Required: Yes

reason

The reason for the action. This value is stored with the step execution record and is accessible in subsequent workflow steps via step output references.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

stepExecutionId

Uniquely identifies the workflow step that sent the step action.

Type: String

Pattern: `^step-[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}$`

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json

{
  "clientToken": "string",
  "imageBuildVersionArn": "string",
  "stepExecutionId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[clientToken](#)

The client token that uniquely identifies the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

[imageBuildVersionArn](#)

The Amazon Resource Name (ARN) of the image build version that received the action request.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):image/[a-z0-9-_]+/[0-9]+\.[0-9]+\.[0-9]+/[0-9]+$`

[stepExecutionId](#)

The workflow step that sent the step action.

Type: String

Pattern: `^step-[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}$`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

IdempotentParameterMismatchException

You have specified a client token for an operation using parameter values that differ from a previous request that used the same client token.

HTTP Status Code: 400

InvalidParameterValueException

The value that you provided for the specified parameter is invalid.

HTTP Status Code: 400

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ResourceInUseException

The resource that you are trying to operate on is currently in use. Review the message details and retry later.

HTTP Status Code: 400

ResourceNotFoundException

At least one of the resources referenced by your request does not exist.

HTTP Status Code: 404

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

StartImagePipelineExecution

Manually triggers a pipeline to create an image.

Request Syntax

```
PUT /StartImagePipelineExecution HTTP/1.1
Content-type: application/json

{
  "clientToken": "string",
  "imagePipelineArn": "string",
  "tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

clientToken

A unique, case-sensitive identifier you provide to ensure that the operation completes no more than one time. If this token matches a previous request, the service ignores the request, but does not return an error. For more information, see [Ensuring idempotency](#) in the *Amazon EC2 API Reference*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

imagePipelineArn

The Amazon Resource Name (ARN) of the image pipeline that you want to manually invoke.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):image-pipeline/[a-z0-9-_]+$`

Required: Yes

tags

The tags for Image Builder to apply to the image resource that's created when pipeline execution starts.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z0-9\s_./=+\-@]*$`

Value Length Constraints: Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "clientToken": "string",
  "imageBuildVersionArn": "string",
  "requestId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

clientToken

The client token that uniquely identifies the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

[imageBuildVersionArn](#)

The Amazon Resource Name (ARN) of the image that the request created.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):image/[a-z0-9-_]+/[0-9]+\.[0-9]+\.[0-9]+/[0-9]+$`

[requestId](#)

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

IdempotentParameterMismatchException

You have specified a client token for an operation using parameter values that differ from a previous request that used the same client token.

HTTP Status Code: 400

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ResourceInUseException

The resource that you are trying to operate on is currently in use. Review the message details and retry later.

HTTP Status Code: 400

ResourceNotFoundException

At least one of the resources referenced by your request does not exist.

HTTP Status Code: 404

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

StartResourceStateUpdate

Begins an asynchronous resource state update for lifecycle changes to the specified image resources.

Request Syntax

```
PUT /StartResourceStateUpdate HTTP/1.1
```

```
Content-type: application/json
```

```
{
  "clientToken": "string",
  "exclusionRules": {
    "amis": {
      "isPublic": boolean,
      "lastLaunched": {
        "unit": "string",
        "value": number
      },
      "regions": [ "string" ],
      "sharedAccounts": [ "string" ],
      "tagMap": {
        "string" : "string"
      }
    },
    "executionRole": "string",
    "includeResources": {
      "amis": boolean,
      "containers": boolean,
      "snapshots": boolean
    },
    "resourceArn": "string",
    "state": {
      "status": "string"
    },
    "updateAt": number
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

clientToken

A unique, case-sensitive identifier you provide to ensure that the operation completes no more than one time. If this token matches a previous request, the service ignores the request, but does not return an error. For more information, see [Ensuring idempotency](#) in the *Amazon EC2 API Reference*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

exclusionRules

Skip action on the image resource and associated resources if specified exclusion rules are met.

Type: [ResourceStateUpdateExclusionRules](#) object

Required: No

executionRole

The name or Amazon Resource Name (ARN) of the IAM role that's used to update image state.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^(?:arn:aws(?:-[a-z]+)*:iam:[0-9]{12}:role/)?[a-zA-Z_0-9+=,.\@\\-_/]+$`

Required: No

includeResources

Specifies which image resources to include in the state update. When specified, the lifecycle action applies to underlying resources. These resources include AMIs, snapshots, and containers in addition to the Image Builder image resource. Requires `executionRole` to also be specified. To delete an image and its underlying resources, you must specify `includeResources`. To

delete only the Image Builder image record without affecting underlying resources, use the `DeleteImage` API instead.

Type: [ResourceStateUpdateIncludeResources](#) object

Required: No

[resourceArn](#)

The Amazon Resource Name (ARN) of the image build version to update. The image must be in one of these terminal states: AVAILABLE, DEPRECATED, DISABLED, FAILED, or CANCELLED. Images with FAILED or CANCELLED status can transition only to DELETED.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):image/[a-z0-9-_]+/[0-9]+\.[0-9]+\.[0-9]+/[0-9]+$`

Required: Yes

[state](#)

Specifies the lifecycle action to take for this request. For AMI-based images, valid values are AVAILABLE, DEPRECATED, DISABLED, and DELETED. For container-based images, only DELETED is supported.

Type: [ResourceState](#) object

Required: Yes

[updateAt](#)

Specifies the timestamp when the state transition takes effect. Use this parameter only when the target status is DEPRECATED. The value must be a future time.

Type: Timestamp

Required: No

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json

{
  "lifecycleExecutionId": "string",
  "resourceArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[lifecycleExecutionId](#)

Identifies the lifecycle runtime instance that started the resource state update.

Type: String

Pattern: `^lce-[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}$`

[resourceArn](#)

The requested Amazon Resource Name (ARN) of the Image Builder resource for the asynchronous update.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):image/[a-z0-9-_/]+/[0-9]+\.[0-9]+\.[0-9]+/[0-9]+$`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

IdempotentParameterMismatchException

You have specified a client token for an operation using parameter values that differ from a previous request that used the same client token.

HTTP Status Code: 400

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ResourceInUseException

The resource that you are trying to operate on is currently in use. Review the message details and retry later.

HTTP Status Code: 400

ResourceNotFoundException

At least one of the resources referenced by your request does not exist.

HTTP Status Code: 404

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

TagResource

Adds a tag to a resource.

Request Syntax

```
POST /tags/resourceArn HTTP/1.1
Content-type: application/json
```

```
{
  "tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The Amazon Resource Name (ARN) of the resource that you want to tag.

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):(?:image-recipe|container-recipe|infrastructure-configuration|distribution-configuration|component|image|image-pipeline|lifecycle-policy|workflow\/(?:build|test|distribution))/[a-z0-9-_.]+(?:\/(?:?:x|[0-9]+)\.?:x|[0-9]+)\.?:x|[0-9]+))(?:\/[0-9]+)?)?$`

Required: Yes

Request Body

The request accepts the following data in JSON format.

tags

The tags to apply to the resource.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z0-9\s_.: /+=\ -@]*$`

Value Length Constraints: Maximum length of 256.

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

ResourceNotFoundException

At least one of the resources referenced by your request does not exist.

HTTP Status Code: 404

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

UntagResource

Removes a tag from a resource.

Request Syntax

```
DELETE /tags/resourceArn?tagKeys=tagKeys HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[resourceArn](#)

The Amazon Resource Name (ARN) of the resource that you want to untag.

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):(?:image-recipe|container-recipe|infrastructure-configuration|distribution-configuration|component|image|image-pipeline|lifecycle-policy|workflow\/(?:build|test|distribution))/[a-z0-9-_]+(?:/(?:x|[0-9]+)\.(?:x|[0-9]+)\.(?:x|[0-9]+))(?:/[0-9]+)?`\$

Required: Yes

[tagKeys](#)

The tag keys to remove from the resource.

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^(?!aws:)[a-zA-Z0-9\s_.:/+=\-\@]*`\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

ResourceNotFoundException

At least one of the resources referenced by your request does not exist.

HTTP Status Code: 404

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

UpdateDistributionConfiguration

Updates a distribution configuration. Distribution configurations define and configure the outputs of your pipeline.

Request Syntax

PUT /UpdateDistributionConfiguration HTTP/1.1

Content-type: application/json

```
{
  "clientToken": "string",
  "description": "string",
  "distributionConfigurationArn": "string",
  "distributions": [
    {
      "amiDistributionConfiguration": {
        "amiTags": {
          "string": "string"
        },
        "description": "string",
        "kmsKeyId": "string",
        "launchPermission": {
          "organizationalUnitArns": [ "string" ],
          "organizationArns": [ "string" ],
          "userGroups": [ "string" ],
          "userIds": [ "string" ]
        },
        "name": "string",
        "targetAccountIds": [ "string" ]
      },
      "containerDistributionConfiguration": {
        "containerTags": [ "string" ],
        "description": "string",
        "targetRepository": {
          "repositoryName": "string",
          "service": "string"
        }
      },
      "fastLaunchConfigurations": [
        {
          "accountId": "string",
          "enabled": boolean,
```

```

        "launchTemplate": {
            "launchTemplateId": "string",
            "launchTemplateName": "string",
            "launchTemplateVersion": "string"
        },
        "maxParallelLaunches": number,
        "snapshotConfiguration": {
            "targetResourceCount": number
        }
    },
    "launchTemplateConfigurations": [
        {
            "accountId": "string",
            "launchTemplateId": "string",
            "setDefaultVersion": boolean
        }
    ],
    "licenseConfigurationArns": [ "string" ],
    "region": "string",
    "s3ExportConfiguration": {
        "diskImageFormat": "string",
        "roleName": "string",
        "s3Bucket": "string",
        "s3Prefix": "string"
    },
    "ssmParameterConfigurations": [
        {
            "amiAccountId": "string",
            "dataType": "string",
            "parameterName": "string"
        }
    ]
}
]
}

```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

clientToken

A unique, case-sensitive identifier you provide to ensure that the operation completes no more than one time. If this token matches a previous request, the service ignores the request, but does not return an error. For more information, see [Ensuring idempotency](#) in the *Amazon EC2 API Reference*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

description

The description of the distribution configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

distributionConfigurationArn

The Amazon Resource Name (ARN) of the distribution configuration that you want to update.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):distribution-configuration/[a-z0-9-_]+$`

Required: Yes

distributions

The distributions of the distribution configuration.

Type: Array of [Distribution](#) objects

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "clientToken": "string",
  "distributionConfigurationArn": "string",
  "requestId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[clientToken](#)

The client token that uniquely identifies the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

[distributionConfigurationArn](#)

The Amazon Resource Name (ARN) of the distribution configuration that was updated by this request.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):distribution-configuration/[a-z0-9-_]+$`

[requestId](#)

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

IdempotentParameterMismatchException

You have specified a client token for an operation using parameter values that differ from a previous request that used the same client token.

HTTP Status Code: 400

InvalidParameterCombinationException

You have specified two or more mutually exclusive parameters. Review the error message for details.

HTTP Status Code: 400

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ResourceInUseException

The resource that you are trying to operate on is currently in use. Review the message details and retry later.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

UpdateImagePipeline

Updates an image pipeline. Use image pipelines to automate the creation and distribution of images. You must specify exactly one recipe for your image, using either a `containerRecipeArn` or an `imageRecipeArn`.

Note

UpdateImagePipeline does not support selective updates for the pipeline. You must specify all of the required properties in the update request, not just the properties that have changed.

Request Syntax

```
PUT /UpdateImagePipeline HTTP/1.1
```

```
Content-type: application/json
```

```
{
  "clientToken": "string",
  "containerRecipeArn": "string",
  "description": "string",
  "distributionConfigurationArn": "string",
  "enhancedImageMetadataEnabled": boolean,
  "executionRole": "string",
  "imagePipelineArn": "string",
  "imageRecipeArn": "string",
  "imageScanningConfiguration": {
    "ecrConfiguration": {
      "containerTags": [ "string" ],
      "repositoryName": "string"
    },
    "imageScanningEnabled": boolean
  },
  "imageTags": {
    "string" : "string"
  },
  "imageTestsConfiguration": {
    "imageTestsEnabled": boolean,
    "timeoutMinutes": number
  },
}
```

```
{
  "infrastructureConfigurationArn": "string",
  "loggingConfiguration": {
    "imageLogGroupName": "string",
    "pipelineLogGroupName": "string"
  },
  "schedule": {
    "autoDisablePolicy": {
      "failureCount": number
    },
    "pipelineExecutionStartCondition": "string",
    "scheduleExpression": "string",
    "timezone": "string"
  },
  "status": "string",
  "workflows": [
    {
      "onFailure": "string",
      "parallelGroup": "string",
      "parameters": [
        {
          "name": "string",
          "value": [ "string" ]
        }
      ],
      "workflowArn": "string"
    }
  ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

clientToken

A unique, case-sensitive identifier you provide to ensure that the operation completes no more than one time. If this token matches a previous request, the service ignores the request, but does not return an error. For more information, see [Ensuring idempotency](#) in the *Amazon EC2 API Reference*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

containerRecipeArn

The Amazon Resource Name (ARN) of the container pipeline to update.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):container-recipe/[a-z0-9-_]+/(?:[0-9]+|x)\.(?:[0-9]+|x)\.(?:[0-9]+|x)$`

Required: No

description

The description of the image pipeline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

distributionConfigurationArn

The Amazon Resource Name (ARN) of the distribution configuration that Image Builder uses to configure and distribute images that this image pipeline has updated.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):distribution-configuration/[a-z0-9-_]+$`

Required: No

enhancedImageMetadataEnabled

Specifies whether to collect additional information about the image being created, including the operating system (OS) version and package list. Defaults to true.

Type: Boolean

Required: No

executionRole

The name or Amazon Resource Name (ARN) for the IAM role you create that grants Image Builder access to perform workflow actions.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^(?:arn:aws(?:-[a-z]+)*:iam:[0-9]{12}:role/)?[a-zA-Z0-9+=,.\@\_/_/]+$`

Required: No

imagePipelineArn

The Amazon Resource Name (ARN) of the image pipeline that you want to update.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):image-pipeline/[a-z0-9-_\+]$`

Required: Yes

imageRecipeArn

The Amazon Resource Name (ARN) of the image recipe that configures images updated by this image pipeline.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):image-recipe/[a-z0-9-_\+]/(?:[0-9]+\|x)\.(?:[0-9]+\|x)\.(?:[0-9]+\|x)$`

Required: No

imageScanningConfiguration

Contains settings for vulnerability scans.

Type: [ImageScanningConfiguration](#) object

Required: No

imageTags

The tags to be applied to the images produced by this pipeline.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z0-9\s_.:/+=\-\@]*$`

Value Length Constraints: Maximum length of 256.

Required: No

imageTestsConfiguration

The image test configuration of the image pipeline.

Type: [ImageTestsConfiguration](#) object

Required: No

infrastructureConfigurationArn

The Amazon Resource Name (ARN) of the infrastructure configuration that Image Builder uses to build images that this image pipeline has updated.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):infrastructure-configuration/[a-z0-9-_]+$`

Required: Yes

loggingConfiguration

Update logging configuration for the output image that's created when the pipeline runs.

Type: [PipelineLoggingConfiguration](#) object

Required: No

schedule

The schedule of the image pipeline.

Type: [Schedule](#) object

Required: No

[status](#)

The status of the image pipeline.

Type: String

Valid Values: DISABLED | ENABLED

Required: No

[workflows](#)

Contains the workflows to run for the pipeline.

Type: Array of [WorkflowConfiguration](#) objects

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "clientToken": "string",
  "imagePipelineArn": "string",
  "requestId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[clientToken](#)

The client token that uniquely identifies the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

imagePipelineArn

The Amazon Resource Name (ARN) of the image pipeline that was updated by this request.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):image-pipeline/[a-z0-9-_$]+`

requestId

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

IdempotentParameterMismatchException

You have specified a client token for an operation using parameter values that differ from a previous request that used the same client token.

HTTP Status Code: 400

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ResourceInUseException

The resource that you are trying to operate on is currently in use. Review the message details and retry later.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

UpdateInfrastructureConfiguration

Updates an infrastructure configuration. An infrastructure configuration defines the environment in which Image Builder builds and tests your image.

Request Syntax

PUT /UpdateInfrastructureConfiguration HTTP/1.1

Content-type: application/json

```
{
  "clientToken": "string",
  "description": "string",
  "infrastructureConfigurationArn": "string",
  "instanceMetadataOptions": {
    "httpPutResponseHopLimit": number,
    "httpTokens": "string"
  },
  "instanceProfileName": "string",
  "instanceTypes": [ "string" ],
  "keyPair": "string",
  "logging": {
    "s3Logs": {
      "s3BucketName": "string",
      "s3KeyPrefix": "string"
    }
  },
  "placement": {
    "availabilityZone": "string",
    "hostId": "string",
    "hostResourceGroupArn": "string",
    "tenancy": "string"
  },
  "resourceTags": {
    "string" : "string"
  },
  "securityGroupIds": [ "string" ],
  "snsTopicArn": "string",
  "subnetId": "string",
  "terminateInstanceOnFailure": boolean
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

clientToken

A unique, case-sensitive identifier you provide to ensure that the operation completes no more than one time. If this token matches a previous request, the service ignores the request, but does not return an error. For more information, see [Ensuring idempotency](#) in the *Amazon EC2 API Reference*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

description

The description of the infrastructure configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

infrastructureConfigurationArn

The Amazon Resource Name (ARN) of the infrastructure configuration that you want to update.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):infrastructure-configuration/[a-z0-9-_$]+`

Required: Yes

instanceMetadataOptions

The instance metadata options that you can set for the HTTP requests that pipeline builds use to launch EC2 build and test instances. For more information about instance metadata options, see one of the following links:

- [Configure the instance metadata options](#) in the [Amazon EC2 User Guide](#) for Linux instances.
- [Configure the instance metadata options](#) in the [Amazon EC2 Windows Guide](#) for Windows instances.

Type: [InstanceMetadataOptions](#) object

Required: No

instanceProfileName

The instance profile to associate with the instance used to customize your Amazon EC2 AMI.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^[\\w+=, .@- ]+$`

Required: Yes

instanceTypes

The instance types of the infrastructure configuration. You can specify one or more instance types to use for this build. Image Builder picks one of these instance types based on availability.

Type: Array of strings

Required: No

keyPair

The key pair of the infrastructure configuration. You can use this to log on to and debug the instance used to create your image.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

logging

The logging configuration of the infrastructure configuration.

Type: [Logging](#) object

Required: No

placement

The instance placement settings that define where the instances that are launched from your image run.

Type: [Placement](#) object

Required: No

resourceTags

The tags attached to the resource created by Image Builder.

Type: String to string map

Map Entries: Maximum number of 30 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z0-9\s_.:/+=\-\@]*$`

Value Length Constraints: Maximum length of 256.

Required: No

securityGroupIds

The security group IDs to associate with the instance used to customize your Amazon EC2 AMI.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

snsTopicArn

The Amazon Resource Name (ARN) of the SNS topic to which Image Builder sends image build event notifications.

Note

EC2 Image Builder is unable to send notifications to SNS topics that are encrypted using keys from other accounts. The key that is used to encrypt the SNS topic must reside in the account that the Image Builder service runs under.

Type: String

Pattern: `^arn:aws[^:]*:sns:[^:]+:[0-9]{12}:[-a-zA-Z0-9-]{1,256}$`

Required: No

subnetId

The subnet ID to place the instance used to customize your Amazon EC2 AMI in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

terminateInstanceOnFailure

Specifies whether to terminate the instance on failure. Set to false if you want Image Builder to retain the instance used to configure your AMI if the build or test phase of your workflow fails. Defaults to true.

Type: Boolean

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "clientToken": "string",
  "infrastructureConfigurationArn": "string",
```

```
"requestId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

clientToken

The client token that uniquely identifies the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

infrastructureConfigurationArn

The Amazon Resource Name (ARN) of the infrastructure configuration that was updated by this request.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):infrastructure-configuration/[a-z0-9-_]+$`

requestId

The request ID that uniquely identifies this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

IdempotentParameterMismatchException

You have specified a client token for an operation using parameter values that differ from a previous request that used the same client token.

HTTP Status Code: 400

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ResourceInUseException

The resource that you are trying to operate on is currently in use. Review the message details and retry later.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

UpdateLifecyclePolicy

Updates the specified lifecycle policy.

Request Syntax

```
PUT /UpdateLifecyclePolicy HTTP/1.1
```

```
Content-type: application/json
```

```
{
  "clientToken": "string",
  "description": "string",
  "executionRole": "string",
  "lifecyclePolicyArn": "string",
  "policyDetails": [
    {
      "action": {
        "includeResources": {
          "amis": boolean,
          "containers": boolean,
          "snapshots": boolean
        },
        "type": "string"
      },
      "exclusionRules": {
        "amis": {
          "isPublic": boolean,
          "lastLaunched": {
            "unit": "string",
            "value": number
          },
          "regions": [ "string" ],
          "sharedAccounts": [ "string" ],
          "tagMap": {
            "string" : "string"
          }
        },
        "tagMap": {
          "string" : "string"
        }
      },
      "filter": {
        "retainAtLeast": number,
```

```
        "type": "string",
        "unit": "string",
        "value": number
    }
}
],
"resourceSelection": {
    "recipes": [
        {
            "name": "string",
            "semanticVersion": "string"
        }
    ],
    "tagMap": {
        "string" : "string"
    }
},
"resourceType": "string",
"status": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

clientToken

A unique, case-sensitive identifier you provide to ensure that the operation completes no more than one time. If this token matches a previous request, the service ignores the request, but does not return an error. For more information, see [Ensuring idempotency](#) in the *Amazon EC2 API Reference*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

description

Optional description for the lifecycle policy.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

executionRole

The name or Amazon Resource Name (ARN) of the IAM role that Image Builder uses to update the lifecycle policy.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^(?:arn:aws(?:-[a-z]+)*:iam:[0-9]{12}:role/)?[a-zA-Z0-9+=,.\@\_/_]+`

Required: Yes

lifecyclePolicyArn

The Amazon Resource Name (ARN) of the lifecycle policy resource.

Type: String

Length Constraints: Maximum length of 1024.

Pattern: `^arn:aws(?:-[a-z]+)*:imagebuilder:[a-z]{2,}(?:-[a-z]+)+-[0-9]+(?::[0-9]{12}|aws):lifecycle-policy/[a-z0-9-_\]+`

Required: Yes

policyDetails

The configuration details for a lifecycle policy resource.

Type: Array of [LifecyclePolicyDetail](#) objects

Array Members: Minimum number of 1 item. Maximum number of 3 items.

Required: Yes

resourceSelection

Selection criteria for resources that the lifecycle policy applies to.

Type: [LifecyclePolicyResourceSelection](#) object

Required: Yes

resourceType

The type of image resource that the lifecycle policy applies to.

Type: String

Valid Values: AMI_IMAGE | CONTAINER_IMAGE

Required: Yes

status

Indicates whether the lifecycle policy resource is enabled.

Type: String

Valid Values: DISABLED | ENABLED

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "lifecyclePolicyArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

lifecyclePolicyArn

The Amazon Resource Name (ARN) of the image lifecycle policy resource that was updated.

Type: String

Length Constraints: Maximum length of 1024.

Pattern: `^arn:aws(?:-[a-z]+)*:imagebuilder:[a-z]{2,}(?:-[a-z]+)+-[0-9]+:(?:[0-9]{12}|aws):lifecycle-policy/[a-z0-9-_]+$`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

CallRateLimitExceededException

You have exceeded the permitted request rate for the specific operation.

HTTP Status Code: 429

ClientException

These errors are usually caused by a client action, such as using an action or resource on behalf of a user that doesn't have permissions to use the action or resource, or specifying an invalid resource identifier.

HTTP Status Code: 400

ForbiddenException

You are not authorized to perform the requested operation.

HTTP Status Code: 403

IdempotentParameterMismatchException

You have specified a client token for an operation using parameter values that differ from a previous request that used the same client token.

HTTP Status Code: 400

InvalidParameterCombinationException

You have specified two or more mutually exclusive parameters. Review the error message for details.

HTTP Status Code: 400

InvalidRequestException

You have requested an action that the service doesn't support.

HTTP Status Code: 400

ResourceInUseException

The resource that you are trying to operate on is currently in use. Review the message details and retry later.

HTTP Status Code: 400

ServiceException

This exception is thrown when the service encounters an unrecoverable exception.

HTTP Status Code: 500

ServiceUnavailableException

The service is unable to process your request at this time.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

Data Types

The EC2 Image Builder API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AccountAggregation](#)
- [AdditionalInstanceConfiguration](#)
- [Ami](#)
- [AmiDistributionConfiguration](#)
- [AutoDisablePolicy](#)
- [Component](#)
- [ComponentConfiguration](#)
- [ComponentFailureContext](#)
- [ComponentParameter](#)
- [ComponentParameterDetail](#)
- [ComponentState](#)
- [ComponentSummary](#)
- [ComponentVersion](#)
- [Container](#)
- [ContainerDistributionConfiguration](#)
- [ContainerRecipe](#)
- [ContainerRecipeSummary](#)
- [CvssScore](#)
- [CvssScoreAdjustment](#)
- [CvssScoreDetails](#)

- [Distribution](#)
- [DistributionConfiguration](#)
- [DistributionConfigurationSummary](#)
- [DistributionFailureContext](#)
- [EbsInstanceBlockDeviceSpecification](#)
- [EcrConfiguration](#)
- [FastLaunchConfiguration](#)
- [FastLaunchLaunchTemplateSpecification](#)
- [FastLaunchSnapshotConfiguration](#)
- [Filter](#)
- [Image](#)
- [ImageAggregation](#)
- [ImageFailureContext](#)
- [ImageLoggingConfiguration](#)
- [ImagePackage](#)
- [ImagePipeline](#)
- [ImagePipelineAggregation](#)
- [ImageRecipe](#)
- [ImageRecipeSummary](#)
- [ImageScanFinding](#)
- [ImageScanFindingAggregation](#)
- [ImageScanFindingsFilter](#)
- [ImageScanningConfiguration](#)
- [ImageScanState](#)
- [ImageState](#)
- [ImageSummary](#)
- [ImageTestsConfiguration](#)
- [ImageVersion](#)
- [InfrastructureConfiguration](#)
- [InfrastructureConfigurationSummary](#)

- [InspectorScoreDetails](#)
- [InstanceBlockDeviceMapping](#)
- [InstanceConfiguration](#)
- [InstanceMetadataOptions](#)
- [LatestVersionReferences](#)
- [LaunchPermissionConfiguration](#)
- [LaunchTemplateConfiguration](#)
- [LifecycleExecution](#)
- [LifecycleExecutionResource](#)
- [LifecycleExecutionResourceAction](#)
- [LifecycleExecutionResourcesImpactedSummary](#)
- [LifecycleExecutionResourceState](#)
- [LifecycleExecutionSnapshotResource](#)
- [LifecycleExecutionState](#)
- [LifecyclePolicy](#)
- [LifecyclePolicyDetail](#)
- [LifecyclePolicyDetailAction](#)
- [LifecyclePolicyDetailActionIncludeResources](#)
- [LifecyclePolicyDetailExclusionRules](#)
- [LifecyclePolicyDetailExclusionRulesAmis](#)
- [LifecyclePolicyDetailExclusionRulesAmisLastLaunched](#)
- [LifecyclePolicyDetailFilter](#)
- [LifecyclePolicyResourceSelection](#)
- [LifecyclePolicyResourceSelectionRecipe](#)
- [LifecyclePolicySummary](#)
- [Logging](#)
- [OutputResources](#)
- [PackageVulnerabilityDetails](#)
- [PipelineLoggingConfiguration](#)
- [Placement](#)

- [ProductCodeListItem](#)
- [RegionFailure](#)
- [RegisterImageOptions](#)
- [Remediation](#)
- [RemediationRecommendation](#)
- [ResourceState](#)
- [ResourceStateUpdateExclusionRules](#)
- [ResourceStateUpdateIncludeResources](#)
- [S3ExportConfiguration](#)
- [S3Logs](#)
- [Schedule](#)
- [SeverityCounts](#)
- [SsmParameterConfiguration](#)
- [SystemsManagerAgent](#)
- [TargetContainerRepository](#)
- [VulnerabilityIdAggregation](#)
- [VulnerablePackage](#)
- [WindowsConfiguration](#)
- [Workflow](#)
- [WorkflowConfiguration](#)
- [WorkflowExecutionMetadata](#)
- [WorkflowParameter](#)
- [WorkflowParameterDetail](#)
- [WorkflowState](#)
- [WorkflowStepExecution](#)
- [WorkflowStepMetadata](#)
- [WorkflowSummary](#)
- [WorkflowVersion](#)

AccountAggregation

Contains counts of vulnerability findings from image scans that run when you create new Image Builder images, or build new versions of existing images. The vulnerability counts are grouped by severity level. The counts are aggregated across resources to create the final tally for the account that owns them.

Contents

accountId

Identifies the account that owns the aggregated resource findings.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

severityCounts

Counts by severity level for medium severity and higher level findings, plus a total for all of the findings.

Type: [SeverityCounts](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AdditionalInstanceConfiguration

In addition to your infrastructure configuration, these settings provide an extra layer of control over your build instances. You can also specify commands to run on launch for all of your build instances.

Image Builder does not automatically install the Systems Manager agent on Windows instances. If your base image includes the Systems Manager agent, then the AMI that you create will also include the agent. For Linux instances, if the base image does not already include the Systems Manager agent, Image Builder installs it. For Linux instances where Image Builder installs the Systems Manager agent, you can choose whether to keep it for the AMI that you create.

Contents

systemsManagerAgent

Contains settings for the Systems Manager agent on your build instance.

Type: [SystemsManagerAgent](#) object

Required: No

userDataOverride

Use this property to provide commands or a command script to run when you launch your build instance.

The `userDataOverride` property replaces any commands that Image Builder might have added to ensure that Systems Manager is installed on your Linux build instance. If you override the user data, make sure that you add commands to install Systems Manager, if it is not pre-installed on your base image.

Note

The user data is always base 64 encoded. For example, the following commands are encoded as `IyEvYm1uL2Jhc2gKbWtkaXIgLXAgL3Zhci9iYi8KdG91Y2ggL3Zhci$:`
`#!/bin/bash`
`mkdir -p /var/bb/`
`touch /var`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 21847.

Pattern: `^(?:[A-Za-z0-9+/]{4})*(?:[A-Za-z0-9+/]{2}==|[A-Za-z0-9+/]{3}=)?$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Ami

Details of an Amazon EC2 AMI.

Contents

accountId

The account ID of the owner of the AMI.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

description

The description of the Amazon EC2 AMI. Minimum and maximum length are in characters.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

image

The AMI ID of the Amazon EC2 AMI.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

name

The name of the Amazon EC2 AMI.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

region

The AWS Region of the Amazon EC2 AMI.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

state

Image status and the reason for that status.

Type: [ImageState](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AmiDistributionConfiguration

Define and configure the output AMIs of the pipeline.

Contents

amiTags

The tags to apply to AMIs distributed to this Region.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z0-9\s_.:/=+\-@]*$`

Value Length Constraints: Maximum length of 256.

Required: No

description

The description of the AMI distribution configuration. Minimum and maximum length are in characters.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

kmsKeyId

The Amazon Resource Name (ARN) that uniquely identifies the KMS key used to encrypt the distributed image. This can be either the Key ARN or the Alias ARN. For more information, see [Key identifiers \(KeyId\)](#) in the *AWS Key Management Service Developer Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

launchPermission

Launch permissions can be used to configure which AWS accounts can use the AMI to launch instances.

Type: [LaunchPermissionConfiguration](#) object

Required: No

name

The name of the output AMI.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 127.

Pattern: `^[-_A-Za-z0-9]{1}[-_A-Za-z0-9\s:{}.]+\[-_A-Za-z0-9\]$`

Required: No

targetAccountIds

The ID of an account to which you want to distribute an image.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 1536 items.

Pattern: `^[0-9]{12}$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AutoDisablePolicy

Defines the rules by which an image pipeline is automatically disabled when it fails.

Contents

failureCount

The number of consecutive scheduled image pipeline executions that must fail before Image Builder automatically disables the pipeline.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 10.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Component

A detailed view of a component.

Contents

arn

The Amazon Resource Name (ARN) of the component.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):(?:image-recipe|container-recipe|infrastructure-configuration|distribution-configuration|component|image|image-pipeline|lifecycle-policy|workflow\/(?:build|test|distribution))\/[a-z0-9-_\+](?:\/(?:?:x|[0-9]+\)\.?:x|[0-9]+\)\.?:x|[0-9]+\))(?:\/[0-9]+\)?)?$`

Required: No

changeDescription

Describes what change has been made in this version of the component, or what makes this version different from other versions of the component.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

data

Component data contains the YAML document content for the component.

Type: String

Required: No

dateCreated

The date that Image Builder created the component.

Type: String

Required: No

description

The description of the component.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

encrypted

The encryption status of the component.

Type: Boolean

Required: No

kmsKeyId

The KMS key identifier used to encrypt the component. This can be either the Key ARN or the Alias ARN. For more information, see [Key identifiers \(KeyId\)](#) in the *AWS Key Management Service Developer Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

name

The name of the component.

Type: String

Pattern: `^[-_A-Za-z-0-9][-_A-Za-z0-9 ]{1,126}[-_A-Za-z-0-9]$`

Required: No

obfuscate

Indicates whether component source is hidden from view in the console, and from component detail results for API, CLI, or SDK operations.

Type: Boolean

Required: No

owner

The owner of the component.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

parameters

Contains parameter details for each of the parameters that the component document defined for the component.

Type: Array of [ComponentParameterDetail](#) objects

Required: No

platform

The operating system platform of the component.

Type: String

Valid Values: Windows | Linux | macOS

Required: No

productCodes

Contains product codes that are used for billing purposes for AWS Marketplace components.

Type: Array of [ProductCodeListItem](#) objects

Required: No

publisher

Contains the name of the publisher if this is a third-party component. Otherwise, this property is empty.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

state

Describes the current status of the component.

Type: [ComponentState](#) object

Required: No

supportedOsVersions

The operating system (OS) version supported by the component. If the OS information is available, Image Builder performs a prefix match against the base image OS version during image recipe creation.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 25 items.

Length Constraints: Minimum length of 1.

Required: No

tags

The tags that apply to the component.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z0-9\s_.:/+=\-\@]*$`

Value Length Constraints: Maximum length of 256.

Required: No

type

The component type specifies whether Image Builder uses the component to build the image or only to test it.

Type: String

Valid Values: BUILD | TEST

Required: No

version

The version of the component.

Type: String

Pattern: `^[0-9]+\.[0-9]+\.[0-9]+$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ComponentConfiguration

Configuration details of the component.

Contents

componentArn

The Amazon Resource Name (ARN) of the component.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):component/[a-z0-9-_/](?:((?:[0-9]+|x)\.([0-9]+|x)\.([0-9]+|x))|([0-9]+\.[0-9]+\.[0-9]+/[0-9]+))$`

Required: Yes

parameters

A group of parameter settings that Image Builder uses to configure the component for a specific recipe.

Type: Array of [ComponentParameter](#) objects

Array Members: Minimum number of 1 item.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ComponentFailureContext

Contains details about the component that caused the image creation process to fail. The details identify the first step that failed when the component ran.

Contents

action

The action that the failed step runs, for example `ExecuteBash`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

componentArn

The Amazon Resource Name (ARN) of the component build version that failed.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):component/[a-z0-9-_/][0-9]+\.[0-9]+\.[0-9]+/[0-9]+$`

Required: No

errorMessage

The error message from the step that failed. Image Builder truncates messages that are longer than 1024 characters. The component log in Amazon CloudWatch Logs contains the full output.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 384000.

Required: No

phaseName

The name of the phase in the component document where the failure occurred, such as `build`, `validate`, or `test`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

stepName

The name of the step in the component document that failed.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ComponentParameter

Contains a key/value pair that sets the named component parameter.

Contents

name

The name of the component parameter to set.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\x00]+`

Required: Yes

value

Sets the value for the named component parameter.

Type: Array of strings

Length Constraints: Minimum length of 0.

Pattern: `[^\x00]*`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ComponentParameterDetail

Defines a parameter that is used to provide configuration details for the component.

Contents

name

The name of this input parameter.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^\x00]+`

Required: Yes

type

The type of input this parameter provides. The currently supported value is "string".

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: `^String|Integer|Boolean|stringList$`

Required: Yes

defaultValue

The default value of this parameter if no input is provided.

Type: Array of strings

Length Constraints: Minimum length of 0.

Pattern: `[^\x00]*`

Required: No

description

Describes this parameter.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `[^\x00]+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ComponentState

A group of fields that describe the current status of components.

Contents

reason

Describes how or why the component changed state.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

status

The current state of the component.

Type: String

Valid Values: DEPRECATED | DISABLED | ACTIVE

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ComponentSummary

A high-level summary of a component.

Contents

arn

The Amazon Resource Name (ARN) of the component.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):(?:image-recipe|container-recipe|infrastructure-configuration|distribution-configuration|component|image|image-pipeline|lifecycle-policy|workflow\/(?:build|test|distribution))\/[a-z0-9-_\+](?:\/(?:?:x|[0-9]+\)\.?:x|[0-9]+\)\.?:x|[0-9]+\))(?:\/[0-9]+\)?)?$`

Required: No

changeDescription

The change description for the current version of the component.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

dateCreated

The original creation date of the component.

Type: String

Required: No

description

The description of the component.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

name

The name of the component.

Type: String

Pattern: `^[_A-Za-z-0-9][_A-Za-z0-9 ]{1,126}[_A-Za-z-0-9]$`

Required: No

obfuscate

Indicates whether component source is hidden from view in the console, and from component detail results for API, CLI, or SDK operations.

Type: Boolean

Required: No

owner

The owner of the component.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

platform

The operating system platform of the component.

Type: String

Valid Values: Windows | Linux | macOS

Required: No

publisher

Contains the name of the publisher if this is a third-party component. Otherwise, this property is empty.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

state

Describes the current status of the component.

Type: [ComponentState](#) object

Required: No

supportedOsVersions

The operating system (OS) version that the component supports. If the OS information is available, Image Builder performs a prefix match against the base image OS version during image recipe creation.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 25 items.

Length Constraints: Minimum length of 1.

Required: No

tags

The tags that apply to the component.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z0-9\s_.:/+=\-\@]*$`

Value Length Constraints: Maximum length of 256.

Required: No

type

The component type specifies whether Image Builder uses the component to build the image or only to test it.

Type: String

Valid Values: BUILD | TEST

Required: No

version

The version of the component.

Type: String

Pattern: `^[0-9]+\.[0-9]+\.[0-9]+$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ComponentVersion

The defining characteristics of a specific version of an AWSTOE component.

Contents

arn

The Amazon Resource Name (ARN) of the component.

Note

Semantic versioning is included in each object's Amazon Resource Name (ARN), at the level that applies to that object as follows:

1. Versionless ARNs and Name ARNs do not include specific values in any of the nodes. The nodes are either left off entirely, or they are specified as wildcards, for example: `x.x.x`.
2. Version ARNs have only the first three nodes: `<major>.<minor>.<patch>`
3. Build version ARNs have all four nodes, and point to a specific build for a specific version of an object.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):(?:image-recipe|container-recipe|infrastructure-configuration|distribution-configuration|component|image|image-pipeline|lifecycle-policy|workflow\/(?:build|test|distribution))\/[a-z0-9-_\]+(?:\/(?:?:x|[0-9]+)\.(?:x|[0-9]+)\.(?:x|[0-9]+))(?:\/[0-9]+)?)?$`

Required: No

dateCreated

The date that the component was created.

Type: String

Required: No

description

The description of the component.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

name

The name of the component.

Type: String

Pattern: `^[_A-Za-z-0-9][_A-Za-z0-9 ]{1,126}[_A-Za-z-0-9]$`

Required: No

owner

The owner of the component.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

platform

The platform of the component.

Type: String

Valid Values: Windows | Linux | macOS

Required: No

productCodes

Contains product codes that are used for billing purposes for AWS Marketplace components.

Type: Array of [ProductCodeListItem](#) objects

Required: No

status

Describes the current status of the component version.

Type: String

Valid Values: DEPRECATED | DISABLED | ACTIVE

Required: No

supportedOsVersions

The operating system (OS) version supported by the component. If OS information is available, Image Builder performs a prefix match against the base image OS version during image recipe creation.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 25 items.

Length Constraints: Minimum length of 1.

Required: No

type

The type of the component denotes whether the component is used to build the image or only to test it.

Type: String

Valid Values: BUILD | TEST

Required: No

version

The semantic version of the component.

Note

The semantic version has four nodes: <major>.<minor>.<patch>/<build>. You can assign values for the first three, and can filter on all of them.

Assignment: For the first three nodes, you can assign any positive integer value, including zero. The upper limit is $2^{30}-1$, or 1073741823, for each node. Image Builder automatically assigns the build number to the fourth node.

Patterns: You can use any numeric pattern that adheres to the assignment requirements for the nodes that you can assign. For example, you might choose a software version pattern, such as 1.0.0, or a date, such as 2021.01.01.

Filtering: You can use wildcards (x) to specify the most recent versions or nodes when selecting the base image or components for your recipe. When you use a wildcard in any node, all nodes to the right of the first wildcard must also be wildcards.

Type: String

Pattern: `^[0-9]+\.[0-9]+\.[0-9]+$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Container

A container encapsulates the runtime environment for an application.

Contents

imageUris

A list of URIs for containers created in the context Region.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

region

Containers and container images are Region-specific. This is the Region context for the container.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ContainerDistributionConfiguration

Container distribution settings for encryption, licensing, and sharing in a specific Region.

Contents

targetRepository

The destination repository for the container distribution configuration.

Type: [TargetContainerRepository](#) object

Required: Yes

containerTags

Tags that are attached to the container distribution configuration.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

description

The description of the container distribution configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ContainerRecipe

A container recipe.

Contents

arn

The Amazon Resource Name (ARN) of the container recipe.

Note

Semantic versioning is included in each object's Amazon Resource Name (ARN), at the level that applies to that object as follows:

1. Versionless ARNs and Name ARNs do not include specific values in any of the nodes. The nodes are either left off entirely, or they are specified as wildcards, for example: x.x.x.
2. Version ARNs have only the first three nodes: <major>.<minor>.<patch>
3. Build version ARNs have all four nodes, and point to a specific build for a specific version of an object.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):(?:image-recipe|container-recipe|infrastructure-configuration|distribution-configuration|component|image|image-pipeline|lifecycle-policy|workflow\/(?:build|test|distribution))\/[a-z0-9-_]+(?:\/(?:?:x|[0-9]+)\.?:x|[0-9]+)\.?:x|[0-9]+))(?:\/[0-9]+)?)?$`

Required: No

components

Build and test components that are included in the container recipe. Recipes require a minimum of one build component, and can have a maximum of 20 build and test components in any combination.

Type: Array of [ComponentConfiguration](#) objects

Array Members: Minimum number of 1 item.

Required: No

containerType

Specifies the type of container, such as Docker.

Type: String

Valid Values: DOCKER

Required: No

dateCreated

The date when this container recipe was created.

Type: String

Required: No

description

The description of the container recipe.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

dockerfileTemplateData

Dockerfiles are text documents that are used to build Docker containers, and ensure that they contain all of the elements required by the application running inside. The template data consists of contextual variables where Image Builder places build information or scripts, based on your container image recipe.

Type: String

Required: No

encrypted

A flag that indicates if the target container is encrypted.

Type: Boolean

Required: No

instanceConfiguration

A group of options that can be used to configure an instance for building and testing container images.

Type: [InstanceConfiguration](#) object

Required: No

kmsKeyId

The Amazon Resource Name (ARN) that uniquely identifies which KMS key is used to encrypt the container image for distribution to the target Region. This can be either the Key ARN or the Alias ARN. For more information, see [Key identifiers \(KeyId\)](#) in the *AWS Key Management Service Developer Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

name

The name of the container recipe.

Type: String

Pattern: `^[_A-Za-z-0-9][_A-Za-z0-9 ]{1,126}[_A-Za-z-0-9]$`

Required: No

owner

The owner of the container recipe.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

parentImage

The base image for customizations specified in the container recipe. This can contain an Image Builder image resource ARN or a container image URI, for example `amazonlinux:latest`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

platform

The system platform for the container, such as Windows or Linux.

Type: String

Valid Values: Windows | Linux | macOS

Required: No

tags

Tags that are attached to the container recipe.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z0-9\s_.:/=+\-@]*$`

Value Length Constraints: Maximum length of 256.

Required: No

targetRepository

The destination repository for the container image.

Type: [TargetContainerRepository](#) object

Required: No

version

The semantic version of the container recipe.

Note

The semantic version has four nodes: <major>.<minor>.<patch>/<build>. You can assign values for the first three, and can filter on all of them.

Assignment: For the first three nodes, you can assign any positive integer value, including zero. The upper limit is $2^{30}-1$, or 1073741823, for each node. Image Builder automatically assigns the build number to the fourth node.

Patterns: You can use any numeric pattern that adheres to the assignment requirements for the nodes that you can assign. For example, you might choose a software version pattern, such as 1.0.0, or a date, such as 2021.01.01.

Filtering: You can use wildcards (x) to specify the most recent versions or nodes when selecting the base image or components for your recipe. When you use a wildcard in any node, all nodes to the right of the first wildcard must also be wildcards.

Type: String

Pattern: `^[0-9]+\.[0-9]+\.[0-9]+$`

Required: No

workingDirectory

The working directory for use during build and test workflows.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ContainerRecipeSummary

A summary of a container recipe

Contents

arn

The Amazon Resource Name (ARN) of the container recipe.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):(?:image-recipe|container-recipe|infrastructure-configuration|distribution-configuration|component|image|image-pipeline|lifecycle-policy|workflow\/(?:build|test|distribution))/[a-z0-9-_]+(?:/(?:(?:x|[0-9]+)\.(?:x|[0-9]+)\.(?:x|[0-9]+))?(?:/[0-9]+)?)?$`

Required: No

containerType

Specifies the type of container, such as "Docker".

Type: String

Valid Values: DOCKER

Required: No

dateCreated

The date when this container recipe was created.

Type: String

Required: No

instanceImage

The base image for a container build and test instance. This can contain an AMI ID or it can specify an AWS Systems Manager (SSM) Parameter Store Parameter, prefixed by `ssm:`, followed by the parameter name or ARN.

If not specified, Image Builder uses the appropriate ECS-optimized AMI as a base image.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

name

The name of the container recipe.

Type: String

Pattern: `^[-_A-Za-z-0-9][-_A-Za-z0-9 ]{1,126}[-_A-Za-z-0-9]$`

Required: No

owner

The owner of the container recipe.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

parentImage

The base image for the container recipe.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

platform

The system platform for the container, such as Windows or Linux.

Type: String

Valid Values: `Windows` | `Linux` | `macOS`

Required: No

tags

Tags that are attached to the container recipe.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z0-9\s_.:/=+\-@]*$`

Value Length Constraints: Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CvssScore

Amazon Inspector generates a risk score for each finding. This score helps you to prioritize findings, to focus on the most critical findings and the most vulnerable resources. The score uses the Common Vulnerability Scoring System (CVSS) format. This format is a modification of the base CVSS score that the National Vulnerability Database (NVD) provides. For more information about severity levels, see [Severity levels for Amazon Inspector findings](#) in the *Amazon Inspector User Guide*.

Contents

baseScore

The CVSS base score.

Type: Double

Valid Range: Minimum value of 0.

Required: No

scoringVector

The vector string of the CVSS score.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

source

The source of the CVSS score.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

version

The CVSS version that generated the score.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CvssScoreAdjustment

Details about an adjustment that Amazon Inspector made to the CVSS score for a finding.

Contents

metric

The metric that Amazon Inspector used to adjust the CVSS score.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

reason

The reason for the CVSS score adjustment.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CvssScoreDetails

Details about the source of the score, and the factors that determined the adjustments to create the final score.

Contents

adjustments

An object that contains details about an adjustment that Amazon Inspector made to the CVSS score for the finding.

Type: Array of [CvssScoreAdjustment](#) objects

Required: No

cvssSource

The source of the finding.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

score

The CVSS score.

Type: Double

Valid Range: Minimum value of 0.

Required: No

scoreSource

The source for the CVSS score.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

scoringVector

A vector that measures the severity of the vulnerability.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

version

The CVSS version that generated the score.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Distribution

Defines the settings for a specific Region.

Contents

region

The target Region.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: Yes

amiDistributionConfiguration

The specific AMI settings; for example, launch permissions or AMI tags.

Type: [AmiDistributionConfiguration](#) object

Required: No

containerDistributionConfiguration

Container distribution settings for encryption, licensing, and sharing in a specific Region.

Type: [ContainerDistributionConfiguration](#) object

Required: No

fastLaunchConfigurations

The Windows faster-launching configurations to use for AMI distribution.

Type: Array of [FastLaunchConfiguration](#) objects

Array Members: Minimum number of 1 item. Maximum number of 1000 items.

Required: No

launchTemplateConfigurations

A group of launchTemplateConfiguration settings that apply to image distribution for specified accounts.

Type: Array of [LaunchTemplateConfiguration](#) objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: No

licenseConfigurationArns

The License Manager Configuration to associate with the AMI in the specified Region.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Pattern: `^arn:aws[^:]*:license-manager:[^:]+:[0-9]{12}:license-configuration:lic-[a-z0-9-_{32}]$`

Required: No

s3ExportConfiguration

Configure export settings to deliver disk images created from your image build, using a file format that is compatible with your VMs in that Region.

Type: [S3ExportConfiguration](#) object

Required: No

ssmParameterConfigurations

Contains settings to update AWS Systems Manager (SSM) Parameter Store Parameters with output AMI IDs from the build by target Region.

Type: Array of [SsmParameterConfiguration](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

DistributionConfiguration

A distribution configuration.

Contents

timeoutMinutes

The maximum duration in minutes for this distribution configuration.

Type: Integer

Valid Range: Minimum value of 30. Maximum value of 720.

Required: Yes

arn

The Amazon Resource Name (ARN) of the distribution configuration.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):(?:image-recipe|container-recipe|infrastructure-configuration|distribution-configuration|component|image|image-pipeline|lifecycle-policy|workflow\/(?:build|test|distribution))\/[a-z0-9-_\]+(?:\/(?:?:x|[0-9]+)\.?:x|[0-9]+)\.?:x|[0-9]+))(?:\/[0-9]+)?)?$`

Required: No

dateCreated

The date on which this distribution configuration was created.

Type: String

Required: No

dateUpdated

The date on which this distribution configuration was last updated.

Type: String

Required: No

description

The description of the distribution configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

distributions

The distribution objects that apply Region-specific settings for the deployment of the image to targeted Regions.

Type: Array of [Distribution](#) objects

Required: No

name

The name of the distribution configuration.

Type: String

Pattern: `^[_A-Za-z-0-9][_A-Za-z0-9 ]{1,126}[_A-Za-z-0-9]$`

Required: No

tags

The tags of the distribution configuration.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z0-9\s_.:/=+\-@]*$`

Value Length Constraints: Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DistributionConfigurationSummary

A high-level overview of a distribution configuration.

Contents

arn

The Amazon Resource Name (ARN) of the distribution configuration.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):(?:image-recipe|container-recipe|infrastructure-configuration|distribution-configuration|component|image|image-pipeline|lifecycle-policy|workflow\/(?:build|test|distribution))\/[a-z0-9-_\]+(?:\/(?:?:x|[0-9]+)\.?:x|[0-9]+)\.?:x|[0-9]+))(?:\/[0-9]+)?)?$`

Required: No

dateCreated

The date on which the distribution configuration was created.

Type: String

Required: No

dateUpdated

The date on which the distribution configuration was updated.

Type: String

Required: No

description

The description of the distribution configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

name

The name of the distribution configuration.

Type: String

Pattern: `^[_A-Za-z-0-9][_A-Za-z0-9 ]{1,126}[_A-Za-z-0-9]$`

Required: No

regions

A list of Regions where the container image is distributed to.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

tags

The tags associated with the distribution configuration.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z0-9\s_./=+\-@]*$`

Value Length Constraints: Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DistributionFailureContext

Contains details about a failure that occurred while Image Builder distributed the image or applied configuration to the distributed image.

Contents

errorMessage

The error message for the distribution failure.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 384000.

Required: No

regionFailures

The details about the failure for each Region where the image didn't finish distribution or configuration.

Type: Array of [RegionFailure](#) objects

Array Members: Minimum number of 1 item. Maximum number of 256 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EbsInstanceBlockDeviceSpecification

Amazon EBS-specific block device mapping specifications.

Contents

deleteOnTermination

Specifies whether to delete the associated device on termination.

Type: Boolean

Required: No

encrypted

Specifies whether to encrypt the device.

Type: Boolean

Required: No

iops

The IOPS value for the device. Required only when volumeType is io1 or io2.

Type: Integer

Valid Range: Minimum value of 100. Maximum value of 64000.

Required: No

kmsKeyId

The Amazon Resource Name (ARN) that uniquely identifies the KMS key to use when encrypting the device. This can be either the Key ARN or the Alias ARN. For more information, see [Key identifiers \(KeyId\)](#) in the *AWS Key Management Service Developer Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

snapshotId

The snapshot that defines the device contents.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

throughput

For GP3 volumes only – The throughput in MiB/s that the volume supports.

Type: Integer

Valid Range: Minimum value of 125. Maximum value of 1000.

Required: No

volumeSize

Overrides the volume size for the device.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 16000.

Required: No

volumeType

Overrides the volume type for the device.

Type: String

Valid Values: `standard` | `io1` | `io2` | `gp2` | `gp3` | `sc1` | `st1`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EcrConfiguration

Settings that Image Builder uses to configure the ECR repository and the output container images that Amazon Inspector scans.

Contents

containerTags

Tags for Image Builder to apply to the output container image that Amazon Inspector scans. Tags can help you identify and manage your scanned images.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

repositoryName

The name of the container repository that Amazon Inspector scans to identify findings for your container images. The name includes the path for the repository location. If you don't provide this information, Image Builder creates a repository in your account named `image-builder-image-scanning-repository` for vulnerability scans of your output container images.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

FastLaunchConfiguration

Define and configure faster launching for output Windows AMIs.

Contents

enabled

A Boolean that represents the current state of faster launching for the Windows AMI. Set to `true` to start using Windows faster launching, or `false` to stop using it.

Type: Boolean

Required: Yes

accountId

The owner account ID for the fast-launch enabled Windows AMI.

Type: String

Pattern: `^[0-9]{12}$`

Required: No

launchTemplate

The launch template that the fast-launch enabled Windows AMI uses when it launches Windows instances to create pre-provisioned snapshots.

Type: [FastLaunchLaunchTemplateSpecification](#) object

Required: No

maxParallelLaunches

The maximum number of parallel instances that are launched for creating resources.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

snapshotConfiguration

Configuration settings for managing the number of snapshots that are created from pre-provisioned instances for the Windows AMI when faster launching is enabled.

Type: [FastLaunchSnapshotConfiguration](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

FastLaunchLaunchTemplateSpecification

Identifies the launch template that the associated Windows AMI uses for launching an instance when faster launching is enabled.

Note

You can specify either the `launchTemplateName` or the `launchTemplateId`, but not both.

Contents

launchTemplateId

The ID of the launch template to use for faster launching for a Windows AMI.

Type: String

Pattern: `^lt-[a-z0-9-_{17}]$`

Required: No

launchTemplateName

The name of the launch template to use for faster launching for a Windows AMI.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

launchTemplateVersion

The version of the launch template to use for faster launching for a Windows AMI.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

FastLaunchSnapshotConfiguration

Configuration settings for creating and managing pre-provisioned snapshots for a fast-launch enabled Windows AMI.

Contents

targetResourceCount

The number of pre-provisioned snapshots to keep on hand for a fast-launch enabled Windows AMI.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 10000.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Filter

A filter name and value pair that is used to return a more specific list of results from a list operation. Filters can be used to match a set of resources by specific criteria, such as tags, attributes, or IDs.

Contents

name

The name of the filter. Filter names are case-sensitive.

Type: String

Pattern: `^[a-zA-Z]{1,1024}$`

Required: No

values

The filter values. Filter values are case-sensitive.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Pattern: `^[0-9a-zA-Z._/ _:,{ }"-]{1,1024}$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Image

An Image Builder image resource that keeps track of all of the settings used to create, configure, and distribute output for that image. You must specify exactly one recipe for the image – either a container recipe (`containerRecipe`), which creates a container image, or an image recipe (`imageRecipe`), which creates an AMI.

Contents

arn

The Amazon Resource Name (ARN) of the image.

Note

Semantic versioning is included in each object's Amazon Resource Name (ARN), at the level that applies to that object as follows:

1. Versionless ARNs and Name ARNs do not include specific values in any of the nodes. The nodes are either left off entirely, or they are specified as wildcards, for example: `x.x.x`.
2. Version ARNs have only the first three nodes: `<major>.<minor>.<patch>`
3. Build version ARNs have all four nodes, and point to a specific build for a specific version of an object.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):(?:image-recipe|container-recipe|infrastructure-configuration|distribution-configuration|component|image|image-pipeline|lifecycle-policy|workflow\/(?:build|test|distribution))\/[a-z0-9-_\]+(?:\/(?:?:x|[0-9]+)\.?:x|[0-9]+)\.?:x|[0-9]+))(?:\/[0-9]+)?)?$`

Required: No

buildType

Indicates the type of build that created this image. The build can be initiated in the following ways:

- **USER_INITIATED** – A manual pipeline build request.
- **SCHEDULED** – A pipeline build initiated by a cron expression in the Image Builder pipeline, or from EventBridge.
- **IMPORT** – A VM import created the image to use as the base image for the recipe.
- **IMPORT_ISO** – An ISO disk import created the image.

Type: String

Valid Values: USER_INITIATED | SCHEDULED | IMPORT | IMPORT_ISO

Required: No

containerRecipe

For container images, this is the container recipe that Image Builder used to create the image. For images that distribute an AMI, this is empty.

Type: [ContainerRecipe](#) object

Required: No

dateCreated

The date on which Image Builder created this image.

Type: String

Required: No

deprecationTime

The time when deprecation occurs for an image resource. This can be a past or future date.

Type: Timestamp

Required: No

distributionConfiguration

The distribution configuration that Image Builder used to create this image.

Type: [DistributionConfiguration](#) object

Required: No

enhancedImageMetadataEnabled

Indicates whether Image Builder collects additional information about the image, such as the operating system (OS) version and package list.

Type: Boolean

Required: No

executionRole

The name or Amazon Resource Name (ARN) for the IAM role you create that grants Image Builder access to perform workflow actions.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^(?:arn:aws(?:-[a-z]+)*:iam:[0-9]{12}:role/)?[a-zA-Z0-9+=,.\@\_/-]+`

Required: No

imageRecipe

For images that distribute an AMI, this is the image recipe that Image Builder used to create the image. For container images, this is empty.

Type: [ImageRecipe](#) object

Required: No

imageScanningConfiguration

Contains settings for vulnerability scans.

Type: [ImageScanningConfiguration](#) object

Required: No

imageSource

The origin of the base image that Image Builder used to build this image.

Type: String

Valid Values: AMAZON_MANAGED | AWS_MARKETPLACE | IMPORTED | CUSTOM

Required: No

imageTestsConfiguration

The image tests that ran when that Image Builder created this image.

Type: [ImageTestsConfiguration](#) object

Required: No

infrastructureConfiguration

The infrastructure that Image Builder used to create this image.

Type: [InfrastructureConfiguration](#) object

Required: No

lifecycleExecutionId

Identifies the last runtime instance of the lifecycle policy to take action on the image.

Type: String

Pattern: `^lce-[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}$`

Required: No

loggingConfiguration

The logging configuration that's defined for the image. Image Builder uses the defined settings to direct execution log output during image creation.

Type: [ImageLoggingConfiguration](#) object

Required: No

name

The name of the image.

Type: String

Pattern: `^[-_A-Za-z-0-9][-_A-Za-z0-9 ]{1,126}[-_A-Za-z-0-9]$`

Required: No

osVersion

The operating system version for instances that launch from this image. For example, Amazon Linux 2, Ubuntu 18, or Microsoft Windows Server 2019.

Type: String

Length Constraints: Minimum length of 1.

Required: No

outputResources

The output resources that Image Builder produces for this image.

Type: [OutputResources](#) object

Required: No

platform

The image operating system platform, such as Linux or Windows.

Type: String

Valid Values: Windows | Linux | macOS

Required: No

scanState

Contains information about the current state of scans for this image.

Type: [ImageScanState](#) object

Required: No

sourcePipelineArn

The Amazon Resource Name (ARN) of the image pipeline that created this image.

Type: String

Required: No

sourcePipelineName

The name of the image pipeline that created this image.

Type: String

Pattern: `^[-_A-Za-z-0-9][-_A-Za-z0-9 ]{1,126}[-_A-Za-z-0-9]$`

Required: No

state

The state of the image.

Type: [ImageState](#) object

Required: No

tags

The tags that apply to this image.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z0-9\s_.:/+=\-\@]*$`

Value Length Constraints: Maximum length of 256.

Required: No

type

Specifies whether this image produces an AMI or a container image.

Type: String

Valid Values: AMI | DOCKER

Required: No

version

The semantic version of the image.

Note

The semantic version has four nodes: <major>.<minor>.<patch>/<build>. You can assign values for the first three, and can filter on all of them.

Assignment: For the first three nodes, you can assign any positive integer value, including zero. The upper limit is $2^{30}-1$, or 1073741823, for each node. Image Builder automatically assigns the build number to the fourth node.

Patterns: You can use any numeric pattern that adheres to the assignment requirements for the nodes that you can assign. For example, you might choose a software version pattern, such as 1.0.0, or a date, such as 2021.01.01.

Filtering: You can use wildcards (x) to specify the most recent versions or nodes when selecting the base image or components for your recipe. When you use a wildcard in any node, all nodes to the right of the first wildcard must also be wildcards.

Type: String

Pattern: `^[0-9]+\.[0-9]+\.[0-9]+$`

Required: No

workflows

Contains the build and test workflows that are associated with the image.

Type: Array of [WorkflowConfiguration](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImageAggregation

Contains vulnerability counts for a specific image.

Contents

imageBuildVersionArn

The Amazon Resource Name (ARN) that identifies the image for this aggregation.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):image/[a-z0-9-_]+/[0-9]+\.[0-9]+\.[0-9]+/[0-9]+$`

Required: No

severityCounts

Counts by severity level for medium severity and higher level findings, plus a total for all of the findings for the specified image.

Type: [SeverityCounts](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImageFailureContext

Contains details about the failure when the image creation process fails. Properties appear in the failure context when the related information is available for the failure.

Contents

componentFailure

The details about the component that failed, if the failure occurred while a component was running.

Type: [ComponentFailureContext](#) object

Required: No

distributionFailure

The details about the distribution failure, if the failure occurred while Image Builder distributed or configured the image.

Type: [DistributionFailureContext](#) object

Required: No

failedStep

The name of the workflow step that failed, as it appears in the workflow document.

Type: String

Pattern: `^[A-Za-z][A-Za-z0-9-_{1,99}]$`

Required: No

imageStatus

The status that the image had when the failure occurred. This indicates the stage of the image creation process where the image failed, for example BUILDING or DISTRIBUTING.

Type: String

Valid Values: PENDING | CREATING | BUILDING | TESTING | DISTRIBUTING | INTEGRATING | AVAILABLE | CANCELLED | FAILED | DEPRECATED | DELETED | DISABLED

Required: No

stepExecutionId

The unique identifier of the workflow step execution that failed.

Type: String

Pattern: `^step-[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}$`

Required: No

workflowArn

The Amazon Resource Name (ARN) of the workflow build version that was running when the image failed.

Type: String

Length Constraints: Maximum length of 1024.

Pattern: `^arn:aws(?:-[a-z]+)*:imagebuilder:[a-z]{2,}(?:-[a-z]+)+-[0-9]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):workflow/(build|test|distribution)/[a-z0-9-_.]+/[0-9]+\.[0-9]+\.[0-9]+/[0-9]+$`

Required: No

workflowExecutionId

The unique identifier of the workflow execution that was running when the image failed.

Type: String

Pattern: `^wf-[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImageLoggingConfiguration

The logging configuration that's defined for the image. Image Builder uses the defined settings to direct execution log output during image creation.

Contents

logGroupName

The log group name that Image Builder uses for image creation. If not specified, the log group name defaults to `/aws/imagebuilder/image-name`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `^[a-zA-Z0-9\-\_\./]{1,512}$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImagePackage

A software package that's installed on top of the base image to create a customized image.

Contents

packageName

The name of the package that's reported to the operating system package manager.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

packageVersion

The version of the package that's reported to the operating system package manager.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImagePipeline

Details of an image pipeline.

Contents

arn

The Amazon Resource Name (ARN) of the image pipeline.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):(?:image-recipe|container-recipe|infrastructure-configuration|distribution-configuration|component|image|image-pipeline|lifecycle-policy|workflow\/(?:build|test|distribution))\/[a-z0-9-_\]+(?:\/(?:?:x|[0-9]+)\.?:x|[0-9]+)\.?:x|[0-9]+))(?:\/[0-9]+)?)?$`

Required: No

consecutiveFailures

Image Builder tracks the number of consecutive failures for scheduled pipeline executions and takes one of the following actions each time it runs on a schedule:

- If the pipeline execution is successful, the number of consecutive failures resets to zero.
- If the pipeline execution fails, Image Builder increments the number of consecutive failures. If the failure count exceeds the limit defined in the `AutoDisablePolicy`, Image Builder disables the pipeline.

The consecutive failure count is also reset to zero under the following conditions:

- The pipeline runs manually and succeeds.
- The pipeline configuration is updated.

If the pipeline runs manually and fails, the count remains the same. The next scheduled run continues to increment where it left off before.

Type: Integer

Valid Range: Minimum value of 0.

Required: No

containerRecipeArn

The Amazon Resource Name (ARN) of the container recipe that is used for this pipeline.

Type: String

Required: No

dateCreated

The date on which this image pipeline was created.

Type: String

Required: No

dateLastRun

This is no longer supported, and does not return a value.

Type: String

Required: No

dateNextRun

The next date when the pipeline is scheduled to run.

Type: String

Required: No

dateUpdated

The date on which this image pipeline was last updated.

Type: String

Required: No

description

The description of the image pipeline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

distributionConfigurationArn

The Amazon Resource Name (ARN) of the distribution configuration associated with this image pipeline.

Type: String

Required: No

enhancedImageMetadataEnabled

Specifies whether to collect additional information about the image being created, including the operating system (OS) version and package list. Defaults to `true`.

Type: Boolean

Required: No

executionRole

The name or Amazon Resource Name (ARN) for the IAM role you create that grants Image Builder access to perform workflow actions.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^(?:arn:aws(?:-[a-z]+)*:iam:[0-9]{12}:role/)?[a-zA-Z0-9+=,.\@\_/-]+$`

Required: No

imageRecipeArn

The Amazon Resource Name (ARN) of the image recipe associated with this image pipeline.

Type: String

Required: No

imageScanningConfiguration

Contains settings for vulnerability scans.

Type: [ImageScanningConfiguration](#) object

Required: No

imageTags

The tags to be applied to the images produced by this pipeline.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z0-9\s_.:/=\-@]*$`

Value Length Constraints: Maximum length of 256.

Required: No

imageTestsConfiguration

The image tests configuration of the image pipeline.

Type: [ImageTestsConfiguration](#) object

Required: No

infrastructureConfigurationArn

The Amazon Resource Name (ARN) of the infrastructure configuration associated with this image pipeline.

Type: String

Required: No

lastRunStatus

The status of the last image that this pipeline built, such as BUILDING, TESTING, FAILED, or AVAILABLE.

Type: String

Valid Values: PENDING | CREATING | BUILDING | TESTING | DISTRIBUTING | INTEGRATING | AVAILABLE | CANCELLED | FAILED | DEPRECATED | DELETED | DISABLED

Required: No

loggingConfiguration

Defines logging configuration for the output image.

Type: [PipelineLoggingConfiguration](#) object

Required: No

name

The name of the image pipeline.

Type: String

Pattern: `^[-_A-Za-z-0-9][-_A-Za-z0-9 ]{1,126}[-_A-Za-z-0-9]$`

Required: No

platform

The platform of the image pipeline.

Type: String

Valid Values: Windows | Linux | macOS

Required: No

schedule

The schedule of the image pipeline.

Type: [Schedule](#) object

Required: No

status

The status of the image pipeline.

Type: String

Valid Values: DISABLED | ENABLED

Required: No

tags

The tags of this image pipeline.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z0-9\s_.:/=+\-@]*$`

Value Length Constraints: Maximum length of 256.

Required: No

workflows

Contains the workflows that run for the image pipeline.

Type: Array of [WorkflowConfiguration](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImagePipelineAggregation

Contains vulnerability counts for a specific image pipeline.

Contents

imagePipelineArn

The Amazon Resource Name (ARN) that identifies the image pipeline for this aggregation.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):image-pipeline/[a-z0-9-_$]+$`

Required: No

severityCounts

Counts by severity level for medium severity and higher level findings, plus a total for all of the findings for the specified image pipeline.

Type: [SeverityCounts](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImageRecipe

An image recipe.

Contents

additionalInstanceConfiguration

Before you create a new AMI, Image Builder launches temporary Amazon EC2 instances to build and test your image configuration. Instance configuration adds a layer of control over those instances. You can define settings and add scripts to run when an instance is launched from your AMI.

Type: [AdditionalInstanceConfiguration](#) object

Required: No

amiTags

Tags that are applied to the AMI that Image Builder creates during the Build phase prior to image distribution.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z0-9\s_.:/=+\-@]*$`

Value Length Constraints: Maximum length of 256.

Required: No

amiWatermarks

The AMI watermark names attached to the output AMI from this recipe. AMI watermarks are lineage markers that automatically propagate to derivative AMIs when the source AMI is copied or distributed.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: `^[A-Za-z0-9()\\[\]./'@_-][A-Za-z0-9 ()\\[\]./'@_-]{1,126}[A-Za-z0-9()\\[\]./'@_-]$`

Required: No

arn

The Amazon Resource Name (ARN) of the image recipe.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):(?:image-recipe|container-recipe|infrastructure-configuration|distribution-configuration|component|image|image-pipeline|lifecycle-policy|workflow\/(?:build|test|distribution))\/[a-z0-9_-]+(?:\/(?:?:x|[0-9]+)\.?:x|[0-9]+)\.?:x|[0-9]+))(?:\/[0-9]+)?$`

Required: No

blockDeviceMappings

The block device mappings to apply when creating images from this recipe.

Type: Array of [InstanceBlockDeviceMapping](#) objects

Required: No

components

The components that are included in the image recipe. Recipes require a minimum of one build component, and can have a maximum of 20 build and test components in any combination.

Type: Array of [ComponentConfiguration](#) objects

Array Members: Minimum number of 1 item.

Required: No

dateCreated

The date on which this image recipe was created.

Type: String

Required: No

description

The description of the image recipe.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

name

The name of the image recipe.

Type: String

Pattern: `^[-_A-Za-z-0-9][-_A-Za-z0-9 ]{1,126}[-_A-Za-z-0-9]$`

Required: No

owner

The owner of the image recipe.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

parentImage

The base image for customizations specified in the image recipe. You can specify the parent image using one of the following options:

- AMI ID
- Image Builder image Amazon Resource Name (ARN)
- AWS Systems Manager (SSM) Parameter Store Parameter, prefixed by `ssm:`, followed by the parameter name or ARN.
- AWS Marketplace product ID

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

platform

The platform of the image recipe.

Type: String

Valid Values: Windows | Linux | macOS

Required: No

tags

The tags of the image recipe.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z0-9\s_.: /+=\ -@]*$`

Value Length Constraints: Maximum length of 256.

Required: No

type

Specifies which type of image is created by the recipe - an AMI or a container image.

Type: String

Valid Values: AMI | DOCKER

Required: No

version

The version of the image recipe.

Type: String

Pattern: `^[0-9]+\.[0-9]+\.[0-9]+$`

Required: No

workingDirectory

The working directory to be used during build and test workflows.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImageRecipeSummary

A summary of an image recipe.

Contents

arn

The Amazon Resource Name (ARN) of the image recipe.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):(?:image-recipe|container-recipe|infrastructure-configuration|distribution-configuration|component|image|image-pipeline|lifecycle-policy|workflow\/(?:build|test|distribution))\/[a-z0-9-_]+(?:\/(?:?:x|[0-9]+)\.?:x|[0-9]+)\.?:x|[0-9]+))(?:\/[0-9]+)?)?$`

Required: No

dateCreated

The date on which this image recipe was created.

Type: String

Required: No

name

The name of the image recipe.

Type: String

Pattern: `^[-_A-Za-z-0-9][-_A-Za-z0-9 ]{1,126}[-_A-Za-z-0-9]$`

Required: No

owner

The owner of the image recipe.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

parentImage

The base image of the image recipe.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

platform

The platform of the image recipe.

Type: String

Valid Values: Windows | Linux | macOS

Required: No

tags

The tags of the image recipe.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z0-9\s_.:/=\-@]*$`

Value Length Constraints: Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImageScanFinding

Contains details about a vulnerability scan finding.

Contents

awsAccountId

The AWS account ID that's associated with the finding.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

description

The description of the finding.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

firstObservedAt

The date and time when the finding was first observed.

Type: Timestamp

Required: No

fixAvailable

Details about whether a fix is available for any of the packages that are identified in the finding through a version update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

imageBuildVersionArn

The Amazon Resource Name (ARN) of the image build version that's associated with the finding.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):image/[a-z0-9-_]+/[0-9]+\.[0-9]+\.[0-9]+/[0-9]+$`

Required: No

imagePipelineArn

The Amazon Resource Name (ARN) of the image pipeline that's associated with the finding.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws):image-pipeline/[a-z0-9-_]+$`

Required: No

inspectorScore

The score that Amazon Inspector assigned for the finding.

Type: Double

Valid Range: Minimum value of 0.

Required: No

inspectorScoreDetails

An object that contains details of the Amazon Inspector score.

Type: [InspectorScoreDetails](#) object

Required: No

packageVulnerabilityDetails

An object that contains the details of a package vulnerability finding.

Type: [PackageVulnerabilityDetails](#) object

Required: No

remediation

An object that contains the details about how to remediate the finding.

Type: [Remediation](#) object

Required: No

severity

The severity of the finding.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

title

The title of the finding.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

type

The type of the finding. Image Builder looks for findings of the type `PACKAGE_VULNERABILITY` that apply to output images, and excludes other types.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

updatedAt

The timestamp when the finding was last updated.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImageScanFindingAggregation

This returns exactly one type of aggregation, based on the filter that Image Builder applies in its API action.

Contents

accountAggregation

Returns an object that contains severity counts based on an account ID.

Type: [AccountAggregation](#) object

Required: No

imageAggregation

Returns an object that contains severity counts based on the Amazon Resource Name (ARN) for a specific image.

Type: [ImageAggregation](#) object

Required: No

imagePipelineAggregation

Returns an object that contains severity counts based on an image pipeline ARN.

Type: [ImagePipelineAggregation](#) object

Required: No

vulnerabilityIdAggregation

Returns an object that contains severity counts based on vulnerability ID.

Type: [VulnerabilityIdAggregation](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImageScanFindingsFilter

A name value pair that Image Builder applies to streamline results from the vulnerability scan findings list action.

Contents

name

The name of the image scan finding filter. Filter names are case-sensitive.

Type: String

Pattern: `^[a-zA-Z]{1,1024}$`

Required: No

values

The filter values. Filter values are case-sensitive.

Type: Array of strings

Array Members: Fixed number of 1 item.

Pattern: `^[0-9a-zA-Z._/ _ : , { } " - ]{1,1024}$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImageScanningConfiguration

Contains settings for Image Builder image resource and container image scans.

Contents

ecrConfiguration

Contains Amazon ECR settings for vulnerability scans.

Type: [EcrConfiguration](#) object

Required: No

imageScanningEnabled

A setting that indicates whether Image Builder keeps a snapshot of the vulnerability scans that Amazon Inspector runs against the build instance when you create a new image.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImageScanState

Shows the vulnerability scan status for a specific image, and the reason for that status.

Contents

reason

The reason for the scan status for the image.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

status

The current state of vulnerability scans for the image.

Type: String

Valid Values: PENDING | SCANNING | COLLECTING | COMPLETED | ABANDONED | FAILED | TIMED_OUT

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImageState

Image status and the reason for that status.

Contents

failureContext

The details about the failure, for images that failed to complete. Image Builder only sets this property when the image status is FAILED.

Type: [ImageFailureContext](#) object

Required: No

reason

The reason for the status of the image.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

status

The status of the image.

Type: String

Valid Values: PENDING | CREATING | BUILDING | TESTING | DISTRIBUTING | INTEGRATING | AVAILABLE | CANCELLED | FAILED | DEPRECATED | DELETED | DISABLED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImageSummary

An image summary.

Contents

arn

The Amazon Resource Name (ARN) of the image.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):(?:image-recipe|container-recipe|infrastructure-configuration|distribution-configuration|component|image|image-pipeline|lifecycle-policy|workflow\/(?:build|test|distribution))/[a-z0-9-_]+(?:/(?:(?:x|[0-9]+)\.(?:x|[0-9]+)\.(?:x|[0-9]+))?(?:/[0-9]+)?)?$`

Required: No

buildType

Indicates the type of build that created this image. The build can be initiated in the following ways:

- **USER_INITIATED** – A manual pipeline build request.
- **SCHEDULED** – A pipeline build initiated by a cron expression in the Image Builder pipeline, or from EventBridge.
- **IMPORT** – A VM import created the image to use as the base image for the recipe.
- **IMPORT_ISO** – An ISO disk import created the image.

Type: String

Valid Values: `USER_INITIATED` | `SCHEDULED` | `IMPORT` | `IMPORT_ISO`

Required: No

dateCreated

The date on which Image Builder created this image.

Type: String

Required: No

deprecationTime

The time when deprecation occurs for an image resource. This can be a past or future date.

Type: Timestamp

Required: No

imageSource

The origin of the base image that Image Builder used to build this image.

Type: String

Valid Values: AMAZON_MANAGED | AWS_MARKETPLACE | IMPORTED | CUSTOM

Required: No

lifecycleExecutionId

Identifies the last runtime instance of the lifecycle policy to take action on the image.

Type: String

Pattern: `^lce-[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}$`

Required: No

loggingConfiguration

The logging configuration that's defined for the image.

Type: [ImageLoggingConfiguration](#) object

Required: No

name

The name of the image.

Type: String

Pattern: `^[-_A-Za-z-0-9][_A-Za-z0-9 ]{1,126}[_A-Za-z-0-9]$`

Required: No

osVersion

The operating system version of the instances that launch from this image. For example, Amazon Linux 2, Ubuntu 18, or Microsoft Windows Server 2019.

Type: String

Length Constraints: Minimum length of 1.

Required: No

outputResources

The output resources that Image Builder produced when it created this image.

Type: [OutputResources](#) object

Required: No

owner

The owner of the image.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

platform

The image operating system platform, such as Linux or Windows.

Type: String

Valid Values: Windows | Linux | macOS

Required: No

state

The state of the image.

Type: [ImageState](#) object

Required: No

tags

The tags that apply to this image.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z0-9\s_.:/=+\-@]*$`

Value Length Constraints: Maximum length of 256.

Required: No

type

Specifies whether this image produces an AMI or a container image.

Type: String

Valid Values: AMI | DOCKER

Required: No

version

The version of the image.

Type: String

Pattern: `^[0-9]+\.[0-9]+\.[0-9]+$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImageTestsConfiguration

Configure image tests for your pipeline build. Tests run after building the image, to verify that the AMI or container image is valid before distributing it.

Contents

imageTestsEnabled

Specifies whether tests run after building the image. When enabled, tests run after the image build and before image distribution. Defaults to `true`.

Type: Boolean

Required: No

timeoutMinutes

The maximum time in minutes that tests are permitted to run.

Note

The timeout property is not currently active. This value is ignored.

Type: Integer

Valid Range: Minimum value of 60. Maximum value of 1440.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImageVersion

The defining characteristics of a specific version of an Image Builder image.

Contents

arn

The Amazon Resource Name (ARN) of a specific version of an Image Builder image.

Note

Semantic versioning is included in each object's Amazon Resource Name (ARN), at the level that applies to that object as follows:

1. Versionless ARNs and Name ARNs do not include specific values in any of the nodes. The nodes are either left off entirely, or they are specified as wildcards, for example: x.x.x.
2. Version ARNs have only the first three nodes: <major>.<minor>.<patch>
3. Build version ARNs have all four nodes, and point to a specific build for a specific version of an object.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):(?:image-recipe|container-recipe|infrastructure-configuration|distribution-configuration|component|image|image-pipeline|lifecycle-policy|workflow\/(?:build|test|distribution))\/[a-z0-9-_.]+(?:\/(?:?:x|[0-9]+)\.(?:x|[0-9]+)\.(?:x|[0-9]+))(?:\/[0-9]+)?)?$`

Required: No

buildType

Indicates the type of build that created this image. The build can be initiated in the following ways:

- **USER_INITIATED** – A manual pipeline build request.
- **SCHEDULED** – A pipeline build initiated by a cron expression in the Image Builder pipeline, or from EventBridge.

- **IMPORT** – A VM import created the image to use as the base image for the recipe.
- **IMPORT_ISO** – An ISO disk import created the image.

Type: String

Valid Values: `USER_INITIATED` | `SCHEDULED` | `IMPORT` | `IMPORT_ISO`

Required: No

dateCreated

The date on which this specific version of the Image Builder image was created.

Type: String

Required: No

imageSource

The origin of the base image that Image Builder used to build this image.

Type: String

Valid Values: `AMAZON_MANAGED` | `AWS_MARKETPLACE` | `IMPORTED` | `CUSTOM`

Required: No

name

The name of this specific version of an Image Builder image.

Type: String

Pattern: `^[-_A-Za-z-0-9][-_A-Za-z0-9 ]{1,126}[-_A-Za-z-0-9]$`

Required: No

osVersion

The operating system version of the Amazon EC2 build instance. For example, Amazon Linux 2, Ubuntu 18, or Microsoft Windows Server 2019.

Type: String

Length Constraints: Minimum length of 1.

Required: No

owner

The owner of the image version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

platform

The operating system platform of the image version, for example "Windows" or "Linux".

Type: String

Valid Values: Windows | Linux | macOS

Required: No

type

Specifies whether this image produces an AMI or a container image.

Type: String

Valid Values: AMI | DOCKER

Required: No

version

Details for a specific version of an Image Builder image. This version follows the semantic version syntax.

Note

The semantic version has four nodes: <major>.<minor>.<patch>/<build>. You can assign values for the first three, and can filter on all of them.

Assignment: For the first three nodes, you can assign any positive integer value, including zero. The upper limit is $2^{30}-1$, or 1073741823, for each node. Image Builder automatically assigns the build number to the fourth node.

Patterns: You can use any numeric pattern that adheres to the assignment requirements for the nodes that you can assign. For example, you might choose a software version pattern, such as 1.0.0, or a date, such as 2021.01.01.

Filtering: You can use wildcards (x) to specify the most recent versions or nodes when selecting the base image or components for your recipe. When you use a wildcard in any node, all nodes to the right of the first wildcard must also be wildcards.

Type: String

Pattern: `^[0-9]+\.[0-9]+\.[0-9]+$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InfrastructureConfiguration

Details of the infrastructure configuration.

Contents

arn

The Amazon Resource Name (ARN) of the infrastructure configuration.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):(?:image-recipe|container-recipe|infrastructure-configuration|distribution-configuration|component|image|image-pipeline|lifecycle-policy|workflow\/(?:build|test|distribution))\/[a-z0-9-_\]+(?:\/(?:?:x|[0-9]+)\.?:x|[0-9]+)\.?:x|[0-9]+))(?:\/[0-9]+)?)?$`

Required: No

dateCreated

The date on which the infrastructure configuration was created.

Type: String

Required: No

dateUpdated

The date on which the infrastructure configuration was last updated.

Type: String

Required: No

description

The description of the infrastructure configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

instanceMetadataOptions

The instance metadata option settings for the infrastructure configuration.

Type: [InstanceMetadataOptions](#) object

Required: No

instanceProfileName

The instance profile of the infrastructure configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^[\\w+=, .@- ]+$`

Required: No

instanceTypes

The instance types of the infrastructure configuration.

Type: Array of strings

Required: No

keyPair

The Amazon EC2 key pair of the infrastructure configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

logging

The logging configuration of the infrastructure configuration.

Type: [Logging](#) object

Required: No

name

The name of the infrastructure configuration.

Type: String

Pattern: `^[-_A-Za-z-0-9][-_A-Za-z0-9 ]{1,126}[-_A-Za-z-0-9]$`

Required: No

placement

The instance placement settings that define where the instances that are launched from your image run.

Type: [Placement](#) object

Required: No

resourceTags

The tags attached to the resource created by Image Builder.

Type: String to string map

Map Entries: Maximum number of 30 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z0-9\s_.:/+=\-\@]*$`

Value Length Constraints: Maximum length of 256.

Required: No

securityGroupIds

The security group IDs of the infrastructure configuration.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

snsTopicArn

The Amazon Resource Name (ARN) of the SNS topic to which Image Builder sends image build event notifications.

Note

EC2 Image Builder is unable to send notifications to SNS topics that are encrypted using keys from other accounts. The key that is used to encrypt the SNS topic must reside in the account that the Image Builder service runs under.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

subnetId

The subnet ID of the infrastructure configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

tags

The tags of the infrastructure configuration.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z0-9\s_.:/+=\~@]*$`

Value Length Constraints: Maximum length of 256.

Required: No

terminateInstanceOnFailure

The terminate instance on failure configuration of the infrastructure configuration.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InfrastructureConfigurationSummary

The infrastructure used when building Amazon EC2 AMIs.

Contents

arn

The Amazon Resource Name (ARN) of the infrastructure configuration.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):(?:image-recipe|container-recipe|infrastructure-configuration|distribution-configuration|component|image|image-pipeline|lifecycle-policy|workflow\/(?:build|test|distribution))\/[a-z0-9-_\]+(?:\/(?:?:x|[0-9]+)\.?:x|[0-9]+)\.?:x|[0-9]+))(?:\/[0-9]+)?)?$`

Required: No

dateCreated

The date on which the infrastructure configuration was created.

Type: String

Required: No

dateUpdated

The date on which the infrastructure configuration was last updated.

Type: String

Required: No

description

The description of the infrastructure configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

instanceProfileName

The instance profile of the infrastructure configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^[\\w+=, .@- ]+$`

Required: No

instanceTypes

The instance types of the infrastructure configuration.

Type: Array of strings

Required: No

name

The name of the infrastructure configuration.

Type: String

Pattern: `^[-_A-Za-z-0-9][-_A-Za-z0-9 ]{1,126}[-_A-Za-z-0-9]$`

Required: No

placement

The instance placement settings that define where the instances that are launched from your image run.

Type: [Placement](#) object

Required: No

resourceTags

The tags attached to the image created by Image Builder.

Type: String to string map

Map Entries: Maximum number of 30 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z0-9\s_.:/=\-@]*$`

Value Length Constraints: Maximum length of 256.

Required: No

tags

The tags of the infrastructure configuration.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z0-9\s_.:/=\-@]*$`

Value Length Constraints: Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InspectorScoreDetails

Information about the factors that influenced the score that Amazon Inspector assigned for a finding.

Contents

adjustedCvss

An object that contains details about an adjustment that Amazon Inspector made to the CVSS score for the finding.

Type: [CvssScoreDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InstanceBlockDeviceMapping

Defines block device mappings for the instance used to configure your image.

Contents

deviceName

The device to which these mappings apply.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

ebs

The Amazon EBS-specific configuration for this mapping.

Type: [EbsInstanceBlockDeviceSpecification](#) object

Required: No

noDevice

Specifies a mapping to remove from the base image.

Type: String

Length Constraints: Fixed length of 0.

Required: No

virtualName

The virtual device name for instance ephemeral devices.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InstanceConfiguration

Defines a custom base AMI and block device mapping configurations of an instance used for building and testing container images.

Contents

blockDeviceMappings

Defines the block devices to attach for building an instance from this Image Builder AMI.

Type: Array of [InstanceBlockDeviceMapping](#) objects

Required: No

image

The base image for a container build and test instance. This can contain an AMI ID or it can specify an AWS Systems Manager (SSM) Parameter Store Parameter, prefixed by `ssm:`, followed by the parameter name or ARN.

If not specified, Image Builder uses the appropriate ECS-optimized AMI as a base image.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InstanceMetadataOptions

The instance metadata options that apply to the HTTP requests that pipeline builds use to launch EC2 build and test instances. For more information about instance metadata options, see [Configure the instance metadata options](#) in the Amazon EC2 User Guide for Linux instances, or [Configure the instance metadata options](#) in the Amazon EC2 Windows Guide for Windows instances.

Contents

httpPutResponseHopLimit

Limit the number of hops that an instance metadata request can traverse to reach its destination. The default is one hop. However, if HTTP tokens are required, container image builds need a minimum of two hops.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 64.

Required: No

httpTokens

Indicates whether a signed token header is required for instance metadata retrieval requests. The values affect the response as follows:

- **required** – When you retrieve the IAM role credentials, version 2.0 credentials are returned in all cases.
- **optional** – You can include a signed token header in your request to retrieve instance metadata, or you can leave it out. If you include it, version 2.0 credentials are returned for the IAM role. Otherwise, version 1.0 credentials are returned.

The default setting is **optional**.

Type: String

Pattern: optional|required

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LatestVersionReferences

The resource ARNs with different wildcard variations of semantic versioning.

Contents

latestMajorVersionArn

The latest version Amazon Resource Name (ARN) with the same major version of the Image Builder resource.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):(?:image-recipe|container-recipe|infrastructure-configuration|distribution-configuration|component|image|image-pipeline|lifecycle-policy|workflow\/(?:build|test|distribution))\/[a-z0-9-_\]+(?:\/(?:?:x|[0-9]+)\.?:x|[0-9]+)\.?:x|[0-9]+))(?:\/[0-9]+)?)?$`

Required: No

latestMinorVersionArn

The latest version Amazon Resource Name (ARN) with the same minor version of the Image Builder resource.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):(?:image-recipe|container-recipe|infrastructure-configuration|distribution-configuration|component|image|image-pipeline|lifecycle-policy|workflow\/(?:build|test|distribution))\/[a-z0-9-_\]+(?:\/(?:?:x|[0-9]+)\.?:x|[0-9]+)\.?:x|[0-9]+))(?:\/[0-9]+)?)?$`

Required: No

latestPatchVersionArn

The latest version Amazon Resource Name (ARN) with the same patch version of the Image Builder resource.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):(?:image-recipe|container-recipe|infrastructure-configuration|distribution-configuration|component|image|image-pipeline|lifecycle-policy|workflow\/(?:build|test|distribution))/[a-z0-9-_\]+(?:\/(?:?:x|[0-9]+)\.?:x|[0-9]+)\.?:x|[0-9]+))(?:\/[0-9]+)?)?$`

Required: No

latestVersionArn

The latest version Amazon Resource Name (ARN) of the Image Builder resource.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):(?:image-recipe|container-recipe|infrastructure-configuration|distribution-configuration|component|image|image-pipeline|lifecycle-policy|workflow\/(?:build|test|distribution))/[a-z0-9-_\]+(?:\/(?:?:x|[0-9]+)\.?:x|[0-9]+)\.?:x|[0-9]+))(?:\/[0-9]+)?)?$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LaunchPermissionConfiguration

Describes the configuration for a launch permission. The launch permission modification request is sent to the [Amazon EC2 ModifyImageAttribute](#) API on behalf of the user for each Region they have selected to distribute the AMI. To make an AMI public, set the launch permission authorized accounts to all. See the examples for making an AMI public at [Amazon EC2 ModifyImageAttribute](#).

Contents

organizationalUnitArns

The ARN for an AWS Organizations organizational unit (OU) that you want to share your AMI with. For more information about key concepts for AWS Organizations, see [AWS Organizations terminology and concepts](#).

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 25 items.

Pattern: `^arn:aws[^:]*:organizations:[0-9]{12}:ou/o-[a-z0-9]{10,32}/ou-[0-9a-z]{4,32}-[0-9a-z]{8,32}`

Required: No

organizationArns

The ARN for an AWS Organization that you want to share your AMI with. For more information, see [What is AWS Organizations?](#).

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 25 items.

Pattern: `^arn:aws[^:]*:organizations:[0-9]{12}:organization/o-[a-z0-9]{10,32}$`

Required: No

userGroups

The name of the group.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

userIds

The AWS account ID.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 1536 items.

Pattern: `^[0-9]{12}$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LaunchTemplateConfiguration

Identifies an Amazon EC2 launch template to use for a specific account.

Contents

launchTemplateId

Identifies the Amazon EC2 launch template to use.

Type: String

Pattern: `^[a-z0-9-]{17}$`

Required: Yes

accountId

The account ID that this configuration applies to.

Type: String

Pattern: `^[0-9]{12}$`

Required: No

setDefaultVersion

Set the specified Amazon EC2 launch template as the default launch template for the specified account.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

LifecycleExecution

Contains metadata from a runtime instance of a lifecycle policy.

Contents

endTime

The timestamp when the lifecycle runtime instance completed.

Type: Timestamp

Required: No

lifecycleExecutionId

Identifies the lifecycle policy runtime instance.

Type: String

Pattern: `^lce-[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}$`

Required: No

lifecyclePolicyArn

The Amazon Resource Name (ARN) of the lifecycle policy that ran.

Type: String

Length Constraints: Maximum length of 1024.

Pattern: `^arn:aws(?:-[a-z]+)*:imagebuilder:[a-z]{2,}(?:-[a-z]+)+-[0-9]+(?:[0-9]{12}|aws):lifecycle-policy/[a-z0-9-_]+$`

Required: No

resourcesImpactedSummary

Contains information about associated resources that are identified for action by the runtime instance of the lifecycle policy.

Type: [LifecycleExecutionResourcesImpactedSummary](#) object

Required: No

startTime

The timestamp when the lifecycle runtime instance started.

Type: Timestamp

Required: No

state

Runtime state that reports if the policy action ran successfully, failed, or was skipped.

Type: [LifecycleExecutionState](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LifecycleExecutionResource

Contains details for a resource that the runtime instance of the lifecycle policy identified for action.

Contents

accountId

The account that owns the impacted resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

action

The action to take for the identified resource.

Type: [LifecycleExecutionResourceAction](#) object

Required: No

endTime

The ending timestamp from the lifecycle action that was applied to the resource.

Type: Timestamp

Required: No

imageUris

For an impacted container image, this identifies a list of URIs for associated container images distributed to ECR repositories.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

region

The AWS Region where the lifecycle execution resource is stored.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

resourceId

Identifies the impacted resource. The resource ID depends on the type of resource, as follows.

- Image Builder image resources: Amazon Resource Name (ARN)
- Distributed AMIs: AMI ID
- Container images distributed to an ECR repository: image URI or SHA Digest

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

snapshots

A list of associated resource snapshots for the impacted resource if it's an AMI.

Type: Array of [LifecycleExecutionSnapshotResource](#) objects

Required: No

startTime

The starting timestamp from the lifecycle action that was applied to the resource.

Type: Timestamp

Required: No

state

The runtime state for the lifecycle execution.

Type: [LifecycleExecutionResourceState](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LifecycleExecutionResourceAction

The lifecycle policy action that was identified for the impacted resource.

Contents

name

The name of the resource that was identified for a lifecycle policy action.

Type: String

Valid Values: AVAILABLE | DELETE | DEPRECATE | DISABLE

Required: No

reason

The reason why the lifecycle policy action is taken.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LifecycleExecutionResourcesImpactedSummary

Contains details for an image resource that was identified for a lifecycle action.

Contents

hasImpactedResources

Indicates whether an image resource that was identified for a lifecycle action has associated resources that are also impacted.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LifecycleExecutionResourceState

Contains the state of an impacted resource that the runtime instance of the lifecycle policy identified for action.

Contents

reason

Messaging that clarifies the reason for the assigned status.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

status

The runtime status of the lifecycle action taken for the impacted resource.

Type: String

Valid Values: FAILED | IN_PROGRESS | SKIPPED | SUCCESS

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LifecycleExecutionSnapshotResource

Contains the state of an impacted snapshot resource that the runtime instance of the lifecycle policy identified for action.

Contents

snapshotId

Identifies the impacted snapshot resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

state

The runtime status of the lifecycle action taken for the snapshot.

Type: [LifecycleExecutionResourceState](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LifecycleExecutionState

The current state of the runtime instance of the lifecycle policy.

Contents

reason

The reason for the current status.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

status

The runtime status of the lifecycle execution.

Type: String

Valid Values: IN_PROGRESS | CANCELLED | CANCELLING | FAILED | SUCCESS | PENDING

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LifecyclePolicy

The configuration details for a lifecycle policy resource.

Contents

arn

The Amazon Resource Name (ARN) of the lifecycle policy resource.

Type: String

Length Constraints: Maximum length of 1024.

Pattern: `^arn:aws(?:-[a-z]+)*:imagebuilder:[a-z]{2,}(?:-[a-z]+)+-[0-9]+:(?:[0-9]{12}|aws):lifecycle-policy/[a-z0-9-_]+$`

Required: No

dateCreated

The timestamp when Image Builder created the lifecycle policy resource.

Type: Timestamp

Required: No

dateLastRun

The timestamp for the last time Image Builder ran the lifecycle policy.

Type: Timestamp

Required: No

dateUpdated

The timestamp when Image Builder updated the lifecycle policy resource.

Type: Timestamp

Required: No

description

Optional description for the lifecycle policy.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

executionRole

The name or Amazon Resource Name (ARN) of the IAM role that Image Builder uses to run the lifecycle policy. This is a custom role that you create.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^(?:arn:aws(?:-[a-z]+)*:iam:[0-9]{12}:role/)?[a-zA-Z_0-9+=,.\@\_/\]+$`

Required: No

name

The name of the lifecycle policy.

Type: String

Pattern: `^[-_A-Za-z-0-9][-_A-Za-z0-9 ]{1,126}[-_A-Za-z-0-9]$`

Required: No

policyDetails

The configuration details for a lifecycle policy resource.

Type: Array of [LifecyclePolicyDetail](#) objects

Array Members: Minimum number of 1 item. Maximum number of 3 items.

Required: No

resourceSelection

Resource selection criteria used to run the lifecycle policy.

Type: [LifecyclePolicyResourceSelection](#) object

Required: No

resourceType

The type of resources the lifecycle policy targets.

Type: String

Valid Values: AMI_IMAGE | CONTAINER_IMAGE

Required: No

status

Indicates whether the lifecycle policy resource is enabled.

Type: String

Valid Values: DISABLED | ENABLED

Required: No

tags

To help manage your lifecycle policy resources, you can assign your own metadata to each resource in the form of tags. Each tag consists of a key and an optional value, both of which you define.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z0-9\s_.:/=+\-@]*$`

Value Length Constraints: Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LifecyclePolicyDetail

The configuration details for a lifecycle policy resource.

Contents

action

Configuration details for the policy action.

Type: [LifecyclePolicyDetailAction](#) object

Required: Yes

filter

Specifies the resources that the lifecycle policy applies to.

Type: [LifecyclePolicyDetailFilter](#) object

Required: Yes

exclusionRules

Additional rules to specify resources that should be exempt from policy actions.

Type: [LifecyclePolicyDetailExclusionRules](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LifecyclePolicyDetailAction

Contains selection criteria for the lifecycle policy.

Contents

type

Specifies the lifecycle action to take.

Type: String

Valid Values: DELETE | DEPRECATE | DISABLE

Required: Yes

includeResources

Specifies the resources that the lifecycle policy applies to.

Type: [LifecyclePolicyDetailActionIncludeResources](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LifecyclePolicyDetailActionIncludeResources

Specifies how the lifecycle policy should apply actions to selected resources.

Contents

amis

Specifies whether the lifecycle action should apply to distributed AMIs.

Type: Boolean

Required: No

containers

Specifies whether the lifecycle action should apply to distributed containers.

Type: Boolean

Required: No

snapshots

Specifies whether the lifecycle action should apply to snapshots associated with distributed AMIs.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LifecyclePolicyDetailExclusionRules

Specifies resources that lifecycle policy actions should not apply to.

Contents

amis

Lists configuration values that apply to AMIs that Image Builder should exclude from the lifecycle action.

Type: [LifecyclePolicyDetailExclusionRulesAmis](#) object

Required: No

tagMap

Contains a list of tags that Image Builder uses to skip lifecycle actions for Image Builder image resources that have them.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z0-9\s_.:/=+\-@]*$`

Value Length Constraints: Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LifecyclePolicyDetailExclusionRulesAmis

Defines criteria for AMIs that are excluded from lifecycle actions.

Contents

isPublic

Configures whether public AMIs are excluded from the lifecycle action.

Type: Boolean

Required: No

lastLaunched

Specifies configuration details for Image Builder to exclude the most recent resources from lifecycle actions.

Type: [LifecyclePolicyDetailExclusionRulesAmisLastLaunched](#) object

Required: No

regions

Configures AWS Regions that are excluded from the lifecycle action.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

sharedAccounts

Specifies AWS accounts whose resources are excluded from the lifecycle action.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 1536 items.

Pattern: `^[0-9]{12}$`

Required: No

tagMap

Lists tags that should be excluded from lifecycle actions for the AMIs that have them.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z0-9\s_.:/=+\-@]*$`

Value Length Constraints: Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LifecyclePolicyDetailExclusionRulesAmisLastLaunched

Defines criteria to exclude AMIs from lifecycle actions based on the last time they were used to launch an instance.

Contents

unit

Defines the unit of time that the lifecycle policy uses to calculate elapsed time since the last instance launched from the AMI. For example: days, weeks, months, or years.

Type: String

Valid Values: DAYS | WEEKS | MONTHS | YEARS

Required: Yes

value

The integer number of units for the time period. For example 6 (months).

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 365.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LifecyclePolicyDetailFilter

Defines filters that the lifecycle policy uses to determine impacted resource.

Contents

type

Filter resources based on either age or count.

Type: String

Valid Values: AGE | COUNT

Required: Yes

value

The number of units for the time period or for the count. For example, a value of 6 might refer to six months or six AMIs.

Note

For count-based filters, this value represents the minimum number of resources to keep on hand. If you have fewer resources than this number, the resource is excluded from lifecycle actions.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: Yes

retainAtLeast

For age-based filters, this is the number of resources to keep on hand after the lifecycle DELETE action is applied. Impacted resources are only deleted if you have more than this number of resources. If you have fewer resources than this number, the impacted resource is not deleted.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 10.

Required: No

unit

Defines the unit of time that the lifecycle policy uses to determine impacted resources. This is required for age-based rules.

Type: String

Valid Values: DAYS | WEEKS | MONTHS | YEARS

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LifecyclePolicyResourceSelection

Resource selection criteria for the lifecycle policy.

Contents

recipes

A list of recipes that are used as selection criteria for the output images that the lifecycle policy applies to.

Type: Array of [LifecyclePolicyResourceSelectionRecipe](#) objects

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Required: No

tagMap

A list of tags that are used as selection criteria for the Image Builder image resources that the lifecycle policy applies to.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z0-9\s_.:/+=\-\@]*$`

Value Length Constraints: Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

LifecyclePolicyResourceSelectionRecipe

Specifies an Image Builder recipe that the lifecycle policy uses for resource selection.

Contents

name

The name of an Image Builder recipe that the lifecycle policy uses for resource selection.

Type: String

Pattern: `^[_A-Za-z-0-9][_A-Za-z0-9 ]{1,126}[_A-Za-z-0-9]$`

Required: Yes

semanticVersion

The version of the Image Builder recipe specified by the name field.

Type: String

Pattern: `^(?:[0-9]+|x)\.(?:[0-9]+|x)\.(?:[0-9]+|x)$`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LifecyclePolicySummary

Contains a summary of lifecycle policy resources.

Contents

arn

The Amazon Resource Name (ARN) of the lifecycle policy summary resource.

Type: String

Length Constraints: Maximum length of 1024.

Pattern: `^arn:aws(?:-[a-z]+)*:imagebuilder:[a-z]{2,}(?:-[a-z]+)+-[0-9]+:(?:[0-9]{12}|aws):lifecycle-policy/[a-z0-9-_]+$`

Required: No

dateCreated

The timestamp when Image Builder created the lifecycle policy resource.

Type: Timestamp

Required: No

dateLastRun

The timestamp for the last time Image Builder ran the lifecycle policy.

Type: Timestamp

Required: No

dateUpdated

The timestamp when Image Builder updated the lifecycle policy resource.

Type: Timestamp

Required: No

description

Optional description for the lifecycle policy.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

executionRole

The name or Amazon Resource Name (ARN) of the IAM role that Image Builder uses to run the lifecycle policy.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^(?:arn:aws(?:-[a-z]+)*:iam:[0-9]{12}:role/)?[a-zA-Z0-9+=,.\@\_/-]+`

Required: No

name

The name of the lifecycle policy.

Type: String

Pattern: `^[-_A-Za-z0-9][-_A-Za-z0-9 ]{1,126}[-_A-Za-z0-9]$`

Required: No

resourceType

The type of resources the lifecycle policy targets.

Type: String

Valid Values: `AMI_IMAGE` | `CONTAINER_IMAGE`

Required: No

status

The lifecycle policy resource status.

Type: String

Valid Values: DISABLED | ENABLED

Required: No

tags

To help manage your lifecycle policy resources, you can assign your own metadata to each resource in the form of tags. Each tag consists of a key and an optional value, both of which you define.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z0-9\s_.:/=+\-@]*$`

Value Length Constraints: Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Logging

Logging configuration defines where Image Builder uploads your logs.

Contents

s3Logs

The Amazon S3 logging configuration.

Type: [S3Logs](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OutputResources

The resources produced by this image.

Contents

amis

The Amazon EC2 AMIs created by this image.

Type: Array of [Ami](#) objects

Required: No

containers

Container images that the pipeline has generated and stored in the output repository.

Type: Array of [Container](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PackageVulnerabilityDetails

Information about package vulnerability findings.

Contents

vulnerabilityId

A unique identifier for this vulnerability.

Type: String

Required: Yes

cvss

CVSS scores for one or more vulnerabilities that Amazon Inspector identified for a package.

Type: Array of [CvssScore](#) objects

Required: No

referenceUrls

Links to web pages that contain details about the vulnerabilities that Amazon Inspector identified for the package.

Type: Array of strings

Array Members: Minimum number of 1 item.

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

relatedVulnerabilities

Vulnerabilities that are often related to the findings for the package.

Type: Array of strings

Required: No

source

The source of the vulnerability information.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

sourceUrl

A link to the source of the vulnerability information.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

vendorCreatedAt

The date and time when this vulnerability was first added to the vendor's database.

Type: Timestamp

Required: No

vendorSeverity

The severity that the vendor assigned to this vulnerability type.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

vendorUpdatedAt

The date and time when the vendor last updated this vulnerability in their database.

Type: Timestamp

Required: No

vulnerablePackages

The packages that this vulnerability impacts.

Type: Array of [VulnerablePackage](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PipelineLoggingConfiguration

The logging configuration that's defined for pipeline execution.

Contents

imageLogGroupName

Specifies the CloudWatch Logs log group name for image build logs. The log group name can contain alphanumeric characters, hyphens, underscores, forward slashes, and periods, up to 512 characters. Log group names not starting with `/aws/imagebuilder/` require an `executionRole` with CloudWatch Logs write permissions. If not specified, defaults to `/aws/imagebuilder/image-name`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `^[a-zA-Z0-9\-\_\./]{1,512}$`

Required: No

pipelineLogGroupName

Specifies the CloudWatch Logs log group name for pipeline execution logs. The log group name can contain alphanumeric characters, hyphens, underscores, forward slashes, and periods, up to 512 characters. Log group names not starting with `/aws/imagebuilder/` require an `executionRole` with CloudWatch Logs write permissions. If not specified, defaults to `/aws/imagebuilder/pipeline/pipeline-name`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `^[a-zA-Z0-9\-\_\./]{1,512}$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Placement

By default, EC2 instances run on shared tenancy hardware. This means that multiple AWS accounts might share the same physical hardware. When you use dedicated hardware, the physical server that hosts your instances is dedicated to your AWS account. Instance placement settings contain the details for the physical hardware where instances that Image Builder launches during image creation will run.

Contents

availabilityZone

The Availability Zone where your build and test instances will launch.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

hostId

The ID of the Dedicated Host on which build and test instances run. This only applies if tenancy is host. If you specify the host ID, you must not specify the resource group ARN. If you specify both, Image Builder returns an error.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

hostResourceGroupArn

The Amazon Resource Name (ARN) of the host resource group in which to launch build and test instances. This only applies if tenancy is host. If you specify the resource group ARN, you must not specify the host ID. If you specify both, Image Builder returns an error.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

tenancy

The tenancy of the instance. An instance with a tenancy of `dedicated` runs on single-tenant hardware. An instance with a tenancy of `host` runs on a Dedicated Host.

If tenancy is set to `host`, then you can optionally specify one target for placement – either host ID or host resource group ARN. If automatic placement is enabled for your host, and you don't specify any placement target, Amazon EC2 will try to find an available host for your build and test instances.

Type: String

Valid Values: `default` | `dedicated` | `host`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ProductCodeListItem

Information about a single product code.

Contents

productCodeId

For AWS Marketplace components, this contains the product code ID that can be stamped onto an EC2 AMI to ensure that components are billed correctly. If this property is empty, it might mean that the component is not published.

Type: String

Pattern: `^[A-Za-z0-9]{1,25}$`

Required: Yes

productCodeType

The owner of the product code that's billed. If this property is empty, it might mean that the component is not published.

Type: String

Valid Values: `marketplace`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RegionFailure

Contains details about a distribution or image configuration failure for a single Region.

Contents

errorMessage

The error message for the failure in the Region.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 384000.

Required: No

imageConfigurationStep

The image configuration step where the failure occurred. Image Builder sets this property when the failure happened during post-distribution configuration, such as launch template updates or virtual machine (VM) export. This property doesn't appear for failures that occurred while Image Builder copied the image to the Region.

Type: String

Valid Values: ASSOCIATE_LICENSES | UPDATE_LAUNCH_TEMPLATES |
PUT_SSM_PARAMETERS | UPDATE_FAST_LAUNCH_CONFIGURATIONS | EXPORT_AMI

Required: No

region

The Region where the failure occurred.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

status

The failure status for the Region. Indicates whether the process failed, was canceled, or timed out.

Type: String

Valid Values: FAILED | CANCELLED | TIMED_OUT

Required: No

targetAccountId

The account ID of the account that the image was distributed to in the Region.

Type: String

Pattern: `^[0-9]{12}$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RegisterImageOptions

Controls Secure Boot and UEFI data settings for the resulting image during ISO imports. For more information, see [UEFI Secure Boot for Amazon EC2 instances](#) in the Amazon EC2 User Guide .

Contents

secureBootEnabled

Specifies whether Secure Boot is enabled for the output AMI. The default value is `true`. To disable Secure Boot for custom unsigned drivers, set this value to `false`.

Type: Boolean

Required: No

uefiData

A Base64-encoded representation of the non-volatile UEFI variable store. You can specify this parameter only when `secureBootEnabled` is `true` or unspecified. You can inspect and modify the UEFI data by using the [python-uefivars tool on GitHub](#).

For more information, see [UEFI variables for Amazon EC2 instances](#).

Type: String

Length Constraints: Minimum length of 0. Maximum length of 64000.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Remediation

Information about how to remediate a finding.

Contents

recommendation

An object that contains information about the recommended course of action to remediate the finding.

Type: [RemediationRecommendation](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RemediationRecommendation

Details about the recommended course of action to remediate the finding.

Contents

text

The recommended course of action to remediate the finding.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

url

A link to more information about the recommended remediation for this vulnerability.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResourceState

The current state of an impacted resource.

Contents

status

Shows the current lifecycle policy action that was applied to an impacted resource.

Type: String

Valid Values: AVAILABLE | DELETED | DEPRECATED | DISABLED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResourceStateUpdateExclusionRules

Additional rules to specify resources that should be exempt from ad-hoc lifecycle actions.

Contents

amis

Defines criteria for AMIs that are excluded from lifecycle actions.

Type: [LifecyclePolicyDetailExclusionRulesAmis](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResourceStateUpdateIncludeResources

Specifies if the lifecycle policy should apply actions to selected resources.

Contents

amis

Specifies whether the lifecycle action should apply to distributed AMIs

Type: Boolean

Required: No

containers

Specifies whether the lifecycle action should apply to distributed containers.

Type: Boolean

Required: No

snapshots

Specifies whether the lifecycle action should apply to snapshots associated with distributed AMIs.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

S3ExportConfiguration

Properties that configure export from your build instance to a compatible file format for your VM.

Contents

diskImageFormat

Export the updated image to one of the following supported disk image formats:

- **Virtual Hard Disk (VHD)** – Compatible with Citrix Xen and Microsoft Hyper-V virtualization products.
- **Stream-optimized ESX Virtual Machine Disk (VMDK)** – Compatible with VMware ESX and VMware vSphere versions 4, 5, and 6.
- **Raw** – Raw format.

Type: String

Valid Values: VMDK | RAW | VHD

Required: Yes

roleName

The name of the role that grants VM Import/Export permission to export images to your S3 bucket.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: Yes

s3Bucket

The S3 bucket in which to store the output disk images for your VM.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: Yes

s3Prefix

The Amazon S3 path for the bucket where the output disk images for your VM are stored.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

S3Logs

Amazon S3 logging configuration.

Contents

s3BucketName

The S3 bucket in which to store the logs.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

s3KeyPrefix

The Amazon S3 path to the bucket where the logs are stored.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Schedule

A schedule configures when and how often a pipeline will automatically create a new image.

Contents

autoDisablePolicy

The policy that configures when Image Builder should automatically disable a pipeline that is failing.

Type: [AutoDisablePolicy](#) object

Required: No

pipelineExecutionStartCondition

The start condition configures when the pipeline should trigger a new image build, as follows. If no value is set Image Builder defaults to `EXPRESSION_MATCH_AND_DEPENDENCY_UPDATES_AVAILABLE`.

- `EXPRESSION_MATCH_AND_DEPENDENCY_UPDATES_AVAILABLE` (default) – When you use semantic version filters on the base image or components in your image recipe, EC2 Image Builder builds a new image only when there are new versions of the base image or components in your recipe that match the filter.



Note

For semantic version syntax, see [CreateComponent](#).

- `EXPRESSION_MATCH_ONLY` – This condition builds a new image every time the CRON expression matches the current time.

Type: String

Valid Values: `EXPRESSION_MATCH_ONLY` | `EXPRESSION_MATCH_AND_DEPENDENCY_UPDATES_AVAILABLE`

Required: No

scheduleExpression

The cron expression determines how often EC2 Image Builder evaluates your `pipelineExecutionStartCondition`.

For information on how to format a cron expression in Image Builder, see [Use cron expressions in EC2 Image Builder](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

timezone

The timezone that applies to the scheduling expression. For example, "Etc/UTC", "America/Los_Angeles" in the [IANA timezone format](#). If not specified this defaults to UTC.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 100.

Pattern: `[a-zA-Z0-9]{2,}(:|\/[a-zA-Z0-9-_+]+)*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SeverityCounts

Includes counts by severity level for medium severity and higher level findings, plus a total for all of the findings for the specified filter.

Contents

all

The total number of findings across all severity levels for the specified filter.

Type: Long

Required: No

critical

The number of critical severity findings for the specified filter.

Type: Long

Required: No

high

The number of high severity findings for the specified filter.

Type: Long

Required: No

medium

The number of medium severity findings for the specified filter.

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SsmParameterConfiguration

Configuration for a single Parameter in the AWS Systems Manager (SSM) Parameter Store in a given Region.

Contents

parameterName

This is the name of the Parameter in the target Region or account. The image distribution creates the Parameter if it doesn't already exist. Otherwise, it updates the parameter.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `^[a-zA-Z0-9_.\-\/]+$`

Required: Yes

amiAccountId

Specify the account that will own the Parameter in a given Region. During distribution, this account must be specified in distribution settings as a target account for the Region.

Type: String

Pattern: `^[0-9]{12}$`

Required: No

dataType

The type of value the parameter contains. We recommend the `aws:ec2:image` data type.

Type: String

Valid Values: `text` | `aws:ec2:image`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SystemsManagerAgent

Contains settings for the Systems Manager agent on your build instance.

Contents

uninstallAfterBuild

Controls whether the Systems Manager agent is removed from your final build image, prior to creating the new AMI. If this is set to true, then the agent is removed from the final image. If it's set to false, then the agent is left in, so that it is included in the new AMI. default value is false.

The default behavior of `uninstallAfterBuild` is to remove the SSM Agent if it was installed by EC2 Image Builder

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TargetContainerRepository

The container repository where the output container image is stored.

Contents

repositoryName

The name of the container repository where the output container image is stored. This name is prefixed by the repository location. For example, `<repository location url>/repository_name`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: Yes

service

Specifies the service in which this image was registered.

Type: String

Valid Values: ECR

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VulnerabilityIdAggregation

Includes counts of image and pipeline resource findings by vulnerability.

Contents

severityCounts

Counts by severity level for medium severity and higher level findings, plus a total for all of the findings for the specified vulnerability.

Type: [SeverityCounts](#) object

Required: No

vulnerabilityId

The vulnerability Id for this set of counts.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VulnerablePackage

Information about a vulnerable package that Amazon Inspector identifies in a finding.

Contents

arch

The architecture of the vulnerable package.

Type: String

Required: No

epoch

The epoch of the vulnerable package.

Type: Integer

Required: No

filePath

The file path of the vulnerable package.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

fixedInVersion

The version of the package that contains the vulnerability fix.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

name

The name of the vulnerable package.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

packageManager

The package manager of the vulnerable package.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

release

The release of the vulnerable package.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

remediation

The code to run in your environment to update packages with a fix available.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

sourceLayerHash

The source layer hash of the vulnerable package.

Type: String

Required: No

version

The version of the vulnerable package.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

WindowsConfiguration

Windows-specific configuration settings for an ISO import, including the edition to install from a multi-edition Windows ISO file.

Contents

imageIndex

The 1-based index that specifies which Windows edition to install from a multi-edition Windows ISO file. A Windows ISO can contain a .wim file with multiple image indexes, each representing a different edition.

Type: Long

Valid Range: Minimum value of 1. Maximum value of 4294967295.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Workflow

Defines a process that Image Builder uses to build and test images during the image creation process.

Contents

arn

The Amazon Resource Name (ARN) of the workflow resource.

Type: String

Length Constraints: Maximum length of 1024.

Pattern: `^arn:aws(?:-[a-z]+)*:imagebuilder:[a-z]{2,}(?:-[a-z]+)-[0-9]+:(?:[0-9]{12}|aws(?:-[a-z]+)?):workflow/(build|test|distribution)/[a-z0-9-_/][0-9]+\.[0-9]+\.[0-9]+/[0-9]+$`

Required: No

changeDescription

Describes what change has been made in this version of the workflow, or what makes this version different from other versions of the workflow.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

data

Contains the YAML document content for the workflow.

Type: String

Required: No

dateCreated

The timestamp when Image Builder created the workflow resource.

Type: String

Required: No

description

The description of the workflow.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

kmsKeyId

The KMS key identifier used to encrypt the workflow resource. This can be either the Key ARN or the Alias ARN. For more information, see [Key identifiers \(KeyId\)](#) in the *AWS Key Management Service Developer Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

name

The name of the workflow resource.

Type: String

Pattern: `^[-_A-Za-z-0-9][-_A-Za-z0-9 ]{1,126}[-_A-Za-z-0-9]$`

Required: No

owner

The owner of the workflow resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

parameters

An array of input parameters that the image workflow uses to control actions or configure settings.

Type: Array of [WorkflowParameterDetail](#) objects

Required: No

state

Describes the current status of the workflow and the reason for that status.

Type: [WorkflowState](#) object

Required: No

tags

The tags that apply to the workflow resource

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z0-9\s_.:/=+\-@]*$`

Value Length Constraints: Maximum length of 256.

Required: No

type

Specifies the image creation stage that the workflow applies to. Image Builder currently supports build and test workflows.

Type: String

Valid Values: BUILD | TEST | DISTRIBUTION

Required: No

version

The workflow resource version. Workflow resources are immutable. To make a change, you can clone a workflow or create a new version.

Type: String

Pattern: `^[0-9]+\.[0-9]+\.[0-9]+$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

WorkflowConfiguration

Contains control settings and configurable inputs for a workflow resource.

Contents

workflowArn

The Amazon Resource Name (ARN) of the workflow resource.

Type: String

Pattern: `^arn:aws(?:-[a-z]+)*:imagebuilder:[a-z]{2,}(?:-[a-z]+)-[0-9]+:(?:[0-9]{12}|aws(?:-[a-z]+)?):workflow/(build|test|distribution)/[a-z0-9-_/](?:((?:([0-9]+|x)\.([0-9]+|x)\.([0-9]+|x))|(?:[0-9]+\.[0-9]+\.[0-9]+/[0-9]+)))$`

Required: Yes

onFailure

The action to take if the workflow fails.

Type: String

Valid Values: CONTINUE | ABORT

Required: No

parallelGroup

Test workflows are defined within named runtime groups called parallel groups. The parallel group is the named group that contains this test workflow. Test workflows within a parallel group can run at the same time. Image Builder starts up to five test workflows in the group at the same time, and starts additional workflows as others complete, until all workflows in the group have completed. This field only applies for test workflows.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `^[A-Za-z0-9][A-Za-z0-9-_+#]{0,99}$`

Required: No

parameters

Contains parameter values for each of the parameters that the workflow document defined for the workflow resource.

Type: Array of [WorkflowParameter](#) objects

Array Members: Minimum number of 1 item.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

WorkflowExecutionMetadata

Metadata that includes details and status from this runtime instance of the workflow.

Contents

endTime

The timestamp when this runtime instance of the workflow finished.

Type: String

Required: No

message

The runtime output message from the workflow, if applicable.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

parallelGroup

The name of the test group that included the test workflow resource at runtime.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `^[A-Za-z0-9][A-Za-z0-9-_{0,99}]$`

Required: No

retried

Indicates retry status for this runtime instance of the workflow.

Type: Boolean

Required: No

startTime

The timestamp when the runtime instance of this workflow started.

Type: String

Required: No

status

The current runtime status for this workflow.

Type: String

Valid Values: PENDING | SKIPPED | RUNNING | COMPLETED | FAILED |
ROLLBACK_IN_PROGRESS | ROLLBACK_COMPLETED | CANCELLED

Required: No

totalStepCount

The total number of steps in the workflow. This should equal the sum of the step counts for steps that succeeded, were skipped, and failed.

Type: Integer

Required: No

totalStepsFailed

A runtime count for the number of steps in the workflow that failed.

Type: Integer

Required: No

totalStepsSkipped

A runtime count for the number of steps in the workflow that were skipped.

Type: Integer

Required: No

totalStepsSucceeded

A runtime count for the number of steps in the workflow that ran successfully.

Type: Integer

Required: No

type

Indicates what type of workflow that Image Builder ran for this runtime instance of the workflow.

Type: String

Valid Values: BUILD | TEST | DISTRIBUTION

Required: No

workflowBuildVersionArn

The Amazon Resource Name (ARN) of the workflow resource build version that ran.

Type: String

Length Constraints: Maximum length of 1024.

Pattern: `^arn:aws(?:-[a-z]+)*:imagebuilder:[a-z]{2,}(?:-[a-z]+)+-[0-9]+:(?:[0-9]{12}|aws(?:-[a-z]+)?):workflow/(build|test|distribution)/[a-z0-9-_.]+/[0-9]+\.[0-9]+\.[0-9]+/[0-9]+$`

Required: No

workflowExecutionId

Unique identifier that Image Builder assigns to keep track of runtime resources each time it runs a workflow.

Type: String

Pattern: `^wf-[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

WorkflowParameter

Contains a key/value pair that sets the named workflow parameter.

Contents

name

The name of the workflow parameter to set.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[^\x00]+`

Required: Yes

value

Sets the value for the named workflow parameter.

Type: Array of strings

Length Constraints: Minimum length of 0.

Pattern: `[^\x00]*`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

WorkflowParameterDetail

Defines a parameter that's used to provide configuration details for the workflow.

Contents

name

The name of this input parameter.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[^\x00]+`

Required: Yes

type

The type of input this parameter provides. The currently supported value is "string".

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: `^string|integer|boolean|stringList$`

Required: Yes

defaultValue

The default value of this parameter if no input is provided.

Type: Array of strings

Length Constraints: Minimum length of 0.

Pattern: `[^\x00]*`

Required: No

description

Describes this parameter.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Pattern: `[^\x00]+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

WorkflowState

A group of fields that describe the current status of workflow.

Contents

reason

Describes how or why the workflow changed state.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

status

The current state of the workflow.

Type: String

Valid Values: DEPRECATED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

WorkflowStepExecution

Contains runtime details for an instance of a workflow that ran for the associated image build version.

Contents

action

The name of the step action.

Type: String

Pattern: `^[A-Za-z][A-Za-z0-9-_{1,99}]$`

Required: No

imageBuildVersionArn

The Amazon Resource Name (ARN) of the image build version that ran the workflow.

Type: String

Pattern: `^arn:aws[^:]*:imagebuilder:[^:]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):image/[a-z0-9-_{1,99}]+/[0-9]+\.[0-9]+\.[0-9]+/[0-9]+$`

Required: No

name

The name of the workflow step.

Type: String

Pattern: `^[A-Za-z][A-Za-z0-9-_{1,99}]$`

Required: No

startTime

The timestamp when the workflow step started.

Type: String

Required: No

stepExecutionId

Uniquely identifies the workflow step that ran for the associated image build version.

Type: String

Pattern: `^step-[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}$`

Required: No

workflowBuildVersionArn

The Amazon Resource Name (ARN) of the workflow resource that ran.

Type: String

Length Constraints: Maximum length of 1024.

Pattern: `^arn:aws(?:-[a-z]+)*:imagebuilder:[a-z]{2,}(?:-[a-z]+)+-[0-9]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):workflow/(build|test|distribution)/[a-z0-9-_.]+/[0-9]+\.[0-9]+\.[0-9]+/[0-9]+$`

Required: No

workflowExecutionId

Uniquely identifies the runtime instance of the workflow that contains the workflow step that ran for the associated image build version.

Type: String

Pattern: `^wf-[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

WorkflowStepMetadata

Runtime details and status for the workflow step.

Contents

action

The step action name.

Type: String

Pattern: `^[A-Za-z][A-Za-z0-9-_{1,99}]$`

Required: No

attemptNumber

The current attempt number for the workflow step. The first run is attempt one. The number increases by one for each retry.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

description

Description of the workflow step.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

endTime

The timestamp when the workflow step finished.

Type: String

Required: No

inputs

Input parameters that Image Builder provides for the workflow step.

Type: String

Required: No

maxAttempts

The maximum number of attempts allowed for the workflow step, based on the retry configuration in the workflow document. If the step doesn't configure retries, the maximum is one attempt.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

message

Detailed output message that the workflow step provides at runtime.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

name

The name of the workflow step.

Type: String

Pattern: `^[A-Za-z][A-Za-z0-9-_{1,99}]$`

Required: No

outputs

The file names that the workflow step created as output for this runtime instance of the workflow.

Type: String

Required: No

rollbackStatus

Reports on the rollback status of the step, if applicable.

Type: String

Valid Values: RUNNING | COMPLETED | SKIPPED | FAILED

Required: No

startTime

The timestamp when the workflow step started.

Type: String

Required: No

status

Runtime status for the workflow step.

Type: String

Valid Values: PENDING | SKIPPED | RUNNING | COMPLETED | FAILED | CANCELLED

Required: No

stepExecutionId

A unique identifier for the workflow step, assigned at runtime.

Type: String

Pattern: ^step-[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

WorkflowSummary

Contains metadata about the workflow resource.

Contents

arn

The Amazon Resource Name (ARN) of the workflow resource.

Type: String

Pattern: `^arn:aws(?:-[a-z]+)*:imagebuilder:[a-z]{2,}(?:-[a-z]+)+-[0-9]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):workflow/(build|test|distribution)/[a-z0-9-_/x\.x\.$`

Required: No

changeDescription

The change description for the current version of the workflow resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

dateCreated

The original creation date of the workflow resource.

Type: String

Required: No

description

Describes the workflow.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

name

The name of the workflow.

Type: String

Pattern: `^[-_A-Za-z-0-9][-_A-Za-z0-9 ]{1,126}[-_A-Za-z-0-9]$`

Required: No

owner

The owner of the workflow resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

state

Describes the current state of the workflow resource.

Type: [WorkflowState](#) object

Required: No

tags

Contains a list of tags that are defined for the workflow.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!aws:)[a-zA-Z0-9\s_.:/+=\-\@]*$`

Value Length Constraints: Maximum length of 256.

Required: No

type

The image creation stage that this workflow applies to. Image Builder currently supports build and test stage workflows.

Type: String

Valid Values: BUILD | TEST | DISTRIBUTION

Required: No

version

The version of the workflow.

Type: String

Pattern: `^[0-9]+\.[0-9]+\.[0-9]+$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

WorkflowVersion

Contains details about this version of the workflow.

Contents

arn

The Amazon Resource Name (ARN) of the workflow resource.

Type: String

Pattern: `^arn:aws(?:-[a-z]+)*:imagebuilder:[a-z]{2,}(?:-[a-z]+)-[0-9]+:(?:[0-9]{12}|aws(?:-[a-z-]+)?):workflow/(build|test|distribution)/[a-z0-9-_.]+/[0-9]+\.[0-9]+\.[0-9]+$`

Required: No

dateCreated

The timestamp when Image Builder created the workflow version.

Type: String

Required: No

description

Describes the workflow.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

name

The name of the workflow.

Type: String

Pattern: `^[-_A-Za-z-0-9][-_A-Za-z0-9 ]{1,126}[-_A-Za-z-0-9]$`

Required: No

owner

The owner of the workflow resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

type

The image creation stage that this workflow applies to. Image Builder currently supports build and test stage workflows.

Type: String

Valid Values: BUILD | TEST | DISTRIBUTION

Required: No

version

The semantic version of the workflow resource. The format includes three nodes: <major>.<minor>.<patch>.

Type: String

Pattern: `^[0-9]+\.[0-9]+\.[0-9]+$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Error Types

This section lists common error types that this AWS service may return. Not all services return all error types listed here. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You don't have permission to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 403

ExpiredTokenException

The security token included in the request has expired. Request a new security token and try again.

HTTP Status Code: 403

IncompleteSignature

The request signature doesn't conform to AWS standards. Verify that you're using valid AWS credentials and that your request is properly formatted. If you're using an SDK, ensure it's up to date.

HTTP Status Code: 403

InternalFailure

The request can't be processed right now because of an internal server issue. Try again later. If the problem persists, contact AWS Support.

HTTP Status Code: 500

MalformedHttpRequestException

The request body can't be processed. This typically happens when the request body can't be decompressed using the specified content encoding algorithm. Verify that the content encoding header matches the compression format used.

HTTP Status Code: 400

NotAuthorized

You don't have permissions to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 401

OptInRequired

Your AWS account needs a subscription for this service. Verify that you've enabled the service in your account.

HTTP Status Code: 403

RequestAbortedException

The request was aborted before a response could be returned. This typically happens when the client closes the connection.

HTTP Status Code: 400

RequestEntityTooLargeException

The request entity is too large. Reduce the size of the request body and try again.

HTTP Status Code: 413

RequestTimeoutException

The request timed out. The server didn't receive the complete request within the expected time frame. Try again.

HTTP Status Code: 408

ServiceUnavailable

The service is temporarily unavailable. Try again later.

HTTP Status Code: 503

ThrottlingException

Your request rate is too high. The AWS SDKs automatically retry requests that receive this exception. Reduce the frequency of requests.

HTTP Status Code: 400

UnknownOperationException

The action or operation isn't recognized. Verify that the action name is spelled correctly and that it's supported by the API version you're using.

HTTP Status Code: 404

UnrecognizedClientException

The X.509 certificate or AWS access key ID you provided doesn't exist in our records. Verify that you're using valid credentials and that they haven't expired.

HTTP Status Code: 403

ValidationError

The input doesn't meet the required format or constraints. Check that all required parameters are included and that values are valid.

HTTP Status Code: 400