



Welcome

AWS IoT FleetWise



API Version 2021-06-17

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

AWS IoT FleetWise: Welcome

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
AssociateVehicleFleet	5
Request Syntax	5
Request Parameters	5
Response Elements	6
Errors	6
See Also	7
BatchCreateVehicle	9
Request Syntax	9
Request Parameters	10
Response Syntax	10
Response Elements	11
Errors	11
See Also	12
BatchUpdateVehicle	14
Request Syntax	14
Request Parameters	15
Response Syntax	15
Response Elements	16
Errors	16
See Also	18
CreateCampaign	19
Request Syntax	19
Request Parameters	20
Response Syntax	26
Response Elements	26
Errors	26
See Also	28
CreateDecoderManifest	30
Request Syntax	30
Request Parameters	32
Response Syntax	34
Response Elements	34

Errors	34
See Also	37
CreateFleet	38
Request Syntax	38
Request Parameters	38
Response Syntax	39
Response Elements	40
Errors	40
See Also	42
CreateModelManifest	43
Request Syntax	43
Request Parameters	43
Response Syntax	44
Response Elements	45
Errors	45
See Also	47
CreateSignalCatalog	49
Request Syntax	49
Request Parameters	49
Response Syntax	50
Response Elements	50
Errors	51
See Also	53
CreateStateTemplate	55
Request Syntax	55
Request Parameters	55
Response Syntax	58
Response Elements	58
Errors	58
See Also	61
CreateVehicle	62
Request Syntax	62
Request Parameters	63
Response Syntax	64
Response Elements	65
Errors	65

See Also	67
DeleteCampaign	69
Request Syntax	69
Request Parameters	69
Response Syntax	69
Response Elements	70
Errors	70
See Also	72
DeleteDecoderManifest	73
Request Syntax	73
Request Parameters	73
Response Syntax	73
Response Elements	74
Errors	74
See Also	75
DeleteFleet	77
Request Syntax	77
Request Parameters	77
Response Syntax	77
Response Elements	78
Errors	78
See Also	79
DeleteModelManifest	81
Request Syntax	81
Request Parameters	81
Response Syntax	81
Response Elements	82
Errors	82
See Also	83
DeleteSignalCatalog	85
Request Syntax	85
Request Parameters	85
Response Syntax	85
Response Elements	86
Errors	86
See Also	87

DeleteStateTemplate	89
Request Syntax	89
Request Parameters	89
Response Syntax	89
Response Elements	90
Errors	90
See Also	91
DeleteVehicle	93
Request Syntax	93
Request Parameters	93
Response Syntax	93
Response Elements	94
Errors	94
See Also	95
DisassociateVehicleFleet	97
Request Syntax	97
Request Parameters	97
Response Elements	98
Errors	98
See Also	99
GetCampaign	101
Request Syntax	101
Request Parameters	101
Response Syntax	101
Response Elements	103
Errors	107
See Also	108
GetDecoderManifest	110
Request Syntax	110
Request Parameters	110
Response Syntax	110
Response Elements	111
Errors	112
See Also	114
GetEncryptionConfiguration	115
Response Syntax	115

Response Elements	115
Errors	116
See Also	118
GetFleet	119
Request Syntax	119
Request Parameters	119
Response Syntax	119
Response Elements	120
Errors	121
See Also	122
GetLoggingOptions	124
Response Syntax	124
Response Elements	124
Errors	124
See Also	125
GetModelManifest	127
Request Syntax	127
Request Parameters	127
Response Syntax	127
Response Elements	128
Errors	129
See Also	130
GetRegisterAccountStatus	132
Response Syntax	132
Response Elements	133
Errors	134
See Also	135
GetSignalCatalog	137
Request Syntax	137
Request Parameters	137
Response Syntax	137
Response Elements	138
Errors	139
See Also	140
GetStateTemplate	142
Request Syntax	142

Request Parameters	142
Response Syntax	142
Response Elements	143
Errors	145
See Also	146
GetVehicle	148
Request Syntax	148
Request Parameters	148
Response Syntax	148
Response Elements	149
Errors	150
See Also	152
GetVehicleStatus	153
Request Syntax	153
Request Parameters	153
Response Syntax	154
Response Elements	154
Errors	155
See Also	156
ImportDecoderManifest	158
Request Syntax	158
Request Parameters	158
Response Syntax	159
Response Elements	159
Errors	159
See Also	162
ImportSignalCatalog	163
Request Syntax	163
Request Parameters	163
Response Syntax	164
Response Elements	164
Errors	165
See Also	167
ListCampaigns	168
Request Syntax	168
Request Parameters	168

Response Syntax	169
Response Elements	170
Errors	170
See Also	171
ListDecoderManifestNetworkInterfaces	173
Request Syntax	173
Request Parameters	173
Response Syntax	174
Response Elements	175
Errors	175
See Also	177
ListDecoderManifests	178
Request Syntax	178
Request Parameters	178
Response Syntax	179
Response Elements	180
Errors	180
See Also	181
ListDecoderManifestSignals	183
Request Syntax	183
Request Parameters	183
Response Syntax	184
Response Elements	185
Errors	186
See Also	187
ListFleets	188
Request Syntax	188
Request Parameters	188
Response Syntax	189
Response Elements	190
Errors	190
See Also	191
ListFleetsForVehicle	193
Request Syntax	193
Request Parameters	193
Response Syntax	194

Response Elements	194
Errors	195
See Also	196
ListModelManifestNodes	198
Request Syntax	198
Request Parameters	198
Response Syntax	199
Response Elements	199
Errors	200
See Also	202
ListModelManifests	203
Request Syntax	203
Request Parameters	203
Response Syntax	204
Response Elements	205
Errors	205
See Also	206
ListSignalCatalogNodes	208
Request Syntax	208
Request Parameters	208
Response Syntax	209
Response Elements	210
Errors	210
See Also	212
ListSignalCatalogs	213
Request Syntax	213
Request Parameters	213
Response Syntax	214
Response Elements	214
Errors	215
See Also	216
ListStateTemplates	217
Request Syntax	217
Request Parameters	217
Response Syntax	218
Response Elements	218

Errors	219
See Also	220
ListTagsForResource	221
Request Syntax	221
Request Parameters	221
Response Syntax	221
Response Elements	222
Errors	222
See Also	223
ListVehicles	225
Request Syntax	225
Request Parameters	225
Response Syntax	227
Response Elements	228
Errors	228
See Also	229
ListVehiclesInFleet	231
Request Syntax	231
Request Parameters	231
Response Syntax	232
Response Elements	232
Errors	233
See Also	234
PutEncryptionConfiguration	236
Request Syntax	236
Request Parameters	236
Response Syntax	237
Response Elements	237
Errors	238
See Also	239
PutLoggingOptions	241
Request Syntax	241
Request Parameters	241
Response Elements	241
Errors	241
See Also	243

RegisterAccount	245
Request Syntax	246
Request Parameters	246
Response Syntax	246
Response Elements	247
Errors	248
See Also	249
TagResource	251
Request Syntax	251
Request Parameters	251
Response Elements	252
Errors	252
See Also	253
UntagResource	255
Request Syntax	255
Request Parameters	255
Response Elements	256
Errors	256
See Also	257
UpdateCampaign	259
Request Syntax	259
Request Parameters	259
Response Syntax	260
Response Elements	261
Errors	262
See Also	263
UpdateDecoderManifest	265
Request Syntax	265
Request Parameters	268
Response Syntax	271
Response Elements	271
Errors	271
See Also	274
UpdateFleet	275
Request Syntax	275
Request Parameters	275

Response Syntax	276
Response Elements	276
Errors	276
See Also	278
UpdateModelManifest	279
Request Syntax	279
Request Parameters	279
Response Syntax	281
Response Elements	281
Errors	281
See Also	283
UpdateSignalCatalog	285
Request Syntax	285
Request Parameters	285
Response Syntax	287
Response Elements	287
Errors	287
See Also	290
UpdateStateTemplate	291
Request Syntax	291
Request Parameters	291
Response Syntax	293
Response Elements	293
Errors	294
See Also	296
UpdateVehicle	297
Request Syntax	297
Request Parameters	297
Response Syntax	299
Response Elements	300
Errors	300
See Also	302
Data Types	303
Actuator	306
Contents	306
See Also	309

Attribute	310
Contents	310
See Also	312
Branch	313
Contents	313
See Also	314
CampaignSummary	315
Contents	315
See Also	317
CanDbcDefinition	318
Contents	318
See Also	318
CanInterface	320
Contents	320
See Also	321
CanSignal	322
Contents	322
See Also	324
CloudWatchLogDeliveryOptions	325
Contents	325
See Also	325
CollectionScheme	326
Contents	326
See Also	326
ConditionBasedCollectionScheme	327
Contents	327
See Also	328
ConditionBasedSignalFetchConfig	329
Contents	329
See Also	329
CreateVehicleError	330
Contents	330
See Also	330
CreateVehicleRequestItem	332
Contents	332
See Also	333

CreateVehicleResponseItem	334
Contents	334
See Also	334
CustomDecodingInterface	336
Contents	336
See Also	336
CustomDecodingSignal	337
Contents	337
See Also	337
CustomProperty	338
Contents	338
See Also	340
CustomStruct	341
Contents	341
See Also	342
DataDestinationConfig	343
Contents	343
See Also	343
DataPartition	345
Contents	345
See Also	346
DataPartitionStorageOptions	347
Contents	347
See Also	348
DataPartitionUploadOptions	349
Contents	349
See Also	349
DecoderManifestSummary	351
Contents	351
See Also	352
FleetSummary	354
Contents	354
See Also	355
FormattedVss	356
Contents	356
See Also	356

IamRegistrationResponse	357
Contents	357
See Also	357
IamResources	359
Contents	359
See Also	359
InvalidNetworkInterface	360
Contents	360
See Also	360
InvalidSignal	362
Contents	362
See Also	362
InvalidSignalDecoder	363
Contents	363
See Also	364
MessageSignal	365
Contents	365
See Also	365
ModelManifestSummary	366
Contents	366
See Also	367
MqttTopicConfig	368
Contents	368
See Also	369
NetworkFileDefinition	370
Contents	370
See Also	370
NetworkInterface	371
Contents	371
See Also	372
Node	373
Contents	373
See Also	374
NodeCounts	376
Contents	376
See Also	377

ObdInterface	378
Contents	378
See Also	379
ObdSignal	380
Contents	380
See Also	382
OnChangeStateTemplateUpdateStrategy	383
Contents	383
See Also	383
PeriodicStateTemplateUpdateStrategy	384
Contents	384
See Also	384
PrimitiveMessageDefinition	385
Contents	385
See Also	385
ROS2PrimitiveMessageDefinition	386
Contents	386
See Also	387
S3Config	388
Contents	388
See Also	389
Sensor	390
Contents	390
See Also	392
SignalCatalogSummary	393
Contents	393
See Also	393
SignalDecoder	395
Contents	395
See Also	396
SignalFetchConfig	397
Contents	397
See Also	397
SignalFetchInformation	399
Contents	399
See Also	400

SignalInformation	401
Contents	401
See Also	402
StateTemplateAssociation	403
Contents	403
See Also	404
StateTemplateSummary	405
Contents	405
See Also	406
StateTemplateUpdateStrategy	408
Contents	408
See Also	408
StorageMaximumSize	410
Contents	410
See Also	410
StorageMinimumTimeToLive	412
Contents	412
See Also	412
StructuredMessage	414
Contents	414
See Also	415
StructuredMessageFieldNameAndDataTypePair	416
Contents	416
See Also	416
StructuredMessageListDefinition	417
Contents	417
See Also	418
Tag	419
Contents	419
See Also	419
TimeBasedCollectionScheme	420
Contents	420
See Also	420
TimeBasedSignalFetchConfig	421
Contents	421
See Also	421

TimePeriod	422
Contents	422
See Also	422
TimestreamConfig	423
Contents	423
See Also	423
TimestreamRegistrationResponse	425
Contents	425
See Also	426
TimestreamResources	427
Contents	427
See Also	427
UpdateVehicleError	428
Contents	428
See Also	428
UpdateVehicleRequestItem	430
Contents	430
See Also	432
UpdateVehicleResponseItem	433
Contents	433
See Also	433
ValidationExceptionField	434
Contents	434
See Also	434
VehicleMiddleware	435
Contents	435
See Also	435
VehicleStatus	436
Contents	436
See Also	437
VehicleSummary	438
Contents	438
See Also	439
Common Parameters	440
Common Error Types	443

Welcome

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

AWS IoT FleetWise is a fully managed service that you can use to collect, model, and transfer vehicle data to the AWS cloud at scale. With AWS IoT FleetWise, you can standardize all of your vehicle data models, independent of the in-vehicle communication architecture, and define data collection rules to transfer only high-value data to the cloud.

For more information, see [What is AWS IoT FleetWise?](#) in the *AWS IoT FleetWise Developer Guide*.

This document was last published on September 30, 2026.

Actions

The following actions are supported:

- [AssociateVehicleFleet](#)
- [BatchCreateVehicle](#)
- [BatchUpdateVehicle](#)
- [CreateCampaign](#)
- [CreateDecoderManifest](#)
- [CreateFleet](#)
- [CreateModelManifest](#)
- [CreateSignalCatalog](#)
- [CreateStateTemplate](#)
- [CreateVehicle](#)
- [DeleteCampaign](#)
- [DeleteDecoderManifest](#)
- [DeleteFleet](#)
- [DeleteModelManifest](#)
- [DeleteSignalCatalog](#)
- [DeleteStateTemplate](#)
- [DeleteVehicle](#)
- [DisassociateVehicleFleet](#)
- [GetCampaign](#)
- [GetDecoderManifest](#)
- [GetEncryptionConfiguration](#)
- [GetFleet](#)
- [GetLoggingOptions](#)
- [GetModelManifest](#)
- [GetRegisterAccountStatus](#)
- [GetSignalCatalog](#)
- [GetStateTemplate](#)

- [GetVehicle](#)
- [GetVehicleStatus](#)
- [ImportDecoderManifest](#)
- [ImportSignalCatalog](#)
- [ListCampaigns](#)
- [ListDecoderManifestNetworkInterfaces](#)
- [ListDecoderManifests](#)
- [ListDecoderManifestSignals](#)
- [ListFleets](#)
- [ListFleetsForVehicle](#)
- [ListModelManifestNodes](#)
- [ListModelManifests](#)
- [ListSignalCatalogNodes](#)
- [ListSignalCatalogs](#)
- [ListStateTemplates](#)
- [ListTagsForResource](#)
- [ListVehicles](#)
- [ListVehiclesInFleet](#)
- [PutEncryptionConfiguration](#)
- [PutLoggingOptions](#)
- [RegisterAccount](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdateCampaign](#)
- [UpdateDecoderManifest](#)
- [UpdateFleet](#)
- [UpdateModelManifest](#)
- [UpdateSignalCatalog](#)
- [UpdateStateTemplate](#)
- [UpdateVehicle](#)

AssociateVehicleFleet

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Adds, or associates, a vehicle with a fleet.

Request Syntax

```
{
  "fleetId": "string",
  "vehicleName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

fleetId

The ID of a fleet.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z0-9:_-]+

Required: Yes

vehicleName

The unique ID of the vehicle to associate with the fleet.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\]+

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

InternalServerErrorException

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

LimitExceededException

A service quota was exceeded.

resourceId

The identifier of the resource that was exceeded.

resourceType

The type of resource that was exceeded.

HTTP Status Code: 400

ResourceNotFoundException

The resource wasn't found.

resourceId

The identifier of the resource that wasn't found.

resourceType

The type of resource that wasn't found.

HTTP Status Code: 400

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

BatchCreateVehicle

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Creates a group, or batch, of vehicles.

Note

You must specify a decoder manifest and a vehicle model (model manifest) for each vehicle.

For more information, see [Create multiple vehicles \(AWS CLI\)](#) in the *AWS IoT FleetWise Developer Guide*.

Request Syntax

```
{
  "vehicles": [
    {
      "associationBehavior": "string",
      "attributes": {
        "string" : "string"
      },
      "decoderManifestArn": "string",
      "modelManifestArn": "string",
      "stateTemplates": [
        {
          "identifier": "string",
          "stateTemplateUpdateStrategy": { ... }
        }
      ],
      "tags": [
        {
          "Key": "string",
          "Value": "string"
        }
      ]
    }
  ]
}
```

```
    }
  ],
  "vehicleName": "string"
}
]
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

vehicles

A list of information about each vehicle to create. For more information, see the [CreateVehicleRequestItem](#) API data type.

Type: Array of [CreateVehicleRequestItem](#) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: Yes

Response Syntax

```
{
  "errors": [
    {
      "code": "string",
      "message": "string",
      "vehicleName": "string"
    }
  ],
  "vehicles": [
    {
      "arn": "string",
      "thingArn": "string",
      "vehicleName": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

errors

A list of information about creation errors, or an empty list if there aren't any errors.

Type: Array of [CreateVehicleError](#) objects

vehicles

A list of information about a batch of created vehicles. For more information, see the [CreateVehicleResponseItem](#) API data type.

Type: Array of [CreateVehicleResponseItem](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

InternalServerException

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

LimitExceededException

A service quota was exceeded.

resourceId

The identifier of the resource that was exceeded.

resourceType

The type of resource that was exceeded.

HTTP Status Code: 400

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

BatchUpdateVehicle

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Updates a group, or batch, of vehicles.

Note

You must specify a decoder manifest and a vehicle model (model manifest) for each vehicle.

For more information, see [Update multiple vehicles \(AWS CLI\)](#) in the *AWS IoT FleetWise Developer Guide*.

Request Syntax

```
{
  "vehicles": [
    {
      "attributes": {
        "string" : "string"
      },
      "attributeUpdateMode": "string",
      "decoderManifestArn": "string",
      "modelManifestArn": "string",
      "stateTemplatesToAdd": [
        {
          "identifier": "string",
          "stateTemplateUpdateStrategy": { ... }
        }
      ],
      "stateTemplatesToRemove": [ "string" ],
      "stateTemplatesToUpdate": [
        {
          "identifier": "string",
```

```
        "stateTemplateUpdateStrategy": { ... }
      },
    ],
    "vehicleName": "string"
  }
]
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[vehicles](#)

A list of information about the vehicles to update. For more information, see the [UpdateVehicleRequestItem](#) API data type.

Type: Array of [UpdateVehicleRequestItem](#) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: Yes

Response Syntax

```
{
  "errors": [
    {
      "code": number,
      "message": "string",
      "vehicleName": "string"
    }
  ],
  "vehicles": [
    {
      "arn": "string",
      "vehicleName": "string"
    }
  ]
}
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

errors

A list of information about errors returned while updating a batch of vehicles, or, if there aren't any errors, an empty list.

Type: Array of [UpdateVehicleError](#) objects

vehicles

A list of information about the batch of updated vehicles.

Note

This list contains only unique IDs for the vehicles that were updated.

Type: Array of [UpdateVehicleResponseItem](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

InternalServerError

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

LimitExceededException

A service quota was exceeded.

resourceId

The identifier of the resource that was exceeded.

resourceType

The type of resource that was exceeded.

HTTP Status Code: 400

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

CreateCampaign

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Creates an orchestration of data collection rules. The AWS IoT FleetWise Edge Agent software running in vehicles uses campaigns to decide how to collect and transfer data to the cloud. You create campaigns in the cloud. After you or your team approve campaigns, AWS IoT FleetWise automatically deploys them to vehicles.

For more information, see [Collect and transfer data with campaigns](#) in the *AWS IoT FleetWise Developer Guide*.

Request Syntax

```
{
  "collectionScheme": { ... },
  "compression": "string",
  "dataDestinationConfigs": [
    { ... }
  ],
  "dataExtraDimensions": [ "string" ],
  "dataPartitions": [
    {
      "id": "string",
      "storageOptions": {
        "maximumSize": {
          "unit": "string",
          "value": number
        },
        "minimumTimeToLive": {
          "unit": "string",
          "value": number
        },
        "storageLocation": "string"
      },
      "uploadOptions": {
        "conditionLanguageVersion": number,
```

```

        "expression": "string"
      }
    ],
    "description": "string",
    "diagnosticsMode": "string",
    "expiryTime": number,
    "name": "string",
    "postTriggerCollectionDuration": number,
    "priority": number,
    "signalCatalogArn": "string",
    "signalsToCollect": [
      {
        "dataPartitionId": "string",
        "maxSampleCount": number,
        "minimumSamplingIntervalMs": number,
        "name": "string"
      }
    ],
    "signalsToFetch": [
      {
        "actions": [ "string" ],
        "conditionLanguageVersion": number,
        "fullyQualifiedName": "string",
        "signalFetchConfig": { ... }
      }
    ],
    "spoolingMode": "string",
    "startTime": number,
    "tags": [
      {
        "Key": "string",
        "Value": "string"
      }
    ],
    "targetArn": "string"
  }
}

```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

collectionScheme

The data collection scheme associated with the campaign. You can specify a scheme that collects data based on time or an event.

Type: [CollectionScheme](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

compression

Determines whether to compress signals before transmitting data to AWS IoT FleetWise. If you don't want to compress the signals, use OFF. If it's not specified, SNAPPY is used.

Default: SNAPPY

Type: String

Valid Values: OFF | SNAPPY

Required: No

dataDestinationConfigs

The destination where the campaign sends data. You can send data to an MQTT topic, or store it in Amazon S3 or Amazon Timestream.

MQTT is the publish/subscribe messaging protocol used by AWS IoT to communicate with your devices.

Amazon S3 optimizes the cost of data storage and provides additional mechanisms to use vehicle data, such as data lakes, centralized data storage, data processing pipelines, and analytics. AWS IoT FleetWise supports at-least-once file delivery to S3. Your vehicle data is stored on multiple AWS IoT FleetWise servers for redundancy and high availability.

You can use Amazon Timestream to access and analyze time series data, and Timestream to query vehicle data so that you can identify trends and patterns.

Type: Array of [DataDestinationConfig](#) objects

Array Members: Minimum number of 1 item. Maximum number of 3 items.

Required: No

dataExtraDimensions

A list of vehicle attributes to associate with a campaign.

Enrich the data with specified vehicle attributes. For example, add `make` and `model` to the campaign, and AWS IoT FleetWise will associate the data with those attributes as dimensions in Amazon Timestream. You can then query the data against `make` and `model`.

Default: An empty array

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Length Constraints: Minimum length of 1. Maximum length of 150.

Pattern: `[a-zA-Z0-9_.]`+

Required: No

dataPartitions

The data partitions associated with the signals collected from the vehicle.

Type: Array of [DataPartition](#) objects

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Required: No

description

An optional description of the campaign to help identify its purpose.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]`+

Required: No

diagnosticsMode

Option for a vehicle to send diagnostic trouble codes to AWS IoT FleetWise. If you want to send diagnostic trouble codes, use `SEND_ACTIVE_DTCS`. If it's not specified, `OFF` is used.

Default: OFF

Type: String

Valid Values: OFF | SEND_ACTIVE_DTCS

Required: No

expiryTime

The time the campaign expires, in seconds since epoch (January 1, 1970 at midnight UTC time). Vehicle data isn't collected after the campaign expires.

Default: 253402214400 (December 31, 9999, 00:00:00 UTC)

Type: Timestamp

Required: No

name

The name of the campaign to create.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\]+

Required: Yes

postTriggerCollectionDuration

How long (in milliseconds) to collect raw data after a triggering event initiates the collection. If it's not specified, 0 is used.

Default: 0

Type: Long

Valid Range: Minimum value of 0. Maximum value of 4294967295.

Required: No

priority

This parameter has been deprecated.

A number indicating the priority of one campaign over another campaign for a certain vehicle or fleet. A campaign with the lowest value is deployed to vehicles before any other campaigns. If it's not specified, 0 is used.

Default: 0

Type: Integer

Valid Range: Minimum value of 0.

Required: No

[signalCatalogArn](#)

The Amazon Resource Name (ARN) of the signal catalog to associate with the campaign.

Type: String

Required: Yes

[signalsToCollect](#)

A list of information about signals to collect.

Note

If you upload a signal as a condition in a data partition for a campaign, then those same signals must be included in `signalsToCollect`.

Type: Array of [SignalInformation](#) objects

Array Members: Minimum number of 0 items. Maximum number of 1000 items.

Required: No

[signalsToFetch](#)

A list of information about signals to fetch.

Type: Array of [SignalFetchInformation](#) objects

Array Members: Minimum number of 1 item. Maximum number of 2 items.

Required: No

spoolingMode

Determines whether to store collected data after a vehicle lost a connection with the cloud. After a connection is re-established, the data is automatically forwarded to AWS IoT FleetWise. If you want to store collected data when a vehicle loses connection with the cloud, use `T0_DISK`. If it's not specified, `OFF` is used.

Default: `OFF`

Type: String

Valid Values: `OFF` | `T0_DISK`

Required: No

startTime

The time, in milliseconds, to deliver a campaign after it was approved. If it's not specified, `0` is used.

Default: `0`

Type: Timestamp

Required: No

tags

Metadata that can be used to manage the campaign.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

targetArn

The ARN of the vehicle or fleet to deploy a campaign to.

Type: String

Required: Yes

Response Syntax

```
{
  "arn": "string",
  "name": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The ARN of the created campaign.

Type: String

Pattern: `arn:aws:iotfleetwise:[a-z0-9-]+:[0-9]{12}:campaign/[a-zA-Z\d\-\_:]{1,100}`

name

The name of the created campaign.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[a-zA-Z\d\-\_:]+`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

ConflictException

The request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

resource

The resource on which there are conflicting operations.

resourceType

The type of resource on which there are conflicting operations..

HTTP Status Code: 400

InternalServerErrorException

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

LimitExceededException

A service quota was exceeded.

resourceId

The identifier of the resource that was exceeded.

resourceType

The type of resource that was exceeded.

HTTP Status Code: 400

ResourceNotFoundException

The resource wasn't found.

resourceId

The identifier of the resource that wasn't found.

resourceType

The type of resource that wasn't found.

HTTP Status Code: 400

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

CreateDecoderManifest

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Creates the decoder manifest associated with a model manifest. To create a decoder manifest, the following must be true:

- Every signal decoder has a unique name.
- Each signal decoder is associated with a network interface.
- Each network interface has a unique ID.
- The signal decoders are specified in the model manifest.

Request Syntax

```
{
  "defaultForUnmappedSignals": "string",
  "description": "string",
  "modelManifestArn": "string",
  "name": "string",
  "networkInterfaces": [
    {
      "canInterface": {
        "name": "string",
        "protocolName": "string",
        "protocolVersion": "string"
      },
      "customDecodingInterface": {
        "name": "string"
      },
      "interfaceId": "string",
      "obdInterface": {
        "dtcRequestIntervalSeconds": number,
        "hasTransmissionEcu": boolean,
        "name": "string",
        "obdStandard": "string",
```

```

        "pidRequestIntervalSeconds": number,
        "requestMessageId": number,
        "useExtendedIds": boolean
    },
    "type": "string",
    "vehicleMiddleware": {
        "name": "string",
        "protocolName": "string"
    }
}
],
"signalDecoders": [
    {
        "canSignal": {
            "factor": number,
            "isBigEndian": boolean,
            "isSigned": boolean,
            "length": number,
            "messageId": number,
            "name": "string",
            "offset": number,
            "signalValueType": "string",
            "startBit": number
        },
        "customDecodingSignal": {
            "id": "string"
        },
        "fullyQualified_name": "string",
        "interfaceId": "string",
        "messageSignal": {
            "structuredMessage": { ... },
            "topicName": "string"
        },
        "obdSignal": {
            "bitMaskLength": number,
            "bitRightShift": number,
            "byteLength": number,
            "isSigned": boolean,
            "offset": number,
            "pid": number,
            "pidResponseLength": number,
            "scaling": number,
            "serviceMode": number,
            "signalValueType": "string",

```

```
        "startByte": number
      },
      "type": "string"
    }
  ],
  "tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[defaultForUnmappedSignals](#)

Use default decoders for all unmapped signals in the model. You don't need to provide any detailed decoding information.

Type: String

Valid Values: CUSTOM_DECODING

Required: No

[description](#)

A brief description of the decoder manifest.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

[modelManifestArn](#)

The Amazon Resource Name (ARN) of the vehicle model (model manifest).

Type: String

Pattern: `arn:aws:iotfleetwise:[a-z0-9-]+:[0-9]{12}:model-manifest/[a-zA-Z\d\-\_:]{1,100}`

Required: Yes

name

The unique name of the decoder manifest to create.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[a-zA-Z\d\-\_:]`+

Required: Yes

networkInterfaces

A list of information about available network interfaces.

Type: Array of [NetworkInterface](#) objects

Array Members: Minimum number of 1 item. Maximum number of 500 items.

Required: No

signalDecoders

A list of information about signal decoders.

Type: Array of [SignalDecoder](#) objects

Array Members: Minimum number of 1 item. Maximum number of 500 items.

Required: No

tags

Metadata that can be used to manage the decoder manifest.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

Response Syntax

```
{  
  "arn": "string",  
  "name": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[arn](#)

The ARN of the created decoder manifest.

Type: String

[name](#)

The name of the created decoder manifest.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\.]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

ConflictException

The request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

resource

The resource on which there are conflicting operations.

resourceType

The type of resource on which there are conflicting operations..

HTTP Status Code: 400

DecoderManifestValidationException

The request couldn't be completed because it contains signal decoders with one or more validation errors.

invalidNetworkInterfaces

The request couldn't be completed because of invalid network interfaces in the request.

invalidSignals

The request couldn't be completed because of invalid signals in the request.

HTTP Status Code: 400

InternalServerError

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

LimitExceededException

A service quota was exceeded.

resourceId

The identifier of the resource that was exceeded.

resourceType

The type of resource that was exceeded.

HTTP Status Code: 400

ResourceNotFoundException

The resource wasn't found.

resourceId

The identifier of the resource that wasn't found.

resourceType

The type of resource that wasn't found.

HTTP Status Code: 400

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

CreateFleet

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Creates a fleet that represents a group of vehicles.

Note

You must create both a signal catalog and vehicles before you can create a fleet.

For more information, see [Fleets](#) in the *AWS IoT FleetWise Developer Guide*.

Request Syntax

```
{
  "description": "string",
  "fleetId": "string",
  "signalCatalogArn": "string",
  "tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

description

A brief description of the fleet to create.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

[fleetId](#)

The unique ID of the fleet to create.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[a-zA-Z0-9:_-]+`

Required: Yes

[signalCatalogArn](#)

The Amazon Resource Name (ARN) of a signal catalog.

Type: String

Required: Yes

[tags](#)

Metadata that can be used to manage the fleet.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

Response Syntax

```
{
  "arn": "string",
  "id": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The ARN of the created fleet.

Type: String

id

The ID of the created fleet.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z0-9:_-]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

ConflictException

The request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

resource

The resource on which there are conflicting operations.

resourceType

The type of resource on which there are conflicting operations..

HTTP Status Code: 400

InternalServerErrorException

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

LimitExceededException

A service quota was exceeded.

resourceId

The identifier of the resource that was exceeded.

resourceType

The type of resource that was exceeded.

HTTP Status Code: 400

ResourceNotFoundException

The resource wasn't found.

resourceId

The identifier of the resource that wasn't found.

resourceType

The type of resource that wasn't found.

HTTP Status Code: 400

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

CreateModelManifest

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Creates a vehicle model (model manifest) that specifies signals (attributes, branches, sensors, and actuators).

For more information, see [Vehicle models](#) in the *AWS IoT FleetWise Developer Guide*.

Request Syntax

```
{
  "description": "string",
  "name": "string",
  "nodes": [ "string" ],
  "signalCatalogArn": "string",
  "tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

description

A brief description of the vehicle model.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: [^\u0000-\u001F\u007F]+

Required: No

name

The name of the vehicle model to create.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\.]+

Required: Yes

nodes

A list of nodes, which are a general abstraction of signals.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 500 items.

Required: Yes

signalCatalogArn

The Amazon Resource Name (ARN) of a signal catalog.

Type: String

Required: Yes

tags

Metadata that can be used to manage the vehicle model.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

Response Syntax

```
{
```

```
"arn": "string",  
"name": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[arn](#)

The ARN of the created vehicle model.

Type: String

[name](#)

The name of the created vehicle model.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

ConflictException

The request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

resource

The resource on which there are conflicting operations.

resourceType

The type of resource on which there are conflicting operations..

HTTP Status Code: 400

InternalServerError

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

InvalidSignalsException

The request couldn't be completed because it contains signals that aren't valid.

invalidSignals

The signals which caused the exception.

HTTP Status Code: 400

LimitExceededException

A service quota was exceeded.

resourceId

The identifier of the resource that was exceeded.

resourceType

The type of resource that was exceeded.

HTTP Status Code: 400

ResourceNotFoundException

The resource wasn't found.

resourceId

The identifier of the resource that wasn't found.

resourceType

The type of resource that wasn't found.

HTTP Status Code: 400

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

CreateSignalCatalog

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Creates a collection of standardized signals that can be reused to create vehicle models.

Request Syntax

```
{
  "description": "string",
  "name": "string",
  "nodes": [
    { ... }
  ],
  "tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

description

A brief description of the signal catalog.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

name

The name of the signal catalog to create.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\.]+

Required: Yes

nodes

A list of information about nodes, which are a general abstraction of signals. For more information, see the [Node](#) API data type.

Type: Array of [Node](#) objects

Array Members: Minimum number of 0 items. Maximum number of 500 items.

Required: No

tags

Metadata that can be used to manage the signal catalog.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

Response Syntax

```
{
  "arn": "string",
  "name": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The ARN of the created signal catalog.

Type: String

name

The name of the created signal catalog.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\.]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

ConflictException

The request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

resource

The resource on which there are conflicting operations.

resourceType

The type of resource on which there are conflicting operations..

HTTP Status Code: 400

InternalServerErrorException

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

InvalidNodeException

The specified node type doesn't match the expected node type for a node. You can specify the node type as branch, sensor, actuator, or attribute.

invalidNodes

The specified node type isn't valid.

reason

The reason the node validation failed.

HTTP Status Code: 400

InvalidSignalsException

The request couldn't be completed because it contains signals that aren't valid.

invalidSignals

The signals which caused the exception.

HTTP Status Code: 400

LimitExceededException

A service quota was exceeded.

resourceId

The identifier of the resource that was exceeded.

resourceType

The type of resource that was exceeded.

HTTP Status Code: 400

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)

- [AWS SDK for Ruby V3](#)

CreateStateTemplate

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Creates a state template. State templates contain state properties, which are signals that belong to a signal catalog that is synchronized between the AWS IoT FleetWise Edge and the AWS Cloud.

Request Syntax

```
{
  "dataExtraDimensions": [ "string" ],
  "description": "string",
  "metadataExtraDimensions": [ "string" ],
  "name": "string",
  "signalCatalogArn": "string",
  "stateTemplateProperties": [ "string" ],
  "tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

dataExtraDimensions

A list of vehicle attributes to associate with the payload published on the state template's MQTT topic. (See [Processing last known state vehicle data using MQTT messaging](#)). For example, if you add `Vehicle.Attributes.Make` and `Vehicle.Attributes.Model`

attributes, AWS IoT FleetWise will enrich the protobuf encoded payload with those attributes in the `extraDimensions` field.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Length Constraints: Minimum length of 1. Maximum length of 150.

Pattern: `[a-zA-Z0-9_.]`+

Required: No

description

A brief description of the state template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]`+

Required: No

metadataExtraDimensions

A list of vehicle attributes to associate with user properties of the messages published on the state template's MQTT topic. (See [Processing last known state vehicle data using MQTT messaging](#)). For example, if you add `Vehicle.Attributes.Make` and `Vehicle.Attributes.Model` attributes, AWS IoT FleetWise will include these attributes as User Properties with the MQTT message.

Default: An empty array

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Length Constraints: Minimum length of 1. Maximum length of 150.

Pattern: `[a-zA-Z0-9_.]`+

Required: No

name

The name of the state template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\]+

Required: Yes

signalCatalogArn

The ARN of the signal catalog associated with the state template.

Type: String

Required: Yes

stateTemplateProperties

A list of signals from which data is collected. The state template properties contain the fully qualified names of the signals.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 500 items.

Length Constraints: Minimum length of 1. Maximum length of 150.

Pattern: [a-zA-Z0-9_\.\]+

Required: Yes

tags

Metadata that can be used to manage the state template.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

Response Syntax

```
{  
  "arn": "string",  
  "id": "string",  
  "name": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[arn](#)

The Amazon Resource Name (ARN) of the state template.

Type: String

[id](#)

The unique ID of the state template.

Type: String

Length Constraints: Fixed length of 26.

Pattern: [A-Z0-9]+

[name](#)

The name of the state template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

ConflictException

The request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

resource

The resource on which there are conflicting operations.

resourceType

The type of resource on which there are conflicting operations..

HTTP Status Code: 400

InternalServerError

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

InvalidSignalsException

The request couldn't be completed because it contains signals that aren't valid.

invalidSignals

The signals which caused the exception.

HTTP Status Code: 400

LimitExceededException

A service quota was exceeded.

resourceId

The identifier of the resource that was exceeded.

resourceType

The type of resource that was exceeded.

HTTP Status Code: 400

ResourceNotFoundException

The resource wasn't found.

resourceId

The identifier of the resource that wasn't found.

resourceType

The type of resource that wasn't found.

HTTP Status Code: 400

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

CreateVehicle

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Creates a vehicle, which is an instance of a vehicle model (model manifest). Vehicles created from the same vehicle model consist of the same signals inherited from the vehicle model.

Note

If you have an existing AWS IoT thing, you can use AWS IoT FleetWise to create a vehicle and collect data from your thing.

For more information, see [Create a vehicle \(AWS CLI\)](#) in the *AWS IoT FleetWise Developer Guide*.

Request Syntax

```
{
  "associationBehavior": "string",
  "attributes": {
    "string" : "string"
  },
  "decoderManifestArn": "string",
  "modelManifestArn": "string",
  "stateTemplates": [
    {
      "identifier": "string",
      "stateTemplateUpdateStrategy": { ... }
    }
  ],
  "tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ],
}
```

```
"vehicleName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

associationBehavior

An option to create a new AWS IoT thing when creating a vehicle, or to validate an existing AWS IoT thing as a vehicle.

Default:

Type: String

Valid Values: CreateIotThing | ValidateIotThingExists

Required: No

attributes

Static information about a vehicle in a key-value pair. For example: "engineType" : "1.3 L R2"

To use attributes with Campaigns or State Templates, you must include them using the request parameters `dataExtraDimensions` and/or `metadataExtraDimensions` (for state templates only) when creating your campaign/state template.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 150.

Key Pattern: [a-zA-Z0-9_.-]+

Required: No

decoderManifestArn

The ARN of a decoder manifest.

Type: String

Required: Yes

[modelManifestArn](#)

The Amazon Resource Name ARN of a vehicle model.

Type: String

Required: Yes

[stateTemplates](#)

Associate state templates with the vehicle. You can monitor the last known state of the vehicle in near real time.

Type: Array of [StateTemplateAssociation](#) objects

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Required: No

[tags](#)

Metadata that can be used to manage the vehicle.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

[vehicleName](#)

The unique ID of the vehicle to create.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[a-zA-Z\d\-\_:\.]+`

Required: Yes

Response Syntax

```
{
```

```
"arn": "string",  
"thingArn": "string",  
"vehicleName": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[arn](#)

The ARN of the created vehicle.

Type: String

[thingArn](#)

The ARN of a created or validated AWS IoT thing.

Type: String

[vehicleName](#)

The unique ID of the created vehicle.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\.]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

ConflictException

The request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

resource

The resource on which there are conflicting operations.

resourceType

The type of resource on which there are conflicting operations..

HTTP Status Code: 400

InternalServerErrorException

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

LimitExceededException

A service quota was exceeded.

resourceId

The identifier of the resource that was exceeded.

resourceType

The type of resource that was exceeded.

HTTP Status Code: 400

ResourceNotFoundException

The resource wasn't found.

resourceId

The identifier of the resource that wasn't found.

resourceType

The type of resource that wasn't found.

HTTP Status Code: 400

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DeleteCampaign

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Deletes a data collection campaign. Deleting a campaign suspends all data collection and removes it from any vehicles.

Request Syntax

```
{  
  "name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

name

The name of the campaign to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\+]

Required: Yes

Response Syntax

```
{  
  "arn": "string",  
}
```



```
"name": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The Amazon Resource Name (ARN) of the deleted campaign.

Note

The ARN isn't returned if a campaign doesn't exist.

Type: String

Pattern: `arn:aws:iotfleetwise:[a-z0-9-]+:[0-9]{12}:campaign/[a-zA-Z\d\-\_:]`
`{1,100}`

name

The name of the deleted campaign.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[a-zA-Z\d\-_:]``+`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

InternalServerErrorException

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

ResourceNotFoundException

The resource wasn't found.

resourceId

The identifier of the resource that wasn't found.

resourceType

The type of resource that wasn't found.

HTTP Status Code: 400

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DeleteDecoderManifest

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Deletes a decoder manifest. You can't delete a decoder manifest if it has vehicles associated with it.

Request Syntax

```
{  
  "name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

name

The name of the decoder manifest to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\]+

Required: Yes

Response Syntax

```
{  
  "arn": "string",  
  "name": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The Amazon Resource Name (ARN) of the deleted decoder manifest.

Type: String

name

The name of the deleted decoder manifest.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\.]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

ConflictException

The request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

resource

The resource on which there are conflicting operations.

resourceType

The type of resource on which there are conflicting operations..

HTTP Status Code: 400

InternalServerErrorException

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DeleteFleet

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Deletes a fleet. Before you delete a fleet, all vehicles must be dissociated from the fleet. For more information, see [Delete a fleet \(AWS CLI\)](#) in the *AWS IoT FleetWise Developer Guide*.

Request Syntax

```
{
  "fleetId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[fleetId](#)

The ID of the fleet to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z0-9:_-]+

Required: Yes

Response Syntax

```
{
  "arn": "string",

```



```
"id": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The Amazon Resource Name (ARN) of the deleted fleet.

Type: String

id

The ID of the deleted fleet.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z0-9:_-]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

InternalServerException

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DeleteModelManifest

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Deletes a vehicle model (model manifest).

Request Syntax

```
{  
  "name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

name

The name of the model manifest to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\]+

Required: Yes

Response Syntax

```
{  
  "arn": "string",  
  "name": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The Amazon Resource Name (ARN) of the deleted model manifest.

Type: String

name

The name of the deleted model manifest.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

ConflictException

The request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

resource

The resource on which there are conflicting operations.

resourceType

The type of resource on which there are conflicting operations..

HTTP Status Code: 400

InternalServerErrorException

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DeleteSignalCatalog

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Deletes a signal catalog.

Request Syntax

```
{  
  "name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

name

The name of the signal catalog to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\]+

Required: Yes

Response Syntax

```
{  
  "arn": "string",  
  "name": "string"  
}
```


Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The Amazon Resource Name (ARN) of the deleted signal catalog.

Type: String

name

The name of the deleted signal catalog.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

ConflictException

The request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

resource

The resource on which there are conflicting operations.

resourceType

The type of resource on which there are conflicting operations..

HTTP Status Code: 400

InternalServerErrorException

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DeleteStateTemplate

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Deletes a state template.

Request Syntax

```
{  
  "identifier": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

identifier

The unique ID of the state template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\.]+

Required: Yes

Response Syntax

```
{  
  "arn": "string",  
  "id": "string",  
}
```

```
"name": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The Amazon Resource Name (ARN) of the state template.

Type: String

id

The unique ID of the state template.

Type: String

Length Constraints: Fixed length of 26.

Pattern: [A-Z0-9]+

name

The name of the state template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\.]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

InternalServerError

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DeleteVehicle

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Deletes a vehicle and removes it from any campaigns.

Request Syntax

```
{  
  "vehicleName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

vehicleName

The ID of the vehicle to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\+]

Required: Yes

Response Syntax

```
{  
  "arn": "string",  
  "vehicleName": "string"  
}
```



```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The Amazon Resource Name (ARN) of the deleted vehicle.

Type: String

vehicleName

The ID of the deleted vehicle.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\.]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

InternalServerErrorException

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

DisassociateVehicleFleet

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Removes, or disassociates, a vehicle from a fleet. Disassociating a vehicle from a fleet doesn't delete the vehicle.

Request Syntax

```
{  
  "fleetId": "string",  
  "vehicleName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

fleetId

The unique ID of a fleet.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z0-9:_-]+

Required: Yes

vehicleName

The unique ID of the vehicle to disassociate from the fleet.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\]+

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

InternalServerError

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

ResourceNotFoundException

The resource wasn't found.

resourceId

The identifier of the resource that wasn't found.

resourceType

The type of resource that wasn't found.

HTTP Status Code: 400

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)

- [AWS SDK for Ruby V3](#)

GetCampaign

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Retrieves information about a campaign.

Request Syntax

```
{  
  "name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

name

The name of the campaign to retrieve information about.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\+]

Required: Yes

Response Syntax

```
{  
  "arn": "string",  
  "collectionScheme": { ... },  
  "compression": "string",  
  "creationTime": number,  
}
```



```

    "dataDestinationConfigs": [
      { ... }
    ],
    "dataExtraDimensions": [ "string" ],
    "dataPartitions": [
      {
        "id": "string",
        "storageOptions": {
          "maximumSize": {
            "unit": "string",
            "value": number
          },
          "minimumTimeToLive": {
            "unit": "string",
            "value": number
          },
          "storageLocation": "string"
        },
        "uploadOptions": {
          "conditionLanguageVersion": number,
          "expression": "string"
        }
      }
    ],
    "description": "string",
    "diagnosticsMode": "string",
    "expiryTime": number,
    "lastModificationTime": number,
    "name": "string",
    "postTriggerCollectionDuration": number,
    "priority": number,
    "signalCatalogArn": "string",
    "signalsToCollect": [
      {
        "dataPartitionId": "string",
        "maxSampleCount": number,
        "minimumSamplingIntervalMs": number,
        "name": "string"
      }
    ],
    "signalsToFetch": [
      {
        "actions": [ "string" ],
        "conditionLanguageVersion": number,

```

```
    "fullyQualifiedNames": "string",  
    "signalFetchConfig": { ... }  
  }  
],  
"spoolingMode": "string",  
"startTime": number,  
"status": "string",  
"targetArn": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The Amazon Resource Name (ARN) of the campaign.

Type: String

Pattern: `arn:aws:iotfleetwise:[a-z0-9-]+:[0-9]{12}:campaign/[a-zA-Z\d\-\_:]`
`{1,100}`

collectionScheme

Information about the data collection scheme associated with the campaign.

Type: [CollectionScheme](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

compression

Whether to compress signals before transmitting data to AWS IoT FleetWise. If OFF is specified, the signals aren't compressed. If it's not specified, SNAPPY is used.

Type: String

Valid Values: OFF | SNAPPY

creationTime

The time the campaign was created in seconds since epoch (January 1, 1970 at midnight UTC time).

Type: Timestamp

dataDestinationConfigs

The destination where the campaign sends data. You can send data to an MQTT topic, or store it in Amazon S3 or Amazon Timestream.

MQTT is the publish/subscribe messaging protocol used by AWS IoT to communicate with your devices.

Amazon S3 optimizes the cost of data storage and provides additional mechanisms to use vehicle data, such as data lakes, centralized data storage, data processing pipelines, and analytics.

You can use Amazon Timestream to access and analyze time series data, and Timestream to query vehicle data so that you can identify trends and patterns.

Type: Array of [DataDestinationConfig](#) objects

Array Members: Minimum number of 1 item. Maximum number of 3 items.

dataExtraDimensions

A list of vehicle attributes associated with the campaign.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Length Constraints: Minimum length of 1. Maximum length of 150.

Pattern: [a-zA-Z0-9_\.]+

dataPartitions

The data partitions associated with the signals collected from the vehicle.

Type: Array of [DataPartition](#) objects

Array Members: Minimum number of 1 item. Maximum number of 20 items.

description

The description of the campaign.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

diagnosticsMode

Option for a vehicle to send diagnostic trouble codes to AWS IoT FleetWise.

Type: String

Valid Values: OFF | SEND_ACTIVE_DTCS

expiryTime

The time the campaign expires, in seconds since epoch (January 1, 1970 at midnight UTC time).
Vehicle data won't be collected after the campaign expires.

Type: Timestamp

lastModificationTime

The last time the campaign was modified.

Type: Timestamp

name

The name of the campaign.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[a-zA-Z\d\-\_:\.]+`

postTriggerCollectionDuration

How long (in seconds) to collect raw data after a triggering event initiates the collection.

Type: Long

Valid Range: Minimum value of 0. Maximum value of 4294967295.

priority

A number indicating the priority of one campaign over another campaign for a certain vehicle or fleet. A campaign with the lowest value is deployed to vehicles before any other campaigns.

Type: Integer

Valid Range: Minimum value of 0.

signalCatalogArn

The ARN of a signal catalog.

Type: String

signalsToCollect

Information about a list of signals to collect data on.

Type: Array of [SignalInformation](#) objects

Array Members: Minimum number of 0 items. Maximum number of 1000 items.

signalsToFetch

Information about a list of signals to fetch data from.

Type: Array of [SignalFetchInformation](#) objects

Array Members: Minimum number of 1 item. Maximum number of 2 items.

spoolingMode

Whether to store collected data after a vehicle lost a connection with the cloud. After a connection is re-established, the data is automatically forwarded to AWS IoT FleetWise.

Type: String

Valid Values: OFF | TO_DISK

startTime

The time, in milliseconds, to deliver a campaign after it was approved.

Type: Timestamp

status

The state of the campaign. The status can be one of: CREATING, WAITING_FOR_APPROVAL, RUNNING, and SUSPENDED.

Type: String

Valid Values: CREATING | WAITING_FOR_APPROVAL | RUNNING | SUSPENDED

targetArn

The ARN of the vehicle or the fleet targeted by the campaign.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

InternalServerErrorException

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

ResourceNotFoundException

The resource wasn't found.

resourceId

The identifier of the resource that wasn't found.

resourceType

The type of resource that wasn't found.

HTTP Status Code: 400

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)

- [AWS SDK for Ruby V3](#)

GetDecoderManifest

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Retrieves information about a created decoder manifest.

Request Syntax

```
{  
  "name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

name

The name of the decoder manifest to retrieve information about.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\+]

Required: Yes

Response Syntax

```
{  
  "arn": "string",  
  "creationTime": number,  
  ...  
}
```

```
"description": "string",  
"lastModificationTime": number,  
"message": "string",  
"modelManifestArn": "string",  
"name": "string",  
"status": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[arn](#)

The Amazon Resource Name (ARN) of the decoder manifest.

Type: String

[creationTime](#)

The time the decoder manifest was created in seconds since epoch (January 1, 1970 at midnight UTC time).

Type: Timestamp

[description](#)

A brief description of the decoder manifest.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

[lastModificationTime](#)

The time the decoder manifest was last updated in seconds since epoch (January 1, 1970 at midnight UTC time).

Type: Timestamp

message

The detailed message for the decoder manifest. When a decoder manifest is in an `INVALID` status, the message contains detailed reason and help information.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

modelManifestArn

The ARN of a vehicle model (model manifest) associated with the decoder manifest.

Type: String

name

The name of the decoder manifest.

Type: String

status

The state of the decoder manifest. If the status is `ACTIVE`, the decoder manifest can't be edited. If the status is marked `DRAFT`, you can edit the decoder manifest.

Type: String

Valid Values: `ACTIVE` | `DRAFT` | `INVALID` | `VALIDATING`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

InternalServerErrorException

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

ResourceNotFoundException

The resource wasn't found.

resourceId

The identifier of the resource that wasn't found.

resourceType

The type of resource that wasn't found.

HTTP Status Code: 400

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetEncryptionConfiguration

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Retrieves the encryption configuration for resources and data in AWS IoT FleetWise.

Response Syntax

```
{
  "creationTime": number,
  "encryptionStatus": "string",
  "encryptionType": "string",
  "errorMessage": "string",
  "kmsKeyId": "string",
  "lastModificationTime": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

creationTime

The time when encryption was configured in seconds since epoch (January 1, 1970 at midnight UTC time).

Type: Timestamp

encryptionStatus

The encryption status.

Type: String

Valid Values: PENDING | SUCCESS | FAILURE

encryptionType

The type of encryption. Set to KMS_BASED_ENCRYPTION to use a KMS key that you own and manage. Set to FLEETWISE_DEFAULT_ENCRYPTION to use an AWS managed key that is owned by the AWS IoT FleetWise service account.

Type: String

Valid Values: KMS_BASED_ENCRYPTION | FLEETWISE_DEFAULT_ENCRYPTION

errorMessage

The error message that describes why encryption settings couldn't be configured, if applicable.

Type: String

kmsKeyId

The ID of the KMS key that is used for encryption.

Type: String

lastModificationTime

The time when encryption was last updated in seconds since epoch (January 1, 1970 at midnight UTC time).

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

InternalServerErrorException

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

ResourceNotFoundException

The resource wasn't found.

resourceId

The identifier of the resource that wasn't found.

resourceType

The type of resource that wasn't found.

HTTP Status Code: 400

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetFleet

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Retrieves information about a fleet.

Request Syntax

```
{  
  "fleetId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[fleetId](#)

The ID of the fleet to retrieve information about.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z0-9:_-]+

Required: Yes

Response Syntax

```
{  
  "arn": "string",  
}
```

```
"creationTime": number,  
"description": "string",  
"id": "string",  
"lastModificationTime": number,  
"signalCatalogArn": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[arn](#)

The Amazon Resource Name (ARN) of the fleet.

Type: String

[creationTime](#)

The time the fleet was created in seconds since epoch (January 1, 1970 at midnight UTC time).

Type: Timestamp

[description](#)

A brief description of the fleet.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

[id](#)

The ID of the fleet.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[a-zA-Z0-9:_-]+`

lastModificationTime

The time the fleet was last updated, in seconds since epoch (January 1, 1970 at midnight UTC time).

Type: Timestamp

signalCatalogArn

The ARN of a signal catalog associated with the fleet.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

InternalServerError

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

ResourceNotFoundException

The resource wasn't found.

resourceId

The identifier of the resource that wasn't found.

resourceType

The type of resource that wasn't found.

HTTP Status Code: 400

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetLoggingOptions

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Retrieves the logging options.

Response Syntax

```
{
  "cloudWatchLogDelivery": {
    "logGroupName": "string",
    "logType": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[cloudWatchLogDelivery](#)

Returns information about log delivery to Amazon CloudWatch Logs.

Type: [CloudWatchLogDeliveryOptions](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

InternalServerError

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)

- [AWS SDK for Ruby V3](#)

GetModelManifest

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Retrieves information about a vehicle model (model manifest).

Request Syntax

```
{  
  "name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

name

The name of the vehicle model to retrieve information about.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\.]+

Required: Yes

Response Syntax

```
{  
  "arn": "string",  
  "creationTime": number,  
  "description": "string",
```

```
"lastModificationTime": number,  
"name": "string",  
"signalCatalogArn": "string",  
"status": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The Amazon Resource Name (ARN) of the vehicle model.

Type: String

creationTime

The time the vehicle model was created, in seconds since epoch (January 1, 1970 at midnight UTC time).

Type: Timestamp

description

A brief description of the vehicle model.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

lastModificationTime

The last time the vehicle model was modified.

Type: Timestamp

name

The name of the vehicle model.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\]+

[signalCatalogArn](#)

The ARN of the signal catalog associated with the vehicle model.

Type: String

[status](#)

The state of the vehicle model. If the status is ACTIVE, the vehicle model can't be edited. You can edit the vehicle model if the status is marked DRAFT.

Type: String

Valid Values: ACTIVE | DRAFT | INVALID | VALIDATING

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

InternalServerError

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

ResourceNotFoundException

The resource wasn't found.

resourceId

The identifier of the resource that wasn't found.

resourceType

The type of resource that wasn't found.

HTTP Status Code: 400

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetRegisterAccountStatus

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Retrieves information about the status of registering your AWS account, IAM, and Amazon Timestream resources so that AWS IoT FleetWise can transfer your vehicle data to the AWS Cloud.

For more information, including step-by-step procedures, see [Setting up AWS IoT FleetWise](#).

Note

This API operation doesn't require input parameters.

Response Syntax

```
{
  "accountStatus": "string",
  "creationTime": number,
  "customerAccountId": "string",
  "iamRegistrationResponse": {
    "errorMessage": "string",
    "registrationStatus": "string",
    "roleArn": "string"
  },
  "lastModificationTime": number,
  "timestreamRegistrationResponse": {
    "errorMessage": "string",
    "registrationStatus": "string",
    "timestreamDatabaseArn": "string",
    "timestreamDatabaseName": "string",
    "timestreamTableArn": "string",
    "timestreamTableName": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

accountStatus

The status of registering your account and resources. The status can be one of:

- REGISTRATION_SUCCESS - The AWS resource is successfully registered.
- REGISTRATION_PENDING - AWS IoT FleetWise is processing the registration request. This process takes approximately five minutes to complete.
- REGISTRATION_FAILURE - AWS IoT FleetWise can't register the AWS resource. Try again later.

Type: String

Valid Values: REGISTRATION_PENDING | REGISTRATION_SUCCESS |
REGISTRATION_FAILURE

creationTime

The time the account was registered, in seconds since epoch (January 1, 1970 at midnight UTC time).

Type: Timestamp

customerAccountId

The unique ID of the AWS account, provided at account creation.

Type: String

iamRegistrationResponse

Information about the registered IAM resources or errors, if any.

Type: [iamRegistrationResponse](#) object

lastModificationTime

The time this registration was last updated, in seconds since epoch (January 1, 1970 at midnight UTC time).

Type: Timestamp

[timestreamRegistrationResponse](#)

Information about the registered Amazon Timestream resources or errors, if any.

Type: [TimestreamRegistrationResponse](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

InternalServerError

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

ResourceNotFoundException

The resource wasn't found.

resourceId

The identifier of the resource that wasn't found.

resourceType

The type of resource that wasn't found.

HTTP Status Code: 400

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)

- [AWS SDK for Ruby V3](#)

GetSignalCatalog

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Retrieves information about a signal catalog.

Request Syntax

```
{  
  "name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

name

The name of the signal catalog to retrieve information about.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\.]+

Required: Yes

Response Syntax

```
{  
  "arn": "string",  
  "creationTime": number,  
  "description": "string",
```

```
"lastModificationTime": number,
"name": "string",
"nodeCounts": {
  "totalActuators": number,
  "totalAttributes": number,
  "totalBranches": number,
  "totalNodes": number,
  "totalProperties": number,
  "totalSensors": number,
  "totalStructs": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The Amazon Resource Name (ARN) of the signal catalog.

Type: String

creationTime

The time the signal catalog was created in seconds since epoch (January 1, 1970 at midnight UTC time).

Type: Timestamp

description

A brief description of the signal catalog.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

lastModificationTime

The last time the signal catalog was modified.

Type: Timestamp

name

The name of the signal catalog.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\+]

nodeCounts

The total number of network nodes specified in a signal catalog.

Type: [NodeCounts](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

InternalServerError

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

ResourceNotFoundException

The resource wasn't found.

resourceId

The identifier of the resource that wasn't found.

resourceType

The type of resource that wasn't found.

HTTP Status Code: 400

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetStateTemplate

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Retrieves information about a state template.

Request Syntax

```
{  
  "identifier": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

identifier

The unique ID of the state template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\+]

Required: Yes

Response Syntax

```
{  
  "arn": "string",  
  "creationTime": number,  
  ...  
}
```

```
{
  "dataExtraDimensions": [ "string" ],
  "description": "string",
  "id": "string",
  "lastModificationTime": number,
  "metadataExtraDimensions": [ "string" ],
  "name": "string",
  "signalCatalogArn": "string",
  "stateTemplateProperties": [ "string" ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The Amazon Resource Name (ARN) of the state template.

Type: String

creationTime

The time the state template was created in seconds since epoch (January 1, 1970 at midnight UTC time).

Type: Timestamp

dataExtraDimensions

A list of vehicle attributes associated with the payload published on the state template's MQTT topic.

Default: An empty array

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Length Constraints: Minimum length of 1. Maximum length of 150.

Pattern: [a-zA-Z0-9_\.]+

description

A brief description of the state template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: [^\u0000-\u001F\u007F]+

id

The unique ID of the state template.

Type: String

Length Constraints: Fixed length of 26.

Pattern: [A-Z0-9]+

lastModificationTime

The time the state template was last updated in seconds since epoch (January 1, 1970 at midnight UTC time).

Type: Timestamp

metadataExtraDimensions

A list of vehicle attributes to associate with user properties of the messages published on the state template's MQTT topic.

Default: An empty array

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Length Constraints: Minimum length of 1. Maximum length of 150.

Pattern: [a-zA-Z0-9_\.]+

name

The name of the state template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\]+

[signalCatalogArn](#)

The ARN of the signal catalog associated with the state template.

Type: String

[stateTemplateProperties](#)

A list of signals from which data is collected. The state template properties contain the fully qualified names of the signals.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 500 items.

Length Constraints: Minimum length of 1. Maximum length of 150.

Pattern: [a-zA-Z0-9_\.\]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

InternalServerErrorException

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

ResourceNotFoundException

The resource wasn't found.

resourceId

The identifier of the resource that wasn't found.

resourceType

The type of resource that wasn't found.

HTTP Status Code: 400

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetVehicle

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Retrieves information about a vehicle.

Request Syntax

```
{
  "vehicleName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[vehicleName](#)

The ID of the vehicle to retrieve information about.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\.]+

Required: Yes

Response Syntax

```
{
  "arn": "string",
  "attributes": {
    "string" : "string"
  }
}
```

```
},
  "creationTime": number,
  "decoderManifestArn": "string",
  "lastModificationTime": number,
  "modelManifestArn": "string",
  "stateTemplates": [
    {
      "identifier": "string",
      "stateTemplateUpdateStrategy": { ... }
    }
  ],
  "vehicleName": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The Amazon Resource Name (ARN) of the vehicle to retrieve information about.

Type: String

attributes

Static information about a vehicle in a key-value pair. For example:

```
"engineType": "1.3 L R2"
```

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 150.

Key Pattern: [a-zA-Z0-9_.-]+

creationTime

The time the vehicle was created in seconds since epoch (January 1, 1970 at midnight UTC time).

Type: Timestamp

[decoderManifestArn](#)

The ARN of a decoder manifest associated with the vehicle.

Type: String

[lastModificationTime](#)

The time the vehicle was last updated in seconds since epoch (January 1, 1970 at midnight UTC time).

Type: Timestamp

[modelManifestArn](#)

The ARN of a vehicle model (model manifest) associated with the vehicle.

Type: String

[stateTemplates](#)

State templates associated with the vehicle.

Type: Array of [StateTemplateAssociation](#) objects

Array Members: Minimum number of 1 item. Maximum number of 20 items.

[vehicleName](#)

The ID of the vehicle.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[a-zA-Z\d\-\_:\.]+`

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

InternalServerErrorException

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

ResourceNotFoundException

The resource wasn't found.

resourceId

The identifier of the resource that wasn't found.

resourceType

The type of resource that wasn't found.

HTTP Status Code: 400

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

GetVehicleStatus

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Retrieves information about the status of campaigns, decoder manifests, or state templates associated with a vehicle.

Request Syntax

```
{
  "maxResults": number,
  "nextToken": "string",
  "vehicleName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

maxResults

The maximum number of items to return, between 1 and 100, inclusive. This parameter is only supported for resources of type CAMPAIGN.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

nextToken

A pagination token for the next set of results.

If the results of a search are large, only a portion of the results are returned, and a `nextToken` pagination token is returned in the response. To retrieve the next set of results, reissue the search request and include the returned token. When all results have been returned, the response does not contain a pagination token value. This parameter is only supported for resources of type `CAMPAIGN`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Required: No

vehicleName

The ID of the vehicle to retrieve information about.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[a-zA-Z\d\-\_:\.]+`

Required: Yes

Response Syntax

```
{
  "campaigns": [
    {
      "campaignName": "string",
      "status": "string",
      "vehicleName": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[campaigns](#)

Lists information about the state of the vehicle with deployed campaigns.

Type: Array of [VehicleStatus](#) objects

[nextToken](#)

The token to retrieve the next set of results, or null if there are no more results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

InternalServerErrorException

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

ResourceNotFoundException

The resource wasn't found.

resourceId

The identifier of the resource that wasn't found.

resourceType

The type of resource that wasn't found.

HTTP Status Code: 400

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ImportDecoderManifest

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Imports new signal decoders into an existing decoder manifest using the CAN DBC files from your local device. The CAN signal name must be unique and not repeated across CAN message definitions in the .dbc file.

Request Syntax

```
{
  "name": "string",
  "networkFileDefinitions": [
    { ... }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

name

The name of the decoder manifest to import.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[a-zA-Z\d\-\_:\.]+`

Required: Yes

networkFileDefinitions

The file to load into an AWS account.

Type: Array of [NetworkFileDefinition](#) objects

Required: Yes

Response Syntax

```
{
  "arn": "string",
  "name": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[arn](#)

The Amazon Resource Name (ARN) of the decoder manifest that was imported.

Type: String

[name](#)

The name of the imported decoder manifest.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\.]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

ConflictException

The request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

resource

The resource on which there are conflicting operations.

resourceType

The type of resource on which there are conflicting operations..

HTTP Status Code: 400

DecoderManifestValidationException

The request couldn't be completed because it contains signal decoders with one or more validation errors.

invalidNetworkInterfaces

The request couldn't be completed because of invalid network interfaces in the request.

invalidSignals

The request couldn't be completed because of invalid signals in the request.

HTTP Status Code: 400

InternalServerError

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

InvalidSignalsException

The request couldn't be completed because it contains signals that aren't valid.

invalidSignals

The signals which caused the exception.

HTTP Status Code: 400

ResourceNotFoundException

The resource wasn't found.

resourceId

The identifier of the resource that wasn't found.

resourceType

The type of resource that wasn't found.

HTTP Status Code: 400

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ImportSignalCatalog

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Creates a signal catalog using your existing VSS formatted content from your local device.

Request Syntax

```
{
  "description": "string",
  "name": "string",
  "tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ],
  "vss": { ... }
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

description

A brief description of the signal catalog.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

name

The name of the signal catalog to import.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\]+

Required: Yes

tags

Metadata that can be used to manage the signal catalog.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

vss

The contents of the Vehicle Signal Specification (VSS) configuration. VSS is a precise language used to describe and model signals in vehicle networks.

Type: [FormattedVss](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

Response Syntax

```
{
  "arn": "string",
  "name": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The Amazon Resource Name (ARN) of the imported signal catalog.

Type: String

name

The name of the imported signal catalog.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\.]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

ConflictException

The request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

resource

The resource on which there are conflicting operations.

resourceType

The type of resource on which there are conflicting operations..

HTTP Status Code: 400

InternalServerErrorException

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

InvalidSignalsException

The request couldn't be completed because it contains signals that aren't valid.

invalidSignals

The signals which caused the exception.

HTTP Status Code: 400

LimitExceededException

A service quota was exceeded.

resourceId

The identifier of the resource that was exceeded.

resourceType

The type of resource that was exceeded.

HTTP Status Code: 400

ResourceNotFoundException

The resource wasn't found.

resourceId

The identifier of the resource that wasn't found.

resourceType

The type of resource that wasn't found.

HTTP Status Code: 400

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListCampaigns

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Lists information about created campaigns.

Note

This API operation uses pagination. Specify the `nextToken` parameter in the request to return more results.

Request Syntax

```
{  
  "listResponseScope": "string",  
  "maxResults": number,  
  "nextToken": "string",  
  "status": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

listResponseScope

When you set the `listResponseScope` parameter to `METADATA_ONLY`, the list response includes: campaign name, Amazon Resource Name (ARN), creation time, and last modification time.

Type: String

Valid Values: `METADATA_ONLY`

Required: No

maxResults

The maximum number of items to return, between 1 and 100, inclusive.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

nextToken

A pagination token for the next set of results.

If the results of a search are large, only a portion of the results are returned, and a nextToken pagination token is returned in the response. To retrieve the next set of results, reissue the search request and include the returned token. When all results have been returned, the response does not contain a pagination token value.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Required: No

status

An optional parameter to filter the results by the status of each created campaign in your account. The status can be one of: CREATING, WAITING_FOR_APPROVAL, RUNNING, or SUSPENDED.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: [A-Z_]*

Required: No

Response Syntax

```
{
```

```
"campaignSummaries": [  
  {  
    "arn": "string",  
    "creationTime": number,  
    "description": "string",  
    "lastModificationTime": number,  
    "name": "string",  
    "signalCatalogArn": "string",  
    "status": "string",  
    "targetArn": "string"  
  }  
],  
"nextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

campaignSummaries

A summary of information about each campaign.

Type: Array of [CampaignSummary](#) objects

nextToken

The token to retrieve the next set of results, or null if there are no more results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

InternalServerErrorException

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListDecoderManifestNetworkInterfaces

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Lists the network interfaces specified in a decoder manifest.

Note

This API operation uses pagination. Specify the `nextToken` parameter in the request to return more results.

Request Syntax

```
{  
  "maxResults": number,  
  "name": "string",  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

maxResults

The maximum number of items to return, between 1 and 100, inclusive.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

name

The name of the decoder manifest to list information about.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\.]+

Required: Yes

nextToken

A pagination token for the next set of results.

If the results of a search are large, only a portion of the results are returned, and a nextToken pagination token is returned in the response. To retrieve the next set of results, reissue the search request and include the returned token. When all results have been returned, the response does not contain a pagination token value.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Required: No

Response Syntax

```
{
  "networkInterfaces": [
    {
      "canInterface": {
        "name": "string",
        "protocolName": "string",
        "protocolVersion": "string"
      },
      "customDecodingInterface": {
        "name": "string"
      },
      "interfaceId": "string",
      "obdInterface": {
```

```
    "dtcRequestIntervalSeconds": number,
    "hasTransmissionEcu": boolean,
    "name": "string",
    "obdStandard": "string",
    "pidRequestIntervalSeconds": number,
    "requestMessageId": number,
    "useExtendedIds": boolean
  },
  "type": "string",
  "vehicleMiddleware": {
    "name": "string",
    "protocolName": "string"
  }
},
"nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

networkInterfaces

A list of information about network interfaces.

Type: Array of [NetworkInterface](#) objects

Array Members: Minimum number of 1 item. Maximum number of 500 items.

nextToken

The token to retrieve the next set of results, or null if there are no more results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

InternalServerError

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

ResourceNotFoundException

The resource wasn't found.

resourceId

The identifier of the resource that wasn't found.

resourceType

The type of resource that wasn't found.

HTTP Status Code: 400

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListDecoderManifests

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Lists decoder manifests.

Note

This API operation uses pagination. Specify the `nextToken` parameter in the request to return more results.

Request Syntax

```
{  
  "listResponseScope": "string",  
  "maxResults": number,  
  "modelManifestArn": "string",  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

listResponseScope

When you set the `listResponseScope` parameter to `METADATA_ONLY`, the list response includes: decoder manifest name, Amazon Resource Name (ARN), creation time, and last modification time.

Type: String

Valid Values: `METADATA_ONLY`

Required: No

maxResults

The maximum number of items to return, between 1 and 100, inclusive.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

modelManifestArn

The Amazon Resource Name (ARN) of a vehicle model (model manifest) associated with the decoder manifest.

Type: String

Required: No

nextToken

A pagination token for the next set of results.

If the results of a search are large, only a portion of the results are returned, and a nextToken pagination token is returned in the response. To retrieve the next set of results, reissue the search request and include the returned token. When all results have been returned, the response does not contain a pagination token value.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Required: No

Response Syntax

```
{
  "nextToken": "string",
  "summaries": [
    {
      "arn": "string",
      "creationTime": number,
```

```
    "description": "string",  
    "lastModificationTime": number,  
    "message": "string",  
    "modelManifestArn": "string",  
    "name": "string",  
    "status": "string"  
  }  
]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

The token to retrieve the next set of results, or null if there are no more results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

summaries

A list of information about each decoder manifest.

Type: Array of [DecoderManifestSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

InternalServerException

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListDecoderManifestSignals

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

A list of information about signal decoders specified in a decoder manifest.

Note

This API operation uses pagination. Specify the `nextToken` parameter in the request to return more results.

Request Syntax

```
{  
  "maxResults": number,  
  "name": "string",  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

maxResults

The maximum number of items to return, between 1 and 100, inclusive.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

name

The name of the decoder manifest to list information about.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\.]+

Required: Yes

nextToken

A pagination token for the next set of results.

If the results of a search are large, only a portion of the results are returned, and a nextToken pagination token is returned in the response. To retrieve the next set of results, reissue the search request and include the returned token. When all results have been returned, the response does not contain a pagination token value.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Required: No

Response Syntax

```
{
  "nextToken": "string",
  "signalDecoders": [
    {
      "canSignal": {
        "factor": number,
        "isBigEndian": boolean,
        "isSigned": boolean,
        "length": number,
        "messageId": number,
        "name": "string",
        "offset": number,
        "signalValueType": "string",
        "startBit": number
      },
    },
  ],
}
```

```

    "customDecodingSignal": {
      "id": "string"
    },
    "fullyQualifiedNames": "string",
    "interfaceId": "string",
    "messageSignal": {
      "structuredMessage": { ... },
      "topicName": "string"
    },
    "obdSignal": {
      "bitMaskLength": number,
      "bitRightShift": number,
      "byteLength": number,
      "isSigned": boolean,
      "offset": number,
      "pid": number,
      "pidResponseLength": number,
      "scaling": number,
      "serviceMode": number,
      "signalValueType": "string",
      "startByte": number
    },
    "type": "string"
  }
]
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

The token to retrieve the next set of results, or null if there are no more results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

signalDecoders

Information about a list of signals to decode.

Type: Array of [SignalDecoder](#) objects

Array Members: Minimum number of 1 item. Maximum number of 500 items.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

InternalServerError

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

ResourceNotFoundException

The resource wasn't found.

resourceId

The identifier of the resource that wasn't found.

resourceType

The type of resource that wasn't found.

HTTP Status Code: 400

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListFleets

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Retrieves information for each created fleet in an AWS account.

Note

This API operation uses pagination. Specify the `nextToken` parameter in the request to return more results.

Request Syntax

```
{
  "listResponseScope": "string",
  "maxResults": number,
  "nextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[listResponseScope](#)

When you set the `listResponseScope` parameter to `METADATA_ONLY`, the list response includes: fleet ID, Amazon Resource Name (ARN), creation time, and last modification time.

Type: String

Valid Values: `METADATA_ONLY`

Required: No

maxResults

The maximum number of items to return, between 1 and 100, inclusive.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

nextToken

A pagination token for the next set of results.

If the results of a search are large, only a portion of the results are returned, and a `nextToken` pagination token is returned in the response. To retrieve the next set of results, reissue the search request and include the returned token. When all results have been returned, the response does not contain a pagination token value.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Required: No

Response Syntax

```
{
  "fleetSummaries": [
    {
      "arn": "string",
      "creationTime": number,
      "description": "string",
      "id": "string",
      "lastModificationTime": number,
      "signalCatalogArn": "string"
    }
  ],
  "nextToken": "string"
}
```


Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[fleetSummaries](#)

A list of information for each fleet.

Type: Array of [FleetSummary](#) objects

[nextToken](#)

The token to retrieve the next set of results, or null if there are no more results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

InternalServerError

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

ResourceNotFoundException

The resource wasn't found.

resourceId

The identifier of the resource that wasn't found.

resourceType

The type of resource that wasn't found.

HTTP Status Code: 400

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListFleetsForVehicle

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Retrieves a list of IDs for all fleets that the vehicle is associated with.

Note

This API operation uses pagination. Specify the `nextToken` parameter in the request to return more results.

Request Syntax

```
{  
  "maxResults": number,  
  "nextToken": "string",  
  "vehicleName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

maxResults

The maximum number of items to return, between 1 and 100, inclusive.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

nextToken

A pagination token for the next set of results.

If the results of a search are large, only a portion of the results are returned, and a `nextToken` pagination token is returned in the response. To retrieve the next set of results, reissue the search request and include the returned token. When all results have been returned, the response does not contain a pagination token value.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Required: No

vehicleName

The ID of the vehicle to retrieve information about.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[a-zA-Z\d\-\_:\ ]+`

Required: Yes

Response Syntax

```
{
  "fleets": [ "string" ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

fleets

A list of fleet IDs that the vehicle is associated with.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z0-9:_-]+

nextToken

The token to retrieve the next set of results, or null if there are no more results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

InternalServerError

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

ResourceNotFoundException

The resource wasn't found.

resourceId

The identifier of the resource that wasn't found.

resourceType

The type of resource that wasn't found.

HTTP Status Code: 400

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListModelManifestNodes

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Lists information about nodes specified in a vehicle model (model manifest).

Note

This API operation uses pagination. Specify the `nextToken` parameter in the request to return more results.

Request Syntax

```
{
  "maxResults": number,
  "name": "string",
  "nextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

maxResults

The maximum number of items to return, between 1 and 100, inclusive.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

name

The name of the vehicle model to list information about.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\.]+

Required: Yes

nextToken

A pagination token for the next set of results.

If the results of a search are large, only a portion of the results are returned, and a `nextToken` pagination token is returned in the response. To retrieve the next set of results, reissue the search request and include the returned token. When all results have been returned, the response does not contain a pagination token value.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Required: No

Response Syntax

```
{
  "nextToken": "string",
  "nodes": [
    { ... }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

The token to retrieve the next set of results, or null if there are no more results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

nodes

A list of information about nodes.

Type: Array of [Node](#) objects

Array Members: Minimum number of 0 items. Maximum number of 500 items.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

InternalServerErrorException

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

LimitExceededException

A service quota was exceeded.

resourceId

The identifier of the resource that was exceeded.

resourceType

The type of resource that was exceeded.

HTTP Status Code: 400

ResourceNotFoundException

The resource wasn't found.

resourceId

The identifier of the resource that wasn't found.

resourceType

The type of resource that wasn't found.

HTTP Status Code: 400

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListModelManifests

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Retrieves a list of vehicle models (model manifests).

Note

This API operation uses pagination. Specify the `nextToken` parameter in the request to return more results.

Request Syntax

```
{  
  "listResponseScope": "string",  
  "maxResults": number,  
  "nextToken": "string",  
  "signalCatalogArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

listResponseScope

When you set the `listResponseScope` parameter to `METADATA_ONLY`, the list response includes: model manifest name, Amazon Resource Name (ARN), creation time, and last modification time.

Type: String

Valid Values: `METADATA_ONLY`

Required: No

maxResults

The maximum number of items to return, between 1 and 100, inclusive.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

nextToken

A pagination token for the next set of results.

If the results of a search are large, only a portion of the results are returned, and a nextToken pagination token is returned in the response. To retrieve the next set of results, reissue the search request and include the returned token. When all results have been returned, the response does not contain a pagination token value.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Required: No

signalCatalogArn

The ARN of a signal catalog. If you specify a signal catalog, only the vehicle models associated with it are returned.

Type: String

Required: No

Response Syntax

```
{
  "nextToken": "string",
  "summaries": [
    {
      "arn": "string",
```

```
    "creationTime": number,
    "description": "string",
    "lastModificationTime": number,
    "name": "string",
    "signalCatalogArn": "string",
    "status": "string"
  }
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

The token to retrieve the next set of results, or null if there are no more results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

summaries

A list of information about vehicle models.

Type: Array of [ModelManifestSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

InternalServerErrorException

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListSignalCatalogNodes

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Lists of information about the signals (nodes) specified in a signal catalog.

Note

This API operation uses pagination. Specify the `nextToken` parameter in the request to return more results.

Request Syntax

```
{
  "maxResults": number,
  "name": "string",
  "nextToken": "string",
  "signalNodeType": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

maxResults

The maximum number of items to return, between 1 and 100, inclusive.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

name

The name of the signal catalog to list information about.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\]+

Required: Yes

nextToken

A pagination token for the next set of results.

If the results of a search are large, only a portion of the results are returned, and a `nextToken` pagination token is returned in the response. To retrieve the next set of results, reissue the search request and include the returned token. When all results have been returned, the response does not contain a pagination token value.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Required: No

signalNodeType

The type of node in the signal catalog.

Type: String

Valid Values: SENSOR | ACTUATOR | ATTRIBUTE | BRANCH | CUSTOM_STRUCT | CUSTOM_PROPERTY

Required: No

Response Syntax

```
{  
  "nextToken": "string",  
  "nodes": [  
    ...  
  ]  
}
```

```
{ ... }  
]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

The token to retrieve the next set of results, or `null` if there are no more results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

nodes

A list of information about nodes.

Type: Array of [Node](#) objects

Array Members: Minimum number of 0 items. Maximum number of 500 items.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

InternalServerException

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

LimitExceededException

A service quota was exceeded.

resourceId

The identifier of the resource that was exceeded.

resourceType

The type of resource that was exceeded.

HTTP Status Code: 400

ResourceNotFoundException

The resource wasn't found.

resourceId

The identifier of the resource that wasn't found.

resourceType

The type of resource that wasn't found.

HTTP Status Code: 400

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListSignalCatalogs

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Lists all the created signal catalogs in an AWS account.

You can use [ListSignalCatalogNodes](#) to list information about each signal (node) specified in a signal catalog.

Note

This API operation uses pagination. Specify the `nextToken` parameter in the request to return more results.

Request Syntax

```
{
  "maxResults": number,
  "nextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[maxResults](#)

The maximum number of items to return, between 1 and 100, inclusive.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

nextToken

A pagination token for the next set of results.

If the results of a search are large, only a portion of the results are returned, and a nextToken pagination token is returned in the response. To retrieve the next set of results, reissue the search request and include the returned token. When all results have been returned, the response does not contain a pagination token value.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Required: No

Response Syntax

```
{
  "nextToken": "string",
  "summaries": [
    {
      "arn": "string",
      "creationTime": number,
      "lastModificationTime": number,
      "name": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

The token to retrieve the next set of results, or null if there are no more results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

summaries

A list of information about each signal catalog.

Type: Array of [SignalCatalogSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

InternalServerError

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListStateTemplates

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Lists information about created state templates.

Request Syntax

```
{  
  "listResponseScope": "string",  
  "maxResults": number,  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

listResponseScope

When you set the `listResponseScope` parameter to `METADATA_ONLY`, the list response includes: state template ID, Amazon Resource Name (ARN), creation time, and last modification time.

Type: String

Valid Values: `METADATA_ONLY`

Required: No

maxResults

The maximum number of items to return, between 1 and 100, inclusive.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

nextToken

The token to retrieve the next set of results, or null if there are no more results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Required: No

Response Syntax

```
{
  "nextToken": "string",
  "summaries": [
    {
      "arn": "string",
      "creationTime": number,
      "description": "string",
      "id": "string",
      "lastModificationTime": number,
      "name": "string",
      "signalCatalogArn": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

The token to retrieve the next set of results, or null if there are no more results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

[summaries](#)

A list of information about each state template.

Type: Array of [StateTemplateSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

InternalServerError

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Lists the tags (metadata) you have assigned to the resource.

Request Syntax

```
{  
  "ResourceARN": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ResourceARN](#)

The ARN of the resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:.*`

Required: Yes

Response Syntax

```
{  
  "Tags": [  
    {
```



```
    "Key": "string",  
    "Value": "string"  
  }  
]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Tags

The list of tags assigned to the resource.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

InternalServerErrorException

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

ResourceNotFoundException

The resource wasn't found.

resourceId

The identifier of the resource that wasn't found.

resourceType

The type of resource that wasn't found.

HTTP Status Code: 400

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListVehicles

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Retrieves a list of summaries of created vehicles.

Note

This API operation uses pagination. Specify the `nextToken` parameter in the request to return more results.

Request Syntax

```
{
  "attributeNames": [ "string" ],
  "attributeValues": [ "string" ],
  "listResponseScope": "string",
  "maxResults": number,
  "modelManifestArn": "string",
  "nextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

attributeNames

The fully qualified names of the attributes. You can use this optional parameter to list the vehicles containing all the attributes in the request. For example, `attributeNames` could be `"Vehicle.Body.Engine.Type, Vehicle.Color"` and the corresponding `attributeValues` could be `"1.3 L R2, Blue"`. In this case, the API will filter vehicles with

an attribute name `Vehicle.Body.Engine.Type` that contains a value of `1.3 L R2` AND an attribute name `Vehicle.Color` that contains a value of `"Blue"`. A request must contain unique values for the `attributeNames` filter and the matching number of `attributeValues` filters to return the subset of vehicles that match the attributes filter condition.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Length Constraints: Minimum length of 1. Maximum length of 150.

Pattern: `[a-zA-Z0-9_.-]+`

Required: No

[attributeValues](#)

Static information about a vehicle attribute value in string format. You can use this optional parameter in conjunction with `attributeNames` to list the vehicles containing all the `attributeValues` corresponding to the `attributeNames` filter. For example, `attributeValues` could be `"1.3 L R2, Blue"` and the corresponding `attributeNames` filter could be `"Vehicle.Body.Engine.Type, Vehicle.Color"`. In this case, the API will filter vehicles with attribute name `Vehicle.Body.Engine.Type` that contains a value of `1.3 L R2` AND an attribute name `Vehicle.Color` that contains a value of `"Blue"`. A request must contain unique values for the `attributeNames` filter and the matching number of `attributeValues` filter to return the subset of vehicles that match the attributes filter condition.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Required: No

[listResponseScope](#)

When you set the `listResponseScope` parameter to `METADATA_ONLY`, the list response includes: vehicle name, Amazon Resource Name (ARN), creation time, and last modification time.

Type: String

Valid Values: `METADATA_ONLY`

Required: No

maxResults

The maximum number of items to return, between 1 and 100, inclusive.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

modelManifestArn

The Amazon Resource Name (ARN) of a vehicle model (model manifest). You can use this optional parameter to list only the vehicles created from a certain vehicle model.

Type: String

Required: No

nextToken

A pagination token for the next set of results.

If the results of a search are large, only a portion of the results are returned, and a nextToken pagination token is returned in the response. To retrieve the next set of results, reissue the search request and include the returned token. When all results have been returned, the response does not contain a pagination token value.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Required: No

Response Syntax

```
{
  "nextToken": "string",
  "vehicleSummaries": [
    {
      "arn": "string",
      "attributes": {
```

```
        "string" : "string"
      },
      "creationTime": number,
      "decoderManifestArn": "string",
      "lastModificationTime": number,
      "modelManifestArn": "string",
      "vehicleName": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

The token to retrieve the next set of results, or null if there are no more results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

vehicleSummaries

A list of vehicles and information about them.

Type: Array of [VehicleSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

InternalServerErrorException

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

ListVehiclesInFleet

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Retrieves a list of summaries of all vehicles associated with a fleet.

Note

This API operation uses pagination. Specify the `nextToken` parameter in the request to return more results.

Request Syntax

```
{  
  "fleetId": "string",  
  "maxResults": number,  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

fleetId

The ID of a fleet.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[a-zA-Z0-9:_-]+`

Required: Yes

maxResults

The maximum number of items to return, between 1 and 100, inclusive.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

nextToken

A pagination token for the next set of results.

If the results of a search are large, only a portion of the results are returned, and a `nextToken` pagination token is returned in the response. To retrieve the next set of results, reissue the search request and include the returned token. When all results have been returned, the response does not contain a pagination token value.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Required: No

Response Syntax

```
{
  "nextToken": "string",
  "vehicles": [ "string" ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

The token to retrieve the next set of results, or `null` if there are no more results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

vehicles

A list of vehicles associated with the fleet.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\.]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

InternalServerError

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

ResourceNotFoundException

The resource wasn't found.

resourceId

The identifier of the resource that wasn't found.

resourceType

The type of resource that wasn't found.

HTTP Status Code: 400

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

PutEncryptionConfiguration

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Creates or updates the encryption configuration. AWS IoT FleetWise can encrypt your data and resources using an AWS managed key. Or, you can use a KMS key that you own and manage. For more information, see [Data encryption](#) in the *AWS IoT FleetWise Developer Guide*.

Request Syntax

```
{  
  "encryptionType": "string",  
  "kmsKeyId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[encryptionType](#)

The type of encryption. Choose KMS_BASED_ENCRYPTION to use a KMS key or FLEETWISE_DEFAULT_ENCRYPTION to use an AWS managed key.

Type: String

Valid Values: KMS_BASED_ENCRYPTION | FLEETWISE_DEFAULT_ENCRYPTION

Required: Yes

[kmsKeyId](#)

The ID of the KMS key that is used for encryption.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Required: No

Response Syntax

```
{  
  "encryptionStatus": "string",  
  "encryptionType": "string",  
  "kmsKeyId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[encryptionStatus](#)

The encryption status.

Type: String

Valid Values: PENDING | SUCCESS | FAILURE

[encryptionType](#)

The type of encryption. Set to KMS_BASED_ENCRYPTION to use an KMS key that you own and manage. Set to FLEETWISE_DEFAULT_ENCRYPTION to use an AWS managed key that is owned by the AWS IoT FleetWise service account.

Type: String

Valid Values: KMS_BASED_ENCRYPTION | FLEETWISE_DEFAULT_ENCRYPTION

[kmsKeyId](#)

The ID of the KMS key that is used for encryption.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

ConflictException

The request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

resource

The resource on which there are conflicting operations.

resourceType

The type of resource on which there are conflicting operations..

HTTP Status Code: 400

InternalServerErrorException

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

ResourceNotFoundException

The resource wasn't found.

resourceId

The identifier of the resource that wasn't found.

resourceType

The type of resource that wasn't found.

HTTP Status Code: 400

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

PutLoggingOptions

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Creates or updates the logging option.

Request Syntax

```
{  
  "cloudWatchLogDelivery": {  
    "logGroupName": "string",  
    "logType": "string"  
  }  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[cloudWatchLogDelivery](#)

Creates or updates the log delivery option to Amazon CloudWatch Logs.

Type: [CloudWatchLogDeliveryOptions](#) object

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

ConflictException

The request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

resource

The resource on which there are conflicting operations.

resourceType

The type of resource on which there are conflicting operations..

HTTP Status Code: 400

InternalServerError

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

ResourceNotFoundException

The resource wasn't found.

resourceId

The identifier of the resource that wasn't found.

resourceType

The type of resource that wasn't found.

HTTP Status Code: 400

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)

- [AWS SDK for Ruby V3](#)

RegisterAccount

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Important

This API operation contains deprecated parameters. Register your account again without the Timestream resources parameter so that AWS IoT FleetWise can remove the Timestream metadata stored. You should then pass the data destination into the [CreateCampaign](#) API operation.

You must delete any existing campaigns that include an empty data destination before you register your account again. For more information, see the [DeleteCampaign](#) API operation. If you want to delete the Timestream inline policy from the service-linked role, such as to mitigate an overly permissive policy, you must first delete any existing campaigns. Then delete the service-linked role and register your account again to enable CloudWatch metrics. For more information, see [DeleteServiceLinkedRole](#) in the *AWS Identity and Access Management API Reference*.

Registers your AWS account, IAM, and Amazon Timestream resources so AWS IoT FleetWise can transfer your vehicle data to the AWS Cloud. For more information, including step-by-step procedures, see [Setting up AWS IoT FleetWise](#).

Note

An AWS account is **not** the same thing as a "user." An [AWS user](#) is an identity that you create using AWS Identity and Access Management (IAM) and takes the form of either an [IAM user](#) or an [IAM role, both with credentials](#). A single AWS account can, and typically does, contain many users and roles.

Request Syntax

```
{
  "iamResources": {
    "roleArn": "string"
  },
  "timestreamResources": {
    "timestreamDatabaseName": "string",
    "timestreamTableName": "string"
  }
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[iamResources](#)

This parameter has been deprecated.

The IAM resource that allows AWS IoT FleetWise to send data to Amazon Timestream.

Type: [iamResources](#) object

Required: No

[timestreamResources](#)

This parameter has been deprecated.

The registered Amazon Timestream resources that AWS IoT FleetWise edge agent software can transfer your vehicle data to.

Type: [TimestreamResources](#) object

Required: No

Response Syntax

```
{
```

```
"creationTime": number,  
"iamResources": {  
  "roleArn": "string"  
},  
"lastModificationTime": number,  
"registerAccountStatus": "string",  
"timestreamResources": {  
  "timestreamDatabaseName": "string",  
  "timestreamTableName": "string"  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[creationTime](#)

The time the account was registered, in seconds since epoch (January 1, 1970 at midnight UTC time).

Type: Timestamp

[iamResources](#)

The registered IAM resource that allows AWS IoT FleetWise to send data to Amazon Timestream.

Type: [IamResources](#) object

[lastModificationTime](#)

The time this registration was last updated, in seconds since epoch (January 1, 1970 at midnight UTC time).

Type: Timestamp

[registerAccountStatus](#)

The status of registering your AWS account, IAM role, and Timestream resources.

Type: String

Valid Values: REGISTRATION_PENDING | REGISTRATION_SUCCESS |
REGISTRATION_FAILURE

[timestreamResources](#)

The registered Amazon Timestream resources that AWS IoT FleetWise edge agent software can transfer your vehicle data to.

Type: [TimestreamResources](#) object

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

ConflictException

The request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

resource

The resource on which there are conflicting operations.

resourceType

The type of resource on which there are conflicting operations..

HTTP Status Code: 400

InternalServerErrorException

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

ResourceNotFoundException

The resource wasn't found.

resourceId

The identifier of the resource that wasn't found.

resourceType

The type of resource that wasn't found.

HTTP Status Code: 400

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

TagResource

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Adds to or modifies the tags of the given resource. Tags are metadata which can be used to manage a resource.

Request Syntax

```
{
  "ResourceARN": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ResourceARN

The ARN of the resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:.*`

Required: Yes

Tags

The new or modified tags for the resource.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

InternalServerError

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

ResourceNotFoundException

The resource wasn't found.

resourceId

The identifier of the resource that wasn't found.

resourceType

The type of resource that wasn't found.

HTTP Status Code: 400

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

UntagResource

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Removes the given tags (metadata) from the resource.

Request Syntax

```
{  
  "ResourceARN": "string",  
  "TagKeys": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ResourceARN](#)

The ARN of the resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:.*`

Required: Yes

[TagKeys](#)

A list of the keys of the tags to be removed from the resource.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

InternalServerErrorException

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

ResourceNotFoundException

The resource wasn't found.

resourceId

The identifier of the resource that wasn't found.

resourceType

The type of resource that wasn't found.

HTTP Status Code: 400

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)

- [AWS SDK for Ruby V3](#)

UpdateCampaign

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Updates a campaign.

Request Syntax

```
{
  "action": "string",
  "dataExtraDimensions": [ "string" ],
  "description": "string",
  "name": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

action

Specifies how to update a campaign. The action can be one of the following:

- APPROVE - To approve delivering a data collection scheme to vehicles.
- SUSPEND - To suspend collecting signal data. The campaign is deleted from vehicles and all vehicles in the suspended campaign will stop sending data.
- RESUME - To reactivate the SUSPEND campaign. The campaign is set to be redeployed to all vehicles on next check-in and the vehicles will resume sending data.
- UPDATE - To update a campaign.

Type: String

Valid Values: APPROVE | SUSPEND | RESUME | UPDATE

Required: Yes

dataExtraDimensions

A list of vehicle attributes to associate with a signal.

Default: An empty array

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Length Constraints: Minimum length of 1. Maximum length of 150.

Pattern: [a-zA-Z0-9_.] +

Required: No

description

The description of the campaign.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: [^\u0000-\u001F\u007F] +

Required: No

name

The name of the campaign to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:] +

Required: Yes

Response Syntax

```
{
```

```
"arn": "string",  
"name": "string",  
"status": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The Amazon Resource Name (ARN) of the campaign.

Type: String

Pattern: `arn:aws:iotfleetwise:[a-z0-9-]+:[0-9]{12}:campaign/[a-zA-Z\d\-\_:]{1,100}`

name

The name of the updated campaign.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[a-zA-Z\d\-\_:]+`

status

The state of a campaign. The status can be one of:

- **CREATING** - AWS IoT FleetWise is processing your request to create the campaign.
- **WAITING_FOR_APPROVAL** - After you create a campaign, it enters this state. Use the [UpdateCampaign](#) API operation to approve the campaign for deployment to the target vehicle or fleet.
- **RUNNING** - The campaign is active.
- **SUSPENDED** - The campaign is suspended. To resume the campaign, use the [UpdateCampaign](#) API operation.

Type: String

Valid Values: CREATING | WAITING_FOR_APPROVAL | RUNNING | SUSPENDED

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

ConflictException

The request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

resource

The resource on which there are conflicting operations.

resourceType

The type of resource on which there are conflicting operations..

HTTP Status Code: 400

InternalServerError

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

ResourceNotFoundException

The resource wasn't found.

resourceId

The identifier of the resource that wasn't found.

resourceType

The type of resource that wasn't found.

HTTP Status Code: 400

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

UpdateDecoderManifest

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Updates a decoder manifest.

A decoder manifest can only be updated when the status is DRAFT. Only ACTIVE decoder manifests can be associated with vehicles.

Request Syntax

```
{
  "defaultForUnmappedSignals": "string",
  "description": "string",
  "name": "string",
  "networkInterfacesToAdd": [
    {
      "canInterface": {
        "name": "string",
        "protocolName": "string",
        "protocolVersion": "string"
      },
      "customDecodingInterface": {
        "name": "string"
      },
      "interfaceId": "string",
      "obdInterface": {
        "dtcRequestIntervalSeconds": number,
        "hasTransmissionEcu": boolean,
        "name": "string",
        "obdStandard": "string",
        "pidRequestIntervalSeconds": number,
        "requestMessageId": number,
        "useExtendedIds": boolean
      },
      "type": "string",
      "vehicleMiddleware": {
        "name": "string",
```

```

        "protocolName": "string"
    }
}
],
"networkInterfacesToRemove": [ "string" ],
"networkInterfacesToUpdate": [
{
    "canInterface": {
        "name": "string",
        "protocolName": "string",
        "protocolVersion": "string"
    },
    "customDecodingInterface": {
        "name": "string"
    },
    "interfaceId": "string",
    "obdInterface": {
        "dtcRequestIntervalSeconds": number,
        "hasTransmissionEcu": boolean,
        "name": "string",
        "obdStandard": "string",
        "pidRequestIntervalSeconds": number,
        "requestMessageId": number,
        "useExtendedIds": boolean
    },
    "type": "string",
    "vehicleMiddleware": {
        "name": "string",
        "protocolName": "string"
    }
}
],
"signalDecodersToAdd": [
{
    "canSignal": {
        "factor": number,
        "isBigEndian": boolean,
        "isSigned": boolean,
        "length": number,
        "messageId": number,
        "name": "string",
        "offset": number,
        "signalValueType": "string",
        "startBit": number
    }
}
]

```

```

    },
    "customDecodingSignal": {
      "id": "string"
    },
    "fullyQualifiedName": "string",
    "interfaceId": "string",
    "messageSignal": {
      "structuredMessage": { ... },
      "topicName": "string"
    },
    "obdSignal": {
      "bitMaskLength": number,
      "bitRightShift": number,
      "byteLength": number,
      "isSigned": boolean,
      "offset": number,
      "pid": number,
      "pidResponseLength": number,
      "scaling": number,
      "serviceMode": number,
      "signalValueType": "string",
      "startByte": number
    },
    "type": "string"
  }
],
"signalDecodersToRemove": [ "string" ],
"signalDecodersToUpdate": [
  {
    "canSignal": {
      "factor": number,
      "isBigEndian": boolean,
      "isSigned": boolean,
      "length": number,
      "messageId": number,
      "name": "string",
      "offset": number,
      "signalValueType": "string",
      "startBit": number
    },
    "customDecodingSignal": {
      "id": "string"
    },
    "fullyQualifiedName": "string",

```

```
"interfaceId": "string",
"messageSignal": {
  "structuredMessage": { ... },
  "topicName": "string"
},
"obdSignal": {
  "bitMaskLength": number,
  "bitRightShift": number,
  "byteLength": number,
  "isSigned": boolean,
  "offset": number,
  "pid": number,
  "pidResponseLength": number,
  "scaling": number,
  "serviceMode": number,
  "signalValueType": "string",
  "startByte": number
},
"type": "string"
}
],
"status": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[defaultForUnmappedSignals](#)

Use default decoders for all unmapped signals in the model. You don't need to provide any detailed decoding information.

Type: String

Valid Values: CUSTOM_DECODING

Required: No

[description](#)

A brief description of the decoder manifest to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: [^\u0000-\u001F\u007F]+

Required: No

name

The name of the decoder manifest to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\.]+

Required: Yes

networkInterfacesToAdd

A list of information about the network interfaces to add to the decoder manifest.

Type: Array of [NetworkInterface](#) objects

Array Members: Minimum number of 1 item. Maximum number of 500 items.

Required: No

networkInterfacesToRemove

A list of network interfaces to remove from the decoder manifest.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 500 items.

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: [-a-zA-Z0-9_\.]+

Required: No

networkInterfacesToUpdate

A list of information about the network interfaces to update in the decoder manifest.

Type: Array of [NetworkInterface](#) objects

Array Members: Minimum number of 1 item. Maximum number of 500 items.

Required: No

[signalDecodersToAdd](#)

A list of information about decoding additional signals to add to the decoder manifest.

Type: Array of [SignalDecoder](#) objects

Array Members: Minimum number of 1 item. Maximum number of 500 items.

Required: No

[signalDecodersToRemove](#)

A list of signal decoders to remove from the decoder manifest.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 500 items.

Length Constraints: Minimum length of 1. Maximum length of 150.

Pattern: [a-zA-Z0-9_ .]+

Required: No

[signalDecodersToUpdate](#)

A list of updated information about decoding signals to update in the decoder manifest.

Type: Array of [SignalDecoder](#) objects

Array Members: Minimum number of 1 item. Maximum number of 500 items.

Required: No

[status](#)

The state of the decoder manifest. If the status is ACTIVE, the decoder manifest can't be edited. If the status is DRAFT, you can edit the decoder manifest.

Type: String

Valid Values: ACTIVE | DRAFT | INVALID | VALIDATING

Required: No

Response Syntax

```
{
  "arn": "string",
  "name": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The Amazon Resource Name (ARN) of the updated decoder manifest.

Type: String

name

The name of the updated decoder manifest.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\.]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

ConflictException

The request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

resource

The resource on which there are conflicting operations.

resourceType

The type of resource on which there are conflicting operations..

HTTP Status Code: 400

DecoderManifestValidationException

The request couldn't be completed because it contains signal decoders with one or more validation errors.

invalidNetworkInterfaces

The request couldn't be completed because of invalid network interfaces in the request.

invalidSignals

The request couldn't be completed because of invalid signals in the request.

HTTP Status Code: 400

InternalServerErrorException

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

LimitExceededException

A service quota was exceeded.

resourceId

The identifier of the resource that was exceeded.

resourceType

The type of resource that was exceeded.

HTTP Status Code: 400

ResourceNotFoundException

The resource wasn't found.

resourceId

The identifier of the resource that wasn't found.

resourceType

The type of resource that wasn't found.

HTTP Status Code: 400

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

UpdateFleet

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Updates the description of an existing fleet.

Request Syntax

```
{
  "description": "string",
  "fleetId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

description

An updated description of the fleet.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

fleetId

The ID of the fleet to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z0-9:_-]+

Required: Yes

Response Syntax

```
{  
  "arn": "string",  
  "id": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The Amazon Resource Name (ARN) of the updated fleet.

Type: String

id

The ID of the updated fleet.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z0-9:_-]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

ConflictException

The request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

resource

The resource on which there are conflicting operations.

resourceType

The type of resource on which there are conflicting operations..

HTTP Status Code: 400

InternalServerErrorException

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

ResourceNotFoundException

The resource wasn't found.

resourceId

The identifier of the resource that wasn't found.

resourceType

The type of resource that wasn't found.

HTTP Status Code: 400

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

UpdateModelManifest

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Updates a vehicle model (model manifest). If created vehicles are associated with a vehicle model, it can't be updated.

Request Syntax

```
{
  "description": "string",
  "name": "string",
  "nodesToAdd": [ "string" ],
  "nodesToRemove": [ "string" ],
  "status": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

description

A brief description of the vehicle model.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

name

The name of the vehicle model to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\.]+

Required: Yes

nodesToAdd

A list of `fullyQualifiedName` of nodes, which are a general abstraction of signals, to add to the vehicle model.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 500 items.

Length Constraints: Minimum length of 1. Maximum length of 150.

Pattern: [a-zA-Z0-9_\.\-]+

Required: No

nodesToRemove

A list of `fullyQualifiedName` of nodes, which are a general abstraction of signals, to remove from the vehicle model.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 500 items.

Length Constraints: Minimum length of 1. Maximum length of 150.

Pattern: [a-zA-Z0-9_\.\-]+

Required: No

status

The state of the vehicle model. If the status is `ACTIVE`, the vehicle model can't be edited. If the status is `DRAFT`, you can edit the vehicle model.

Type: String

Valid Values: ACTIVE | DRAFT | INVALID | VALIDATING

Required: No

Response Syntax

```
{
  "arn": "string",
  "name": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The Amazon Resource Name (ARN) of the updated vehicle model.

Type: String

name

The name of the updated vehicle model.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\.]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

ConflictException

The request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

resource

The resource on which there are conflicting operations.

resourceType

The type of resource on which there are conflicting operations..

HTTP Status Code: 400

InternalServerErrorException

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

InvalidSignalsException

The request couldn't be completed because it contains signals that aren't valid.

invalidSignals

The signals which caused the exception.

HTTP Status Code: 400

ResourceNotFoundException

The resource wasn't found.

resourceId

The identifier of the resource that wasn't found.

resourceType

The type of resource that wasn't found.

HTTP Status Code: 400

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

UpdateSignalCatalog

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Updates a signal catalog.

Request Syntax

```
{
  "description": "string",
  "name": "string",
  "nodesToAdd": [
    { ... }
  ],
  "nodesToRemove": [ "string" ],
  "nodesToUpdate": [
    { ... }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

description

A brief description of the signal catalog to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

name

The name of the signal catalog to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\.]+

Required: Yes

nodesToAdd

A list of information about nodes to add to the signal catalog.

Type: Array of [Node](#) objects

Array Members: Minimum number of 0 items. Maximum number of 500 items.

Required: No

nodesToRemove

A list of fullyQualifiedName of nodes to remove from the signal catalog.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 500 items.

Length Constraints: Minimum length of 1. Maximum length of 150.

Pattern: [a-zA-Z0-9_\.\-]+

Required: No

nodesToUpdate

A list of information about nodes to update in the signal catalog.

Type: Array of [Node](#) objects

Array Members: Minimum number of 0 items. Maximum number of 500 items.

Required: No

Response Syntax

```
{
  "arn": "string",
  "name": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The ARN of the updated signal catalog.

Type: String

name

The name of the updated signal catalog.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

ConflictException

The request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

resource

The resource on which there are conflicting operations.

resourceType

The type of resource on which there are conflicting operations..

HTTP Status Code: 400

InternalServerError

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

InvalidNodeException

The specified node type doesn't match the expected node type for a node. You can specify the node type as branch, sensor, actuator, or attribute.

invalidNodes

The specified node type isn't valid.

reason

The reason the node validation failed.

HTTP Status Code: 400

InvalidSignalsException

The request couldn't be completed because it contains signals that aren't valid.

invalidSignals

The signals which caused the exception.

HTTP Status Code: 400

LimitExceededException

A service quota was exceeded.

resourceId

The identifier of the resource that was exceeded.

resourceType

The type of resource that was exceeded.

HTTP Status Code: 400

ResourceNotFoundException

The resource wasn't found.

resourceId

The identifier of the resource that wasn't found.

resourceType

The type of resource that wasn't found.

HTTP Status Code: 400

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

UpdateStateTemplate

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Updates a state template.

Request Syntax

```
{  
  "dataExtraDimensions": [ "string" ],  
  "description": "string",  
  "identifier": "string",  
  "metadataExtraDimensions": [ "string" ],  
  "stateTemplatePropertiesToAdd": [ "string" ],  
  "stateTemplatePropertiesToRemove": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

dataExtraDimensions

A list of vehicle attributes to associate with the payload published on the state template's MQTT topic. (See [Processing last known state vehicle data using MQTT messaging](#)). For example, if you add `Vehicle.Attributes.Make` and `Vehicle.Attributes.Model` attributes, AWS IoT FleetWise will enrich the protobuf encoded payload with those attributes in the `extraDimensions` field.

Default: An empty array

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Length Constraints: Minimum length of 1. Maximum length of 150.

Pattern: [a-zA-Z0-9_.] +

Required: No

description

A brief description of the state template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: [^\u0000-\u001F\u007F] +

Required: No

identifier

The unique ID of the state template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:] +

Required: Yes

metadataExtraDimensions

A list of vehicle attributes to associate with user properties of the messages published on the state template's MQTT topic. (See [Processing last known state vehicle data using MQTT messaging](#)). For example, if you add `Vehicle.Attributes.Make` and `Vehicle.Attributes.Model` attributes, AWS IoT FleetWise will include these attributes as User Properties with the MQTT message.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Length Constraints: Minimum length of 1. Maximum length of 150.

Pattern: [a-zA-Z0-9_.] +

Required: No

stateTemplatePropertiesToAdd

Add signals from which data is collected as part of the state template.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 500 items.

Length Constraints: Minimum length of 1. Maximum length of 150.

Pattern: [a-zA-Z0-9_.]+

Required: No

stateTemplatePropertiesToRemove

Remove signals from which data is collected as part of the state template.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 500 items.

Length Constraints: Minimum length of 1. Maximum length of 150.

Pattern: [a-zA-Z0-9_.]+

Required: No

Response Syntax

```
{
  "arn": "string",
  "id": "string",
  "name": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The Amazon Resource Name (ARN) of the state template.

Type: String

id

The unique ID of the state template.

Type: String

Length Constraints: Fixed length of 26.

Pattern: [A-Z0-9]+

name

The name of the state template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\.]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

InternalServerErrorException

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

InvalidSignalsException

The request couldn't be completed because it contains signals that aren't valid.

invalidSignals

The signals which caused the exception.

HTTP Status Code: 400

LimitExceededException

A service quota was exceeded.

resourceId

The identifier of the resource that was exceeded.

resourceType

The type of resource that was exceeded.

HTTP Status Code: 400

ResourceNotFoundException

The resource wasn't found.

resourceId

The identifier of the resource that wasn't found.

resourceType

The type of resource that wasn't found.

HTTP Status Code: 400

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

UpdateVehicle

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Updates a vehicle.

Request Syntax

```
{
  "attributes": {
    "string" : "string"
  },
  "attributeUpdateMode": "string",
  "decoderManifestArn": "string",
  "modelManifestArn": "string",
  "stateTemplatesToAdd": [
    {
      "identifier": "string",
      "stateTemplateUpdateStrategy": { ... }
    }
  ],
  "stateTemplatesToRemove": [ "string" ],
  "stateTemplatesToUpdate": [
    {
      "identifier": "string",
      "stateTemplateUpdateStrategy": { ... }
    }
  ],
  "vehicleName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

attributes

Static information about a vehicle in a key-value pair. For example:

```
"engineType": "1.3 L R2"
```

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 150.

Key Pattern: [a-zA-Z0-9_.-]+

Required: No

attributeUpdateMode

The method the specified attributes will update the existing attributes on the vehicle.

Use `Overwrite` to replace the vehicle attributes with the specified attributes. Or use `Merge` to combine all attributes.

This is required if attributes are present in the input.

Type: String

Valid Values: `Overwrite` | `Merge`

Required: No

decoderManifestArn

The ARN of the decoder manifest associated with this vehicle.

Type: String

Required: No

modelManifestArn

The ARN of a vehicle model (model manifest) associated with the vehicle.

Type: String

Required: No

stateTemplatesToAdd

Associate state templates with the vehicle.

Type: Array of [StateTemplateAssociation](#) objects

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Required: No

[stateTemplatesToRemove](#)

Remove state templates from the vehicle.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\]+

Required: No

[stateTemplatesToUpdate](#)

Change the stateTemplateUpdateStrategy of state templates already associated with the vehicle.

Type: Array of [StateTemplateAssociation](#) objects

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Required: No

[vehicleName](#)

The unique ID of the vehicle to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\]+

Required: Yes

Response Syntax

```
{
```

```
"arn": "string",  
"vehicleName": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[arn](#)

The ARN of the updated vehicle.

Type: String

[vehicleName](#)

The ID of the updated vehicle.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\.]+

Errors

For information about the errors that are common to all actions, see [Common Error Types](#).

AccessDeniedException

You don't have sufficient permission to perform this action.

HTTP Status Code: 400

ConflictException

The request has conflicting operations. This can occur if you're trying to perform more than one operation on the same resource at the same time.

resource

The resource on which there are conflicting operations.

resourceType

The type of resource on which there are conflicting operations..

HTTP Status Code: 400

InternalServerError

The request couldn't be completed because the server temporarily failed.

retryAfterSeconds

The number of seconds to wait before retrying the command.

HTTP Status Code: 500

LimitExceededException

A service quota was exceeded.

resourceId

The identifier of the resource that was exceeded.

resourceType

The type of resource that was exceeded.

HTTP Status Code: 400

ResourceNotFoundException

The resource wasn't found.

resourceId

The identifier of the resource that wasn't found.

resourceType

The type of resource that wasn't found.

HTTP Status Code: 400

ThrottlingException

The request couldn't be completed due to throttling.

quotaCode

The quota identifier of the applied throttling rules for this request.

retryAfterSeconds

The number of seconds to wait before retrying the command.

serviceCode

The code for the service that couldn't be completed due to throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

fieldList

The list of fields that fail to satisfy the constraints specified by an AWS service.

reason

The reason the input failed to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET V4](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python \(Boto3\)](#)
- [AWS SDK for Ruby V3](#)

Data Types

The AWS IoT FleetWise API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [Actuator](#)
- [Attribute](#)
- [Branch](#)
- [CampaignSummary](#)
- [CanDbcDefinition](#)
- [CanInterface](#)
- [CanSignal](#)
- [CloudWatchLogDeliveryOptions](#)
- [CollectionScheme](#)
- [ConditionBasedCollectionScheme](#)
- [ConditionBasedSignalFetchConfig](#)
- [CreateVehicleError](#)
- [CreateVehicleRequestItem](#)
- [CreateVehicleResponseItem](#)
- [CustomDecodingInterface](#)
- [CustomDecodingSignal](#)
- [CustomProperty](#)
- [CustomStruct](#)
- [DataDestinationConfig](#)
- [DataPartition](#)

- [DataPartitionStorageOptions](#)
- [DataPartitionUploadOptions](#)
- [DecoderManifestSummary](#)
- [FleetSummary](#)
- [FormattedVss](#)
- [IamRegistrationResponse](#)
- [IamResources](#)
- [InvalidNetworkInterface](#)
- [InvalidSignal](#)
- [InvalidSignalDecoder](#)
- [MessageSignal](#)
- [ModelManifestSummary](#)
- [MqttTopicConfig](#)
- [NetworkFileDefinition](#)
- [NetworkInterface](#)
- [Node](#)
- [NodeCounts](#)
- [ObdInterface](#)
- [ObdSignal](#)
- [OnChangeStateTemplateUpdateStrategy](#)
- [PeriodicStateTemplateUpdateStrategy](#)
- [PrimitiveMessageDefinition](#)
- [ROS2PrimitiveMessageDefinition](#)
- [S3Config](#)
- [Sensor](#)
- [SignalCatalogSummary](#)
- [SignalDecoder](#)
- [SignalFetchConfig](#)
- [SignalFetchInformation](#)
- [SignalInformation](#)

- [StateTemplateAssociation](#)
- [StateTemplateSummary](#)
- [StateTemplateUpdateStrategy](#)
- [StorageMaximumSize](#)
- [StorageMinimumTimeToLive](#)
- [StructuredMessage](#)
- [StructuredMessageFieldNameAndDataTypePair](#)
- [StructuredMessageListDefinition](#)
- [Tag](#)
- [TimeBasedCollectionScheme](#)
- [TimeBasedSignalFetchConfig](#)
- [TimePeriod](#)
- [TimestreamConfig](#)
- [TimestreamRegistrationResponse](#)
- [TimestreamResources](#)
- [UpdateVehicleError](#)
- [UpdateVehicleRequestItem](#)
- [UpdateVehicleResponseItem](#)
- [ValidationExceptionField](#)
- [VehicleMiddleware](#)
- [VehicleStatus](#)
- [VehicleSummary](#)

Actuator

A signal that represents a vehicle device such as the engine, heater, and door locks. Data from an actuator reports the state of a certain vehicle device.

Note

Updating actuator data can change the state of a device. For example, you can turn on or off the heater by updating its actuator data.

Contents

dataType

The specified data type of the actuator.

Type: String

Valid Values: INT8 | UINT8 | INT16 | UINT16 | INT32 | UINT32 | INT64 | UINT64 | BOOLEAN | FLOAT | DOUBLE | STRING | UNIX_TIMESTAMP | INT8_ARRAY | UINT8_ARRAY | INT16_ARRAY | UINT16_ARRAY | INT32_ARRAY | UINT32_ARRAY | INT64_ARRAY | UINT64_ARRAY | BOOLEAN_ARRAY | FLOAT_ARRAY | DOUBLE_ARRAY | STRING_ARRAY | UNIX_TIMESTAMP_ARRAY | UNKNOWN | STRUCT | STRUCT_ARRAY

Required: Yes

fullyQualifiedName

The fully qualified name of the actuator. For example, the fully qualified name of an actuator might be `Vehicle.Front.Left.Door.Lock`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 150.

Pattern: `[a-zA-Z0-9_.]+`

Required: Yes

allowedValues

A list of possible values an actuator can take.

Type: Array of strings

Required: No

assignedValue

This member has been deprecated.

A specified value for the actuator.

Type: String

Required: No

comment

A comment in addition to the description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

deprecationMessage

The deprecation message for the node or the branch that was moved or deleted.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

description

A brief description of the actuator.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

max

The specified possible maximum value of an actuator.

Type: Double

Required: No

min

The specified possible minimum value of an actuator.

Type: Double

Required: No

structFullyQualifiedName

The fully qualified name of the struct node for the actuator if the data type of the actuator is `Struct` or `StructArray`. For example, the struct fully qualified name of an actuator might be `Vehicle.Door.LockStruct`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 150.

Pattern: `[a-zA-Z0-9_.]+`

Required: No

unit

The scientific unit for the actuator.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Attribute

A signal that represents static information about the vehicle, such as engine type or manufacturing date.

Contents

dataType

The specified data type of the attribute.

Type: String

Valid Values: INT8 | UINT8 | INT16 | UINT16 | INT32 | UINT32 | INT64 | UINT64 | BOOLEAN | FLOAT | DOUBLE | STRING | UNIX_TIMESTAMP | INT8_ARRAY | UINT8_ARRAY | INT16_ARRAY | UINT16_ARRAY | INT32_ARRAY | UINT32_ARRAY | INT64_ARRAY | UINT64_ARRAY | BOOLEAN_ARRAY | FLOAT_ARRAY | DOUBLE_ARRAY | STRING_ARRAY | UNIX_TIMESTAMP_ARRAY | UNKNOWN | STRUCT | STRUCT_ARRAY

Required: Yes

fullyQualifiedName

The fully qualified name of the attribute. For example, the fully qualified name of an attribute might be `Vehicle.Body.Engine.Type`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 150.

Pattern: `[a-zA-Z0-9_.]+`

Required: Yes

allowedValues

A list of possible values an attribute can be assigned.

Type: Array of strings

Required: No

assignedValue

This member has been deprecated.

A specified value for the attribute.

Type: String

Required: No

comment

A comment in addition to the description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

defaultValue

The default value of the attribute.

Type: String

Required: No

deprecationMessage

The deprecation message for the node or the branch that was moved or deleted.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

description

A brief description of the attribute.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

max

The specified possible maximum value of the attribute.

Type: Double

Required: No

min

The specified possible minimum value of the attribute.

Type: Double

Required: No

unit

The scientific unit for the attribute.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Branch

A group of signals that are defined in a hierarchical structure.

Contents

fullyQualifiedName

The fully qualified name of the branch. For example, the fully qualified name of a branch might be `Vehicle.Body.Engine`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 150.

Pattern: `[a-zA-Z0-9_.]+`

Required: Yes

comment

A comment in addition to the description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^[^\\u0000-\\u001F\\u007F]+`

Required: No

deprecationMessage

The deprecation message for the node or the branch that was moved or deleted.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^[^\\u0000-\\u001F\\u007F]+`

Required: No

description

A brief description of the branch.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CampaignSummary

Information about a campaign.

You can use the [ListCampaigns](#) API operation to return this information about multiple created campaigns.

Contents

creationTime

The time the campaign was created.

Type: Timestamp

Required: Yes

lastModificationTime

The last time the campaign was modified.

Type: Timestamp

Required: Yes

arn

The Amazon Resource Name (ARN) of a campaign.

Type: String

Pattern: `arn:aws:iotfleetwise:[a-z0-9-]+:[0-9]{12}:campaign/[a-zA-Z\d\-\_:]`
`{1,100}`

Required: No

description

The description of the campaign.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

name

The name of a campaign.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\.]+\

Required: No

signalCatalogArn

The ARN of the signal catalog associated with the campaign.

Type: String

Required: No

status

The state of a campaign. The status can be one of the following:

- **CREATING** - AWS IoT FleetWise is processing your request to create the campaign.
- **WAITING_FOR_APPROVAL** - After a campaign is created, it enters the **WAITING_FOR_APPROVAL** state. To allow AWS IoT FleetWise to deploy the campaign to the target vehicle or fleet, use the [UpdateCampaign](#) API operation to approve the campaign.
- **RUNNING** - The campaign is active.
- **SUSPENDED** - The campaign is suspended. To resume the campaign, use the [UpdateCampaign](#) API operation.

Type: String

Valid Values: CREATING | WAITING_FOR_APPROVAL | RUNNING | SUSPENDED

Required: No

targetArn

The ARN of a vehicle or fleet to which the campaign is deployed.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CanDbcDefinition

Configurations used to create a decoder manifest.

Contents

canDbcFiles

A list of DBC files. You can upload only one DBC file for each network interface and specify up to five (inclusive) files in the list. The DBC file can be a maximum size of 200 MB.

Type: Array of Base64-encoded binary data objects

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Length Constraints: Minimum length of 0. Maximum length of 200000000.

Required: Yes

networkInterface

Contains information about a network interface.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: [-a-zA-Z0-9_.] +

Required: Yes

signalsMap

Pairs every signal specified in your vehicle model with a signal decoder.

Type: String to string map

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CanInterface

A single controller area network (CAN) device interface.

Contents

name

The unique name of the interface.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z0-9_.]+

Required: Yes

protocolName

The name of the communication protocol for the interface.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: [a-zA-Z0-9_.]+

Required: No

protocolVersion

The version of the communication protocol for the interface.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: [a-zA-Z0-9_.]+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CanSignal

Information about a single controller area network (CAN) signal and the messages it receives and transmits.

Contents

factor

A multiplier used to decode the CAN message.

Type: Double

Required: Yes

isBigEndian

Whether the byte ordering of a CAN message is big-endian.

Type: Boolean

Required: Yes

isSigned

Determines whether the message is signed (`true`) or not (`false`). If it's signed, the message can represent both positive and negative numbers. The `isSigned` parameter only applies to the `INTEGER` raw signal type, and it doesn't affect the `FLOATING_POINT` raw signal type.

Type: Boolean

Required: Yes

length

How many bytes of data are in the message.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 2147483647.

Required: Yes

messageId

The ID of the message.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 2147483647.

Required: Yes

offset

The offset used to calculate the signal value. Combined with factor, the calculation is $value = raw_value * factor + offset$.

Type: Double

Required: Yes

startBit

Indicates the beginning of the CAN signal. This should always be the least significant bit (LSB).

This value might be different from the value in a DBC file. For little endian signals, `startBit` is the same value as in the DBC file. For big endian signals in a DBC file, the start bit is the most significant bit (MSB). You will have to calculate the LSB instead and pass it as the `startBit`.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 2147483647.

Required: Yes

name

The name of the signal.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[a-zA-Z0-9_.]+`

Required: No

signalValueType

The value type of the signal. The default value is `INTEGER`.

Type: String

Valid Values: INTEGER | FLOATING_POINT

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CloudWatchLogDeliveryOptions

The log delivery option to send data to Amazon CloudWatch Logs.

Contents

logType

The type of log to send data to Amazon CloudWatch Logs.

Type: String

Valid Values: OFF | ERROR

Required: Yes

logGroupName

The Amazon CloudWatch Logs group the operation sends data to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `[\.\-_\/#A-Za-z0-9]+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CollectionScheme

Specifies what data to collect and how often or when to collect it.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

conditionBasedCollectionScheme

Information about a collection scheme that uses a simple logical expression to recognize what data to collect.

Type: [ConditionBasedCollectionScheme](#) object

Required: No

timeBasedCollectionScheme

Information about a collection scheme that uses a time period to decide how often to collect data.

Type: [TimeBasedCollectionScheme](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ConditionBasedCollectionScheme

Information about a collection scheme that uses a simple logical expression to recognize what data to collect.

Contents

expression

The logical expression used to recognize what data to collect. For example, `$variable. `Vehicle.OutsideAirTemperature` >= 105.0`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: Yes

conditionLanguageVersion

Specifies the version of the conditional expression language.

Type: Integer

Valid Range: Fixed value of 1.

Required: No

minimumTriggerIntervalMs

The minimum duration of time between two triggering events to collect data, in milliseconds.

Note

If a signal changes often, you might want to collect data at a slower rate.

Type: Long

Valid Range: Minimum value of 0. Maximum value of 4294967295.

Required: No

triggerMode

Whether to collect data for all triggering events (ALWAYS). Specify (RISING_EDGE), or specify only when the condition first evaluates to false. For example, triggering on "AirbagDeployed"; Users aren't interested on triggering when the airbag is already exploded; they only care about the change from not deployed => deployed.

Type: String

Valid Values: ALWAYS | RISING_EDGE

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ConditionBasedSignalFetchConfig

Specifies the condition under which a signal fetch occurs.

Contents

conditionExpression

The condition that must be satisfied to trigger a signal fetch.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 400.

Required: Yes

triggerMode

Indicates the mode in which the signal fetch is triggered.

Type: String

Valid Values: ALWAYS | RISING_EDGE

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CreateVehicleError

An HTTP error resulting from creating a vehicle.

Contents

code

An HTTP error code.

Type: String

Required: No

message

A description of the HTTP error.

Type: String

Required: No

vehicleName

The ID of the vehicle with the error.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\.]+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CreateVehicleRequestItem

Information about the vehicle to create.

Contents

decoderManifestArn

The Amazon Resource Name (ARN) of a decoder manifest associated with the vehicle to create.

Type: String

Required: Yes

modelManifestArn

The ARN of the vehicle model (model manifest) to create the vehicle from.

Type: String

Required: Yes

vehicleName

The unique ID of the vehicle to create.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[a-zA-Z\d\-\_:\ ]+`

Required: Yes

associationBehavior

An option to create a new AWS IoT thing when creating a vehicle, or to validate an existing thing as a vehicle.

Type: String

Valid Values: `CreateIotThing` | `ValidateIotThingExists`

Required: No

attributes

Static information about a vehicle in a key-value pair. For example: "engine Type" : "v6"

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 150.

Key Pattern: [a-zA-Z0-9_.-]+

Required: No

stateTemplates

Associate state templates to track the state of the vehicle. State templates determine which signal updates the vehicle sends to the cloud.

Type: Array of [StateTemplateAssociation](#) objects

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Required: No

tags

Metadata which can be used to manage the vehicle.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CreateVehicleResponseItem

Information about a created vehicle.

Contents

arn

The ARN of the created vehicle.

Type: String

Required: No

thingArn

The ARN of a created or validated AWS IoT thing.

Type: String

Required: No

vehicleName

The unique ID of the vehicle to create.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\.]+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CustomDecodingInterface

Represents a custom network interface as defined by the customer.

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Contents

name

The name of the interface.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\.]+

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CustomDecodingSignal

Information about signals using a custom decoding protocol as defined by the customer.

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Contents

id

The ID of the signal.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 150.

Pattern: `(?!.*\\.\.)([a-zA-Z0-9_\-#:.])+`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CustomProperty

Represents a member of the complex data structure. The data type of the property can be either primitive or another struct.

Contents

dataType

The data type for the custom property.

Type: String

Valid Values: INT8 | UINT8 | INT16 | UINT16 | INT32 | UINT32 | INT64 | UINT64 | BOOLEAN | FLOAT | DOUBLE | STRING | UNIX_TIMESTAMP | INT8_ARRAY | UINT8_ARRAY | INT16_ARRAY | UINT16_ARRAY | INT32_ARRAY | UINT32_ARRAY | INT64_ARRAY | UINT64_ARRAY | BOOLEAN_ARRAY | FLOAT_ARRAY | DOUBLE_ARRAY | STRING_ARRAY | UNIX_TIMESTAMP_ARRAY | UNKNOWN | STRUCT | STRUCT_ARRAY

Required: Yes

fullyQualifiedName

The fully qualified name of the custom property. For example, the fully qualified name of a custom property might be `ComplexDataTypes.VehicleDataTypes.SVMCamera.FPS`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 150.

Pattern: `[a-zA-Z0-9_.]+`

Required: Yes

comment

A comment in addition to the description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: [^\u0000-\u001F\u007F]+

Required: No

dataEncoding

Indicates whether the property is binary data.

Type: String

Valid Values: BINARY | TYPED

Required: No

deprecationMessage

The deprecation message for the node or the branch that was moved or deleted.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: [^\u0000-\u001F\u007F]+

Required: No

description

A brief description of the custom property.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: [^\u0000-\u001F\u007F]+

Required: No

structFullyQualifiedName

The fully qualified name of the struct node for the custom property if the data type of the custom property is Struct or StructArray.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 150.

Pattern: [a-zA-Z0-9_\.]+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CustomStruct

The custom structure represents a complex or higher-order data structure.

Contents

fullyQualifiedName

The fully qualified name of the custom structure. For example, the fully qualified name of a custom structure might be `ComplexDataTypes.VehicleDataTypes.SVMCamera`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 150.

Pattern: `[a-zA-Z0-9_.]+`

Required: Yes

comment

A comment in addition to the description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

deprecationMessage

The deprecation message for the node or the branch that was moved or deleted.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

description

A brief description of the custom structure.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DataDestinationConfig

The destination where the campaign sends data. You can send data to an MQTT topic, or store it in Amazon S3 or Amazon Timestream.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

mqttTopicConfig

The MQTT topic to which the AWS IoT FleetWise campaign routes data.

Type: [MqttTopicConfig](#) object

Required: No

s3Config

The Amazon S3 bucket where the AWS IoT FleetWise campaign sends data.

Type: [S3Config](#) object

Required: No

timestreamConfig

The Amazon Timestream table where the campaign sends data.

Type: [TimestreamConfig](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DataPartition

The configuration for signal data storage and upload options. You can only specify these options when the campaign's spooling mode is TO_DISK.

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Contents

id

The ID of the data partition. The data partition ID must be unique within a campaign. You can establish a data partition as the default partition for a campaign by using `default` as the ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9]+`

Required: Yes

storageOptions

The storage options for a data partition.

Type: [DataPartitionStorageOptions](#) object

Required: Yes

uploadOptions

The upload options for the data partition.

Type: [DataPartitionUploadOptions](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DataPartitionStorageOptions

Size, time, and location options for the data partition.

Contents

maximumSize

The maximum storage size of the data stored in the data partition.

Note

Newer data overwrites older data when the partition reaches the maximum size.

Type: [StorageMaximumSize](#) object

Required: Yes

minimumTimeToLive

The amount of time that data in this partition will be kept on disk.

- After the designated amount of time passes, the data can be removed, but it's not guaranteed to be removed.
- Before the time expires, data in this partition can still be deleted if the partition reaches its configured maximum size.
- Newer data will overwrite older data when the partition reaches the maximum size.

Type: [StorageMinimumTimeToLive](#) object

Required: Yes

storageLocation

The folder name for the data partition under the campaign storage folder.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DataPartitionUploadOptions

The upload options for the data partition. If upload options are specified, you must also specify storage options. See [DataPartitionStorageOptions](#).

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Contents

expression

The logical expression used to recognize what data to collect. For example, `$variable.`Vehicle.OutsideAirTemperature` >= 105.0`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: Yes

conditionLanguageVersion

The version of the condition language. Defaults to the most recent condition language version.

Type: Integer

Valid Range: Fixed value of 1.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DecoderManifestSummary

Information about a created decoder manifest. You can use the [ListDecoderManifests](#) API operation to return this information about multiple decoder manifests.

Contents

creationTime

The time the decoder manifest was created in seconds since epoch (January 1, 1970 at midnight UTC time).

Type: Timestamp

Required: Yes

lastModificationTime

The time the decoder manifest was last updated in seconds since epoch (January 1, 1970 at midnight UTC time).

Type: Timestamp

Required: Yes

arn

The ARN of a vehicle model (model manifest) associated with the decoder manifest.

Type: String

Required: No

description

A brief description of the decoder manifest.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

message

The detailed message for the decoder manifest. When a decoder manifest is in an `INVALID` status, the message contains detailed reason and help information.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

modelManifestArn

The ARN of a vehicle model (model manifest) associated with the decoder manifest.

Type: String

Required: No

name

The name of the decoder manifest.

Type: String

Required: No

status

The state of the decoder manifest. If the status is `ACTIVE`, the decoder manifest can't be edited. If the status is marked `DRAFT`, you can edit the decoder manifest.

Type: String

Valid Values: `ACTIVE` | `DRAFT` | `INVALID` | `VALIDATING`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

FleetSummary

Information about a fleet.

You can use the [ListFleets](#) API operation to return this information about multiple fleets.

Contents

arn

The Amazon Resource Name (ARN) of the fleet.

Type: String

Required: Yes

creationTime

The time the fleet was created, in seconds since epoch (January 1, 1970 at midnight UTC time).

Type: Timestamp

Required: Yes

id

The unique ID of the fleet.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z0-9:_-]+

Required: Yes

signalCatalogArn

The ARN of the signal catalog associated with the fleet.

Type: String

Required: Yes

description

A brief description of the fleet.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

lastModificationTime

The time the fleet was last updated in seconds since epoch (January 1, 1970 at midnight UTC time).

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

FormattedVss

[Vehicle Signal Specification \(VSS\)](#) is a precise language used to describe and model signals in vehicle networks. The JSON file collects signal specifications in a VSS format.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

vssJson

Provides the VSS in JSON format.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

IamRegistrationResponse

Information about registering an AWS Identity and Access Management (IAM) resource so AWS IoT FleetWise edge agent software can transfer your vehicle data to Amazon Timestream.

Contents

registrationStatus

The status of registering your IAM resource. The status can be one of `REGISTRATION_SUCCESS`, `REGISTRATION_PENDING`, `REGISTRATION_FAILURE`.

Type: String

Valid Values: `REGISTRATION_PENDING` | `REGISTRATION_SUCCESS` | `REGISTRATION_FAILURE`

Required: Yes

roleArn

The Amazon Resource Name (ARN) of the IAM role to register.

Type: String

Required: Yes

errorMessage

A message associated with a registration error.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

IamResources

The IAM resource that enables AWS IoT FleetWise edge agent software to send data to Amazon Timestream.

For more information, see [IAM roles](#) in the *AWS Identity and Access Management User Guide*.

Contents

roleArn

The Amazon Resource Name (ARN) of the IAM resource that allows AWS IoT FleetWise to send data to Amazon Timestream. For example, `arn:aws:iam::123456789012:role/SERVICE-ROLE-ARN`.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:(aws[a-zA-Z0-9-]*):iam::(\d{12})?:role((\u002F)|(\u002F[\u0021-\u007F]+\u002F))[\w+=,.\u002D-]+)`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InvalidNetworkInterface

A reason a vehicle network interface isn't valid.

Contents

interfaceId

The ID of the interface that isn't valid.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: [-a-zA-Z0-9_.]+

Required: No

reason

A message about why the interface isn't valid.

Type: String

Valid Values: DUPLICATE_NETWORK_INTERFACE | CONFLICTING_NETWORK_INTERFACE | NETWORK_INTERFACE_TO_ADD_ALREADY_EXISTS | CAN_NETWORK_INTERFACE_INFO_IS_NULL | OBD_NETWORK_INTERFACE_INFO_IS_NULL | NETWORK_INTERFACE_TO_REMOVE_ASSOCIATED_WITH_SIGNALS | VEHICLE_MIDDLEWARE_NETWORK_INTERFACE_INFO_IS_NULL | CUSTOM_DECODING_SIGNAL_NETWORK_INTERFACE_INFO_IS_NULL

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InvalidSignal

A reason that a signal isn't valid.

Contents

name

The name of the signal that isn't valid.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 150.

Pattern: [a-zA-Z0-9_.]+

Required: No

reason

A message about why the signal isn't valid.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InvalidSignalDecoder

A reason that a signal decoder isn't valid.

Contents

hint

The possible cause for the invalid signal decoder.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

name

The name of a signal decoder that isn't valid.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 150.

Pattern: `[a-zA-Z0-9_.]+`

Required: No

reason

A message about why the signal decoder isn't valid.

Type: String

Valid Values: DUPLICATE_SIGNAL | CONFLICTING_SIGNAL |
SIGNAL_TO_ADD_ALREADY_EXISTS |
SIGNAL_NOT_ASSOCIATED_WITH_NETWORK_INTERFACE |
NETWORK_INTERFACE_TYPE_INCOMPATIBLE_WITH_SIGNAL_DECODER_TYPE |
SIGNAL_NOT_IN_MODEL | CAN_SIGNAL_INFO_IS_NULL | OBD_SIGNAL_INFO_IS_NULL
| NO_DECODER_INFO_FOR_SIGNAL_IN_MODEL | MESSAGE_SIGNAL_INFO_IS_NULL
| SIGNAL_DECODER_TYPE_INCOMPATIBLE_WITH_MESSAGE_SIGNAL_TYPE |

STRUCT_SIZE_MISMATCH | NO_SIGNAL_IN_CATALOG_FOR_DECODER_SIGNAL |
SIGNAL_DECODER_INCOMPATIBLE_WITH_SIGNAL_CATALOG | EMPTY_MESSAGE_SIGNAL |
CUSTOM_DECODING_SIGNAL_INFO_IS_NULL

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MessageSignal

The decoding information for a specific message which support higher order data types.

Contents

structuredMessage

The structured message for the message signal. It can be defined with either a `primitiveMessageDefinition`, `structuredMessageListDefinition`, or `structuredMessageDefinition` recursively.

Type: [StructuredMessage](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

topicName

The topic name for the message signal. It corresponds to topics in ROS 2.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 150.

Pattern: `[a-zA-Z0-9_\-#:. / ]+`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ModelManifestSummary

Information about a vehicle model (model manifest). You can use the [ListModelManifests](#) API operation to return this information about multiple vehicle models.

Contents

creationTime

The time the vehicle model was created, in seconds since epoch (January 1, 1970 at midnight UTC time).

Type: Timestamp

Required: Yes

lastModificationTime

The time the vehicle model was last updated, in seconds since epoch (January 1, 1970 at midnight UTC time).

Type: Timestamp

Required: Yes

arn

The Amazon Resource Name (ARN) of the vehicle model.

Type: String

Required: No

description

A brief description of the vehicle model.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

name

The name of the vehicle model.

Type: String

Required: No

signalCatalogArn

The ARN of the signal catalog associated with the vehicle model.

Type: String

Required: No

status

The state of the vehicle model. If the status is ACTIVE, the vehicle model can't be edited. If the status is DRAFT, you can edit the vehicle model.

Type: String

Valid Values: ACTIVE | DRAFT | INVALID | VALIDATING

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MqttTopicConfig

The MQTT topic to which the AWS IoT FleetWise campaign routes data. For more information, see [Device communication protocols](#) in the *AWS IoT Core Developer Guide*.

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Contents

executionRoleArn

The ARN of the role that grants AWS IoT FleetWise permission to access and act on messages sent to the MQTT topic.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:(aws[a-zA-Z0-9-]*):iam::(\d{12})?:role((\u002F)|(\u002F[\u0021-\u007F]+\u002F))[\w+=,.\@-]+)`

Required: Yes

mqttTopicArn

The ARN of the MQTT topic.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:.*`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

NetworkFileDefinition

Specifications for defining a vehicle network.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

canDbc

Information, including CAN DBC files, about the configurations used to create a decoder manifest.

Type: [CanDbcDefinition](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

NetworkInterface

Represents a node and its specifications in an in-vehicle communication network. All signal decoders must be associated with a network node.

To return this information about all the network interfaces specified in a decoder manifest, use the [ListDecoderManifestNetworkInterfaces](#) API operation.

Contents

interfaceId

The ID of the network interface.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: [-a-zA-Z0-9_.]+

Required: Yes

type

The network protocol for the vehicle. For example, CAN_SIGNAL specifies a protocol that defines how data is communicated between electronic control units (ECUs). OBD_SIGNAL specifies a protocol that defines how self-diagnostic data is communicated between ECUs.

Type: String

Valid Values: CAN_INTERFACE | OBD_INTERFACE | VEHICLE_MIDDLEWARE | CUSTOM_DECODING_INTERFACE

Required: Yes

canInterface

Information about a network interface specified by the Controller Area Network (CAN) protocol.

Type: [CanInterface](#) object

Required: No

customDecodingInterface

Information about a [custom network interface](#).

Type: [CustomDecodingInterface](#) object

Required: No

obdInterface

Information about a network interface specified by the on-board diagnostic (OBD) II protocol.

Type: [ObdInterface](#) object

Required: No

vehicleMiddleware

The vehicle middleware defined as a type of network interface. Examples of vehicle middleware include ROS2 and SOME/IP.

Type: [VehicleMiddleware](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Node

A general abstraction of a signal. A node can be specified as an actuator, attribute, branch, or sensor.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

actuator

Information about a node specified as an actuator.

Note

An actuator is a digital representation of a vehicle device.

Type: [Actuator](#) object

Required: No

attribute

Information about a node specified as an attribute.

Note

An attribute represents static information about a vehicle.

Type: [Attribute](#) object

Required: No

branch

Information about a node specified as a branch.

Note

A group of signals that are defined in a hierarchical structure.

Type: [Branch](#) object

Required: No

property

Represents a member of the complex data structure. The datatype of the property can be either primitive or another struct.

Type: [CustomProperty](#) object

Required: No

sensor

An input component that reports the environmental condition of a vehicle.

Note

You can collect data about fluid levels, temperatures, vibrations, or battery voltage from sensors.

Type: [Sensor](#) object

Required: No

struct

Represents a complex or higher-order data structure.

Type: [CustomStruct](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

NodeCounts

Information about the number of nodes and node types in a vehicle network.

Contents

totalActuators

The total number of nodes in a vehicle network that represent actuators.

Type: Integer

Required: No

totalAttributes

The total number of nodes in a vehicle network that represent attributes.

Type: Integer

Required: No

totalBranches

The total number of nodes in a vehicle network that represent branches.

Type: Integer

Required: No

totalNodes

The total number of nodes in a vehicle network.

Type: Integer

Required: No

totalProperties

The total properties for the node.

Type: Integer

Required: No

totalSensors

The total number of nodes in a vehicle network that represent sensors.

Type: Integer

Required: No

totalStructs

The total structure for the node.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ObdInterface

A network interface that specifies the on-board diagnostic (OBD) II network protocol.

Contents

name

The name of the interface.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z0-9_.] +

Required: Yes

requestMessageId

The ID of the message requesting vehicle data.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 2147483647.

Required: Yes

dtcRequestIntervalSeconds

The maximum number message requests per diagnostic trouble code per second.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 2147483647.

Required: No

hasTransmissionEcu

Whether the vehicle has a transmission control module (TCM).

Type: Boolean

Required: No

obdStandard

The standard OBD II PID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

pidRequestIntervalSeconds

The maximum number message requests per second.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 2147483647.

Required: No

useExtendedIds

Whether to use extended IDs in the message.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ObdSignal

Information about signal messages using the on-board diagnostics (OBD) II protocol in a vehicle.

Contents

byteLength

The length of a message.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 8.

Required: Yes

offset

The offset used to calculate the signal value. Combined with scaling, the calculation is $value = raw_value * scaling + offset$.

Type: Double

Required: Yes

pid

The diagnostic code used to request data from a vehicle for this signal.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 2147483647.

Required: Yes

pidResponseLength

The length of the requested data.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 2147483647.

Required: Yes

scaling

A multiplier used to decode the message.

Type: Double

Required: Yes

serviceMode

The mode of operation (diagnostic service) in a message.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 2147483647.

Required: Yes

startByte

Indicates the beginning of the message.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 2147483647.

Required: Yes

bitMaskLength

The number of bits to mask in a message.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 8.

Required: No

bitRightShift

The number of positions to shift bits in the message.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 2147483647.

Required: No

isSigned

Determines whether the message is signed (`true`) or not (`false`). If it's signed, the message can represent both positive and negative numbers. The `isSigned` parameter only applies to the `INTEGER` raw signal type, and it doesn't affect the `FLOATING_POINT` raw signal type. The default value is `false`.

Type: Boolean

Required: No

signalValueType

The value type of the signal. The default value is `INTEGER`.

Type: String

Valid Values: `INTEGER` | `FLOATING_POINT`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OnChangeStateTemplateUpdateStrategy

Vehicles associated with the state template will stream telemetry data when there is a change.

Contents

The members of this exception structure are context-dependent.

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PeriodicStateTemplateUpdateStrategy

Vehicles associated with the state template will stream telemetry data during a specified time period.

Contents

stateTemplateUpdateRate

The length of time between state template updates.

Type: [TimePeriod](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PrimitiveMessageDefinition

Represents a primitive type node of the complex data structure.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

ros2PrimitiveMessageDefinition

Information about a PrimitiveMessage using a ROS 2 compliant primitive type message of the complex data structure.

Type: [ROS2PrimitiveMessageDefinition](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ROS2PrimitiveMessageDefinition

Represents a ROS 2 compliant primitive type message of the complex data structure.

Contents

primitiveType

The primitive type (integer, floating point, boolean, etc.) for the ROS 2 primitive message definition.

Type: String

Valid Values: BOOL | BYTE | CHAR | FLOAT32 | FLOAT64 | INT8 | UINT8 | INT16 | UINT16 | INT32 | UINT32 | INT64 | UINT64 | STRING | WSTRING

Required: Yes

offset

The offset used to calculate the signal value. Combined with scaling, the calculation is $value = raw_value * scaling + offset$.

Type: Double

Required: No

scaling

A multiplier used to decode the message.

Type: Double

Required: No

upperBound

An optional attribute specifying the upper bound for STRING and WSTRING.

Type: Long

Valid Range: Minimum value of 0. Maximum value of 2048.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

S3Config

The Amazon S3 bucket where the AWS IoT FleetWise campaign sends data. Amazon S3 is an object storage service that stores data as objects within buckets. For more information, see [Creating, configuring, and working with Amazon S3 buckets](#) in the *Amazon Simple Storage Service User Guide*.

Contents

bucketArn

The Amazon Resource Name (ARN) of the Amazon S3 bucket.

Type: String

Length Constraints: Minimum length of 16. Maximum length of 100.

Pattern: `arn:(aws[a-zA-Z0-9-]*):s3:::.+`

Required: Yes

dataFormat

Specify the format that files are saved in the Amazon S3 bucket. You can save files in an Apache Parquet or JSON format.

- Parquet - Store data in a columnar storage file format. Parquet is optimal for fast data retrieval and can reduce costs. This option is selected by default.
- JSON - Store data in a standard text-based JSON file format.

Type: String

Valid Values: JSON | PARQUET

Required: No

prefix

Enter an S3 bucket prefix. The prefix is the string of characters after the bucket name and before the object name. You can use the prefix to organize data stored in Amazon S3 buckets. For more information, see [Organizing objects using prefixes](#) in the *Amazon Simple Storage Service User Guide*.

By default, AWS IoT FleetWise sets the prefix `processed-data/year=YY/month=MM/date=DD/hour=HH/` (in UTC) to data it delivers to Amazon S3. You can enter a prefix to

append it to this default prefix. For example, if you enter the prefix `vehicles`, the prefix will be `vehicles/processed-data/year=YY/month=MM/date=DD/hour=HH/`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `[a-zA-Z0-9-_:./!*'()]+`

Required: No

storageCompressionFormat

By default, stored data is compressed as a .gzip file. Compressed files have a reduced file size, which can optimize the cost of data storage.

Type: String

Valid Values: NONE | GZIP

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Sensor

An input component that reports the environmental condition of a vehicle.

Note

You can collect data about fluid levels, temperatures, vibrations, or battery voltage from sensors.

Contents

dataType

The specified data type of the sensor.

Type: String

Valid Values: INT8 | UINT8 | INT16 | UINT16 | INT32 | UINT32 | INT64 | UINT64 | BOOLEAN | FLOAT | DOUBLE | STRING | UNIX_TIMESTAMP | INT8_ARRAY | UINT8_ARRAY | INT16_ARRAY | UINT16_ARRAY | INT32_ARRAY | UINT32_ARRAY | INT64_ARRAY | UINT64_ARRAY | BOOLEAN_ARRAY | FLOAT_ARRAY | DOUBLE_ARRAY | STRING_ARRAY | UNIX_TIMESTAMP_ARRAY | UNKNOWN | STRUCT | STRUCT_ARRAY

Required: Yes

fullyQualifiedName

The fully qualified name of the sensor. For example, the fully qualified name of a sensor might be `Vehicle.Body.Engine.Battery`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 150.

Pattern: `[a-zA-Z0-9_\.]+`

Required: Yes

allowedValues

A list of possible values a sensor can take.

Type: Array of strings

Required: No

comment

A comment in addition to the description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

deprecationMessage

The deprecation message for the node or the branch that was moved or deleted.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

description

A brief description of a sensor.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

max

The specified possible maximum value of the sensor.

Type: Double

Required: No

min

The specified possible minimum value of the sensor.

Type: Double

Required: No

structFullyQualifiedName

The fully qualified name of the struct node for a sensor if the data type of the actuator is `Struct` or `StructArray`. For example, the struct fully qualified name of a sensor might be `Vehicle.ADAS.CameraStruct`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 150.

Pattern: `[a-zA-Z0-9_.]+`

Required: No

unit

The scientific unit of measurement for data collected by the sensor.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SignalCatalogSummary

Information about a collection of standardized signals, which can be attributes, branches, sensors, or actuators.

Contents

arn

The Amazon Resource Name (ARN) of the signal catalog.

Type: String

Required: No

creationTime

The time the signal catalog was created in seconds since epoch (January 1, 1970 at midnight UTC time).

Type: Timestamp

Required: No

lastModificationTime

The time the signal catalog was last updated in seconds since epoch (January 1, 1970 at midnight UTC time).

Type: Timestamp

Required: No

name

The name of the signal catalog.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SignalDecoder

Information about a signal decoder.

Contents

fullyQualifiedName

The fully qualified name of a signal decoder as defined in a vehicle model.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 150.

Pattern: [a-zA-Z0-9_.] +

Required: Yes

interfaceId

The ID of a network interface that specifies what network protocol a vehicle follows.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: [-a-zA-Z0-9_.] +

Required: Yes

type

The network protocol for the vehicle. For example, CAN_SIGNAL specifies a protocol that defines how data is communicated between electronic control units (ECUs). OBD_SIGNAL specifies a protocol that defines how self-diagnostic data is communicated between ECUs.

Type: String

Valid Values: CAN_SIGNAL | OBD_SIGNAL | MESSAGE_SIGNAL |
CUSTOM_DECODING_SIGNAL

Required: Yes

canSignal

Information about signal decoder using the Controller Area Network (CAN) protocol.

Type: [CanSignal](#) object

Required: No

customDecodingSignal

Information about a [custom signal decoder](#).

Type: [CustomDecodingSignal](#) object

Required: No

messageSignal

The decoding information for a specific message which supports higher order data types.

Type: [MessageSignal](#) object

Required: No

obdSignal

Information about signal decoder using the on-board diagnostic (OBD) II protocol.

Type: [ObdSignal](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SignalFetchConfig

The configuration of the signal fetch operation.

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

conditionBased

The configuration of a condition-based signal fetch operation.

Type: [ConditionBasedSignalFetchConfig](#) object

Required: No

timeBased

The configuration of a time-based signal fetch operation.

Type: [TimeBasedSignalFetchConfig](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SignalFetchInformation

Information about the signal to be fetched.

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Contents

actions

The actions to be performed by the signal fetch.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 2 items.

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

fullyQualifiedName

The fully qualified name of the signal to be fetched.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 150.

Pattern: [a-zA-Z0-9_.]+

Required: Yes

signalFetchConfig

The configuration of the signal fetch operation.

Type: [SignalFetchConfig](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

conditionLanguageVersion

The version of the condition language used.

Type: Integer

Valid Range: Fixed value of 1.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SignalInformation

Information about a signal.

Contents

name

The name of the signal.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 150.

Pattern: `[\w|*|-]+\([\. [\w|*|-]+\)`*

Required: Yes

dataPartitionId

The ID of the data partition this signal is associated with.

The ID must match one of the IDs provided in `dataPartitions`. This is accomplished either by specifying a particular data partition ID or by using `default` for an established default partition. You can establish a default partition in the `DataPartition` data type.

Note

If you upload a signal as a condition for a campaign's data partition, the same signal must be included in `signalsToCollect`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9]+`

Required: No

maxSampleCount

The maximum number of samples to collect.

Type: Long

Valid Range: Minimum value of 1. Maximum value of 4294967295.

Required: No

minimumSamplingIntervalMs

The minimum duration of time (in milliseconds) between two triggering events to collect data.

Note

If a signal changes often, you might want to collect data at a slower rate.

Type: Long

Valid Range: Minimum value of 0. Maximum value of 4294967295.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

StateTemplateAssociation

The state template associated with a vehicle. State templates contain state properties, which are signals that belong to a signal catalog that is synchronized between the AWS IoT FleetWise Edge and the AWS Cloud.

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Contents

identifier

The unique ID of the state template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\.]+

Required: Yes

stateTemplateUpdateStrategy

The update strategy for the state template. Vehicles associated with the state template can stream telemetry data with either an onChange or periodic update strategy.

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Type: [StateTemplateUpdateStrategy](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

StateTemplateSummary

Information about a state template.

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Contents

arn

The Amazon Resource Name (ARN) of the state template.

Type: String

Required: No

creationTime

The time the state template was created, in seconds since epoch (January 1, 1970 at midnight UTC time).

Type: Timestamp

Required: No

description

A brief description of the state template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `[^\u0000-\u001F\u007F]+`

Required: No

id

The unique ID of the state template.

Type: String

Length Constraints: Fixed length of 26.

Pattern: [A-Z0-9]+

Required: No

lastModificationTime

The time the state template was last updated, in seconds since epoch (January 1, 1970 at midnight UTC time).

Type: Timestamp

Required: No

name

The name of the state template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\.]+

Required: No

signalCatalogArn

The Amazon Resource Name (ARN) of the signal catalog associated with the state template.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

StateTemplateUpdateStrategy

The update strategy for the state template. Vehicles associated with the state template can stream telemetry data with either an onChange or periodic update strategy.

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

onChange

Vehicles associated with the state template will stream telemetry data when there is a change.

Type: [OnChangeStateTemplateUpdateStrategy](#) object

Required: No

periodic

Vehicles associated with the state template will stream telemetry data during a specified time period.

Type: [PeriodicStateTemplateUpdateStrategy](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

StorageMaximumSize

The maximum storage size for the data partition.

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Contents

unit

The data type of the data to store.

Type: String

Valid Values: MB | GB | TB

Required: Yes

value

The maximum amount of time to store data.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1073741824.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

StorageMinimumTimeToLive

Information about the minimum amount of time that data will be kept.

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Contents

unit

The time increment type.

Type: String

Valid Values: HOURS | DAYS | WEEKS

Required: Yes

value

The minimum amount of time to store the data.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 876600.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

StructuredMessage

The structured message for the message signal. It can be defined with either a `primitiveMessageDefinition`, `structuredMessageListDefinition`, or `structuredMessageDefinition` recursively.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

primitiveMessageDefinition

Represents a primitive type node of the complex data structure.

Type: [PrimitiveMessageDefinition](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

structuredMessageDefinition

Represents a struct type node of the complex data structure.

Type: Array of [StructuredMessageFieldNameAndDataTypePair](#) objects

Array Members: Minimum number of 1 item. Maximum number of 500 items.

Required: No

structuredMessageListDefinition

Represents a list type node of the complex data structure.

Type: [StructuredMessageListDefinition](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

StructuredMessageFieldNameAndDataTypePair

Represents a StructureMessageName to DataType map element.

Contents

dataType

The data type.

Type: [StructuredMessage](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

fieldName

The field name of the structured message. It determines how a data value is referenced in the target language.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 150.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

StructuredMessageListDefinition

Represents a list type node of the complex data structure.

Contents

listType

The type of list of the structured message list definition.

Type: String

Valid Values: FIXED_CAPACITY | DYNAMIC_UNBOUNDED_CAPACITY |
DYNAMIC_BOUNDED_CAPACITY

Required: Yes

memberType

The member type of the structured message list definition.

Type: [StructuredMessage](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

name

The name of the structured message list definition.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 150.

Required: Yes

capacity

The capacity of the structured message list definition when the list type is FIXED_CAPACITY or DYNAMIC_BOUNDED_CAPACITY.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 2147483647.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Tag

A set of key/value pairs that are used to manage the resource.

Contents

Key

The tag's key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

Value

The tag's value.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TimeBasedCollectionScheme

Information about a collection scheme that uses a time period to decide how often to collect data.

Contents

periodMs

The time period (in milliseconds) to decide how often to collect data. For example, if the time period is 60000, the Edge Agent software collects data once every minute.

Type: Long

Valid Range: Minimum value of 10000. Maximum value of 86400000.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TimeBasedSignalFetchConfig

Used to configure a frequency-based vehicle signal fetch.

Contents

executionFrequencyMs

The frequency with which the signal fetch will be executed.

Type: Long

Valid Range: Minimum value of 1. Maximum value of 9223372036854775807.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TimePeriod

The length of time between state template updates.

Contents

unit

A unit of time.

Type: String

Valid Values: `MILLISECOND` | `SECOND` | `MINUTE` | `HOURL`

Required: Yes

value

A number of time units.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 2147483647.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TimestreamConfig

The Amazon Timestream table where the AWS IoT FleetWise campaign sends data. Timestream stores and organizes data to optimize query processing time and to reduce storage costs. For more information, see [Data modeling](#) in the *Amazon Timestream Developer Guide*.

Contents

executionRoleArn

The Amazon Resource Name (ARN) of the task execution role that grants AWS IoT FleetWise permission to deliver data to the Amazon Timestream table.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:(aws[a-zA-Z0-9-]*):iam::(\d{12})?:(role((\u002F)|(\u002F[\u0021-\u007F]+\u002F))[\w+=,.\u002D-]+)`

Required: Yes

timestreamTableArn

The Amazon Resource Name (ARN) of the Amazon Timestream table.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:(aws[a-zA-Z0-9-]*):timestream:[a-zA-Z0-9-]+:[0-9]{12}:database/[a-zA-Z0-9_.-]+/table/[a-zA-Z0-9_.-]+`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TimestreamRegistrationResponse

Information about the registered Amazon Timestream resources or errors, if any.

Contents

registrationStatus

The status of registering your Amazon Timestream resources. The status can be one of REGISTRATION_SUCCESS, REGISTRATION_PENDING, REGISTRATION_FAILURE.

Type: String

Valid Values: REGISTRATION_PENDING | REGISTRATION_SUCCESS | REGISTRATION_FAILURE

Required: Yes

timestreamDatabaseName

The name of the Timestream database.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 255.

Pattern: [a-zA-Z0-9_.-]+

Required: Yes

timestreamTableName

The name of the Timestream database table.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 255.

Pattern: [a-zA-Z0-9_.-]+

Required: Yes

errorMessage

A message associated with a registration error.

Type: String

Required: No

timestreamDatabaseArn

The Amazon Resource Name (ARN) of the Timestream database.

Type: String

Required: No

timestreamTableArn

The ARN of the Timestream database table.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TimestreamResources

The registered Amazon Timestream resources that AWS IoT FleetWise edge agent software can transfer your vehicle data to.

Contents

timestreamDatabaseName

The name of the registered Amazon Timestream database.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 255.

Pattern: [a-zA-Z0-9_.-]+

Required: Yes

timestreamTableName

The name of the registered Amazon Timestream database table.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 255.

Pattern: [a-zA-Z0-9_.-]+

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UpdateVehicleError

An HTTP error resulting from updating the description for a vehicle.

Contents

code

The relevant HTTP error code (400+).

Type: Integer

Required: No

message

A message associated with the error.

Type: String

Required: No

vehicleName

The ID of the vehicle with the error.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\.]+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UpdateVehicleRequestItem

Information about the vehicle to update.

Important

AWS IoT FleetWise is no longer open to new customers. Existing customers can continue to use the service as normal. For more information, see [AWS IoT FleetWise availability change](#).

Contents

vehicleName

The unique ID of the vehicle to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\+]

Required: Yes

attributes

Static information about a vehicle in a key-value pair. For example:

```
"engineType": "1.3 L R2"
```

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 150.

Key Pattern: [a-zA-Z0-9_\.-\+]

Required: No

attributeUpdateMode

The method the specified attributes will update the existing attributes on the vehicle.

Use `Overwrite` to replace the vehicle attributes with the specified attributes. Or use `Merge` to combine all attributes.

This is required if attributes are present in the input.

Type: String

Valid Values: Overwrite | Merge

Required: No

decoderManifestArn

The ARN of the signal decoder manifest associated with the vehicle to update.

Type: String

Required: No

modelManifestArn

The ARN of the vehicle model (model manifest) associated with the vehicle to update.

Type: String

Required: No

stateTemplatesToAdd

Associate additional state templates to track the state of the vehicle. State templates determine which signal updates the vehicle sends to the cloud.

Type: Array of [StateTemplateAssociation](#) objects

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Required: No

stateTemplatesToRemove

Remove existing state template associations from the vehicle.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\]+

Required: No

stateTemplatesToUpdate

Change the stateTemplateUpdateStrategy of state templates already associated with the vehicle.

Type: Array of [StateTemplateAssociation](#) objects

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UpdateVehicleResponseItem

Information about the updated vehicle.

Contents

arn

The Amazon Resource Name (ARN) of the updated vehicle.

Type: String

Required: No

vehicleName

The unique ID of the updated vehicle.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\.]+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ValidationExceptionField

A validation error due to mismatch between the expected data type, length, or pattern of the parameter and the input.

Contents

message

A message about the validation error.

Type: String

Required: Yes

name

The name of the parameter field with the validation error.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VehicleMiddleware

The vehicle middleware defined as a type of network interface. Examples of vehicle middleware include ROS2 and SOME/IP.

Contents

name

The name of the vehicle middleware.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

protocolName

The protocol name of the vehicle middleware.

Type: String

Valid Values: ROS_2

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VehicleStatus

Information about a campaign associated with a vehicle.

Contents

campaignName

The name of a campaign.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\.]+

Required: No

status

The status of a campaign, which can be one of the following:

- **CREATED** - The campaign exists but is not yet approved.
- **READY** - The campaign is approved but has not been deployed to the vehicle. Data has not arrived at the vehicle yet.
- **HEALTHY** - The campaign is deployed to the vehicle.
- **SUSPENDED** - The campaign is suspended and data collection is paused.
- **DELETING** - The campaign is being removed from the vehicle.
- **READY_FOR_CHECKIN** - The campaign is approved and waiting for vehicle check-in before deployment.

Type: String

Valid Values: **CREATED** | **READY** | **HEALTHY** | **SUSPENDED** | **DELETING** | **READY_FOR_CHECKIN**

Required: No

vehicleName

The unique ID of the vehicle.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\]+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VehicleSummary

Information about a vehicle.

To return this information about vehicles in your account, you can use the [ListVehicles](#) API operation.

Contents

arn

The Amazon Resource Name (ARN) of the vehicle.

Type: String

Required: Yes

creationTime

The time the vehicle was created in seconds since epoch (January 1, 1970 at midnight UTC time).

Type: Timestamp

Required: Yes

decoderManifestArn

The ARN of a decoder manifest associated with the vehicle.

Type: String

Required: Yes

lastModificationTime

The time the vehicle was last updated in seconds since epoch (January 1, 1970 at midnight UTC time).

Type: Timestamp

Required: Yes

modelManifestArn

The ARN of a vehicle model (model manifest) associated with the vehicle.

Type: String

Required: Yes

vehicleName

The unique ID of the vehicle.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [a-zA-Z\d\-_:\.]+

Required: Yes

attributes

Static information about a vehicle in a key-value pair. For example:

```
"engineType": "1.3 L R2"
```

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 150.

Key Pattern: [a-zA-Z0-9_\. -]+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Error Types

This section lists common error types that this AWS service may return. Not all services return all error types listed here. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You don't have permission to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 403

ExpiredTokenException

The security token included in the request has expired. Request a new security token and try again.

HTTP Status Code: 403

IncompleteSignature

The request signature doesn't conform to AWS standards. Verify that you're using valid AWS credentials and that your request is properly formatted. If you're using an SDK, ensure it's up to date.

HTTP Status Code: 403

InternalFailure

The request can't be processed right now because of an internal server issue. Try again later. If the problem persists, contact AWS Support.

HTTP Status Code: 500

MalformedHttpRequestException

The request body can't be processed. This typically happens when the request body can't be decompressed using the specified content encoding algorithm. Verify that the content encoding header matches the compression format used.

HTTP Status Code: 400

NotAuthorized

You don't have permissions to perform this action. Verify that your IAM policy includes the required permissions.

HTTP Status Code: 401

OptInRequired

Your AWS account needs a subscription for this service. Verify that you've enabled the service in your account.

HTTP Status Code: 403

RequestAbortedException

The request was aborted before a response could be returned. This typically happens when the client closes the connection.

HTTP Status Code: 400

RequestEntityTooLargeException

The request entity is too large. Reduce the size of the request body and try again.

HTTP Status Code: 413

RequestTimeoutException

The request timed out. The server didn't receive the complete request within the expected time frame. Try again.

HTTP Status Code: 408

ServiceUnavailable

The service is temporarily unavailable. Try again later.

HTTP Status Code: 503

ThrottlingException

Your request rate is too high. The AWS SDKs automatically retry requests that receive this exception. Reduce the frequency of requests.

HTTP Status Code: 400

UnknownOperationException

The action or operation isn't recognized. Verify that the action name is spelled correctly and that it's supported by the API version you're using.

HTTP Status Code: 404

UnrecognizedClientException

The X.509 certificate or AWS access key ID you provided doesn't exist in our records. Verify that you're using valid credentials and that they haven't expired.

HTTP Status Code: 403

ValidationError

The input doesn't meet the required format or constraints. Check that all required parameters are included and that values are valid.

HTTP Status Code: 400